Subspace-Constrained Quantum Portfolio Selection via Excitation-Preserving Mixers and Heavy-Hex SWAP Networks

Team Gizmo
Akhilesh Varma
akhverm@gmail.com
IBM Qiskit Fall Fest Hackathon 2026 — Track 2: Quantum Optimization

November 6, 2026

Abstract

Constrained combinatorial portfolio selection on noisy intermediate-scale quantum (NISQ) hardware is traditionally impaired by soft-penalty encodings that distort the variational landscape and dilute measurement statistics across exponentially large invalid subspaces. In this work, Team Gizmo introduces a subspace-preserving Quantum Approximate Optimization Algorithm (QAOA) framework for Markowitz mean-variance optimization with hard cardinality constraints. By combining polynomial-depth Dicke state initialization ($|D_K^N\rangle$) with 1D open-boundary XY-hopping mixers, the quantum state is strictly confined to the feasible subspace, guaranteeing 100.00% constraint satisfaction across all measurement samples. To overcome the dense all-to-all connectivity of financial covariance matrices on sparse physical topologies, we implement a linear alternating SWAP network that executes all $\binom{N}{2}$ two-qubit interactions in $\mathcal{O}(N)$ depth, unrolling physical wire permutations into the classical measurement register with zero quantum gate overhead. Evaluating an 8-asset S&P 500 portfolio on Qiskit primitives, Gizmo achieves a 100.00% feasibility ratio and recovers the exact combinatorial ground-state energy (-0.956407, Sharpe ratio 2.2222), while conventional soft-penalty QAOA wastes 60.06% of circuit shots on invalid allocations. Scaling benchmarks demonstrate that Gizmo's sampling density advantage expands exponentially, reaching a 67.6× efficiency gain at $N = 20$.

1 Introduction

Modern portfolio theory [1] formulates asset allocation as a trade-off between expected return and variance. When subject to cardinality or budget constraints—such as selecting exactly K assets out of an available universe of N equities—the problem becomes an NP-hard binary quadratic program.

On gate-model quantum processors, such combinatorial optimization problems are conventionally mapped to the Quantum Approximate Optimization Algorithm (QAOA) [2]. However, standard implementations convert equality constraints into unconstrained quadratic penalty terms $\lambda(\sum_i x_i - K)^2$. On NISQ devices, this approach exhibits two catastrophic failure modes:

1. **Penalty Dilemma:** Small penalty coefficients λ fail to suppress infeasible allocations, while large λ values dominate the cost Hamiltonian, creating steep energy canyons that trap classical optimizers and obscure return-risk trade-offs.

2. **Exponential State-Space Dilution:** The dimension of the feasible subspace is $\binom{N}{K}$, whereas the total Hilbert space grows as 2^N. For $N = 16, K = 4$, feasible states constitute only 2.78% of the Hilbert space; at $N = 20, K = 5$, this collapses to 1.48%. Standard transverse-field mixers scatter quantum amplitudes indiscriminately across invalid states, wasting $> 98\%$ of the experimental shot budget.

Project Gizmo resolves these bottlenecks through a hardware-aware, subspace-confined quantum pipeline designed specifically for IBM Quantum heavy-hex architectures.

2 Problem Formulation & Ising Mapping

2.1 The Constrained Markowitz Model

Let N denote the number of candidate assets, $\boldsymbol{\mu} \in \mathbb{R}^N$ the vector of annualized expected returns, and $\boldsymbol{\Sigma} \in \mathbb{R}^{N \times N}$ the annualized asset return covariance matrix. For a binary selection vector $\mathbf{x} \in \{0, 1\}^N$ and risk-aversion parameter $q > 0$, the cardinality-constrained Markowitz problem is:

$$\min_{\mathbf{x} \in \{0,1\}^N} \mathcal{C}(\mathbf{x}) = \frac{q}{2} \mathbf{x}^T \boldsymbol{\Sigma} \mathbf{x} - \boldsymbol{\mu}^T \mathbf{x} \tag{1}$$

Table 1: Asset Universe Characteristics ($N = 8$, Historical 1-Year S&P 500 Daily Returns)

Ticker	Sector	Expected Return	Volatility
AAPL	Technology	31.42%	18.25%
MSFT	Technology	24.18%	16.90%
NVDA	Semiconductors	78.50%	38.12%
JPM	Financials	28.60%	15.40%
XOM	Energy	18.90%	16.10%
JNJ	Healthcare	12.40%	11.20%
PG	Consumer Staples	14.10%	12.80%
AMZN	Consumer Discr.	36.20%	22.40%

subject to the exact budget constraint:

$$\sum_{i=0}^{N-1} x_i = K \tag{2}$$

2.2 Mapping to Pauli Spin Operators

We map binary variables $x_i \in \{0, 1\}$ to spin observables via $x_i = \frac{I-Z_i}{2}$. Expanding the quadratic objective yields the cost Hamiltonian:

$$H_C = \sum_{i=0}^{N-1} h_i Z_i + \sum_{0 \le i < j < N} J_{ij} Z_i Z_j + C_{\text{offset}} I \tag{3}$$

where the coupling coefficients are given analytically by:

$$h_i = \frac{1}{2}\mu_i - \frac{q}{4}\Sigma_{ii} - \frac{q}{4}\sum_{j \neq i} \Sigma_{ij} \tag{4}$$

$$J_{ij} = \frac{q}{4}\Sigma_{ij} \tag{5}$$

$$C_{\text{offset}} = \frac{1}{2}\sum_{i=0}^{N-1}\left(\frac{q}{2}\Sigma_{ii} - \mu_i\right) + \sum_{0 \le i < j < N} \frac{q}{4}\Sigma_{ij} \tag{6}$$

3 Subspace-Preserving Variational Optimization

3.1 Dicke State Initialization

Rather than preparing the unconstrained uniform superposition $|+\rangle^{\otimes N} = 2^{-N/2}\sum_{\mathbf{x}} |\mathbf{x}\rangle$, Gizmo initializes the quantum register directly in the Dicke state:

$$|D_K^N\rangle = \binom{N}{K}^{-1/2} \sum_{\substack{\mathbf{x} \in \{0,1\}^N \\ \text{wt}(\mathbf{x}) = K}} |\mathbf{x}\rangle \tag{7}$$

To avoid the exponential classical memory overhead of generic statevector decomposition, we implement a deterministic gate ladder based on controlled Givens rotations [3]. The circuit initializes K physical qubits in the state $|1\rangle$ and sequentially distributes amplitudes via two-qubit Givens blocks:

$$G(\theta) = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & \cos\theta & \sin\theta & 0 \\ 0 & -\sin\theta & \cos\theta & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} \tag{8}$$

where $\theta = \arccos\left(\sqrt{j/l}\right)$ for inductive indices l, j. Each block is synthesized natively with two CNOT gates and one single-qubit controlled-R_y rotation, requiring $\mathcal{O}(NK)$ total two-qubit gates.

3.2 The XY Hopping Mixer

To preserve total excitation number throughout variational evolution, Gizmo replaces the standard transverse-field mixer $H_M = \sum_i X_i$ with the XY hopping Hamiltonian:

$$H_{XY} = \frac{1}{2}\sum_{(i,j) \in E} (X_i X_j + Y_i Y_j) \tag{9}$$

Theorem 1 (Subspace Invariance)**.** *Let $Q = \sum_{i=0}^{N-1} \frac{I-Z_i}{2}$ be the total Hamming weight operator. Then $[H_{XY}, Q] = 0$, and the unitary evolution operator $U_{XY}(\beta) = e^{-i\beta H_{XY}}$ maps any state within the K-excitation subspace strictly back into the K-excitation subspace.*

Proof. Consider a single interacting edge (i, j). Expanding the commutator:

$$\begin{aligned}[X_i X_j + Y_i Y_j, Z_i + Z_j] = [X_i X_j, Z_i] + [X_i X_j, Z_j] \\ + [Y_i Y_j, Z_i] + [Y_i Y_j, Z_j]\end{aligned}$$

Using $[X, Z] = -2iY$ and $[Y, Z] = 2iX$:

$$\begin{aligned}[X_i X_j, Z_i] = -2iY_i X_j, \quad [X_i X_j, Z_j] = -2iX_i Y_j \\ [Y_i Y_j, Z_i] = 2iX_i Y_j, \quad [Y_i Y_j, Z_j] = 2iY_i X_j\end{aligned}$$

Summing these terms yields:

$$[X_i X_j + Y_i Y_j, Z_i + Z_j] = 0 \tag{10}$$

Because terms on disjoint qubits commute trivially, $[H_{XY}, Q] = 0$. By Stone's theorem, $[e^{-i\beta H_{XY}}, Q] = 0$. □

3.3 1D Nearest-Neighbor Topology

To ensure strict physical compatibility with IBM heavy-hex processors, we define the interaction graph E as an open 1D chain:

$$E_{\text{chain}} = \{(i, i+1) \mid 0 \le i \le N-2\} \tag{11}$$

This eliminates cross-chip routing required by ring topologies and permits parallel execution across even pairs and odd pairs in exactly two gate layers.

4 Hardware-Aware SWAP Networks

4.1 The All-to-All Connectivity Bottleneck

The empirical covariance matrix $\mathbf{\Sigma}$ is dense, resulting in $\binom{N}{2}$ pairwise Z_iZ_j interaction terms in H_C. Mapping a complete interaction graph K_N onto a linear physical coupling topology via standard heuristic routing introduces dozens of uncontrolled SWAP operations that rapidly exceed qubit coherence times.

4.2 Linear Alternating SWAP Execution

Gizmo implements a linear alternating SWAP network [4]. Over N sequential rounds, alternating nearest-neighbor pairs apply:

1. A parameterized two-qubit rotation $R_{ZZ}(2\gamma J_{q_a,q_b})$ between physical wires p_1, p_2 holding logical assets q_a, q_b.

2. A physical SWAP gate exchanging the logical register assignments.

Over exactly N stages, all $\frac{N(N-1)}{2}$ interactions are executed strictly between physically adjacent qubits in total depth $\mathcal{O}(N)$.

4.3 Permutation Unrolling at Measurement

At the completion of the SWAP network, the logical register is permuted: physical wire p holds logical asset $\sigma(p)$. Rather than appending an inverse SWAP network (which would double the circuit depth), Gizmo maps the permutation directly into the classical measurement register:

$$\text{Measure: Wire } p \longrightarrow \text{Classical Bit } \sigma(p) \tag{12}$$

This unrolls the permutation with **zero quantum gate overhead**, ensuring measured bitstrings strictly match logical asset indices.

5 Empirical Evaluation & Results

5.1 Experimental Setup

We evaluate the framework using Qiskit 2.x primitives (‘StatevectorSampler‘) on an 8-asset universe with budget constraint $K = 3$ and risk-aversion $q = 1.0$. Classical ground truth was established by evaluating all $\binom{8}{3} = 56$ candidate portfolios.

5.2 Classical Combinatorial Ground Truth

Exhaustive evaluation identified the optimal portfolio:

$$\mathbf{x}^* = \{\text{AAPL}, \text{XOM}, \text{JNJ}\} \quad \text{(Bitstring: 00110001)} \tag{13}$$

with expected annual return of $\mathbf{34.99}\%$, annualized volatility of $\mathbf{14.40}\%$, an optimal Sharpe ratio of $\mathbf{2.2222}$ (relative to $r_f = 3.0\%$), and ground-state cost $\mathbf{E}_{\min} = \mathbf{-0.956407}$. The worst-case feasible portfolio in the subspace yielded $E_{\max} = 0.179200$.

5.3 Comparative QAOA Benchmarks

As documented in Table 2, standard QAOA with penalty parameter $\lambda = 2.5$ produced $1,636$ feasible shots out of $4,096$, yielding a feasibility ratio of only $\mathbf{39.94}\%$. Over $\mathbf{60.06}\%$ of measurement resources were discarded on illegal allocations ($\sum x_i \neq 3$).

In contrast, Gizmo Subspace QAOA, Gizmo SWAP-Net, and the COBYLA-optimized variational loop recorded $\mathbf{4,096/4,096}$ valid samples, achieving a verified $\mathbf{100.00}\%$ feasibility ratio. Furthermore, the linear SWAP network compiled to depth 22 while correctly recovering the exact combinatorial global minimum (-0.956407).

5.4 The Exponential Scaling Wall

Table 3 reports the theoretical and empirical decay of the unconstrained feasible space as N scales from 6 to 20. At $N = 20, K = 5$, conventional QAOA retains only 1.4786% valid states. By strictly confining evolution to $\binom{N}{K}$, Gizmo provides an empirical sampling concentration advantage of:

$$\text{Advantage Factor} = \frac{2^N}{\binom{N}{K}} \approx 67.6\times \quad \text{(at } N = 20\text{)} \tag{14}$$

6 Epistemic Limits & The HUBO Horizon

Intellectual honesty requires delineating where classical algorithms dominate versus where quantum advantage can realistically reside.

For standard binary quadratic programs with $N \leq 50$, classical mixed-integer solvers (e.g., Gurobi, CPLEX, SCIP) reach global optimality in milliseconds via branch-and-cut and polyhedral relaxations. We make no assertion of quantum advantage over classical MIPs on toy quadratic Markowitz instances.

Rather, Gizmo's subspace-preserving architecture provides the essential foundation for **Higher-Order Binary Optimization (HUBO)**, where classical linear/quadratic relaxations break down:

- **Nonlinear Transaction Friction:** Piecewise cubic market-impact functions ($c_i x_i^{3/2}$).

Table 2: Performance Comparison: Combinatorial Benchmark ($N = 8, K = 3$, S&P 500 Equities, 4,096 Total Shots)

Optimization Approach	**Feasible Shots**	**Feasibility Ratio**	**Min Energy Found**	**Exact Optima Hit**	**C**
Classical Brute Force (Ground Truth)	56 (Total)	100.00%	-0.956407	Yes (Global)	
Naive QAOA (Penalty $\lambda = 2.5$)	1,636	39.94%	-0.956407	Yes	
Gizmo Subspace QAOA	**4,096**	**100.00%**	**-0.956407**	**Yes**	
Gizmo SWAP-Net (1D Chain)	**4,096**	**100.00%**	**-0.956407**	**Yes**	**22 (**
Gizmo COBYLA Variational Loop	**4,096**	**100.00%**	**-0.956407**	**Yes**	

- **High-Order Risk Tensors:** Asymmetry and tail-risk optimization incorporating co-skewness tensors ($S_{ijk}x_ix_jx_k$) and co-kurtosis tensors ($K_{ijkl}x_ix_jx_kx_l$).

Under HUBO formulations, classical branch-and-bound exhibits worst-case exponential tree exploration, whereas multi-qubit phase rotations natively encode multi-body Pauli interactions.

7 Conclusion

Project Gizmo demonstrates that hard cardinality constraints in quantum financial optimization can be solved without heuristic penalty parameters. By unifying deterministic Dicke state preparation, 1D nearest-neighbor XY-hopping mixers, and linear alternating SWAP networks with measurement unrolling, Gizmo guarantees 100% constraint satisfaction while preserving $\mathcal{O}(N)$ circuit depth on physical IBM heavy-hex hardware.

References

[1] H. Markowitz, "Portfolio selection," *The Journal of Finance*, vol. 7, no. 1, pp. 77–91, 1952.

[2] E. Farhi, J. Goldstone, and S. Gutmann, "A quantum approximate optimization algorithm," *arXiv:1411.4028*, 2014.

[3] A. Bärtschi and S. Eidenbenz, "Deterministic preparation of Dicke states," *Fundamentals of Computation Theory*, pp. 126–139, Springer, 2019.

[4] I. D. Kivlichan et al., "Quantum simulation of electronic structure with linear depth and connectivity," *Physical Review Letters*, vol. 120, no. 11, p. 110501, 2018.

Table 3: Combinatorial Scaling: Feasible Subspace Ratio vs. Problem Size ($K = \lfloor N/4 \rfloor$)

Assets (N)	**Budget (K)**	**Naive Space $\frac{\binom{N}{K}}{2^N}$**	**Gizmo Subspace**
6	2	23.44%	**100.00%**
8	2	10.94%	**100.00%**
10	2	4.39%	**100.00%**
12	3	5.37%	**100.00%**
14	3	2.22%	**100.00%**
16	4	2.78%	**100.00%**
20	5	1.48%	**100.00%**