

TranS: Transition-based Knowledge Graph Embedding with Synthetic Relation Representation

Xuanyu Zhang, Qing Yang and Dongliang Xu

DXM-DI-AI

Abstract

Knowledge graph embedding (KGE) aims to learn continuous vectors of relations and entities in knowledge graph. Recently, transition-based KGE methods have achieved promising performance, where the single relation vector learns to translate head entity to tail entity. However, this scoring pattern is not suitable for complex scenarios where the same entity pair has different relations. Previous models usually focus on the improvement of entity representation for 1-to-N, N-to-1 and N-to-N relations, but ignore the single relation vector. In this paper, we propose a novel transition-based method, TranS, for knowledge graph embedding. The single relation vector in traditional scoring patterns is replaced with synthetic relation representation, which can solve these issues effectively and efficiently. Experiments on a large knowledge graph dataset, ogbl-wikikg2, show that our model achieves state-of-the-art results.

1 Introduction

Knowledge graphs (KGs), such as Freebase (Bollacker et al., 2008), Yago (Rebele et al., 2016) and Wikidata (Vrandečić and Krötzsch, 2014), play an important role in many applications, including question answering, information retrieval and so on. KG is usually represented as the form of triplets (*head entity, relation, tail entity*)(denoted as (h, r, t)), where *relation* indicates the relationship between the two entities. With the rapid development of deep learning, many representation learning methods (Bordes et al., 2013; Wang et al., 2014; Fan et al., 2014; Lin et al., 2015; Ji et al., 2015, 2016; Xie et al., 2017; Qian et al., 2018; Chao et al., 2020; Yu et al., 2021; Chen et al., 2021; Wang et al., 2022) are proposed to obtain low-dimensional embedding vectors of entities and relations in KG.

Generally speaking, knowledge graph embedding (KGE) methods can be roughly divided into




Figure 1: Examples from ogbl-wikikg2. It is difficult for single relation vector to represent different relations between the same entity pairs.

the following directions: translational distance (Bordes et al., 2013; Wang et al., 2014; Fan et al., 2014; Lin et al., 2015; Ji et al., 2015), semantic matching (Nickel et al., 2011; García-Durán et al., 2014; Yang et al., 2014; Nickel et al., 2016; Trouillon et al., 2016) and neural networks (Bordes et al., 2014; Liu et al., 2016; Li et al., 2016; Gilmer et al., 2017; Xu et al., 2019). Because transition-based KGE method like TransE (Bordes et al., 2013) is simple but effective, this series of models are becoming more and more popular in both academia and industry. Specifically, TransE makes the difference between two entity vectors (h and t) approximate to the relation vector (r), i.e., $t - h \approx r$. That is to say, the relation r is characterized by the translating vector r . However, TransE is not suitable to deal with complex relations like one-to-many/many-to-one/many-to-many. Especially, the same entity pair usually has many different relations. For example, in Figure 1, after graduating from Erasmus University Rotterdam, the professor became a professor of the same university. The composer, producer, screenwriter, editor and direc-

Model	Embedding	Scoring Function	Scoring Pattern
TransE	$\mathbf{h}, \mathbf{t} \in \mathbb{R}^d, \mathbf{r} \in \mathbb{R}^d$	$- \mathbf{h} + \mathbf{r} - \mathbf{t} _{1/2}$	$ \mathbf{R}_h - \mathbf{R}_t + \mathbf{r} $
TransR	$\mathbf{h}, \mathbf{t} \in \mathbb{R}^d, \mathbf{r} \in \mathbb{R}^k, \mathbf{M}_r \in \mathbb{R}^{k \times d}$	$- \mathbf{M}_r \mathbf{h} + \mathbf{r} - \mathbf{M}_r \mathbf{t} _2^2$	$ \mathbf{R}_h - \mathbf{R}_t + \mathbf{r} $
TransH	$\mathbf{h}, \mathbf{t} \in \mathbb{R}^d, \mathbf{r}, \mathbf{w}_r \in \mathbb{R}^d$	$- (\mathbf{h} - \mathbf{w}_r^\top \mathbf{h} \mathbf{w}_r) + \mathbf{r} - (\mathbf{t} - \mathbf{w}_r^\top \mathbf{t} \mathbf{w}_r) _2^2$	$ \mathbf{R}_h - \mathbf{R}_t + \mathbf{r} $
ITransF	$\mathbf{h}, \mathbf{t} \in \mathbb{R}^d, \mathbf{r} \in \mathbb{R}^d$	$ \boldsymbol{\alpha}_r^H \cdot \mathbf{D} \cdot \mathbf{h} + \mathbf{r} - \boldsymbol{\alpha}_r^T \cdot \mathbf{D} \cdot \mathbf{t} _\ell$	$ \mathbf{R}_h - \mathbf{R}_t + \mathbf{r} $
TransAt	$\mathbf{h}, \mathbf{t} \in \mathbb{R}^d, \mathbf{r} \in \mathbb{R}^d$	$P_r(\sigma(\mathbf{r}_h) \mathbf{h}) + \mathbf{r} - P_r(\sigma(\mathbf{r}_t) \mathbf{t})$	$ \mathbf{R}_h - \mathbf{R}_t + \mathbf{r} $
TransD	$\mathbf{h}, \mathbf{t}, \mathbf{w}_h \mathbf{w}_t \in \mathbb{R}^d, \mathbf{r}, \mathbf{w}_r \in \mathbb{R}^k$	$- (\mathbf{w}_r \mathbf{w}_h^\top + \mathbf{I}) \mathbf{h} + \mathbf{r} - (\mathbf{w}_r \mathbf{w}_t^\top + \mathbf{I}) \mathbf{t} _2^2$	$ \mathbf{R}_h - \mathbf{R}_t + \mathbf{r} $
TransM	$\mathbf{h}, \mathbf{t} \in \mathbb{R}^d, \mathbf{r} \in \mathbb{R}^d$	$-\theta_r \mathbf{h} + \mathbf{r} - \mathbf{t} _{1/2}$	$ \mathbf{R}_h - \mathbf{R}_t + \mathbf{r} $
TransSparse	$\mathbf{h}, \mathbf{t} \in \mathbb{R}^d, \mathbf{r} \in \mathbb{R}^k, \mathbf{M}_r(\theta_r) \in \mathbb{R}^{k \times d}$ $\mathbf{h}, \mathbf{t} \in \mathbb{R}^d, \mathbf{M}_r^1(\theta_r^1), \mathbf{M}_r^2(\theta_r^2) \in \mathbb{R}^{k \times d}$	$- \mathbf{M}_r(\theta_r) \mathbf{h} + \mathbf{r} - \mathbf{M}_r(\theta_r) \mathbf{t} _{1/2}^2$ $- \mathbf{M}_r^1(\theta_r^1) \mathbf{h} + \mathbf{r} - \mathbf{M}_r^2(\theta_r^2) \mathbf{t} _{1/2}^2$	$ \mathbf{R}_h - \mathbf{R}_t + \mathbf{r} $
TranS	$\mathbf{h}, \mathbf{t}, \tilde{\mathbf{h}}, \tilde{\mathbf{t}} \in \mathbb{R}^d, \mathbf{r}, \bar{\mathbf{r}}, \hat{\mathbf{r}} \in \mathbb{R}^d$	$- \mathbf{h} \circ \tilde{\mathbf{t}} - \mathbf{t} \circ \tilde{\mathbf{h}} + \bar{\mathbf{r}} \circ \mathbf{h} + \mathbf{r} + \hat{\mathbf{r}} \circ \mathbf{t} $	$ \mathbf{R}_h - \mathbf{R}_t + \bar{\mathbf{r}} + \mathbf{r} + \hat{\mathbf{r}} $

Table 1: Transition-based knowledge graph embedding models.

tor of the film, Indramalati, can be the same person, Jyoti Prasad Agarwala. As shown in Table 1, although previous models like TransH/R/D (Wang et al., 2014; Lin et al., 2015; Ji et al., 2015) solved the problem of 1-to-N, N-to-1 and N-to-N, they still continued the TransE pattern, $\mathbf{R}_t - \mathbf{R}_h \approx \mathbf{r}$, where \mathbf{R}_t and \mathbf{R}_h are the deformation of \mathbf{t} and \mathbf{h} respectively. Even if the entity vector is represented by hyperplane or multiple embedding spaces, single relation vector \mathbf{r} still cannot represent different relationships when facing the same entity pair.

To solve these issues, we propose a novel transition-based knowledge graph embedding model, TranS, which replaces tradition scoring pattern with synthetic relation pattern, i.e., $\mathbf{R}_t - \mathbf{R}_h \approx \bar{\mathbf{r}} + \mathbf{r} + \hat{\mathbf{r}}$. The final relation representation is the sum of multiple relation vectors. It can handle not only complex relations in knowledge graph, but also the situation in Figure 1, where orange solid lines denote \mathbf{r} , and blue dotted lines denote $\bar{\mathbf{r}}, \hat{\mathbf{r}}$. Experiments on a large knowledge graph dataset, ogbl-wikikg2, show that our proposed model achieves state-of-the-art results.

2 Methodology

In this section, we will first introduce our proposed TranS model. And we then introduce the loss function during training and differences among different KGE methods.

2.1 TranS

Our proposed TranS model first breaks the traditional scoring patterns $\mathbf{R}_t - \mathbf{R}_h \approx \mathbf{r}$ in previous models (Bordes et al., 2013; Wang et al., 2014; Fan et al., 2014; Lin et al., 2015; Chao et al., 2020; Yu et al., 2021; Wang et al., 2022). It replaces sin-

gle relation vector \mathbf{r} with synthetic relation vectors $\bar{\mathbf{r}} + \mathbf{r} + \hat{\mathbf{r}}$, where $\bar{\mathbf{r}}, \hat{\mathbf{r}}$ are related to head and tail entities. That is to say, we want $\mathbf{R}_t - \mathbf{R}_h \approx \bar{\mathbf{r}} + \mathbf{r} + \hat{\mathbf{r}}$. The illustration of TranS is shown in Figure 2 (f). Two entity and three relation representations together make up our proposed scoring function $f_r(h, t)$. Especially, the synthetic relation representation consists of the sum of three different relation vectors. To make full use of context information, we use combined vectors with Hadamard product to represent $\mathbf{h}, \mathbf{t}, \bar{\mathbf{r}}$ and $\hat{\mathbf{r}}$ separately:

$$\begin{aligned} f_r(h, t) &= -||\mathbf{R}_h - \mathbf{R}_t + \mathbf{R}_r|| \\ \mathbf{R}_h &= \mathbf{h} \circ \tilde{\mathbf{t}} \\ \mathbf{R}_t &= \mathbf{t} \circ \tilde{\mathbf{h}} \\ \mathbf{R}_r &= \bar{\mathbf{r}} \circ \mathbf{h} + \mathbf{r} + \hat{\mathbf{r}} \circ \mathbf{t} \end{aligned} \quad (1)$$

where \mathbf{h}, \mathbf{t} and \mathbf{r} denote main vectors similar to traditional scoring patterns. $\tilde{\mathbf{h}}$ is auxiliary head entity vector and $\tilde{\mathbf{t}}$ is auxiliary tail entity vector. And $\bar{\mathbf{r}}$ is auxiliary relation vector related to head entity and $\hat{\mathbf{r}}$ is auxiliary relation vector related to tail entity. \mathbf{R}_h is the representation of the head that combines information of the tail, and \mathbf{R}_t is the representation of the tail integrating information of the head. $\bar{\mathbf{r}} \circ \mathbf{h}$ is the representation of the relation that combines information of the head, and $\hat{\mathbf{r}} \circ \mathbf{t}$ is the representation of another relation integrating information of the tail. Thus the final equations can be represented as follows:

$$-||\mathbf{h} \circ \tilde{\mathbf{t}} - \mathbf{t} \circ \tilde{\mathbf{h}} + \bar{\mathbf{r}} \circ \mathbf{h} + \mathbf{r} + \hat{\mathbf{r}} \circ \mathbf{t}|| \quad (2)$$

Following previous works (Yu et al., 2021; Wang et al., 2022), we add an unit vector \mathbf{e} to \mathbf{R}_h and \mathbf{R}_t , i.e., $\mathbf{h} \circ \tilde{\mathbf{t}} \rightarrow \mathbf{h} \circ (\tilde{\mathbf{t}} + \mathbf{e})$, $\mathbf{t} \circ \tilde{\mathbf{h}} \rightarrow \mathbf{t} \circ (\tilde{\mathbf{h}} + \mathbf{e})$. And considering the OOV problem, we also use the




Figure 2: Comparison of different transition-based KGE models.

NodePiece (Galkin et al., 2021) to learn a fixed-size entity vocabulary.

2.2 Training

In the training process, we use the self-adversarial negative sampling loss (Sun et al., 2019) as the loss function. The loss function is as follows:

$$\begin{aligned} \mathcal{L} = & -\log \sigma(\gamma - d_r(\mathbf{h}, \mathbf{t})) \\ & - \sum_{i=1}^n \frac{1}{k} \log \sigma(d_r(\mathbf{h}'_i, \mathbf{t}'_i) - \gamma) \end{aligned} \quad (3)$$

where γ is a fixed margin, σ is the sigmoid function, and $(\mathbf{h}'_i, \mathbf{r}, \mathbf{t}'_i)$ is the i -th negative triplet.

2.3 Comparison

As shown in Figure 2, the main difference between our model (f) and previous transition-based KGE methods (a,b,c,d,e) is the synthetic relation representation. That is to say, it changes single relation representation \mathbf{r} in tradition scoring pattern $\mathbf{R}_t - \mathbf{R}_h \approx \mathbf{r}$ to synthetic relation representation $\bar{\mathbf{r}} + \mathbf{r} + \hat{\mathbf{r}}$ in our proposed new pattern $\mathbf{R}_t - \mathbf{R}_h \approx \bar{\mathbf{r}} + \mathbf{r} + \hat{\mathbf{r}}$. Specifically, different from InterHT (Wang et al., 2022), the relation part of our scoring function is the sum of multiple relation

vectors $\mathbf{R}_r = \bar{\mathbf{r}} \circ \mathbf{h} + \mathbf{r} + \hat{\mathbf{r}} \circ \mathbf{t}$ rather than single vector \mathbf{r} . Comparing with TripleRE (Yu et al., 2021), where three relations are applied into three parts ($\mathbf{R}_h = \mathbf{h} \circ \mathbf{r}^h$, $\mathbf{R}_t = \mathbf{t} \circ \mathbf{r}^t$, $\mathbf{R}_r = \mathbf{r}^m$) of traditional scoring patterns with addition and subtraction operations, our proposed TranS only applies synthetic relation vectors into the relation part $\mathbf{R}_r = \bar{\mathbf{r}} \circ \mathbf{h} + \mathbf{r} + \hat{\mathbf{r}} \circ \mathbf{t}$ of scoring functions with vector addition operation.

3 Experiments

In this section, we will first introduce the dataset and metric. Then we will introduce implementation details and experimental results further.

3.1 Dataset and Metric

The ogbl-wikikg2 (Hu et al., 2020) is a large KG dataset extracted from Wikidata (Vrandečić and Krötzsch, 2014). It contains a set of triplet edges, capturing the different types of relations between entities in the world. The statistics of the dataset are show in Table 3. It contains 2,500,604 entities, 535 relation types and 17,137,181 edges. Following official guidelines, we evaluate the KGE performance by predicting new triplet edges according to the training edges. The evaluation metric fol-

Model	#Params	#Dims	Test MRR	Valid MRR
TransE	1251M	500	0.4256 ± 0.0030	0.4272 ± 0.0030
RotatE	1250M	250	0.4332 ± 0.0025	0.4353 ± 0.0028
PairRE	500M	200	0.5208 ± 0.0027	0.5423 ± 0.0020
AutoSF	500M	-	0.5458 ± 0.0052	0.5510 ± 0.0063
ComplEx	1251M	250	0.5027 ± 0.0027	0.3759 ± 0.0016
TripleRE	501M	200	0.5794 ± 0.0020	0.6045 ± 0.0024
ComplEx-RP	250M	50	0.6392 ± 0.0045	0.6561 ± 0.0070
AutoSF + NodePiece	6.9M	-	0.5703 ± 0.0035	0.5806 ± 0.0047
TripleREv2 + NodePiece	7.3M	200	0.6582 ± 0.0020	0.6616 ± 0.0018
InterHT + NodePiece	19.2M	200	0.6779 ± 0.0018	0.6893 ± 0.0015
TripleREv3 + NodePiece	36.4M	200	0.6866 ± 0.0014	0.6955 ± 0.0008
TranS + NodePiece	19.2M	200	0.6882 ± 0.0019	0.6988 ± 0.0006

Table 2: Results on the ogbl-wikikg2 dataset.

Data	#Number
Nodes	2,500,604
Relations	535
Edges	17,137,181
Train	16,109,182
Validation	429,456
Test	598,543

Table 3: Statistics of the ogbl-wikikg2 dataset.

lows the standard filtered metric widely used in KG. Specifically, each test triplet edges are corrupted by replacing its head or tail with randomly-sampled 1,000 negative entities, while ensuring the resulting triplets do not appear in KG. The goal is to rank the true head (or tail) entities higher than the negative entities, which is measured by Mean Reciprocal Rank (MRR).

We use original dataset splitting configuration. It splits the triplets according to time, simulating a realistic KG completion scenario that aims to fill in missing triplets that are not present at a certain timestamp. Specifically, the training set contains 16,109,182 triplets, the validation set contains 429,456 triplets, and the test set contains 598,543 triplets.

3.2 Implementation Details

In our experiments, the Adam (Kingma and Ba, 2014) is used as our optimizer with 0.0005 learning rate. The batch size of the model is set to 512. To prevent overfitting, we use dropout technique,

and set it to 0.1. The negative sampling size is set to 128. And the dimension of each embedding vector in Eq. 2 is set to 200. The maximum number of training steps is 800 thousand. We validate the model every 20 thousand steps. The number of anchors for NodePiece are 20 thousand. And γ in the loss function is set to 6. These hyper-parameters are selected according to the performance on the validation set.

3.3 Results

The results are shown in Table 2. Our model achieves 0.6988 (validation set) and 0.6882 (test set) on MRR, which outperforms previous best model, TripleREv3, on the ogbl-wikikg2 dataset. Especially, the parameters of our model (19.2M) are about half of TripleREv3 (36.4M). The experimental results show that our proposed method can improve the model performance effectively with fewer parameters. Besides, we also construct the 38.4M TranS (large) model, the best score of which can reach 0.7101 (validation set) and 0.6992 (test set) on MRR.

4 Conclusion

In this paper, we propose a novel transition-based knowledge graph embedding model, TranS, to solve the issues of complex relations, especially the situation of same entity pair with different relations. TranS replaces tradition scoring pattern with synthetic relation pattern. And the final relation representation is the sum of different relation vectors. Experiments on the ogbl-wikikg2 dataset show that our model achieves state-of-the-art results.

References

- Kurt Bollacker, Colin Evans, Praveen Paritosh, Tim Sturge, and Jamie Taylor. 2008. Freebase: a collaboratively created graph database for structuring human knowledge. In *Proceedings of the 2008 ACM SIGMOD international conference on Management of data*, pages 1247–1250.
- Antoine Bordes, Xavier Glorot, Jason Weston, and Yoshua Bengio. 2014. A semantic matching energy function for learning with multi-relational data. *Mach. Learn.*, 94(2):233–259.
- Antoine Bordes, Nicolas Usunier, Alberto García-Durán, Jason Weston, and Oksana Yakhnenko. 2013. Translating embeddings for modeling multi-relational data. *Advances in neural information processing systems*, 26.
- Linlin Chao, Jianshan He, Taifeng Wang, and Wei Chu. 2020. Pairre: Knowledge graph embeddings via paired relation vectors. *arXiv preprint arXiv:2011.03798*.
- Yihong Chen, Pasquale Minervini, Sebastian Riedel, and Pontus Stenetorp. 2021. Relation prediction as an auxiliary training objective for improving multi-relational graph representations. In *3rd Conference on Automated Knowledge Base Construction*.
- Miao Fan, Qiang Zhou, Emily Chang, and Fang Zheng. 2014. Transition-based knowledge graph embedding with relational mapping properties. In *Proceedings of the 28th Pacific Asia conference on language, information and computing*, pages 328–337.
- Mikhail Galkin, Jiapeng Wu, Etienne Denis, and William L Hamilton. 2021. Nodepiece: Compositional and parameter-efficient representations of large knowledge graphs. *arXiv preprint arXiv:2106.12144*.
- Alberto García-Durán, Antoine Bordes, and Nicolas Usunier. 2014. Effective blending of two and three-way interactions for modeling multi-relational data. In *Proceedings of the 2014th European Conference on Machine Learning and Knowledge Discovery in Databases - Volume Part I*, ECMLPKDD’14, page 434–449, Berlin, Heidelberg. Springer-Verlag.
- Justin Gilmer, Samuel S. Schoenholz, Patrick F. Riley, Oriol Vinyals, and George E. Dahl. 2017. Neural message passing for quantum chemistry. In *Proceedings of the 34th International Conference on Machine Learning - Volume 70*, ICML’17, page 1263–1272. JMLR.org.
- Weihua Hu, Matthias Fey, Marinka Zitnik, Yuxiao Dong, Hongyu Ren, Bowen Liu, Michele Catasta, and Jure Leskovec. 2020. Open graph benchmark: Datasets for machine learning on graphs. *arXiv preprint arXiv:2005.00687*.
- Guoliang Ji, Shizhu He, Liheng Xu, Kang Liu, and Jun Zhao. 2015. Knowledge graph embedding via dynamic mapping matrix. In *Proceedings of the 53rd annual meeting of the association for computational linguistics and the 7th international joint conference on natural language processing (volume 1: Long papers)*, pages 687–696.
- Guoliang Ji, Kang Liu, Shizhu He, and Jun Zhao. 2016. Knowledge graph completion with adaptive sparse transfer matrix. In *Thirtieth AAAI conference on artificial intelligence*.
- Diederik P Kingma and Jimmy Ba. 2014. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*.
- Yujia Li, Richard Zemel, Marc Brockschmidt, and Daniel Tarlow. 2016. Gated graph sequence neural networks. In *Proceedings of ICLR’16*.
- Yankai Lin, Zhiyuan Liu, Maosong Sun, Yang Liu, and Xuan Zhu. 2015. Learning entity and relation embeddings for knowledge graph completion. In *Twenty-ninth AAAI conference on artificial intelligence*.
- Quan Liu, Hui Jiang, Zhen-Hua Ling, Si Wei, and Yu Hu. 2016. Probabilistic reasoning via deep learning: Neural association models. *CoRR*, abs/1603.07704.
- Maximilian Nickel, Lorenzo Rosasco, and Tomaso Poggio. 2016. Holographic embeddings of knowledge graphs. In *Proceedings of the Thirtieth AAAI Conference on Artificial Intelligence*, AAAI’16, page 1955–1961. AAAI Press.
- Maximilian Nickel, Volker Tresp, and Hans-Peter Kriegel. 2011. A three-way model for collective learning on multi-relational data. In *Proceedings of the 28th International Conference on International Conference on Machine Learning*, ICML’11, page 809–816, Madison, WI, USA. Omnipress.
- Wei Qian, Cong Fu, Yu Zhu, Deng Cai, and Xiaofei He. 2018. Translating embeddings for knowledge graph completion with relation attention mechanism. In *IJCAI*, pages 4286–4292.
- Thomas Rebele, Fabian Suchanek, Johannes Hoffart, Joanna Biega, Erdal Kuzey, and Gerhard Weikum. 2016. Yago: A multilingual knowledge base from wikipedia, wordnet, and geonames. In *International semantic web conference*, pages 177–185. Springer.
- Zhiqing Sun, Zhi-Hong Deng, Jian-Yun Nie, and Jian Tang. 2019. Rotate: Knowledge graph embedding by relational rotation in complex space. *arXiv preprint arXiv:1902.10197*.
- Théo Trouillon, Johannes Welbl, Sebastian Riedel, Éric Gaussier, and Guillaume Bouchard. 2016. Complex embeddings for simple link prediction. In *International conference on machine learning*, pages 2071–2080. PMLR.

Denny Vrandečić and Markus Krötzsch. 2014. Wikidata: a free collaborative knowledgebase. *Communications of the ACM*, 57(10):78–85.

Baoxin Wang, Qingye Meng, Ziyue Wang, Dayong Wu, Wanxiang Che, Shijin Wang, Zhigang Chen, and Cong Liu. 2022. Interht: Knowledge graph embeddings by interaction between head and tail entities. *arXiv preprint arXiv:2202.04897*.

Zhen Wang, Jianwen Zhang, Jianlin Feng, and Zheng Chen. 2014. Knowledge graph embedding by translating on hyperplanes. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 28.

Qizhe Xie, Xuezhe Ma, Zihang Dai, and Eduard Hovy. 2017. An interpretable knowledge transfer model for knowledge base completion. *arXiv preprint arXiv:1704.05908*.

Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. 2019. **How powerful are graph neural networks?** In *International Conference on Learning Representations*.

Bishan Yang, Wen-tau Yih, Xiaodong He, Jianfeng Gao, and Li Deng. 2014. Embedding entities and relations for learning and inference in knowledge bases. *arXiv preprint arXiv:1412.6575*.

Long Yu, ZhiCong Luo, Deng Lin, HuanYong Liu, and YaFeng Deng. 2021. Triplere: Knowledge graph embeddings via triple relation vectors. *viXra preprint viXra:2112.0095*.