

Relatório de Inteligência - RIT-001

Lumma Stealer Analysis

João Pedro Rosa Cezarino

September 10, 2025



**Threat
Intelligence**

Summary

1	Introdução	2
2	Sumário	3
3	Pontos Chave	4
4	Detalhes da Ameaça	5
5	Capabilities, Adversary Infrastructure & Victim	6
6	Perfil da Ameaça	7
7	Modus Operandi	8
8	Análise do Hash Encontrado	9
9	Vítimas	10
10	Recomendações	11
11	Conclusão	12
12	Diamond Model	13
13	Técnicas, Táticas e Procedimentos (TTPs)	14
14	Artifacts	15
14.0.1	Endpoint Artifacts	15
14.0.2	Network Artifacts	15
14.0.3	Malware Hashes	16
14.0.4	Vulnerabilities	16
14.0.5	Detection & Response	17
15	Referências	21

1 Introdução

- **Report ID:** RIT-001
- **Date:** 09/09/2025
- **Prioridade:** High
- **Autor:** João Pedro Rosa Cezarino
- **Título:** Lumma Stealer Analysis
- **Nível de Confiabilidade:** B2 - Usually reliable and Probably true.
- **Information Sensitivity:** TLP:GREEN

Este Relatório de Inteligência descreve as principais informações e atualizações sobre a ameaça Lumma Stealer e tem como objetivo auxiliar na tomada de decisão dos riscos cibernéticos.

2 Sumário

O Lumma Stealer, também conhecido como LummaC2, é um malware do tipo Infostealer, identificado desde 2022, que opera sob um modelo de Malware-as-a-Service (MaaS). Desde Janeiro deste ano, observou-se um crescimento exponencial e uma sofisticação operacional, tornando-o um dos infostealers mais dominantes no mercado.

A relevância deste relatório reside na necessidade de compreender as diversas Táticas, Técnicas e Procedimentos (TTPs) empregadas pelo Lumma Stealer, que incluem o uso de sites falsos de CAPTCHA, malvertising, e a exploração de plataformas legítimas para distribuição. Tornando-o um risco persistente para organizações em todos os Setores.

Suas capacidades visam o roubo de credenciais de navegadores, carteiras de criptomoeda e outros dados sensíveis e, portanto, a análise aprofundada da cadeia de infecção deste malware é crucial para fortalecer as defesas e proteger as organizações contra esta ameaça.

3 Pontos Chave

- **Browser Credentials:** Usernames, passwords, cookies, and autofill data from over 10 major web browsers.
- **Cryptocurrency Wallets:** Data from numerous cryptocurrency wallet applications and browser extensions.
- **Two-Factor Authentication (2FA) Tokens:** Information from 2FA extensions, potentially allowing attackers to bypass multi-factor authentication.
- **System Information:** Detailed information about the compromised machine, including hardware, OS version, and IP address.
- **Application Data:** Credentials and data from various applications, including FTP clients and messaging apps like Telegram.

4 Detalhes da Ameaça

The primary function of Lumma Stealer is to harvest and exfiltrate a wide variety of sensitive data from victim machines. The malware is written in C and is continuously updated with advanced features to evade detection and maximize data theft. Its MaaS model allows affiliates to customize and deploy the malware easily. The primary types of data targeted include:

- **Browser Credentials:** Usernames, passwords, cookies, and autofill data from over 10 major web browsers.
- **Cryptocurrency Wallets:** Data from numerous cryptocurrency wallet applications and browser extensions.
- **Two-Factor Authentication (2FA) Tokens:** Information from 2FA extensions, potentially allowing attackers to bypass multi-factor authentication.
- **System Information:** Detailed information about the compromised machine, including hardware, OS version, and IP address.
- **Application Data:** Credentials and data from various applications, including FTP clients and messaging apps like Telegram.

The malware employs a multi-stage, often fileless, execution chain using obfuscated PowerShell scripts and Living Off the Land Binaries (LOLBINS) like `mshta.exe` to evade detection. A particularly effective delivery method is the “Click-Fix” technique, where victims are tricked by fake CAPTCHA pages into pasting and executing malicious commands in the Windows Run dialog, bypassing browser-based security controls. Data is exfiltrated via HTTP POST requests to a resilient and frequently changing Command and Control (C2) infrastructure.

5 Capabilities, Adversary Infrastructure & Victim

- Credential harvesting (browsers, crypto wallets, extensions)
- System reconnaissance (hostname, hardware ID, geolocation)
- Exfiltration via Telegram bots & C2 servers
- MaaS infrastructure with tiered subscription models

6 Perfil da Ameaça

The threat actor “Shamel” (also known as “Lumma”) is a Russian-speaking developer responsible for creating and maintaining the Lumma Stealer. The malware has been advertised on Russian-language underground forums since August 2022. Shamel operates a Malware-as-a-Service (MaaS) business, selling subscriptions to the stealer via Telegram and a dedicated website. This model allows a broad range of cybercriminals, from low-skilled individuals to sophisticated groups like the ransomware operator Octo Tempest, to use the malware for initial access and data theft. Subscription tiers range from approximately \$250 per month to \$20,000 for access to the source code, making it a commercially successful and widely distributed threat.

7 Modus Operandi




Figure 1: Lumma stealer infection chain

8 Análise do Hash Encontrado

65eb366739361b97fb68c0ac4b9fbaad2ac26e0c30a21ef0ad0a756177e22e94

9 Vítimas

O grupo RansomHouse tem como alvo principal países como Estados Unidos, Europa e Ásia. Os 10 principais setores mais afetados pelo RansomHouse de 1º de janeiro de 2023 a 22 de maio de 2024 foram os setores: farmacêuticos, tecnológicos, assistência médica, serviços de suporte empresarial e aeroespacial.

10 Recomendações

1. **User Awareness Training:** Educate employees to recognize phishing, malvertising, and social engineering tactics like the “ClickFix” fake CAPTCHA. Emphasize caution against downloading software from untrusted sources or executing commands from websites.
2. **Endpoint Detection and Response (EDR):** Deploy and configure an EDR solution to monitor for anomalous process behavior, such as mshta.exe spawning PowerShell, or unauthorized processes accessing browser credential stores.
3. **Restrict Script Execution:** Use application control policies to restrict the execution of PowerShell and other scripting languages for users who do not require them for their job functions.
4. **Network Filtering:** Block connections to known malicious domains and newly registered domains (NRDs), which are frequently used for C2 infrastructure. Use DNS filtering and web gateways to prevent access to malware distribution sites.
5. **Credential Hygiene:** Encourage the use of password managers instead of saving credentials in browsers. Enforce Multi-Factor Authentication (MFA) across all critical services to mitigate the impact of stolen credentials.
6. **Regular Software Updates:** Keep operating systems, browsers, and other software patched and up-to-date to protect against vulnerabilities that could be exploited in multi-stage attacks.

11 Conclusão

The Lumma Stealer represents a mature and resilient threat within the cybercrime ecosystem, amplified by its accessible MaaS model. Its reliance on sophisticated social engineering and evasive execution techniques makes it a danger that bypasses traditional signature-based defenses. Organizations must adopt a multi-layered security posture that combines advanced technical controls with robust user education to effectively mitigate the risk of credential theft and subsequent network compromise.

12 Diamond Model




Figure 2: Lumma stealer infection chain

13 Técnicas, Táticas e Procedimentos (TTPs)

Kill Chain Stage	Tactic	Technique	Procedure (Concise)	D3FEND
S1 Reconnaissance	-	-	Identificação de softwares/temas populares para atrair vítimas	-
S2 Weaponization	-	-	Afiliado empacota carga Lumma usando crypters	-
S3 Delivery	Initial Access	Phishing (T1566.002)	Links maliciosos via e-mail, malvertising, YouTube, GitHub	D3-URLA
S4 Exploitation	Initial Access	User Execution (T1204.002)	Execução de arquivo malicioso ou ClickFix	D3-EFA
S5 Installation	Execution	PowerShell (T1059.001), Mshta (T1218.005)	Scripts ofuscados e LOLBIN mshta.exe	D3-PSA / D3-LONA
S6 C2	C2	Web Protocols (T1071.001)	Comunicação com servidor C2 via HTTP/HTTPS POST	D3-OTF
S7 Actions on Obj.	Credential Access	Browser Creds (T1555.003)	Roubo de cookies e senhas de navegadores	D3-FPA

14 Artifacts

14.0.1 Endpoint Artifacts

Type	Description	Tactic
Registry Key	HKCU\Software\Microsoft\Windows\CurrentVersion\Run [T1547.001] [67]	Persistence
File Drop	%AppData%\Roaming\lumma\ [67]	Execution, Persistence [T1059]
File Drop	Arquivos .accde, .bat, .a3x no %AppData%\Local\Temp\ [68-71]	Execution, Defense Evasion [T1059, T1027]
Process Injection	Injeção em msbuild.exe, regasm.exe, regsvcs.exe, explorer.exe [40]	Defense Evasion [T1055]

14.0.2 Network Artifacts

Type	Description	Kill Chain Stage
HTTP POST	Exfiltração de dados para C2 com URIs como /c2sock e User-Agent TeslaBrowser/5.5 [44, 67]	C2, Exfiltration [T1041, T1071.001]
Telegram API	Bot usado para uploads de credenciais [43, 67]	C2 [T1102.002]
C2 URLs (Exemplos)	hxxps://payment-confirmation.82736[.]store/pgg46, hxxps://booking[.]procedeed-verific[.]com/goo_pdf [72] hxxps://h3.errantrefrainundocked.shop/riii2.aspx [33] hxxps://dogalmedical[.]org, hxxps://t[.]me/lolypop343 [73]	C2 [T1071.001]

14.0.3 Malware Hashes

Type	File Hash	Description	Kill Chain Stage
SHA256	65eb366739361b97fb689a440fb62ac26e0c30a21ef0ad0a756177e22e94	Installation, C2 (Exemplo Lumma Stealer v4) [67]	
SHA256	7b3bd767ff532b3593	Installation, C2 (Exemplo Lumma Stealer) [74]	a6494257d
SHA1	e32145901e539b4d33221e448511536f521ce5	Delivery (Arquivo Compactado de campanha Forcepoint) [73]	
SHA1	ec69088d1409444de6	Installation (Payload EXE de campanha Forcepoint) [73]	
SHA1	2c8ec98431a788f18f18657d742deb741a927b3	Delivery (Script AutoIT .a3x de campanha Forcepoint) [73]	

14.0.4 Vulnerabilities

CVE #	CVSS Score	Patch Available (Y/N)	Remediation	Date Reported	Patch Applied (Y/N/N/A)
CVE-2017-11882	7.8	S	Aplicar patch Microsoft Office KB2553204 [67]	2017-11-15	N/A

CVE #	CVSS Score	Patch Available (Y/N)	Remediation	Date Reported	Patch Applied (Y/N/N/A)
CVE-2021-40444	8.8	S	Bloquear controles ActiveX, aplicar patch MS [67]	2021-09-07	N/A

14.0.5 Detection & Response

Tactic (MITRE ATT&CK)	Technique (MITRE ATT&CK)	D3FEND Procedure Control	Rule / Query Name	Type	Description	Reference
Credential Access [TA0006]	T1555.003 Coleta de credenciais de navegadores Web Browsers	Credential Hardening [D3-CH]	Lumma_Browser_Signer_IOC [75]	Sigma	Detecta acesso anormal a arquivos de navegador [75]	MITRE ATT&CK
Persistence [TA0003]	T1547.00 Registry Run Keys / Startup Folder	Persistência via chave de registro Run [75]	Lumma_F Registry Monitoring [D3-RM]	Sigma	Alerta quando uma chave Run suspeita é criada [75]	Sysmon Logs
Exfiltration [TA0010]	T1041: Exfiltração via C2 HTTPS Over C2 Channel	Exfiltração via C2 HTTPS [75]	Lumma_HTTPS_Exfil [75]	Sigma	Detecta exfiltração anômala POST HTTPS [75]	Suricata Rule

Tactic (MITRE ATT&CK)	Technique (MITRE ATT&CK)	Procedure	D3FEND Control	Rule / Query Name	Type	Description	Reference
Execution [TA0002]	T1059.00 Power-Shell	Execução de co- mandos Power-Shell ofusca- dos [33]	Script Analysis [D3-SA]	Suspicious Power-Shell com- mand line [57]	EDR Alert	Detecta coman- dos Power-Shell sus- peitos ou codi- ficados	Microsoft De- fender for End- point [57]
Defense Evasion [TA0005]	T1027.001 Binary Padding	Aumento do tamanho do binário para evasão [38]	Executable Code Analysis [D3- ECA]	Larger Lum- maS- tealer Sam- ples [34]	Behavioral	Detecta exe- cutáveis Lumma incomu- mente grandes	G DATA [34]
Defense Evasion [TA0005]	T1027.01 Com- mand Obfus- cation	Ofuscação de co- mandos Power- Shell [33]	Script Analysis [D3-SA]	Trojan:Po [76]	Antivirus	Detecção de co- mandos Power- Shell ofusca- dos	Microsoft De- fender An- tivirus [76]
Defense Evasion [TA0005]	T1055: Process Injec- tion	Injeção de código mali- cioso em pro- cessos legíti- mos [40]	Process Self- Modification Preven- tion [D3- PSMP]	Process hollow- ing de- tected [57]	EDR Alert	Detecta esvazia- mento de pro- cesso e injeção de código	Microsoft De- fender for End- point [57]

Tactic (MITRE ATT&CK)	Technique (MITRE ATT&CK)	Procedure	D3FEND Control	Rule / Query Name	Type	Description	Reference
Collection [TA0009]	T1115: Clipboard Data	Cópia de comandos maliciosos para a área de transferência [35, 50]	Clipboard Data Monitoring [D3-CDM]	ClickFix com-mands execution [77]	Query	Identificação de comandos ClickFix a partir do registro Run-MRU	Microsoft Defender XDR [77]
Command and Control [TA0011]	T1071.001 Web Protocols	Comunicação C2 via HTTP/HTTPS para domínios específicos [31, 43, 44]	Traffic Filtering [D3-TF]	Suspicious Connection to TLDs or Steam-community API [63]	Sigma	Detecta conexões de rede para TLDs suspeitos e Steam-community.com	WithSecure™ Labs [63]
Command and Control [TA0011]	T1071.00 Web Protocols	Comunicação inicial C2 via POST request [78]	Traffic Filtering [D3-TF]	Lumma Stealer - Possible egress POST request [78]	Sigma	Detecta solicitações POST iniciais com User Agent e URI específicos	WithSecure™ Labs [78]

Tactic (MITRE ATT&CK)	Technique (MITRE ATT&CK)	Procedure	D3FEND Control	Rule / Query Name	Type	Description	Reference
Defense Evasion [TA0005]	T1027: Obfus- cated Files or Informa- tion	Uso de ofus- cação de fluxo de controle indireto (Indi- rect Control Flow) [39]	Executable Code Analysis [D3- ECA]	Win32.Trojan- Stealer.Lumma (genérico) [74]	Antivirus LummaStealer	Detecção baseada em car- acterís- ticas de ofus- cação do Lumma	G DATA [74]
Defense Evasion [TA0005]	T1027: Obfus- cated Files or Informa- tion	Bypass AMSI para evitar varredura de payload [41]	Executab Code Analysis [D3- ECA]	Behavior: [76]	Antivirus	Detecção de compor- tamento de bypass AMSI	Microsoft De- fender An- tivirus [76]

15 Referências

1. Forcepoint. [Unmasking the Lumma Stealer Campaign](#). Acessado em 10 de setembro de 2025.
2. Netskope. [Lumma Stealer: Fake CAPTCHAs & New Techniques to Evade Detection](#).
3. Netskope Threat Labs. [LummaStealer IOCs](#).
4. Microsoft Security. [Lumma Stealer: Breaking down the delivery techniques and capabilities of a prolific infostealer](#).
5. Trellix. [A Deep Dive into the Latest Version of Lumma InfoStealer](#).
6. Darktrace. [The Rise of the Lumma Info-Stealer](#).
7. G DATA Software. [LummaStealer: Fake reCAPTCHA leads to info stealer infection](#).
8. WithSecure Labs. [Reverse Engineering a Lumma Infection](#).