BRONZE VALVES

Our bronze valves are manufactured with precision and built for durability, corrosion resistance and dependable performance in demanding industrial applications.

FEATURES

- High quality bronze construction for long service life
- Excellent corrosion and rust resistance
- Smooth operation with tight shut-off
- Suitable for a wide range of industrial media
- Tested for strength, pressure and leakage
- Available in various sizes and end connections

APPLICATIONS

- Water & Waste Water Treatment
- Oil, Gas & Petrochemical Industries
- Marine & Ship Building
- HVAC & General Industrial Applications



BRONZE GLOBE VALVES

- Durable bronze body
- Accurate flow regulation
- Reliable and leak-proof performance
- Ideal for throttling and stopping flow

Size Range	1/4" to 4"
Pressure Rating	PN 10 / PN 16
End Connection	Screwed (BSP / NPT), Flanged
Working Temp.	-10°C to 180°C
Suitable Media	Water, Oil, Gas, Air, Steam



BRONZE BALL VALVES

- Full port for maximum flow
- Quarter turn operation
- Strong, compact and leak-tight
- Suitable for on/off applications

Size Range	1/4" to 4"
Pressure Rating	PN 20 / 600 WOG
End Connection	Screwed (BSP / NPT)
Working Temp.	-10°C to 180°C
Suitable Media	Water, Oil, Gas, Air, Steam



BRONZE GATE VALVES

- Rising stem for easy operation
- Tight shut-off performance
- Robust construction
- Ideal for isolation applications

Size Range	1/2" to 4"
Pressure Rating	PN 10 / PN 16
End Connection	Screwed (BSP / NPT), Flanged
Working Temp.	-10°C to 180°C
Suitable Media	Water, Oil, Gas, Air, Steam

INDUSTRIAL VALVES

Our range of industrial valves is engineered to deliver reliable performance, tight shut-off and long service life in a wide range of demanding industrial applications.

FEATURES

- Robust construction for long service life
- Precision machining for leak-proof performance
- Compact design for easy installation
- Tested for strength and reliability
- Suitable for a wide range of industrial media

APPLICATIONS

- Water & Waste Water Treatment
- Oil, Gas & Petrochemical Industries
- Marine & Ship Building
- HVAC & General Industrial Applications
- Steam & Thermal Applications

DUCTILE IRON GATE VALVE



- Rising stem design
- Tight shut-off
- Low flow resistance
- Suitable for water and general applications

Size Range	½" to 12"
Pressure Rating	PN 10 / PN 16
End Connection	Flanged (BS EN 1092-2)
Working Temp.	-10°C to 120°C
Suitable Media	Water, Air, Non aggressive liquids

BUTTERFLY VALVE WAFER TYPE



- Lightweight design
- Quick 90° operation
- Bubble tight shut-off
- Ideal for water, HVAC & industrial use

Size Range	2" to 12"
Pressure Rating	PN 10 / PN 16
End Connection	Wafer (Between Flanges)
Working Temp.	-10°C to 110°C
Suitable Media	Water, Air, Gas, Mild Chemicals



STAINLESS STEEL SWING CHECK VALVE

- Automatic operation
- Prevent backflow
- Strong and durable construction
- Low pressure drop

Size Range	½" to 8"
Pressure Rating	PN 16
End Connection	Flanged (BS EN 1092-2)
Working Temp.	-20°C to 180°C
Suitable Media	Water, Oil, Gas, Chemicals

BRASS BALL VALVE



- Full port for maximum flow
- Quarter turn operation
- Leak-proof performance
- Ideal for water, air and gas

Size Range	½" to 4"
Pressure Rating	PN 25
End Connection	Screwed (BSP / NPT)
Working Temp.	-10°C to 120°C
Suitable Media	Water, Air, Gas, Oil

BRONZE SAFETY VALVE



- Protects system from overpressure
- Precision set pressure
- Reliable and durable
- Suitable for steam, air and gases

Size Range	½" to 2"
Pressure Rating	Up to 16 Bar
End Connection	Screwed (BSP / NPT)
Working Temp.	-10°C to 200°C
Suitable Media	Steam, Air, Gas

INDUSTRIAL VALVES & ACCESSORIES

A comprehensive range of industrial valves and accessories designed for efficient flow control and reliable performance in various industrial applications.

FEATURES

- Wide range for diverse industrial applications
- Reliable performance in demanding conditions
- Easy installation and maintenance
- Suitable for various fluids and gases
- Available in multiple materials and sizes

APPLICATIONS

- Water & Waste Water Treatment
- Oil, Gas & Petrochemical Industries
- Marine & Ship Building
- HVAC & General Industrial Applications
- Pumping & Pipeline Systems
- Power Plants
- Food & Beverage Industries

GLOBE VALVE



- Precise flow regulation
- Throttling service
- Leak-proof performance
- Long service life

Size Range	½" to 12"
Pressure Rating	PN 16 / PN 25
End Connection	Flanged (BS EN 1092-2)
Material	SS 304 / SS 316 / CI
Application	Water, Oil, Steam, Gas

DIAPHRAGM VALVE



- Tight shut-off
- Corrosion resistant
- Suitable for slurry service
- Low maintenance

Size Range	½" to 8"
Pressure Rating	PN 10 / PN 16
End Connection	Flanged (BS EN 1092-2)
Material	CI / DI / PP
Application	Water, Chemicals, Slurry, Acid

NEEDLE VALVE



- Accurate flow control
- High pressure resistance
- Compact design
- Leak-tight shut-off

Size Range	1/8" to 1"
Pressure Rating	Up to 6000 PSI
End Connection	Threaded (BSP / NPT)
Material	SS 304 / SS 316
Application	Oil, Gas, Instrumentation, Hydraulic

BALL VALVE (FLANGED)



- Full bore design
- Bubble tight shut-off
- Low torque operation
- Suitable for high pressure

Size Range	½" to 12"
Pressure Rating	PN 16 / PN 40
End Connection	Flanged (BS EN 1092-2)
Material	CS / SS 304 / SS 316
Application	Water, Oil, Gas, Steam

BALL VALVE (THREADED)



- Compact design
- Easy installation
- Leak-proof performance
- Suitable for various media

Size Range	½" to 4"
Pressure Rating	Up to 1000 PSI
End Connection	Threaded (BSP / NPT)
Material	CS / SS 304 / SS 316
Application	Water, Oil, Gas, Air

CHECK VALVE (SWING)



- Automatic operation
- Prevent backflow
- Low pressure drop
- Durable construction

Size Range	½" to 12"
Pressure Rating	PN 16 / PN 25
End Connection	Flanged (BS EN 1092-2)
Material	CI / DI / SS 304 / SS 316
Application	Water, Oil, Gas, Steam

CHECK VALVE (LIFT)



- Compact and robust
- Threaded connection
- Prevent backflow
- Long service life

Size Range	½" to 2"
Pressure Rating	Up to 2000 PSI
End Connection	Threaded (BSP / NPT)
Material	SS 304 / SS 316
Application	Water, Oil, Gas, Air

PRESSURE REDUCING VALVE



- Maintains downstream pressure
- Protects system components
- Stable performance
- Easy adjustment

Size Range	½" to 2"
Pressure Rating	Up to 16 Bar
End Connection	Threaded (BSP / NPT)
Material	SS 304 / SS 316
Application	Water, Air, Gas, Oil

SAFETY RELIEF VALVE



- Protects system from overpressure
- Automatic operation
- High discharge capacity
- Reliable performance

Size Range	½" to 2"
Pressure Rating	Up to 40 Bar
End Connection	Flanged / Threaded
Material	CI / CS / SS 304 / SS 316
Application	Steam, Air, Gas, Liquid