INDUSTRIAL ACCESSORIES & GAUGES

A wide range of industrial accessories and pressure gauges designed for accurate measurement, secure connections and efficient operation in all types of industrial systems.

FEATURES

- Accurate and reliable performance
- Wide selection for multiple applications
- Easy installation and maintenance
- Suitable for various industrial environments
- Available in different materials and sizes

APPLICATIONS

- Water & Waste Water Treatment
- Oil, Gas & Petrochemical Industries
- Marine & Ship Building
- HVAC & General Industrial Applications
- Pumping & Pipeline Systems
- Power Plants
- Food & Beverage Industries

BOURDON TUBE PRESSURE GAUGE



Dial Size	1½" / 2" / 2½" / 4"
Connection	1/8" / 1/4" BSP / NPT
Range	0 to 10000 PSI
Accuracy	±1.6% F.S.D.
Application	Water, Oil, Gas, Air, Steam

GLYCERINE FILLED PRESSURE GAUGE



Dial Size	2" / 2½" / 4"
Connection	1/4" BSP / NPT
Range	0 to 6000 PSI
Accuracy	±1.6% F.S.D.
Application	Hydraulic, Oil, Gas, Vibration Areas

COMPOUND GAUGE



Dial Size	2" / 2½" / 4"
Connection	1/4" BSP / NPT
Range	-1 to 15 Bar
Accuracy	±1.6% F.S.D.
Application	Vacuum, Compressor, Pumps

DIGITAL PRESSURE GAUGE



Dial Size	2½" / 4"
Connection	1/4" BSP / NPT
Range	0 to 10000 PSI
Accuracy	±0.5% F.S.D.
Application	High Accuracy Measurement

HOSE PIPE



Size Range	1/4" to 2"
Type	R1 / R2 / R3 / R6
Pressure Rating	Up to 6000 PSI
Material	Synthetic Rubber
Application	Hydraulic, Pneumatic, Water, Oil

HOSE ASSEMBLY



Size Range	1/4" to 2"
Type	Hydraulic Hose Assemblies
Pressure Rating	Up to 6000 PSI
End Fittings	BSP / NPT / JIC / ORFS
Application	Hydraulic Systems, Machinery

PIPE NIPPLE (GI)



Size Range	1/8" to 4"
Thread Type	BSP / NPT
Material	Galvanized Iron
Pressure Rating	Up to 150 PSI
Application	Water, Air, Gas, Oil

PIPE CAP (GI)



Size Range	1/8" to 4"
Thread Type	BSP / NPT
Material	Galvanized Iron
Pressure Rating	Up to 150 PSI
Application	Water, Air, Gas, Oil

HEX PLUG (GI)



Size Range	1/8" to 4"
Thread Type	BSP / NPT
Material	Galvanized Iron
Pressure Rating	Up to 150 PSI
Application	Water, Air, Gas, Oil

REDUCING NIPPLE (GI)



Size Range	1/4" x 1/8" to 4" x 2"
Thread Type	BSP / NPT
Material	Galvanized Iron
Pressure Rating	Up to 150 PSI
Application	Water, Air, Gas, Oil

BUSHING (GI)



Size Range	1/8" x 1/4" to 4" x 3"
Thread Type	BSP / NPT
Material	Galvanized Iron
Pressure Rating	Up to 150 PSI
Application	Water, Air, Gas, Oil

HEX ADAPTOR (SS)



Size Range	1/8" to 2"
Thread Type	BSP / NPT
Material	SS 304 / SS 316
Pressure Rating	Up to 3000 PSI
Application	Water, Oil, Gas, Chemicals

INSTRUMENTATION & PROCESS CONTROL SOLUTIONS

A comprehensive range of instrumentation and process control components designed for accurate monitoring, measurement and control in industrial systems.

FEATURES

- Accurate & reliable performance
- Durable construction for industrial use
- Wide range of models and configurations
- Corrosion resistant materials
- Easy installation and maintenance
- Suitable for various industrial applications

APPLICATIONS

- Process Industries
- Chemical & Petrochemical
- Power Plants
- Water & Waste Water Treatment
- Oil & Gas / Refineries
- HVAC & Building Services

THERMOWELL (BAR STOCK TYPE)



- Protects temperature sensor
- Withstands high pressure
- Corrosion resistant
- Various flange & thread options

Size Range	1/2" to 2"
Material	SS 304 / SS 316
Connection	Threaded / Flanged
Pressure Rating	Up to 2500 PSI
Application	Temperature Measurement

MAGNETIC FLOW METER



- No moving parts
- High accuracy
- Wide turndown ratio
- Suitable for conductive liquids

Size Range	15 mm to 3000 mm
Accuracy	±0.5% of reading
Material	SS 316 / Lined
Connection	Flanged
Application	Water, Effluent, Chemicals

ROTAMETER (VARIABLE AREA FLOW METER)



- Direct reading flow rate
- Simple design
- Low pressure drop
- Easy to install

Size Range	15 NB to 100 NB
Material	SS 304 / Acrylic
Connection	Threaded / Flanged
Pressure Rating	Up to 10 Bar
Application	Water, Air, Gas

SIGHT FLOW INDICATOR



- Visual flow indication
- Rugged & reliable
- Compact design
- Low maintenance

Size Range	15 NB to 150 NB
Material	CI / CS / SS 304
Connection	Flanged
Pressure Rating	Up to 16 Bar
Application	Liquids in Pipelines

PULSATION DAMPENER



- Absorbs pressure pulsations
- Protects system components
- Extends equipment life
- Different material options

Size Range	1/2" to 2"
Material	SS / Rubber / PP
Connection	Threaded
Pressure Rating	Up to 250 Bar
Application	Pumps, Dosing Systems

PRESSURE SNUBBER



- Protects gauge from surges
- Reduces pressure spikes
- Compact & durable
- Easy installation

Size Range	1/4" to 1/2"
Material	SS 316
Connection	Threaded
Pressure Rating	Up to 6000 PSI
Application	Pressure Gauges, Hydraulic Systems

SYPHON TUBE



- Protects gauge from heat
- Allows condensation
- Various configurations
- Durable construction

Size Range	1/4" to 1"
Material	SS 304 / SS 316
Connection	Threaded
Pressure Rating	Up to 400 Bar
Application	Steam, Hot Oil, Hot Water

GAUGE COCK



- Isolates pressure gauges
- Smooth operation
- Leak tight shut-off
- Compact design

Size Range	1/4" to 1/2"
Material	Brass / SS 316
Connection	Threaded
Pressure Rating	Up to 6000 PSI
Application	Gauge Isolation

NEEDLE MANIFOLD VALVE (2 VALVE)



- Precise flow control
- Compact manifold design
- High pressure capability
- Stainless steel construction

Connection	1/2" NPT (F)
Material	SS 316
Pressure Rating	Up to 6000 PSI
Configuration	2 Valve Manifold
Application	Differential Pressure Transmitters

AIR HEADER (DISTRIBUTION MANIFOLD)



- Distributes compressed air
- Reduces pressure drops
- Custom port configurations
- Heavy duty construction

Size Range	1/2" to 2"
Material	CS / SS 304
Connection	Threaded
Pressure Rating	Up to 16 Bar
Application	Compressed Air Systems

CONDENSATE POT



- Collects steam condensate
- Improves steam efficiency
- Robust cast construction
- Easy maintenance

Size Range	1/2" to 2"
Material	Cast Iron / CS
Connection	Threaded
Pressure Rating	Up to 16 Bar
Application	Steam Lines

RTD TEMPERATURE SENSOR



- Accurate temperature sensing
- Pt100 / Pt1000 options
- Various probe lengths
- With protection tube

Type	Pt100 / Pt1000
Material	SS 304 / SS 316
Connection	Threaded / Flanged
Temperature Range	-50°C to 400°C
Application	Temperature Measurement