PIPE FITTINGS & ACCESSORIES

A comprehensive range of pipe fittings and accessories designed for secure connections, leak-proof performance and long service life in industrial applications.

FEATURES

- Corrosion resistant materials
- Precision manufacturing for perfect fit
- Leak-proof and reliable performance
- Wide range of sizes and connections
- Suitable for various industrial applications

APPLICATIONS

- Water & Waste Water Treatment
- Oil, Gas & Petrochemical Industries
- Marine & Ship Building
- HVAC & General Industrial Applications
- Pumping & Pipeline Systems
- Food & Beverage Industries

STAINLESS STEEL 90° ELBOW



- Smooth finish
- Corrosion resistant
- High strength
- Long service life

Size Range	1/8" to 4"
Thread Type	BSP / NPT
Material	SS 304 / 316
Pressure Rating	Up to 3000 PSI
Application	Water, Oil, Gas, Chemicals

STAINLESS STEEL TEE



- Strong and durable
- Leak-proof connection
- Excellent corrosion resistance

Size Range	1/8" to 4"
Thread Type	BSP / NPT
Material	SS 304 / 316
Pressure Rating	Up to 3000 PSI
Application	Water, Oil, Gas, Chemicals

GI PIPE COUPLING



- Galvanized finish
- Durable & reliable
- For joining two pipes

Size Range	1/8" to 6"
Thread Type	BSP / NPT
Material	Galvanized Iron
Pressure Rating	Up to 150 PSI
Application	Water, Air, General Service

BRASS UNION



- Easy installation
- Strong & leak-proof
- Corrosion resistant

Size Range	1/8" to 4"
Thread Type	BSP / NPT
Material	Brass
Pressure Rating	Up to 600 PSI
Application	Water, Oil, Gas, Air

PRESSURE GAUGE



- Accurate pressure measurement
- Sturdy SS case
- AISI 316 wetted parts
- Dual scale (psi & bar)

Dial Size	1½" / 2" / 2½" / 4"
Connection	1/8" / 1/4" BSP / NPT
Material	SS 304 / SS 316
Pressure Rating	0 to 10000 PSI
Application	Water, Oil, Gas, Air, Steam

HOSE CONNECTOR (SS)



- Strong & durable
- Corrosion resistant
- Secure hose connection
- Easy to install

Size Range	1/4" to 2"
Thread Type	BSP / NPT
Material	SS 304 / 316
Pressure Rating	Up to 300 PSI
Application	Water, Air, Chemicals

UNION CONNECTOR (SS)



- Quick installation
- Leak-proof joint
- High pressure resistance

Size Range	1/8" to 4"
Thread Type	BSP / NPT
Material	SS 304 / 316
Pressure Rating	Up to 3000 PSI
Application	Water, Oil, Gas, Chemicals

HEX NIPPLE (SS)



- Hex design for easy tightening
- Leak-proof connection
- Strong & durable

Size Range	1/8" to 4"
Thread Type	BSP / NPT
Material	SS 304 / 316
Pressure Rating	Up to 3000 PSI
Application	Water, Oil, Gas, Air

REDUCING BUSH (GI)



- Reduces pipe size
- Galvanized finish
- Strong & durable
- Corrosion resistant

Size Range	1/4" to 6"
Thread Type	BSP / NPT
Material	Galvanized Iron
Pressure Rating	Up to 150 PSI
Application	Water, Air, General Service

HEX ADAPTOR (SS)



- Male / Female connection
- Precision machined
- Corrosion resistant

Size Range	1/8" to 4"
Thread Type	BSP / NPT
Material	SS 304 / 316
Pressure Rating	Up to 3000 PSI
Application	Water, Oil, Gas, Air

FLANGES & STRAINERS & Y TYPE

A wide range of flanges, strainers and Y type strainers manufactured to international standards for pipeline protection and reliable performance in industrial systems.

FEATURES

- Manufactured to international standards
- Strong and durable construction
- Excellent corrosion resistance
- Easy installation and maintenance
- Suitable for high pressure and temperature

APPLICATIONS

- Water & Waste Water Treatment
- Oil, Gas & Petrochemical Industries
- Marine & Ship Building
- HVAC & General Industrial Applications
- Pumping & Pipeline Systems
- Power Plants
- Food & Beverage Industries

SLIP ON FLANGE



- Easy to install
- Cost effective
- Suitable for low pressure applications

Size Range	½" to 24"
Pressure Rating	Class 150
Standard	ASME B16.5
Material	Carbon Steel
Face Type	RF / FF
Application	Water, Oil, Gas, General Service

WELD NECK FLANGE



- High strength and durability
- Suitable for high pressure and high temperature
- Smooth stress transition

Size Range	½" to 24"
Pressure Rating	Class 150 to 2500
Standard	ASME B16.5
Material	Carbon Steel
Face Type	RF
Application	Oil, Gas, Steam, Petrochemical

BLIND FLANGE



- Used to close the end of a piping system
- Provides easy access for inspection

Size Range	½" to 24"
Pressure Rating	Class 150 to 600
Standard	ASME B16.5
Material	Carbon Steel
Face Type	RF / FF
Application	Water, Oil, Gas, General Service

CAST IRON Y STRAINER



- Removes dirt and solid particles
- Protects valves and equipment
- Easy cover removal for cleaning

Size Range	½" to 12"
Pressure Rating	PN 16
End Connection	Flanged (BS EN 1092-2)
Material	Cast Iron (CI)
Application	Water, Oil, Steam

DUCTILE IRON Y STRAINER



- High strength and long service life
- Efficient filtration performance
- Suitable for high pressure systems

Size Range	½" to 12"
Pressure Rating	PN 16 / PN 25
End Connection	Flanged (BS EN 1092-2)
Material	Ductile Iron (DI)
Application	Water, Oil, Gas

STAINLESS STEEL Y STRAINER



- Corrosion resistant
- Suitable for aggressive media
- Easy installation and cleaning

Size Range	½" to 12"
Pressure Rating	PN 16 / PN 25
End Connection	Flanged (ANSI / BS)
Material	SS 304 / SS 316
Application	Water, Chemicals, Food, Pharma

BASKET STRAINER



- Large filtration area
- High dirt holding capacity
- Ideal for heavy duty applications

Size Range	½" to 12"
Pressure Rating	PN 16
End Connection	Flanged (BS EN 1092-2)
Material	Cast Iron / Ductile Iron
Application	Water, Oil, Steam

SIMPLEX STRAINER



- Compact and rugged design
- Easy maintenance
- Threaded connections

Size Range	¼" to 2"
Pressure Rating	Up to 300 PSI
End Connection	Screwed (BSP / NPT)
Material	SS 304 / CS
Application	Water, Oil, Gas, Air

DOUBLE WINDOW SIGHT FLOW INDICATOR



- Visual flow indication
- Reinforced toughened glass
- Suitable for liquids

Size Range	½" to 6"
Pressure Rating	PN 16
End Connection	Flanged (BS EN 1092-2)
Material	Cast Iron / Ductile Iron
Application	Water, Oil, Chemicals

INDUSTRIAL FITTINGS & ACCESSORIES

A comprehensive range of industrial fittings and accessories designed to ensure secure connections, leak-proof performance and long service life in all types of industrial applications.

FEATURES

- Precision manufacturing for perfect fit
- Leak-proof and reliable performance
- Corrosion resistant materials
- Easy installation and maintenance
- Wide range of sizes and configurations
- Suitable for various industrial applications

APPLICATIONS

- Water & Waste Water Treatment
- Oil, Gas & Petrochemical Industries
- Marine & Ship Building
- HVAC & General Industrial Applications
- Pumping & Pipeline Systems
- Power Plants
- Food & Beverage Industries

HEX NUT



- High strength
- Durable and reliable
- Corrosion resistant
- Precision threads

Size Range	1/8" to 4"
Thread Type	BSP / NPT
Material	SS 304 / SS 316 / GI / MS
Standard	DIN / IS / ANSI
Application	Piping, Machinery, General Use

HEX BOLT



- High tensile strength
- Excellent durability
- Corrosion resistant
- Perfect for heavy duty use

Size Range	1/4" to 2"
Thread Type	BSP / UNC
Material	SS 304 / SS 316 / GI / MS
Standard	DIN / IS / ANSI
Application	Piping, Flange, Machinery

STUD BOLT (ALL THREAD)



- Full thread for strong holding
- High load capacity
- Available in all sizes
- Corrosion resistant

Size Range	1/4" to 4"
Thread Type	BSP / UNC
Material	SS 304 / SS 316 / GI / MS
Standard	DIN / IS / ANSI
Application	Flanges, Machinery, Pipeline

LOCK WASHER



- Prevents loosening
- Vibration resistant
- Reusable
- Corrosion resistant

Size Range	1/8" to 2"
Type	Spring / Split
Material	SS 304 / SS 316 / GI
Standard	DIN 127 / IS 3063
Application	Piping, Machinery, General Use

UNION (MALE-FEMALE)



- Easy assembly & disassembly
- Leak-proof joint
- Strong & durable
- Suitable for high pressure

Size Range	1/8" to 4"
Thread Type	BSP / NPT
Material	SS 304 / SS 316 / GI
Pressure Rating	Up to 3000 PSI
Application	Water, Oil, Gas, Air

REDUCING UNION



- Connects different pipe sizes
- Leak-proof & reliable
- Corrosion resistant
- Easy to install

Size Range	1/8" to 2"
Thread Type	BSP / NPT
Material	SS 304 / SS 316 / GI
Pressure Rating	Up to 3000 PSI
Application	Water, Oil, Gas, Air

HALF COUPLING



- Joins two pipes securely
- High strength
- Corrosion resistant
- Leak-proof connection

Size Range	1/8" to 4"
Thread Type	BSP / NPT
Material	SS 304 / SS 316 / GI
Pressure Rating	Up to 3000 PSI
Application	Piping, Plumbing, Industrial

FULL COUPLING



- Strong & durable
- Perfect alignment
- Corrosion resistant
- Suitable for high pressure

Size Range	1/8" to 4"
Thread Type	BSP / NPT
Material	SS 304 / SS 316 / GI
Pressure Rating	Up to 3000 PSI
Application	Water, Oil, Gas, Air

ROUND BAR (SS)



- High strength
- Corrosion resistant
- Smooth finish
- Available in various sizes

Size Range	6mm to 100mm
Material	SS 304 / SS 316
Standard	ASTM / AISI
Length	3 Meter / 6 Meter
Application	Fabrication, Machinery, Industrial Use

THREADED PIPE NIPPLE (BSP)



- Precision threads
- Leak-proof connection
- Strong & durable
- Corrosion resistant

Size Range	1/8" to 4"
Thread Type	BSP (Male)
Material	SS 304 / SS 316 / GI
Pressure Rating	Up to 3000 PSI
Application	Piping, Plumbing, Industrial

LONG PIPE NIPPLE (BSP)



- Extra length for deep connections
- Strong & durable
- Corrosion resistant
- High pressure resistance

Size Range	1/8" to 4"
Thread Type	BSP (Male)
Material	SS 304 / SS 316 / GI
Pressure Rating	Up to 3000 PSI
Application	Piping, Oil, Gas, Water

HEX PLUG (BSP)



- Seals the end of pipe
- Leak-proof
- High strength
- Easy installation

Size Range	1/8" to 4"
Thread Type	BSP (Male)
Material	SS 304 / SS 316 / GI
Pressure Rating	Up to 3000 PSI
Application	Water, Oil, Gas, Air

HOSE CLAMP (SS)



- Closes the end of pipe
- Leak-proof
- Corrosion resistant
- Easy installation

Size Range	8mm to 100mm
Material	SS 304
Type	Worm Drive
Application	Hose, Pipe, Tubing

INDUSTRIAL FITTINGS & ACCESSORIES

A comprehensive range of industrial fittings and accessories designed to ensure secure connections, leak-proof performance and long service life in all types of industrial applications.

FEATURES

- Precision manufacturing for perfect fit
- Leak-proof and reliable performance
- Corrosion resistant materials
- Easy installation and maintenance
- Wide range of sizes and configurations
- Suitable for various industrial applications

APPLICATIONS

- Water & Waste Water Treatment
- Oil, Gas & Petrochemical Industries
- Marine & Ship Building
- HVAC & General Industrial Applications
- Pumping & Pipeline Systems
- Power Plants
- Food & Beverage Industries

BUTT WELD ELBOW 90°



- Smooth flow transition
- High pressure resistance
- Durable & long lasting

Size Range	½" to 24"
Schedule	SCH 10 to SCH 160
Material	ASTM A234 WPB SS 304 / 316
Ends	Butt Weld
Application	Oil, Gas, Chemical, Power Plants

BUTT WELD TEE



- Efficient flow distribution
- Strong & leak-proof joints
- Available in all standard sizes

Size Range	½" to 24"
Schedule	SCH 10 to SCH 160
Material	ASTM A234 WPB SS 304 / 316
Ends	Butt Weld
Application	Piping, Chemical, Petrochemical

BUTT WELD REDUCER (CONCENTRIC)



- Smooth bore transition
- Reduces pressure loss
- Corrosion resistant

Size Range	½" to 24"
Schedule	SCH 10 to SCH 160
Material	ASTM A234 WPB SS 304 / 316
Ends	Butt Weld
Application	Oil, Gas, Water, Steam Lines

BUTT WELD CAP



- Secure pipe termination
- Withstands high pressure
- Strong & reliable

Size Range	½" to 24"
Schedule	SCH 10 to SCH 160
Material	ASTM A234 WPB SS 304 / 316
Ends	Butt Weld
Application	Piping, Pressure Vessels, Tanks

SOCKET WELD COUPLING



- High strength coupling
- Leak-proof connection
- Ideal for high pressure

Size Range	1/8" to 4"
Pressure Rating	Up to 6000 PSI
Material	ASTM A105 SS 304 / 316
Ends	Socket Weld
Application	High Pressure Piping Systems

SOCKET WELD UNION



- Easy assembly & dismantling
- Leak-proof performance
- Reusable & durable

Size Range	1/8" to 4"
Pressure Rating	Up to 6000 PSI
Material	ASTM A105 SS 304 / 316
Ends	Socket Weld
Application	Oil, Gas, Chemical, Hydraulic Systems

THREADED BUSH (REDUCING)



- Reduce pipe size
- Strong & durable
- Easy installation

Size Range	1/8" to 4"
Thread Type	BSP / NPT
Material	GI / SS 304 / 316
Ends	Male x Female
Application	Piping, Plumbing, Industrial

THREADED CROSS



- Connects four pipes
- High strength
- Leak-proof joints

Size Range	1/8" to 4"
Thread Type	BSP / NPT
Material	GI / SS 304 / 316
Ends	Female (All)
Application	Piping, Chemical, Water Lines

BARBED HOSE TAIL



- Strong grip on hose
- Leak-resistant connection
- Easy to install

Size Range	1/8" to 4"
Thread Type	BSP / NPT
Material	SS 304 / 316 / Brass
Ends	Male Thread
Application	Hose, Water, Air, Fluid Transfer

PIPE HANGER (ROLLER TYPE)



- Supports pipe with movement
- Reduces friction
- Easy installation

Size Range	½" to 12"
Material	MS / SS
Finish	Galvanized
Type	Roller Type
Application	Piping Support, HVAC, Industrial

EXPANSION BELLOW (METALLIC)



- Absorbs thermal movement
- Reduces stress on piping
- Durable construction

Size Range	1" to 24"
Material	SS 304 / 316
Pressure Rating	Up to 16 Bar
Ends	Flanged / Welded
Application	Steam, Hvac, Process Piping

Y-STRAINER (THREADED)



- Removes dirt & particles
- Protects valves & equipment
- Easy cleaning

Size Range	1/2" to 4"
Thread Type	BSP / NPT
Material	CI / SS 304 / 316
Ends	Female Thread
Application	Water, Oil, Steam, Pipelines

INDUSTRIAL FITTINGS & ACCESSORIES

A comprehensive range of industrial fittings and accessories designed to ensure secure connections, leak-proof performance and long service life in all types of industrial applications.

FEATURES

- Precision manufacturing for perfect fit
- Leak-proof and reliable performance
- Corrosion resistant materials
- Easy installation and maintenance
- Wide range of sizes and configurations
- Suitable for various industrial applications

APPLICATIONS

- Water & Waste Water Treatment
- Oil, Gas & Petrochemical Industries
- Marine & Ship Building
- HVAC & General Industrial Applications
- Pumping & Pipeline Systems
- Power Plants
- Food & Beverage Industries

CAMLOCK COUPLING TYPE A (ADAPTER)



- Quick connect system
- Stainless steel 316
- Durable & leak-proof
- Easy to operate

Size Range	1/2" to 6"
Material	SS 316 / Alu / PP
Pressure Rating	Up to 250 PSI
Application	Liquid Transfer

CAMLOCK COUPLING TYPE B (COUPLER)



- Secure locking
- Multiple material options
- High pressure resistance
- Long service life

Size Range	1/2" to 6"
Material	SS 316 / Alu / PP
Pressure Rating	Up to 250 PSI
Application	Chemical, Water, Oil Transfer

TRI CLAMP FERRULE (LONG TYPE)



- Hygienic connection
- SS 304 / SS 316
- Smooth internal surface
- Ideal for food & pharma

Size Range	1/2" to 4"
Material	SS 304 / SS 316
Standard	ISO / 3A / DIN
Application	Food, Dairy, Pharma, Beverage

TRI CLAMP CLAMP (SINGLE PIN)



- Strong & reliable clamp
- SS 304 / SS 316
- Easy installation
- Corrosion resistant

Size Range	1/2" to 6"
Material	SS 304 / SS 316
Standard	ISO / 3A / DIN
Application	Piping, Food, Pharma, Dairy

SIGHT GLASS (FLANGED TYPE)



- Visual flow indication
- Cast Iron / SS Body
- High pressure resistant
- Clear view & durable

Size Range	15 NB to 100 NB
Material	CI / SS 304 / SS 316
Pressure Rating	Up to 16 Bar
Application	Steam, Water, Oil Lines

NEEDLE VALVE (INSTRUMENTATION)



- Precise flow control
- SS 316 construction
- High pressure capability
- Compact & durable

Size Range	1/8" to 1/2"
Material	SS 316
Pressure Rating	Up to 6000 PSI
Application	Instrumentation, Hydraulic, Gas

SOLENOID VALVE (2 WAY)



- Electric operated
- Brass / SS body
- Normally Closed / Open
- High performance

Size Range	1/4" to 2"
Material	Brass / SS 304
Pressure Rating	Up to 16 Bar
Application	Water, Air, Gas, Chemical

PNEUMATIC FITTING (ELBOW)



- Push-in connection
- Nickel plated brass
- Leak-proof & secure
- Easy & quick installation

Tube OD	4 mm to 12 mm
Material	Brass / PU
Pressure Rating	Up to 150 PSI
Application	Pneumatic Systems

QUICK RELEASE COUPLING (EURO TYPE)



- Fast connection
- High flow capacity
- Nickel plated brass
- Leak-proof performance

Size Range	1/4" to 1"
Material	Brass (Nickel Plated)
Pressure Rating	Up to 300 PSI
Application	Air, Water, Gas

HYDRAULIC QUICK COUPLER (MALE)



- High pressure rated
- Hardened steel
- Secure locking
- Long working life

Size Range	1/4" to 1"
Material	Carbon Steel
Pressure Rating	Up to 5000 PSI
Application	Hydraulic Systems

FLOAT VALVE (BALL TYPE)



- Automatic water level control
- Brass body
- Corrosion resistant
- Easy to install

Size Range	1/2" to 2"
Material	Brass
Pressure Rating	Up to 10 Bar
Application	Water Tanks, Overhead Tank

AIR FILTER REGULATOR LUBRICATOR (FRL)



- Filters, regulates & lubricates
- Modular design
- High efficiency
- Improves equipment life

Port Size	1/4" to 1/2"
Material	Aluminium / Polycarbonate
Pressure Rating	Up to 150 PSI
Application	Pneumatic Systems

THERMODYNAMIC STEAM TRAP



- Efficient condensate removal
- Cast steel construction
- No moving parts
- Long service life

Size Range	15 NB to 50 NB
Material	Cast Steel
Pressure Rating	Up to 32 Bar
Application	Steam Lines

SS FLEXIBLE METAL HOSE (BRAIDED)



- Absorbs vibration
- SS 304 / SS 316
- High temperature resistant
- Long durability

Size Range	1/2" to 4"
Material	SS 304 / SS 316
Pressure Rating	Up to 16 Bar
Application	Steam, Water, Oil, Chemicals

FOOT VALVE (WITH STRAINER)



- Prevents backflow
- Bronze body
- With SS strainer
- Easy installation

Size Range	1/2" to 2"
Material	Bronze / Brass
Pressure Rating	Up to 16 Bar
Application	Pumping Systems

FLOAT SWITCH (CABLE TYPE)



- Automatic level control
- Polypropylene body
- High quality cable
- Reliable performance

Cable Length	3 Meter / 5 Meter
Voltage	230V AC / 50 Hz
Application	Water Tanks, Sumps, Pumps