

1 > make h

This command is a help command that shows the user several different commands that can be executed in the makefile. A makefile how to guide with targets & purposes.

2 > make

This is the makefile default command which compiles everything by default. So, all the java programs defined in the p variable.

3 > make p=Hello r

This command compiles the java program making p=Hello & runs the default makefile arguments.

4 > make p=Hello r0

This command compiles the java program with p=Hello however there are no arguments passed on top.

5 > make p=Hello r1

This command compiles such that p=Hello1 & includes the default arguments of the makefile.

Last login: Sat Sep 9 15:35:36 on ttys000

aditikanaujia@Aditis-Air-2 ~ % cd Desktop/coding/BA/hw0-kanaujia

aditikanaujia@Aditis-Air-2 hw0-kanaujia % pwd

/Users/aditikanaujia/Desktop/coding/BA/hw0-kanaujia

aditikanaujia@Aditis-Air-2 hw0-kanaujia % ls

HINTS	JavaNotes.pdf	TestOutput	hw0-yap.pdf
Hello.java	Makefile	bin	make-include
Hello1.java	README	hw0-yap.iml	

aditikanaujia@Aditis-Air-2 hw0-kanaujia %

```
Last login: Sat Sep  9 15:35:36 on ttys000
aditikanaujia@Aditis-Air-2 ~ % cd Desktop/coding/BA/hw0-kanaujia
aditikanaujia@Aditis-Air-2 hw0-kanaujia % pwd
/Users/aditikanaujia/Desktop/coding/BA/hw0-kanaujia
aditikanaujia@Aditis-Air-2 hw0-kanaujia % ls
HINTS                JavaNotes.pdf      TestOutput          hw0-yap.pdf
Hello.java           Makefile           bin                 make-include
Hello1.java          README             hw0-yap.iml
aditikanaujia@Aditis-Air-2 hw0-kanaujia % make p=Hello
test -d bin || mkdir bin
/usr/bin/javac -d bin *.java
aditikanaujia@Aditis-Air-2 hw0-kanaujia % make p=Hello r
/usr/bin/java -classpath bin Hello 111 10 1 true abc
Hello, world!
=====
ss = 111
nn = 10
mm = 1
=====
aditikanaujia@Aditis-Air-2 hw0-kanaujia %
```



```
aditikanaujia@Aditis-Air-2 hw0-kanaujia % make p=Hello r
/usr/bin/java -classpath bin Hello 111 10 1 true abc
Hello, world!
```

```
=====
```

```
ss = 111
nn = 10
mm = 1
```

```
=====
```

```
aditikanaujia@Aditis-Air-2 hw0-kanaujia % make p=Hello r0
/usr/bin/java -classpath bin Hello
Hello, world!
```

```
=====
```

```
ss = 1111
nn = 100
mm = 10
```

```
=====
```

```
aditikanaujia@Aditis-Air-2 hw0-kanaujia % make p=Hello r1
/usr/bin/java -classpath bin Hello1 111 10 1 true abc
Hello, one world!
```

```
=====
```

```
Random integers between 0 and 99:
93, 70, 57, 97, 9, 20, 84, 12, 97, 65
```

```
=====
```

```
aditikanaujia@Aditis-Air-2 hw0-kanaujia %
```