

Monday October 18

Real-life representations are often prone to corruption. Biological codes, like RNA, may mutate naturally¹ and during measurement; cosmic radiation and other ambient noise can flip bits in computer storage². One way to recover from corrupted data is to introduce or exploit redundancy.

Consider the following algorithm to introduce redundancy in a string of 0s and 1s.

Create redundancy by repeating each bit three times

```

1 procedure redun3( $a_{k-1} \dots a_0$ : a nonempty bitstring)
2 for  $i := 0$  to  $k-1$ 
3    $c_{3i} := a_i$ 
4    $c_{3i+1} := a_i$ 
5    $c_{3i+2} := a_i$ 
6 return  $c_{3k-1} \dots c_0$ 

```

Handwritten notes: $001 = a_2 a_1 a_0$
 $i=0 \quad c_0:=1 \quad c_1:=1 \quad c_2:=1$
 $i=1 \quad c_3:=0 \quad c_4:=0 \quad c_5:=0$
 $i=2 \quad c_6:=0 \quad c_7:=0 \quad c_8:=0$
 Output: 000000111

Decode sequence of bits using majority rule on consecutive three bit sequences

```

1 procedure decode3( $c_{3k-1} \dots c_0$ : a nonempty bitstring whose length is an integer multiple of 3)
2 for  $i := 0$  to  $k-1$ 
3   if exactly two or three of  $c_{3i}, c_{3i+1}, c_{3i+2}$  are set to 1
4      $a_i := 1$ 
5   else
6      $a_i := 0$ 
7 return  $a_{k-1} \dots a_0$ 

```

Handwritten notes: $100 \ 000 \ 000 \ 101 = c_8 c_7 c_6 c_5 c_4 c_3 c_2 c_1$

Simplest input to **redun3** is 0 or 1

Give a recursive definition of the set of outputs of the **redun3** procedure, *Out*,

Basis Step: $000 \in \text{Out}$ and $111 \in \text{Out}$

Recursive Step: If $x \in \text{Out}$ then $x111 \in \text{Out}$ and $x000 \in \text{Out}$

Consider the message $m = 0001$ so that the sender calculates $\text{redun3}(m) = \text{redun3}(0001) = 000000000111$.

Introduce 2 errors into the message so that the signal received by the receiver is 100000000101 but the receiver is still able to decode the original message.


Handwritten notes: $i=0 \quad 101 \quad a_0=1 \quad i=1 \quad 000 \quad a_1=0 \quad i=2 \quad 000 \quad a_2=0 \quad i=3 \quad 100 \quad a_3=0$

Challenge: what is the biggest number of errors you can introduce?

Building a circuit for lines 3-6 in **decode** procedure: given three input bits, we need to determine whether the majority is a 0 or a 1.

x	y	z	a_i	
c_{3i}	c_{3i+1}	c_{3i+2}	a_i	
1	1	1	1	*
1	1	0	1	*
1	0	1	1	*
1	0	0	0	*
0	1	1	1	*
0	1	0	0	*
0	0	1	0	*
0	0	0	0	*

Circuit



¹Mutations of specific RNA codons have been linked to many disorders and cancers.

²This RadioLab podcast episode goes into more detail on bit flips: <https://www.wnycstudios.org/story/bit-flip>


$$\text{DNF : } (x \wedge y \wedge z) \vee (x \wedge y \wedge \neg z) \vee (x \wedge \neg y \wedge z) \vee (\neg x \wedge y \wedge z)$$

$$\text{CNF : } (\neg x \vee y \vee z) \wedge (x \vee \neg y \vee z) \wedge (x \vee y \vee \neg z) \wedge (x \vee y \vee z)$$

$$\text{alternative: } (x \wedge (y \vee z)) \vee (\neg x \wedge y \wedge z)$$

$$\text{or even: } (x \wedge (y \vee z)) \vee (y \wedge z)$$

which saves two gates



Definition: The **Cartesian product** of the sets A and B , $A \times B$, is the set of all ordered pairs (a, b) , where $a \in A$ and $b \in B$. That is: $A \times B = \{(a, b) \mid (a \in A) \wedge (b \in B)\}$. The Cartesian product of the sets A_1, A_2, \dots, A_n , denoted by $A_1 \times A_2 \times \dots \times A_n$, is the set of ordered n-tuples (a_1, a_2, \dots, a_n) , where a_i belongs to A_i for $i = 1, 2, \dots, n$. That is,

$$A_1 \times A_2 \times \dots \times A_n = \{(a_1, a_2, \dots, a_n) \mid a_i \in A_i \text{ for } i = 1, 2, \dots, n\}$$

Recall that S is defined as the set of all RNA strands, nonempty strings made of the bases in $B = \{A, U, G, C\}$. We define the functions

$mutation: S \times \mathbb{Z}^+ \times B \rightarrow S$

$insertion: S \times \mathbb{Z}^+ \times B \rightarrow S$

$deletion: \{s \in S \mid rnalen(s) > 1\} \times \mathbb{Z}^+ \rightarrow S$ with rules

```

1 procedure mutation( $b_1 \dots b_n$ : a RNA strand,  $k$ : a positive integer,  $b$ : an element of  $B$ )
2 for  $i := 1$  to  $n$ 
3   if  $i = k$ 
4      $c_i := b$ 
5   else
6      $c_i := b_i$ 
7 return  $c_1 \dots c_n$  {The return value is a RNA strand made of the  $c_i$  values}

```

```

1 procedure insertion( $b_1 \dots b_n$ : a RNA strand,  $k$ : a positive integer,  $b$ : an element of  $B$ )
2 if  $k > n$ 
3   for  $i := 1$  to  $n$ 
4      $c_i := b_i$ 
5    $c_{n+1} := b$ 
6 else
7   for  $i := 1$  to  $k - 1$ 
8      $c_i := b_i$ 
9    $c_k := b$ 
10  for  $i := k + 1$  to  $n + 1$ 
11     $c_i := b_{i-1}$ 
12 return  $c_1 \dots c_{n+1}$  {The return value is a RNA strand made of the  $c_i$  values}

```

```

1 procedure deletion( $b_1 \dots b_n$ : a RNA strand with  $n > 1$ ,  $k$ : a positive integer)
2 if  $k > n$ 
3    $m := n$ 
4   for  $i := 1$  to  $n$ 
5      $c_i := b_i$ 
6 else
7    $m := n - 1$ 
8   for  $i := 1$  to  $k - 1$ 
9      $c_i := b_i$ 
10  for  $i := k$  to  $n - 1$ 
11     $c_i := b_{i+1}$ 
12 return  $c_1 \dots c_m$  {The return value is a RNA strand made of the  $c_i$  values}

```

Trace the pseudocode to find the output of $mutation((AUC, 3, G))$

AUG

$b_1 b_2 b_3 = AUC$
 $n = 3$
 $k = 3$
 $b = G$

Fill in the blanks so that $insertion((AUC, 4, G)) = AUCG$

Fill in the blanks ~~input~~ so that $deletion((GG, 2)) = G$

Notice: input must have at least two bases.

Review

1.

In this question, we will consider how to build a logic circuit with inputs x_0, y_0, x_1, y_1 and output z such that $z = 1$ exactly when $(x_1x_0)_{2,2} < (y_1y_0)_{2,2}$ and $z = 0$ exactly when $(x_1x_0)_{2,2} \geq (y_1y_0)_{2,2}$.

- (a) The first step towards designing this logic circuit is to construct its input-output table. How many rows does this table have (not including the header row labelling the columns)?
- (b) What is the output for the row whose input values are $x_0 = 0, y_0 = 1, x_1 = 1, y_1 = 0$?
- (c) What is the output for the row whose input values are $x_0 = 0, y_0 = 1, x_1 = 0, y_1 = 1$?

2.

Recall the procedures *redun3* and *decode3* from class.

- (a) Give the output of *redun3*(100).
- (b) If the output of running *redun3* is 000000111000111, what was its input?
- (c) Give the output of *decode3*(100).
- (d) How many distinct possible inputs to *decode3* give the output 01?

3.

Recall the procedures *mutation* and *intertion* and *deletion* from class.

- (a) Trace the pseudocode to find the output of *mutation*((AUC, 2, U))
- (b) Trace the pseudocode to find the output of *insertion*((AUC, 1, G))
- (c) Trace the pseudocode to find the output of *deletion*((AUC, 1))

Wednesday October 20

Definition: A **predicate** is a function from a given set (domain) to $\{T, F\}$.

A predicate can be applied, or **evaluated** at, an element of the domain.

Usually, a predicate *describes a property* that domain elements may or may not have.

Two predicates over the same domain are **equivalent** means they evaluate to the same truth values for all possible assignments of domain elements to the input. In other words, they are equivalent means that they are equal as functions.

To define a predicate, we must specify its domain and its value at each domain element. The rule assigning truth values to domain elements can be specified using a formula, English description, in a table (if the domain is finite), or recursively (if the domain is recursively defined).

Domain

Input	$V(x)$ $[x]_{2c,3} > 0$	$N(x)$ $[x]_{2c,3} < 0$	$Mystery(x)$	$Z(x)$ $[x]_{2c,3} = 0$	$Y(x)$	$P_2(x)$ $V(x) \rightarrow N(x)$
000	<u>F</u>	<u>F</u>	<u>T</u>	<u>T</u>	<u>T</u>	<u>T</u>
001	<u>T</u>	<u>F</u>	<u>T</u>	<u>F</u>	<u>T</u>	<u>F</u>
010	<u>T</u>	<u>F</u>	<u>T</u>	<u>F</u>	<u>T</u>	<u>F</u>
011	<u>T</u>	<u>F</u>	<u>F</u>	<u>F</u>	<u>T</u>	<u>F</u>
100	<u>F</u>	<u>T</u>	<u>F</u>	<u>F</u>	<u>T</u>	<u>T</u>
101	<u>F</u>	<u>T</u>	<u>T</u>	<u>F</u>	<u>T</u>	<u>F</u>
110	<u>F</u>	<u>T</u>	<u>F</u>	<u>F</u>	<u>T</u>	<u>T</u>
111	<u>F</u>	<u>T</u>	<u>T</u>	<u>F</u>	<u>T</u>	<u>F</u>

The domain for each of the predicates $V(x)$, $N(x)$, $Mystery(x)$ is $\{000, 001, 010, 011, 100, 101, 110, 111\}$.

Fill in the table of values for the predicate $N(x)$ based on the formula given.

$$\begin{aligned}
 &V(111) \\
 &= [111]_{2c,3} > 0 \\
 &= -4 + 2 + 1 > 0 \\
 &= -1 > 0 \\
 &= F
 \end{aligned}$$

Definition: The **truth set** of a predicate is the collection of all elements in its domain where the predicate evaluates to T .

Notice that specifying the domain and the truth set is sufficient for defining a predicate.

The truth set for the predicate $V(x)$ is $\{001, 010, 011\}$.

The truth set for the predicate $N(x)$ is $\{100, 101, 110, 111\}$.

The truth set for the predicate $Mystery(x)$ is $\{000, 001, 010, 101, 111\}$.

The truth set for $Y(x)$ is \emptyset

The truth set for $Z(x)$ is $\{000\}$

The **universal quantification** of predicate $P(x)$ over domain U is the statement " $P(x)$ for all values of x in the domain U " and is written $\forall x P(x)$ or $\forall x \in U P(x)$. When the domain is finite, universal quantification over the domain is equivalent to iterated *conjunction* (ands). $\forall x V(x)$ would mean $V(000) \wedge V(001) \wedge V(010) \wedge V(011) \wedge V(100) \wedge V(101) \wedge V(110) \wedge V(111)$

example:

The **existential quantification** of predicate $P(x)$ over domain U is the statement "There exists an element x in the domain U such that $P(x)$ " and is written $\exists x P(x)$ for $\exists x \in U P(x)$. When the domain is finite, existential quantification over the domain is equivalent to iterated *disjunction* (ors). $\exists x V(x)$ would mean $V(000) \vee V(001) \vee V(010) \vee V(011) \vee V(100) \vee V(101) \vee V(110) \vee V(111)$

example:

An element for which $P(x) = F$ is called a **counterexample** of $\forall x P(x)$.

An element for which $P(x) = T$ is called a **witness** of $\exists x P(x)$.

Statements involving predicates and quantifiers are **logically equivalent** means they have the same truth value no matter which predicates (domains and functions) are substituted in.

Quantifier version of De Morgan's laws: $\neg \forall x P(x) \equiv \exists x (\neg P(x))$

$\neg \exists x Q(x) \equiv \forall x (\neg Q(x))$

Examples of quantifications using $V(x), N(x), \text{Mystery}(x)$:

True or False: $\exists x (V(x) \wedge N(x))$

There's at least one x such that $[x]_{2c,3} > 0$ and $[x]_{2c,3} \leq 0$

True or False: $\forall x (V(x) \rightarrow N(x))$

Counterexample $x = 001$

True or False: $\exists x (N(x) \leftrightarrow \text{Mystery}(x))$

witness $x = 011$

Rewrite $\neg \forall x (V(x) \oplus \text{Mystery}(x))$ into a logical equivalent statement.

$$\equiv \exists x \neg (V(x) \oplus \text{Mystery}(x)) \equiv \exists x (V(x) \leftrightarrow \text{Mystery}(x))$$

$P_1(x)$ is $V(x) \wedge N(x)$

$P_2(x)$ is $V(x) \rightarrow N(x)$

$P_3(x)$ is $N(x) \leftrightarrow \text{Mystery}(x)$

Using truth table:

$\forall x P(x)$ means T in all rows

$\exists x P(x)$ means T is some row

Notice that these are examples where the predicates have *finite* domain. How would we evaluate quantifications where the domain may be infinite?

Example predicates on S , the set of RNA strands (an infinite set)

$H : S \rightarrow \{T, F\}$ where $H(s) = T$ for all s .

Truth set of H is S

$F_A : S \rightarrow \{T, F\}$ defined recursively by:

"first base is A"

Basis step: $F_A(A) = T, F_A(C) = F_A(G) = F_A(U) = F$

Recursive step: If $s \in S$ and $b \in B$, then $F_A(sb) = F_A(s)$.

Example where F_A evaluates to T is ACG

$$F_A(ACG) = F_A(AC) = F_A(A) = T$$

Example where F_A evaluates to F is GCG

$$F_A(GCG) = F_A(GC) = F_A(G) = F$$

Review

1.

Recall the predicates $V(x)$, $N(x)$, and $Mystery(x)$ on domain $\{000, 001, 010, 011, 100, 101, 110, 111\}$ from class. Which of the following is true? (Select all and only that apply.)

- (a) $(\forall x V(x)) \vee (\forall x N(x))$
- (b) $(\exists x V(x)) \wedge (\exists x N(x)) \wedge (\exists x Mystery(x))$
- (c) $\exists x (V(x) \wedge N(x) \wedge Mystery(x))$
- (d) $\forall x (V(x) \oplus N(x))$
- (e) $\forall x (Mystery(x) \rightarrow V(x))$

2.

Consider the following predicates, each of which has as its domain the set of all bitstrings whose leftmost bit is 1

$E(x)$ is T exactly when $(x)_2$ is even, and is F otherwise

$L(x)$ is T exactly when $(x)_2 < 3$, and is F otherwise

$M(x)$ is T exactly when $(x)_2 > 256$ and is F otherwise.

- (a) What is $E(110)$?
- (b) Why is $L(00)$ undefined?
 - i. Because the domain of L is infinite
 - ii. Because 00 does not have 1 in the leftmost position
 - iii. Because 00 has length 2, not length 3
 - iv. Because $(00)_{2,2} = 0$ which is less than 3
- (c) Is there a bitstring of width (where width is the number of bits) 6 at which $M(x)$ evaluates to T ?

3.

For this question, we will use the following predicate.

F_A with domain S is defined recursively by:

Basis step: $F_A(A) = T$, $F_A(C) = F_A(G) = F_A(U) = F$

Recursive step: If $s \in S$ and $b \in B$, then $F_A(sb) = F_A(s)$

Which of the following is true? (Select all and only that apply.)

- (a) $F_A(AA)$
- (b) $F_A(AC)$
- (c) $F_A(AG)$
- (d) $F_A(AU)$

(e) $F_{\mathbf{A}}(\mathbf{CA})$

(f) $F_{\mathbf{A}}(\mathbf{CC})$

(g) $F_{\mathbf{A}}(\mathbf{CG})$

(h) $F_{\mathbf{A}}(\mathbf{CU})$

Friday October 22

Recall the definitions: The set of RNA strands S is defined (recursively) by:

Basis Step: $A \in S, C \in S, U \in S, G \in S$
 Recursive Step: If $s \in S$ and $b \in B$, then $sb \in S$

where sb is string concatenation.

The function $rnalen$ that computes the length of RNA strands in S is defined recursively by:

Basis Step: If $b \in B$ then $rnalen(b) = 1$
 Recursive Step: If $s \in S$ and $b \in B$, then $rnalen(sb) = 1 + rnalen(s)$

Practice: $rnalen(AC) = 1 + rnalen(A) = 1 + 1 = 2$.

The function $basecount$ that computes the number of a given base b appearing in a RNA strand s is defined recursively by:

$basecount : S \times B \rightarrow \mathbb{N}$
 Basis Step: If $b_1 \in B, b_2 \in B$ $basecount(b_1, b_2) = \begin{cases} 1 & \text{when } b_1 = b_2 \\ 0 & \text{when } b_1 \neq b_2 \end{cases}$
 Recursive Step: If $s \in S, b_1 \in B, b_2 \in B$ $basecount(sb_1, b_2) = \begin{cases} 1 + basecount(s, b_2) & \text{when } b_1 = b_2 \\ basecount(s, b_2) & \text{when } b_1 \neq b_2 \end{cases}$

Practice: $basecount(AC, G) = basecount(A, G) = 0$

Using functions to define predicates: "the value of this function at input is"

L with domain $S \times \mathbb{Z}^+$ is defined by, for $s \in S$ and $n \in \mathbb{Z}^+$,

$$L(s, n) = \begin{cases} T & \text{if } rnalen(s) = n \\ F & \text{otherwise} \end{cases}$$

In other words, $L(s, n)$ means $rnalen(s) = n$

BC with domain $S \times B \times \mathbb{N}$ is defined by, for $s \in S$ and $b \in B$ and $n \in \mathbb{N}$,

domain of $basecount$ \swarrow \nwarrow codomain of $basecount$

$$BC(s, b, n) = \begin{cases} T & \text{if } basecount(s, b) = n \\ F & \text{otherwise} \end{cases}$$

In other words, $BC(s, b, n)$ means $basecount(s, b) = n$

Example where L evaluates to T : $(AC, 2)$ Why? $rnalen(AC) = 1 + rnalen(A) = 1 + 1 = 2$.

Example where BC evaluates to T : $(AC, G, 0)$ Why? $basecount(AC, G) = 0$

Example where L evaluates to F : $(AC, 3)$ Why? $rnalen(AC) \neq 3$

Example where BC evaluates to F : $(AC, G, 3)$ Why? $basecount(AC, G) \neq 3$

$$\exists t \text{ BC}(t) \quad \exists (s, b, n) \in S \times B \times \mathbb{N} (\text{basecount}((s, b)) = n)$$

In English: There is a 3-tuple of strand, base, nonnegative integer where applying basecount to ordered pair of this strand and this base results in this nonneg int as the value.
Witness that proves this existential quantification is true: $(AC, G, 0)$

$$\forall t \text{ BC}(t) \quad \forall (s, b, n) \in S \times B \times \mathbb{N} (\text{basecount}((s, b)) = n)$$

In English: For every choice of strand, base, nonnegative integer, plugging in these values to the equation give true equality.
Counterexample that proves this universal quantification is false: $(AC, G, 2)$

New predicates from old

1. Define the **new** predicate with domain $S \times B$ and rule

$$\text{basecount}((s, b)) = 3$$

Example domain element where predicate is T: (GGG, G)

2. Define the **new** predicate with domain $S \times \mathbb{N}$ and rule

$$\text{basecount}((s, \underline{A})) = n$$

Example domain element where predicate is T: $(AA, 2)$ or $(GGG, 0)$

3. Define the **new** predicate with domain $S \times B$ and rule

$$\exists n \in \mathbb{N} (\text{basecount}((s, b)) = n)$$

Example domain element where predicate is T:

$$\text{strand} \quad \text{base} \\ (AG, A)$$

$$\exists n \in \mathbb{N} (\text{basecount}((AG, A)) = n) \\ \text{choose witness } n=1.$$

4. Define the **new** predicate with domain S and rule

$$\forall b \in B (\text{basecount}((s, b)) = 1)$$

Example domain element where predicate is T:

$$ACUG$$

$$\begin{aligned} \text{basecount}((s, G)) &= 1 \\ \text{basecount}((s, A)) &= 1 \\ \text{basecount}((s, C)) &= 1 \\ \text{basecount}((s, U)) &= 1 \end{aligned}$$

Notation: for a predicate P with domain $X_1 \times \dots \times X_n$ and a n -tuple (x_1, \dots, x_n) with each $x_i \in X$, we can write $P(x_1, \dots, x_n)$ to mean $P((x_1, \dots, x_n))$.

Nested quantifiers

$$\forall t \quad BC(t) \quad t \in S \times B \times \mathbb{N}$$

$$\forall s \in S \left(\forall b \in B \forall n \in \mathbb{N} (basecount((s, b)) = n) \right)$$

In English: For every strand, for every base, for every nonneg int we have the equation holds.

Counterexample that proves this universal quantification is false:

$$S = AC \quad b = G \quad n = 1$$

$$\forall n \in \mathbb{N} \left(\forall s \in S \forall b \in B (basecount((s, b)) = n) \right)$$

In English: For every nonnegative integer, for every strand, for every base, we have that the equation holds.

Counterexample that proves this universal quantification is false:

$$n = 1 \quad S = AC \quad b = G$$

Alternating nested quantifiers

Order matters
 \forall vs. \exists matters.

$$\forall s \in S \left(\exists b \in B (basecount((s, b)) = 3) \right)$$

In English: For each RNA strand there is a base that occurs 3 times in this strand.

Write the negation and use De Morgan's law to find a logically equivalent version where the negation is applied only to the BC predicate (not next to a quantifier).

$$\begin{aligned} & \neg \forall s \exists b (basecount((s, b)) = 3) \\ & \equiv \exists s \neg \exists b (basecount((s, b)) = 3) \\ & \equiv \exists s \forall b \neg (basecount((s, b)) = 3) \end{aligned}$$

* Is the original statement **True** or **False**? Counterexample $S = AC$

	Basecount
$b = A$	1
$b = C$	1
$b = U$	0
$b = G$	0

Not 3

$$\exists s \in S \left(\forall b \in B \exists n \in \mathbb{N} (basecount((s, b)) = n) \right)$$

In English: There is an RNA strand so that for each base there is some nonnegative integer that counts the number of occurrences of that base in this strand.

Write the negation and use De Morgan's law to find a logically equivalent version where the negation is applied only to the BC predicate (not next to a quantifier).

$$\begin{aligned} & \neg \exists s \forall b \exists n (basecount((s, b)) = n) \\ & \equiv \forall s \exists b \forall n \neg (basecount((s, b)) = n) \end{aligned}$$

Is the original statement **True** or **False**? Witness $S = AUGG$.

$s = \underline{AUGG}$

$$\forall b \in B \exists n \in \mathbb{N} (\text{basecount}(s, b) = n)$$

$b = A$ $\exists n \in \mathbb{N} (\text{basecount}(AUGG, A) = n)$
witness $n = 1$

$b = C$ $\exists n \in \mathbb{N} (\text{basecount}(AUGG, C) = n)$
witness $n = 0$

$b = U$ $\exists n \in \mathbb{N} (\text{basecount}(AUGG, U) = n)$
witness $n = 1$

$b = G$ $\exists n \in \mathbb{N} (\text{basecount}(AUGG, G) = n)$
witness $n = 2$

Review

1.

Recall the predicate L with domain $S \times \mathbb{Z}^+$ from class, $L((s, n))$ means $rnalen(s) = n$. Which of the following is true? (Select all and only that apply.)

- (a) $\exists s \in S \exists n \in \mathbb{Z}^+ L((s, n))$
- (b) $\exists s \in S \forall n \in \mathbb{Z}^+ L((s, n))$
- (c) $\forall n \in \mathbb{Z}^+ \exists s \in S L((s, n))$
- (d) $\forall s \in S \exists n \in \mathbb{Z}^+ L((s, n))$
- (e) $\exists n \in \mathbb{Z}^+ \forall s \in S L((s, n))$

2.

Recall the predicate BC with domain $S \times B \times \mathbb{N}$ from class, $BC((s, b, n))$ means $basecount((s, b)) = n$. Match each sentence to its English translation, or select none of the above.

- (a) $\forall s \in S \exists n \in \mathbb{N} \forall b \in B basecount((s, b)) = n$
- (b) $\forall s \in S \forall b \in B \exists n \in \mathbb{N} basecount((s, b)) = n$
- (c) $\forall s \in S \forall n \in \mathbb{N} \exists b \in B basecount((s, b)) = n$
- (d) $\forall b \in B \forall n \in \mathbb{N} \exists s \in S basecount((s, b)) = n$
- (e) $\forall n \in \mathbb{N} \forall b \in B \exists s \in S basecount((s, b)) = n$

- i. For each RNA strand and each possible base, the number of that base in that strand is a nonnegative integer.
- ii. For each RNA strand and each nonnegative integer, there is a base that occurs this many times in this strand.
- iii. Every RNA strand has the same number of each base, and that number is a nonnegative integer.
- iv. For every given nonnegative integer, there is a strand where each possible base appears the given number of times.
- v. For every given base and nonnegative integer, there is an RNA strand that has this base occurring this many times.

Challenge: Express symbolically

There are (at least) two different RNA strands that have the same number of As.