



DC-2

Sun, 19 Apr 2026 10:01:07 UTC

TABLE OF CONTENTS

- Vulnerabilities by Host
 - 192.168.0.103
- Compliance 'FAILED'
- Compliance 'SKIPPED'
- Compliance 'PASSED'
- Compliance 'INFO', 'WARNING', 'ERROR'
- Remediations
 - Suggested Remediations

Vulnerabilities by Host

Collapse All | Expand All

192.168.0.103



Scan Information

Start time:

Sun Apr 19 09:53:17 2026

End time:

Sun Apr 19 10:01:07 2026

Host Information

IP:

192.168.0.103

MAC Address:

08:00:27:BB:1A:A8

OS:

Linux Kernel 3.16 on Debian 8.0 (jessie)

Vulnerabilities

201420 - Debian Linux SEoL (8.x)

-

Synopsis

An unsupported version of Debian Linux is installed on the remote host.

Description

According to its version, Debian Linux is 8.x. It is, therefore, no longer maintained by its vendor or provider.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it may contain security vulnerabilities.

See Also

<https://www.debian.org/News/2018/20180601>

Solution

Upgrade to a version of Debian Linux that is currently supported.

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

Plugin Information

Published: 2024/07/03, Modified: 2025/03/26

Plugin Output

tcp/80/www

```
OS : Debian Linux 8.0
Security End of Life : June 17, 2018
Time since Security End of Life (Est.) : >= 7 years
```

10114 - ICMP Timestamp Request Remote Date Disclosure -

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

```
The difference between the local and remote clocks is -13 seconds.
```

18261 - Apache Banner Linux Distribution Disclosure -

Synopsis

The name of the Linux distribution running on the remote host was found in the banner of the web server.

Description

Nessus was able to extract the banner of the Apache web server and determine which Linux distribution the remote host is running.

Solution

If you do not wish to display this information, edit 'httpd.conf' and set the directive 'ServerTokens Prod' and restart Apache.

Risk Factor

None

Plugin Information

Published: 2005/05/15, Modified: 2025/03/31

Plugin Output

tcp/0

```
The Linux distribution detected was :  
- Debian 8.0 (jessie)
```

48204 - Apache HTTP Server Version -

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0030
XREF	IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2023/08/17

Plugin Output

tcp/80/www

```
URL : http://192.168.0.103/  
Version : 2.4.99  
Source : Server: Apache/2.4.10 (Debian)  
backported : 1  
os : ConvertedDebian
```

39521 - Backported Security Patch Detection (WWW) -

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote HTTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2015/07/07

Plugin Output

tcp/80/www

```
Give Nessus credentials to perform local checks.
```

45590 - Common Platform Enumeration (CPE) -

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>
<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2025/07/14

Plugin Output

```
tcp/0

Following application CPE's matched on the remote system :

cpe:/a:apache:http_server:2.4.10 -> Apache Software Foundation Apache HTTP Server
cpe:/a:apache:http_server:2.4.99 -> Apache Software Foundation Apache HTTP Server
```

54615 - Device Type -

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

Remote device type : general-purpose
Confidence level : 95

35716 - Ethernet Card Manufacturer Detection -

Synopsis

The manufacturer can be identified from the Ethernet OUI.

Description

Each ethernet MAC address starts with a 24-bit Organizationally Unique Identifier (OUI). These OUIs are registered by IEEE.

See Also

<https://standards.ieee.org/faqs/regauth.html>
<http://www.nessus.org/u?794673b4>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/02/19, Modified: 2020/05/13

Plugin Output

tcp/0

The following card manufacturers were identified :

08:00:27:BB:1A:A8 : PCS Systemtechnik GmbH

86420 - Ethernet MAC Addresses -

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

The following is a consolidated list of detected MAC addresses:
- 08:00:27:BB:1A:A8

10107 - HTTP Server Type and Version -

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/80/www

The remote web server type is :
Apache/2.4.10 (Debian)

24260 - HyperText Transfer Protocol (HTTP) Information -

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/80/www

Response Code : HTTP/1.1 301 Moved Permanently

Protocol version : HTTP/1.1
HTTP/2 TLS Support: No
HTTP/2 Cleartext Support: No
SSL : no
Keep-Alive : yes
Options allowed : (Not implemented)
Headers :

Date: Sun, 19 Apr 2026 09:55:37 GMT
Server: Apache/2.4.10 (Debian)
Location: http://dc-2/

```
Content-Length: 0
Keep-Alive: timeout=5, max=100
Connection: Keep-Alive
Content-Type: text/html; charset=UTF-8

Response Body :
```

11219 - Nessus SYN scanner -

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/80/www

```
Port 80/tcp was found to be open
```

19506 - Nessus Scan Information -

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2025/06/25

Plugin Output

tcp/0

```
Information about this scan :

Nessus version : 10.9.3
Nessus build : 20023
Plugin feed version : 202508200628
Scanner edition used : Nessus

ERROR: Your plugins have not been updated since 2025/8/20
Performing a scan with an older plugin set will yield out-of-date results and
produce an incomplete audit. Please run nessus-update-plugins to get the
newest vulnerability checks from Nessus.org.

Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : DC-2
Scan policy used : Advanced Scan
Scanner IP : 192.168.0.100
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 308.652 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialled checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 100
Max checks : 5
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/4/19 9:54 UTC
Scan duration : 419 sec
Scan for malware : no
```

209654 - OS Fingerprints Detected -

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

```
tcp/0

Following OS Fingerprints were found

Remote operating system : CentOS Linux 7 Linux Kernel 3.10
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 3.16 on Debian 8.0 (jessie)
Confidence level : 95
Method : HTTP
Type : general-purpose
Fingerprint : unknown

Remote operating system : Linux
Confidence level : 59
```



```
Method : SinFP
Type : general-purpose
Fingerprint : SinFP:
P1:B10113:F0x12:W29200:00204ffff:M1460:
P2:B10113:F0x12:W28960:00204ffff0402080affffff4445414401030307:M1460:
P3:B00000:F0x00:W0:00:M0
P4:191303_7_p=80
```

11936 - OS Identification -

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

```
tcp/0

Remote operating system : Linux Kernel 3.16 on Debian 8.0 (jessie)
Confidence level : 95
Method : HTTP

The remote host is running Linux Kernel 3.16 on Debian 8.0 (jessie)
```

22964 - Service Detection -

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2024/03/26

Plugin Output

```
tcp/80/www

A web server is running on this port.
```

25220 - TCP/IP Timestamps Supported -

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

104410 - Target Credential Status by Authentication Protocol - Failure for Provided Credentials -

Synopsis

Nessus was unable to log into the detected authentication protocol, using the provided credentials, in order to perform credentialed checks.

Description

Nessus failed to successfully authenticate directly to the remote target on an available authentication protocol. Nessus was able to connect to the remote port and identify that the service running on the port supports an authentication protocol, but Nessus failed to authenticate to the remote service using the provided credentials.

There may have been a failure in protocol negotiation or communication that prevented authentication from being attempted or all of the provided credentials for the authentication protocol may have been invalid. A protocol failure may indicate a compatibility issue with the protocol configuration. A protocol failure due to an environmental issue such as resource or congestion issues may also prevent valid credentials from being identified. See plugin output for error details.

Please note the following :

- This plugin reports per protocol, so it is possible for valid credentials to be provided for one protocol and not another. For example, authentication may succeed via SSH but fail via SMB, while no credentials were provided for an available SNMP service.
- Providing valid credentials for all available authentication protocols may improve scan coverage, but the value of successful authentication for a given protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol. For example, successful authentication via SSH is more valuable for Linux targets than for Windows targets, and likewise successful authentication via SMB is more valuable for Windows targets than for Linux targets.

Solution

Address the reported problem(s) so that credentialed checks can be executed.

Risk Factor

None

References

XREF IAVB:0001-B-0503

Plugin Information

Published: 2017/11/06, Modified: 2020/10/19

Plugin Output

tcp/7744

```
Nessus was unable to log into the following host for which
credentials have been provided :

Protocol : SSH
Port : 7744
Failure details :

- User : jerry
```

```
- Plugin : ssh_rate_limiting.nasl
Plugin ID : 122501
Plugin Name : SSH Rate Limited Device
Message :
Failed to authenticate using the supplied password.

- Plugin : netstat_portscan.nasl
Plugin ID : 14272
Plugin Name : Netstat Portscanner (SSH)
Message :
Failed to authenticate using the supplied password.

- Plugin : ssh_check_compression.nasl
Plugin ID : 104411
Plugin Name : SSH Compression Error Checking
Message :
Failed to authenticate using the supplied password.

- Plugin : ssh_get_info2.nasl
Plugin ID : 97993
Plugin Name : OS Identification and Installed Software Enumeration over SSH v2 (Using New SSH Library)
Message :
Failed to authenticate using the supplied password.
```

10287 - Traceroute Information -

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2023/12/04

Plugin Output

```
udp/0

For your information, here is the traceroute from 192.168.0.100 to 192.168.0.103 :
192.168.0.100
192.168.0.103

Hop Count: 1
```

Compliance 'FAILED'

Compliance 'SKIPPED'

Compliance 'PASSED'

Compliance 'INFO', 'WARNING', 'ERROR'

Remediations

Suggested Remediations

© 2026 Tenable™, Inc. All rights reserved.