tenable Nessus

Report generated by Tenable Nessus™

DC-3

Tue, 13 Oct 2026 16:36:11 UTC

TABLE OF CONTENTS

Vulnerabilities by Plugin

- 10114 (1) - ICMP Timestamp Request Remote Date Disclosure
- 10107 (1) - HTTP Server Type and Version
- 10287 (1) - Traceroute Information
- 11936 (1) - OS Identification
- 18261 (1) - Apache Banner Linux Distribution Disclosure
- 19506 (1) - Nessus Scan Information
- 24260 (1) - HyperText Transfer Protocol (HTTP) Information
- 35716 (1) - Ethernet Card Manufacturer Detection
- 39521 (1) - Backported Security Patch Detection (WWW)
- 45590 (1) - Common Platform Enumeration (CPE)
- 48204 (1) - Apache HTTP Server Version
- 54615 (1) - Device Type
- 86420 (1) - Ethernet MAC Addresses
- 91822 (1) - Database Authentication Failure(s) for Provided Credentials
- 104410 (1) - Target Credential Status by Authentication Protocol - Failure for Provided Credentials
- 106658 (1) - JQuery Detection
- 135860 (1) - WMI Not Available
- 209654 (1) - OS Fingerprints Detected

Compliance 'FAILED'

Compliance 'SKIPPED'

Compliance 'PASSED'

Compliance 'INFO', 'WARNING', 'ERROR'

Remediations

- Suggested Remediations

Vulnerabilities by Plugin

Collapse All | Expand All

10114 (1) - ICMP Timestamp Request Remote Date Disclosure -

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

192.168.0.110 (icmp/0)

```
The remote clock is synchronized with the local clock.
```

10107 (1) - HTTP Server Type and Version -

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

192.168.0.110 (tcp/80)

```
The remote web server type is :

Apache/2.4.18 (Ubuntu)
```

10287 (1) - Traceroute Information -

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2023/12/04

Plugin Output

192.168.0.110 (udp/0)

```
For your information, here is the traceroute from 192.168.0.114 to 192.168.0.110 :
192.168.0.114
192.168.0.110

Hop Count: 1
```

11936 (1) - OS Identification -

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

192.168.0.110 (tcp/0)

```
Remote operating system : Ubuntu 16.x
Confidence level : 85
Method : HTTP

The remote host is running Ubuntu 16.x
```

18261 (1) - Apache Banner Linux Distribution Disclosure -

Synopsis

The name of the Linux distribution running on the remote host was found in the banner of the web server.

Description

Nessus was able to extract the banner of the Apache web server and determine which Linux distribution the remote host is running.

Solution

If you do not wish to display this information, edit 'httpd.conf' and set the directive 'ServerTokens Prod' and restart Apache.

Risk Factor

None

Plugin Information

Published: 2005/05/15, Modified: 2025/03/31

Plugin Output

192.168.0.110 (tcp/0)

```
The Linux distribution detected was :
- Ubuntu 16.04 (xenial)
- Ubuntu 16.10 (yakkety)
```

19506 (1) - Nessus Scan Information -

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2025/06/25

Plugin Output

192.168.0.110 (tcp/0)

```
Information about this scan :

Nessus version : 10.9.3
Nessus build : 20023
Plugin feed version : 202508200628
Scanner edition used : Nessus

ERROR: Your plugins have not been updated since 2025/8/20
Performing a scan with an older plugin set will yield out-of-date results and
produce an incomplete audit. Please run nessus-update-plugins to get the
newest vulnerability checks from Nessus.org.

Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : DC-3
Scan policy used : Advanced Scan
Scanner IP : 192.168.0.114
Port scanner(s) : nessus_syn_scanner
Port range : 65535
Ping RTT : 120.438 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 100
Max checks : 5
Recv timeout : 5
Backports : Detected
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/10/13 16:33 UTC
Scan duration : 137 sec
Scan for malware : no
```

24260 (1) - HyperText Transfer Protocol (HTTP) Information -

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

192.168.0.110 (tcp/80)

```
Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1
HTTP/2 TLS Support: No
HTTP/2 Cleartext Support: No
SSL : no
Keep-Alive : yes
Options allowed : (Not implemented)
Headers :

Date: Tue, 13 Oct 2026 16:35:04 GMT
Server: Apache/2.4.18 (Ubuntu)
Expires: Wed, 17 Aug 2005 00:00:00 GMT
Last-Modified: Tue, 13 Oct 2026 16:35:05 GMT
Cache-Control: no-store, no-cache, must-revalidate, post-check=0, pre-check=0
Pragma: no-cache
Vary: Accept-Encoding
Content-Length: 7097
Keep-Alive: timeout=5, max=100
Connection: Keep-Alive
Content-Type: text/html; charset=utf-8

Response Body :

<pre>
</pre>

<!DOCTYPE html>
<html lang="en-gb" dir="ltr">
<head>
<meta name="viewport" content="width=device-width, initial-scale=1.0" />
<meta charset="utf-8" />
<base href="http://192.168.0.110/" />
<meta name="description" content="A website for DC-3" />
<meta name="generator" content="Joomla! - Open Source Content Management" />
<title>Home</title>
<link href="/index.php?format=feed&amp;type=rss" rel="alternate" type="application/rss+xml" title="RSS 2.0" />
<link href="/index.php?format=feed&amp;type=atom" rel="alternate" type="application/atom+xml" title="Atom 1.0" />
<link href="/templates/protostar/favicon.ico" rel="shortcut icon" type="image/vnd.microsoft.icon" />
<link href="/templates/protostar/css/template.css?18218c33b7d09f844d70f84b50bb7b72" rel="stylesheet" />
<link href="//fonts.googleapis.com/css?family=Open+Sans" rel="stylesheet" />
<style>

h1, h2, h3, h4, h5, h6, .site-title {
font-family: 'Open Sans', sans-serif;
}
</style>
<script type="application/json" class="joomla-script-options new">{"system.keepalive":
{"interval":840000,"uri":"\/index.php\/component\/ajax\/?format=json"}}</script>
<script src="/media/jui/js/jquery.min.js?18218c33b7d09f844d70f84b50bb7b72"></script>
<script src="/media/jui/js/jquery-noconflict.js?18218c33b7d09f844d70f84b50bb7b72"></script>
<script src="/media/jui/js/jquery-migrate.min.js?18218c33b7d09f844d70f84b50bb7b72"></script>
<script src="/media/system/js/caption.js?18218c33b7d09f844d70f84b50bb7b72"></script>
<script src="/media/jui/js/bootstrap.min.js?18218c33b7d09f844d70f84b50bb7b72"></script>
<script src="/templates/protostar/js/template.js?18218c33b7d09f844d70f84b50bb7b72"></script>
<!--[if lt IE 9]><script src="/media/jui/js/html5.js?18218c33b7d09f844d70f84b50bb7b72"></script><![endif]-->
<script src="/media/system/js/core.js?18218c33b7d09f844d70f84b50bb7b72"></script>
<!--[if lt IE 9]><script src="/media/system/js/polyfill.event.js?18218c33b7d09f844d70f84b50bb7b72"></script><![endif]-->
<script src="/media/system/js/keepalive.js?18218c33b7d09f844d70f84b50bb7b72"></script>
<script>
jQuery(window).on('load', function() {
new JCaption('img.caption');
});jQuery(function($){ $(".hasTooltip").tooltip({"html": true,"container": "body"}); });
</script>

</head>
<body class="site com_content view-featured no-layout no-task itemid-101">
<!-- Body -->
<div class="body" id="top">
<div class="container">
<!-- Header -->
<header class="header" role="banner">
<div class="header-inner clearfix">
<a class="brand pull-left" href="/">
```

```
<span class="site-title" title="DC-3">DC-3</span></a>
<div class="header-search pull-right">

</div>
</div>
</header>

<div class="row-fluid">
<main id="content" role="main" class="span9">
<!-- Begin Content -->

<div id="system-message-container">
</div>

<div class="blog-featured" itemscope itemtype="https://schema.org/Blog">
<div class="page-header">
<h1>
Home</h1>
</div>

<div class="items-leading clearfix">
<div class="leading-0 clearfix"
itemprop="blogPost" itemscope itemtype="https://schema.org/BlogPosting">


<h2 class="item-title" itemprop="headline">
<a href="/index.php/2-uncategorised/1-welcome" itemprop="url">
Welcome to DC-3</a>
</h2>



<dl class="article-info muted">


<dt class="article-info-term">
Details</dt>

<dd class="createdby" itemprop="author" itemscope itemtype="https://schema.org/Person">
Written by <span itemprop="name">admin</span></dd>









</dl>



<h3>Welcome to DC-3.</h3>
<p>This time, there is only one flag, one entry point and no clues.</p>
<p>To get the flag, you'll obviously have to gain root privileges.</p>
<p>How you get to be root is up to you - and, obviously, the system.</p>
<p>Good luck - and I hope you enjoy this little challenge.  :-)</p>



</div>
</div>



</div>


<ul itemscope itemtype="https://schema.org/BreadcrumbList" class="breadcrumb">
<li>
You are here:  
</li>

<li itemprop="itemListElement" itemscope itemtype="https://schema.org/ListItem" class="active">
<span itemprop="name">
Home</span>
<meta itemprop="position" content="1">
</li>
</ul>

<!-- End Content -->
</main>
<div id="aside" class="span3">
<!-- Begin Right Sidebar -->
<div class="well _menu"><h3 class="page-header">Main Menu</h3><ul class="nav menu">
<li class="item-101 default current active"><a href="/index.php" >Home</a></li></ul>
</div><div class="well "><h3 class="page-header">Login Form</h3><form action="/index.php" method="post" id="login-form" class="form-
inline">
<div class="userdata">
<div id="form-login-username" class="control-group">
<div class="controls">
<div class="input-prepend">
<span class="add-on">
<span class="icon-user hasTooltip" title="Username"></span>
<label for="modlgn-username" class="element-invisible">Username</label>
</span>
<input id="modlgn-username" type="text" name="username" class="input-small" tabindex="0" size="18" placeholder="Username" />
</div>
```

```
</div>
</div>
<div id="form-login-password" class="control-group">
<div class="controls">
<div class="input-prepend">
<span class="add-on">
<span class="icon-lock hasTooltip" title="Password">
</span>
<label for="modlgn-passwd" class="element-invisible">Password</label>
</span>
<input id="modlgn-passwd" type="password" name="password" class="input-small" tabindex="0" size="18" placeholder="Password" />
</div>
</div>
</div>
<div id="form-login-remember" class="control-group checkbox">
<label for="modlgn-remember" class="control-label">Remember Me</label> <input id="modlgn-remember" type="checkbox" name="remember"
class="inputbox" value="yes"/>
</div>
<div id="form-login-submit" class="control-group">
<div class="controls">
<button type="submit" tabindex="0" name="Submit" class="btn btn-primary login-button">Log in</button>
</div>
</div>
<ul class="unstyled">
<li>
<a href="/index.php/component/users/?view=remind&amp;Itemid=101">
Forgot your username?</a>
</li>
<li>
<a href="/index.php/component/users/?view=reset&amp;Itemid=101">
Forgot your password?</a>
</li>
</ul>
<input type="hidden" name="option" value="com_users" />
<input type="hidden" name="task" value="user.login" />
<input type="hidden" name="return" value="aHR0cDovLzE5Mi4xNjguMC4xMTAv" />
<input type="hidden" name="62c765a56f0d5b80c727be1275fc88f8" value="1" /></div>
</form>
</div>
<!-- End Right Sidebar -->
</div>
</div>
</div>
</div>
<!-- Footer -->
<footer class="footer" role="contentinfo">
<div class="container">
<hr />

<p class="pull-right">
<a href="#top" id="back-top">
Back to Top</a>
</p>
<p>
&copy; 2026 DC-3</p>
</div>
</footer>

</body>
</html>
```

35716 (1) - Ethernet Card Manufacturer Detection -

Synopsis

The manufacturer can be identified from the Ethernet OUI.

Description

Each ethernet MAC address starts with a 24-bit Organizationally Unique Identifier (OUI). These OUIs are registered by IEEE.

See Also

https://standards.ieee.org/faqs/regauth.html
http://www.nessus.org/u?794673b4

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/02/19, Modified: 2020/05/13

Plugin Output

192.168.0.110 (tcp/0)

```
The following card manufacturers were identified :

08:00:27:94:3F:DD : PCS Systemtechnik GmbH
```

39521 (1) - Backported Security Patch Detection (WWW) -

Synopsis

Security patches are backported.

Description

Security patches may have been 'backported' to the remote HTTP server without changing its version number.

Banner-based checks have been disabled to avoid false positives.

Note that this test is informational only and does not denote any security problem.

See Also

https://access.redhat.com/security/updates/backporting/?sc_cid=3093

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/06/25, Modified: 2015/07/07

Plugin Output

192.168.0.110 (tcp/80)

```
Give Nessus credentials to perform local checks.
```

45590 (1) - Common Platform Enumeration (CPE) -

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

http://cpe.mitre.org/
https://nvd.nist.gov/products/cpe

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2025/07/14

Plugin Output

192.168.0.110 (tcp/0)

```
Following application CPE's matched on the remote system :
```

```
cpe:/a:apache:http_server:2.4.18 -> Apache Software Foundation Apache HTTP Server
cpe:/a:apache:http_server:2.4.99 -> Apache Software Foundation Apache HTTP Server
cpe:/a:jquery:jquery:1.12.4 -> jQuery
```

48204 (1) - Apache HTTP Server Version -

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

https://httpd.apache.org/

Solution

n/a

Risk Factor

None

References

XREF	IAVT:0001-T-0030
XREF	IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2023/08/17

Plugin Output

192.168.0.110 (tcp/80)

```
URL : http://192.168.0.110/
Version : 2.4.99
Source : Server: Apache/2.4.18 (Ubuntu)
backported : 1
os : ConvertedUbuntu
```

54615 (1) - Device Type -

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

192.168.0.110 (tcp/0)

```
Remote device type : general-purpose
Confidence level : 85
```

86420 (1) - Ethernet MAC Addresses -

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

192.168.0.110 (tcp/0)

```
The following is a consolidated list of detected MAC addresses:
- 08:00:27:94:3F:DD
```

91822 (1) - Database Authentication Failure(s) for Provided Credentials -

Synopsis

Database credentialed checks for one or more detected database systems have been disabled.

Description

Nessus was unable to log into one or more detected database systems for which credentials have been provided in order to perform authenticated checks.

Solution

Address the problem(s) so that the credentialed checks can be executed.

Risk Factor

None

Plugin Information

Published: 2016/06/24, Modified: 2017/12/19

Plugin Output

192.168.0.110 (tcp/0)

```
Nessus was unable to log into the following database systems for which
credentials have been provided :

Database : MySQL
Port : 3306
Failure details :
Error establishing connection to MySQL server on port 3306.
```

104410 (1) - Target Credential Status by Authentication Protocol - Failure for Provided Credentials -

Synopsis

Nessus was unable to log into the detected authentication protocol, using the provided credentials, in order to perform credentialed checks.

Description

Nessus failed to successfully authenticate directly to the remote target on an available authentication protocol. Nessus was able to connect to the remote port and identify that the service running on the port supports an authentication protocol, but Nessus failed to authenticate to the remote service using the provided credentials.

There may have been a failure in protocol negotiation or communication that prevented authentication from being attempted or all of the provided credentials for the authentication protocol may have been invalid. A protocol failure may indicate a compatibility issue with the protocol configuration. A protocol failure due to an environmental issue such as resource or congestion issues may also prevent valid credentials from being identified. See plugin output for error details.

Please note the following :

- This plugin reports per protocol, so it is possible for valid credentials to be provided for one protocol and not another. For example, authentication may succeed via SSH but fail via SMB, while no credentials were provided for an available SNMP service.

- Providing valid credentials for all available authentication protocols may improve scan coverage, but the value of successful authentication for a given protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol. For example, successful authentication via SSH is more valuable for Linux targets than for Windows targets, and likewise successful authentication via SMB is more valuable for Windows targets than for Linux targets.

Solution

Address the reported problem(s) so that credentialed checks can be executed.

Risk Factor

None

References

XREF IAVB:0001-B-0503

Plugin Information

Published: 2017/11/06, Modified: 2020/10/19

Plugin Output

192.168.0.110 (tcp/3306)

```
Nessus was unable to log into the following host for which
credentials have been provided :

Database : MySQL
Port : 3306
Failure details :
admin > Error establishing connection to MySQL server on port 3306.
```

106658 (1) - JQuery Detection -

Synopsis

The web server on the remote host uses JQuery.

Description

Nessus was able to detect JQuery on the remote host.

See Also

https://jquery.com/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/02/07, Modified: 2024/02/08

Plugin Output

192.168.0.110 (tcp/80)

```
URL : http://192.168.0.110/media/jui/js/jquery.min.js?18218c33b7d09f844d70f84b50bb7b72
Version : 1.12.4
```

135860 (1) - WMI Not Available -

Synopsis

WMI queries could not be made against the remote host.

Description

WMI (Windows Management Instrumentation) is not available on the remote host over DCOM. WMI queries are used to gather information about the remote host, such as its current state, network interface configuration, etc.

Without this information Nessus may not be able to identify installed software or security vunerabilities that exist on the remote host.

See Also

https://docs.microsoft.com/en-us/windows/win32/wmisdk/wmi-start-page

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2020/04/21, Modified: 2025/07/21

Plugin Output

192.168.0.110 (tcp/445)

```
Can't connect to the 'root\CIMV2' WMI namespace.
```

209654 (1) - OS Fingerprints Detected -

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, “OS Identification”, the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

192.168.0.110 (tcp/0)

```
Following OS Fingerprints were found

Remote operating system : Ubuntu 16.x
Confidence level : 85
Method : HTTP
Type : general-purpose
Fingerprint : unknown
```

Compliance 'FAILED'

Compliance 'SKIPPED'

Compliance 'PASSED'

Compliance 'INFO', 'WARNING', 'ERROR'

Remediations

Suggested Remediations

© 2026 Tenable™, Inc. All rights reserved.