

Optimization for Machine Learning

Lecture 12: Compression (with Error-Feedback)

Sebastian Stich

CISPA – <https://cms.cispa.saarland/optml24/>

July 9, 2024

Projects

Project: Final steps

- ▶ Poster printing: please send your poster in pdf format to Yuan Gao (yuan.gao@cispa.de) before Monday, July 15, 8am.
- ▶ (You can also print the poster yourself. We can reimburse the costs up to 20 EUR in exchange of a proper receipt.)
- ▶ Upload the final report by June 26 to CMS (you can make adjustments after the poster presentation, and take suggestions/comments into account).

Lecture: July 16

- ▶ 16:15h, Research Talk by Kumar Kshitij Patel, (PhD Student at TTIC).
- ▶ 17:15-18:00h, Poster Session.

Exam Factsheet

- ▶ 2.5 hours
- ▶ closed book
 - ▶ you can bring **one double-sided A4 page** cheat sheet
- ▶ materials
 - ▶ all topics covered in the lecture
- ▶ practice exams
 - ▶ link to old exams posted on the course website
 - ▶ note that for these exams the syllabus might have been (slightly) different

Exam Registration (on CMS/LSF)

- ▶ **mandatory, latest 1 week before the exam!**
- ▶ please register early, the deadline is strict even if there are technical problems (on either side)
- ▶ the registration link should work for all that have finalized their project
- ▶ if you cannot register (but think you should be able to) please reach out ASAP!

Evaluation (UdS)

Please fill out the evaluation forms provided by UdS:


Lecture: Link to the Evaluation form for the Lecture

Exercises: Link to the Evaluation form for the Exercises

(you can click on these links, or you find the same link also on the course material page)

Lecture 12


Distributed Training



- ▶ limited bandwidth connections
- ▶ high latency

Communication Bottleneck

$$\text{SGD: } x_{t+1} = x_t - \gamma g(x_t)$$



- We need to communicate \mathbb{R}^d vectors (model parameters, or gradients) in every communication round.

Q: Can we compress these messages?

Lecture Outline

Setting and Baseline

Compression

Quantization

Error Feedback

Training Objective

$$\min_{\mathbf{x} \in \mathbb{R}^d} \left[f(\mathbf{x}) := \frac{1}{n} \sum_{i=1}^n \underbrace{f_i(\mathbf{x})}_{\text{data } \mathcal{D}_i \text{ on client } i} \right] \quad f_i(\mathbf{x}) = \begin{cases} \mathbb{E}_{\xi \sim \mathcal{D}_i} F(\mathbf{x}, \xi) \\ \frac{1}{m} \sum_{j=1}^m f_{ij}(\mathbf{x}) \end{cases}$$

- For simplicity, we will again first discuss the homogeneous setting ($f_i = f_j, \forall i, j$).

Simplified Scenario:

- Consider $n = 1$ worker device, that communicates with a server.

Baseline: Stochastic Gradient Descent

Stochastic Gradient Descent (SGD):

γ stepsize

$$\underbrace{\mathbf{g}_t = \mathbf{g}(\mathbf{x})}_{\text{uniform data sample}}$$

$$\mathbf{x}_{t+1} := \underbrace{\mathbf{x}_t - \gamma \mathbf{g}_t}_{\text{model update}}$$

Assumptions:

- ▶ $f: \mathbb{R}^d \rightarrow \mathbb{R}$ convex and L -smooth
- ▶ $\mathbb{E}[\mathbf{g}(\mathbf{x})] = \nabla f(\mathbf{x}), \forall x \in \mathbb{R}^d$
- ▶ $\mathbb{E} \|\mathbf{g}(\mathbf{x}) - \nabla f(\mathbf{x})\|^2 \leq \sigma^2, \forall x \in \mathbb{R}^d$

Convergence: the iteration complexity to reach $\mathbb{E} f(\mathbf{x}_{\text{out}}) - f^* \leq \epsilon$ is

$$\mathcal{O} \left(\frac{\sigma^2}{\epsilon^2} + \frac{L}{\epsilon} \right) \cdot R_0$$

with $R_0 = \|\mathbf{x}_0 - \mathbf{x}^*\|^2$.

Lecture Outline

Setting and Baseline

Compression


Quantization

Error Feedback

Motivation

- ▶ Instead of sending the full gradient vector $\mathbf{g}_t \in \mathbb{R}^d$ from the worker to the server, can we compress the gradient?

Schematic:



Compressor:

- ▶ $\mathcal{Q}: \mathbb{R}^d \rightarrow \mathcal{X}$ (possibly **lossy compression**)
- ▶ $\mathcal{Q}^{-1}: \mathcal{X} \rightarrow \mathbb{R}^d$

Convention:

- ▶ We will often use the shorthand $\mathcal{Q}(\mathbf{g})$ to denote $\mathcal{Q}^{-1}(\mathcal{Q}(\mathbf{g})) \in \mathbb{R}^d$.

Properties

Motivation:

- Suppose we want to study **compressed SGD**:

$$\mathbf{x}_{t+1} = \mathbf{x}_t - \gamma \mathcal{Q}(\mathbf{g}_t)$$

same compression of \mathbf{g}_t

- It would be very convenient if $\mathbb{E}[\mathcal{Q}(\mathbf{g})] = \nabla f(\mathbf{x})$.

Definition 12.1 (Unbiased ω -quantization)

A compressor $\mathcal{Q}: \mathbb{R}^d \rightarrow \mathbb{R}^d$ is an unbiased $\omega \geq 0$ quantizer, if

$$\mathbb{E}_{\mathcal{Q}} \mathcal{Q}(\mathbf{x}) = \mathbf{x}, \quad \forall \mathbf{x} \in \mathbb{R}^d \quad \text{unbiased}$$

and

$$\mathbb{E}_{\mathcal{Q}} \|\mathcal{Q}(\mathbf{x}) - \mathbf{x}\|^2 \leq \omega \|\mathbf{x}\|^2, \quad \forall \mathbf{x} \in \mathbb{R}^d.$$

Examples

$$\mathbf{x} \in \mathbb{R}^d = \begin{pmatrix} x_1 \\ x_2 \\ \vdots \\ x_k \\ \vdots \\ x_d \end{pmatrix} \left. \vphantom{\begin{pmatrix} x_1 \\ x_2 \\ \vdots \\ x_k \\ \vdots \\ x_d \end{pmatrix}} \right\} k \text{ coordinates} \Rightarrow Q(\mathbf{x}) = \begin{pmatrix} 0 \\ 0 \\ \vdots \\ x_i \\ \vdots \\ 0 \end{pmatrix} \cdot \frac{d}{k}$$

to make it unbiased!

► random sparsification

$Q(\mathbf{x}) = \frac{d}{k} \cdot M \odot \mathbf{x}$, where $M \in \{0, 1\}^d$ is a mask that selects k random coordinates

$$E[Q(x)] = \sum_{\substack{i \\ \text{coordinate } i \\ \text{is picked or not}}} \frac{k}{d} \cdot (x_i) \cdot \frac{d}{k} + \left(1 - \frac{k}{d}\right) \cdot 0 = x_i$$

Exercise: compute w !

► quantization

$$Q(\mathbf{x}) = \text{sign}(\mathbf{x}) \cdot \|\mathbf{x}\| \cdot \frac{1}{s} \cdot \text{round}\left(s \frac{|\mathbf{x}|}{\|\mathbf{x}\|}\right),$$

$$\text{where round}(x) = \begin{cases} \lceil x \rceil, & \text{with probability } x - \lfloor x \rfloor \quad 30\% \\ \lfloor x \rfloor, & \text{with probability } \lceil x \rceil - x \quad 70\% \end{cases}$$

$$\text{Expectation: } 0.7 \cdot 1 + 0.3 \cdot 2 = 1.3$$

$$x = 1.3$$

Quantized SGD [AGL⁺17] $\mathcal{Q}_{\text{quantized}} \text{SGD}$

Input: $\mathbf{x}_0 \in \mathbb{R}^d$, ω -quantizer \mathcal{Q} , $\gamma > 0$:

$$\mathbf{x}_{t+1} = \mathbf{x}_t - \gamma \mathcal{Q}(\mathbf{g}(\mathbf{x})).$$

Theorem 12.2

Let $f: \mathbb{R}^d \rightarrow \mathbb{R}$ be *convex*, L -smooth and let $R_0 = \|\mathbf{x}_0 - \mathbf{x}^*\|^2$ and $\gamma \leq \frac{1}{2L(1+\omega)}$.

Then there exists a stepsize γ such that $\frac{1}{T} \sum_{t=0}^{T-1} (\mathbb{E} f(\mathbf{x}_t) - f^*) \leq \epsilon$ for

$$T = \mathcal{O} \left(\frac{\sigma^2}{\epsilon^2} + \frac{L}{\epsilon} \right) \cdot R_0 \cdot (1 + \omega)$$

iterations of quantized SGD with an ω -quantizer.

↑
more iterations!

Proof

We expand, and use the property of the ω -quantizer:

$$\begin{aligned}\mathbb{E} \|\mathbf{x}_{t+1} - \mathbf{x}^*\|^2 &= \mathbb{E} \|\mathbf{x}_t - \mathbf{x}^*\|^2 - 2\gamma \mathbb{E} \mathcal{Q}(\mathbf{g}(\mathbf{x}_t))^\top (\mathbf{x}_t - \mathbf{x}^*) + \gamma^2 \mathbb{E} \|\mathcal{Q}(\mathbf{g}(\mathbf{x}_t))\|^2 \\ &\leq \mathbb{E} \|\mathbf{x}_t - \mathbf{x}^*\|^2 - 2\gamma \mathbb{E} \nabla f(\mathbf{x}_t)^\top (\mathbf{x}_t - \mathbf{x}^*) + \gamma^2 \underbrace{(1 + \omega)}_{\text{unbiased quant!}} \left(\|\nabla f(\mathbf{x}_t)\|^2 + \sigma^2 \right) \\ &\leq \mathbb{E} \|\mathbf{x}_t - \mathbf{x}^*\|^2 - 2\gamma (\mathbb{E} f(\mathbf{x}_t) - f^*) + \gamma^2 (1 + \omega) (2L(\mathbb{E} f(\mathbf{x}_t) - f^*) + \sigma^2)\end{aligned}$$

with convexity and smoothness. Now, by $\gamma \leq \frac{1}{2(1+\omega)L}$,

$$\gamma (\mathbb{E} f(\mathbf{x}_t) - f^*) \leq \mathbb{E} \|\mathbf{x}_t - \mathbf{x}^*\|^2 - \mathbb{E} \|\mathbf{x}_{t+1} - \mathbf{x}^*\|^2 + \gamma^2 (1 + \omega) \sigma^2.$$

With the usual procedure, summing over $t = 0, \dots, T-1$, dividing by T and γ :

$$\frac{1}{T} \sum_{t=0}^{T-1} (\mathbb{E} f(\mathbf{x}_t) - f^*) \leq \frac{R_0}{\gamma} + \underbrace{\gamma(1 + \omega)\sigma^2}$$

and the theorem follows by minimizing in γ .

Discussion

- ▶ While quantization decreases the per-iteration communication cost, the worst-case complexity bounds to not show a total speedup, when taking the full cost of the optimization (iterations \times cost per iteration) into account.
- ▶ In practice, a speedup can often be still observed.
- ▶ In practice, the 'top- k ' compressor often significantly outperforms 'random- k ' (which is supported by theory).

Q: Can we compressed SGD converge with a provable speedup, supporting also biased compressors such as 'top- k '?

Biased Compressors

Definition 12.3 ((biased) δ -compressor)

A compressor $\mathcal{C}: \mathbb{R}^d \rightarrow \mathbb{R}^d$ is an $\delta > 0$ compressor, if

$$\mathbb{E}_{\mathcal{C}} \|\mathcal{C}(\mathbf{x}) - \mathbf{x}\|^2 \leq (1 - \delta) \|\mathbf{x}\|^2, \quad \forall \mathbf{x} \in \mathbb{R}^d.$$

- ▶ Note that we do not impose a condition for unbiasedness.
- ▶ If $\mathcal{Q}(\mathbf{x})$ is a ω quantizer, then $\frac{1}{1+\omega} \mathcal{Q}(\mathbf{x})$ is a $\delta = \frac{1}{1+\omega}$ compressor (exercise).

Examples

- ▶ random sparsification

$\mathcal{C}(\mathbf{x}) = M \odot \mathbf{x}$, where $M \in \{0, 1\}^d$ is a mask that selects k random coordinates.

- ▶ top- k sparsification

$\mathcal{C}(\mathbf{x}) = \text{top}_k(\mathbf{x})$

$d = \frac{1}{d}$, d dimension

$k=1$ pick index i , s.t. $|x_i| \geq |x_j| \forall j \neq i$

$$\mathbf{x} = \begin{pmatrix} x_1 \\ \vdots \\ x_i \\ \vdots \\ x_d \end{pmatrix} \rightsquigarrow \mathcal{C}(\mathbf{x}) = \begin{pmatrix} 0 \\ \vdots \\ x_i \\ \vdots \\ 0 \end{pmatrix} \quad \|\text{top}_1(\mathbf{x}) - \mathbf{x}\|^2 = \sum_{i=1}^d (\text{top}_1(\mathbf{x}) - x_i)^2 = \sum_{i \neq \text{top 1 coordinate}} (x_i)^2$$

- ▶ rank- k approximation

- ▶ arbitrary black box compressors: Zip, JPEG, etc.

$$\leq \left(1 - \frac{1}{d}\right) \cdot \sum_{i=1}^d (x_i)^2 = \left(1 - \frac{1}{d}\right) \cdot \|\mathbf{x}\|^2$$

Error Feedback SGD/Error Compensated SGD

Input: $\mathbf{x}_0 \in \mathbb{R}^d$, stepsize $\gamma > 0$, correction buffer $\mathbf{e}_0 = \mathbf{0} \in \mathbb{R}^d$. At iteration t :

$$\mathbf{g}_t = \mathbf{g}(\mathbf{x}_t) \quad (\text{stochastic gradient})$$

$$\mathbf{v}_t = \mathcal{C}(\mathbf{e}_t + \gamma \mathbf{g}_t) \quad (\text{compressed \& error compensated update})$$

$$\mathbf{x}_{t+1} = \mathbf{x}_t - \mathbf{v}_t$$

$$\mathbf{e}_{t+1} = \mathbf{e}_t + \underbrace{\gamma \mathbf{g}_t - \mathbf{v}_t}_{\text{compression error}} \quad (\text{tracking the compression error})$$

Convergence

Theorem 12.4 ([SCJ18, SK20])

Let $f: \mathbb{R}^d \rightarrow \mathbb{R}$ be *convex, L -smooth* and let $R_0 = \|\mathbf{x}_0 - \mathbf{x}^*\|^2$ and $\gamma \leq \frac{\delta}{10L}$. Then there exists a stepsize γ such that $\frac{1}{T} \sum_{t=0}^{T-1} (\mathbb{E} f(\mathbf{x}_t) - f^*) \leq \epsilon$ for

$$T = \mathcal{O} \left(\frac{\sigma^2}{\epsilon^2} + \underbrace{\frac{\sqrt{(1-\delta)L\sigma^2}}{\epsilon^{3/2}\delta}}_{\text{"ignore"}} + \frac{L}{\delta\epsilon} \right) \cdot R_0,$$

iterations of error-compensated SGD with an δ -compressor.

- ▶ The compressor quality δ only impacts the optimization term, but not the stochastic term.
- ▶ For instance, for a compressor with $\delta = \frac{1}{1+\omega}$, the speedup can reach a factor of $(1+\omega)$ in comparison to quantization without error feedback (with the same per-iteration communication costs).

Convergence

- The proof of Theorem 12.4 follows a similar template as the proof for asynchronous SGD/Hogwild. However, as the technical details are somewhat more involved, we leave the full prove as an **exercise** and prove here a variant under stronger assumptions:

Theorem 12.5

Let $f: \mathbb{R}^d \rightarrow \mathbb{R}$ be convex, L -smooth and let $R_0 = \|\mathbf{x}_0 - \mathbf{x}^*\|^2$ and $\gamma \leq \frac{1}{4L}$. Additionally, assume the stochastic gradients are bounded, $\mathbb{E} \|\mathbf{g}_t\|^2 \leq B^2, \forall t$. Then there exists a stepsize γ such that $\frac{1}{T} \sum_{t=0}^{T-1} (\mathbb{E} f(\mathbf{x}_t) - f^*) \leq \epsilon$ for

$$T = \mathcal{O} \left(\frac{B^2}{\epsilon^2} + \frac{\sqrt{(1-\delta)LB^2}}{\epsilon^{3/2}\delta} + \frac{L}{\epsilon} \right) \cdot R_0,$$

δ is hidden in the assumption

iterations of error-compensated SGD with an δ -compressor.

- Note: the strong condition $\mathbb{E} \|\mathbf{g}_t\|^2 \leq B^2$ allow us to relax the condition on the stepsize ($\gamma \leq \frac{\delta}{10L}$ in Theorem 4, vs. $\gamma \leq \frac{1}{4L}$ in Theorem 5).

Proof I: Virtual Sequence

For the analysis, it will be convenient to define a sequence of **virtual** iterates $\tilde{\mathbf{x}}_t$. We define

$$\tilde{\mathbf{x}}_t = \mathbf{x}_t - \mathbf{e}_t$$

with $\tilde{\mathbf{x}}_0 = \mathbf{x}_0$ (note that $\mathbf{e}_0 = \mathbf{0}$). We observe that

$$\tilde{\mathbf{x}}_{t+1} = \mathbf{x}_{t+1} - \mathbf{e}_{t+1} = (\mathbf{x}_t - \mathbf{v}_t) - (\mathbf{e}_t + \gamma \mathbf{g}_t - \mathbf{v}_t) = \tilde{\mathbf{x}}_t - \gamma \mathbf{g}_t.$$

Proof II: Technical Lemmas

Lemma 12.6 (Decrease)

For $\gamma \leq \gamma_{\text{crit}} = \frac{1}{4L}$ it holds

$$\begin{aligned}\mathbb{E} \|\tilde{\mathbf{x}}_{t+1} - \mathbf{x}^*\|^2 &\leq \mathbb{E} \|\tilde{\mathbf{x}}_t - \mathbf{x}^*\|^2 - \frac{\gamma}{2} (\mathbb{E} f(\mathbf{x}_t) - f^*) + \gamma^2 \sigma^2 + 2L\gamma \mathbb{E} \|\mathbf{x}_t - \tilde{\mathbf{x}}_t\|^2 \\ &\quad \left(\leq \mathbb{E} \|\tilde{\mathbf{x}}_t - \mathbf{x}^*\|^2 - \frac{\gamma}{2} (\mathbb{E} f(\mathbf{x}_t) - f^*) + \gamma^2 B^2 + 2L\gamma \mathbb{E} \|\mathbf{x}_t - \tilde{\mathbf{x}}_t\|^2 \right).\end{aligned}$$

- We use $\sigma^2 \leq B^2$. The first equation can also be used in the proof of Theorem 4 (see exercises).

Lemma 12.7 (Difference)

With the notation for $R_t = \|\mathbf{x}_t - \tilde{\mathbf{x}}_t\|^2$, it holds

$$\mathbb{E} R_t \leq \frac{4(1 - \delta)\gamma^2 B^2}{\delta^2}$$

Proof III: Combine the Lemmas

We now plug Lemma 12.6 into the statement of Lemma 12.7:

$$\mathbb{E} \|\tilde{\mathbf{x}}_{t+1} - \mathbf{x}^*\|^2 \leq \mathbb{E} \|\tilde{\mathbf{x}}_t - \mathbf{x}^*\|^2 - \frac{\gamma}{2}(\mathbb{E} f(\mathbf{x}_t) - f^*) + \gamma^2 B^2 + \frac{8(1-\delta)L\gamma^3 B^2}{\delta^2}.$$

Now we re-arrange, sum over $t = 0, \dots, T-1$ and divide by (γT) :

$$\begin{aligned} \frac{1}{2T} \sum_{t=0}^{T-1} (\mathbb{E} f(\mathbf{x}_t) - f^*) &\leq \frac{1}{\gamma T} \sum_{t=0}^{T-1} \left(\mathbb{E} \|\tilde{\mathbf{x}}_t - \mathbf{x}^*\|^2 - \mathbb{E} \|\tilde{\mathbf{x}}_{t+1} - \mathbf{x}^*\|^2 \right) + \gamma B^2 + \frac{8(1-\delta)L\gamma^2 B^2}{\delta^2} \\ &= \mathcal{O} \left(\frac{R_0}{\gamma T} + \gamma B^2 + \gamma^2 \frac{(1-\delta)LB^2}{\delta^2} \right). \end{aligned}$$

Now the proof follows by choosing the optimal stepsize (see [Exercise Sheet 6](#)).

Proof of Lemma 12.6

We prove here a stronger statement. We expand and take expectation:

$$\begin{aligned}\mathbb{E} \|\tilde{\mathbf{x}}_{t+1} - \mathbf{x}^*\|^2 &= \mathbb{E} \|\tilde{\mathbf{x}}_t - \mathbf{x}^*\|^2 - 2\gamma \mathbb{E} \mathbf{g}_t^\top (\mathbf{x}_t - \mathbf{x}^*) + \gamma^2 \mathbb{E} \|\mathbf{g}_t\|^2 + 2\gamma \mathbb{E} \mathbf{g}_t^\top (\mathbf{x}_t - \tilde{\mathbf{x}}_t) \\ &\leq \underbrace{\mathbb{E} \|\tilde{\mathbf{x}}_t - \mathbf{x}^*\|^2 - 2\gamma \mathbb{E} \nabla f(\mathbf{x}_t)^\top (\mathbf{x}_t - \mathbf{x}^*) + \gamma^2 (\mathbb{E} \|\nabla f(\mathbf{x}_t)\|^2 + \sigma^2)}_{\text{difference}} + 2\gamma \mathbb{E} \nabla f(\mathbf{x}_t)^\top (\mathbf{x}_t - \tilde{\mathbf{x}}_t)\end{aligned}$$

Now we use:

- ▶ $-\nabla f(\mathbf{x}_t)^\top (\mathbf{x}_t - \mathbf{x}^*) \leq -(f(\mathbf{x}_t) - f^*)$, by convexity
- ▶ $\nabla f(\mathbf{x}_t)^\top (\mathbf{x}_t - \tilde{\mathbf{x}}_t) \leq \frac{1}{2L} \|\nabla f(\mathbf{x}_t)\|^2 + 2L \|\mathbf{x}_t - \tilde{\mathbf{x}}_t\|^2$ $\mathbf{a}^\top \mathbf{b} \leq \frac{1}{2\lambda} \|\mathbf{a}\|^2 + \frac{\lambda}{2} \|\mathbf{b}\|^2$
- ▶ $\|\nabla f(\mathbf{x}_t)\|^2 \leq 2L(f(\mathbf{x}_t) - f^*)$, by smoothness

Putting all these together:

$$\mathbb{E} \|\tilde{\mathbf{x}}_{t+1} - \mathbf{x}^*\|^2 \leq \mathbb{E} \|\tilde{\mathbf{x}}_t - \mathbf{x}^*\|^2 - \gamma (2 - 2L\gamma - 1) (\mathbb{E} f(\mathbf{x}_t) - f^*) + \gamma^2 \sigma^2 + 2L\gamma \mathbb{E} \|\mathbf{x}_t - \tilde{\mathbf{x}}_t\|^2$$

and the choice of $\gamma \leq \frac{1}{4L}$ makes the term in the bracket positive ($\frac{1}{2}$).

Proof of Lemma 12.7 I

We prove this lemma by recursion.

Note that for any $\beta > 0$: $\|\mathbf{a} + \mathbf{b}\|^2 \leq (1 + \beta) \|\mathbf{a}\|^2 + (1 + 1/\beta) \|\mathbf{b}\|^2$.

$$\begin{aligned} \mathbb{E} R_{t+1} &= \mathbb{E} \|\mathbf{x}_{t+1} - \tilde{\mathbf{x}}_{t+1}\|^2 \\ &= \mathbb{E} \left\| \underbrace{\mathbf{x}_t - \tilde{\mathbf{x}}_t}_{=\mathbf{e}_t} + \underbrace{\gamma \mathbf{g}_t - \mathbf{v}_t}_{\parallel} \right\|^2 \\ &= \mathbb{E} \|\mathbf{e}_t + \gamma \mathbf{g}_t - \mathcal{C}(\mathbf{e}_t + \gamma \mathbf{g}_t)\|^2 \quad \leftarrow \text{of the form } \|\gamma - \mathcal{C}(\gamma)\|^2 \\ &\leq (1 - \delta) \mathbb{E} \|\mathbf{e}_t + \gamma \mathbf{g}_t\|^2 \quad \leq (1 - \delta) \cdot \|\gamma\|^2 \\ &\leq (1 - \delta)(1 + \beta) \mathbb{E} R_t + (1 - \delta)(1 + 1/\beta) \gamma^2 \mathbb{E} \|\mathbf{g}_t\|^2 \\ &\leq (1 - \delta)(1 + \beta) \mathbb{E} R_t + (1 - \delta)(1 + 1/\beta) \gamma^2 B^2 \\ &\leq \underbrace{(1 - \delta/2) \mathbb{E} R_t}_{\text{exponentially decreasing,}} + \underbrace{\frac{2(1 - \delta) \gamma^2}{\delta} B^2}_{\text{residual}} \quad (*) \end{aligned}$$

for the choice $\beta = \frac{\delta}{2(1-\delta)}$ such that $(1 + 1/\beta) = (2 - \delta)/\delta \leq 2/\delta$.

Proof of Lemma 12.7 II

Now we plug-in the bound on $\mathbb{E}R_t$:

$$\begin{aligned} ER_{t+1} &\leq (1 - \delta/2) \left(\frac{4(1 - \delta)\gamma^2 B^2}{\delta^2} \right) + \frac{2(1 - \delta)\gamma^2 B^2}{\delta} \\ &\leq \frac{4(1 - \delta)\gamma^2 B^2}{\delta^2} \end{aligned}$$

Note that $(1 - \delta/2)\frac{2}{\delta^2} + \frac{1}{\delta} = \frac{2}{\delta^2}$.

Discussion

- ▶ Only the higher order terms depend on δ .
- ▶ “compression for free” with error feedback
- ▶ Intuition: gradients stored in the error buffer \mathbf{e}_t are transmitted with a delay τ . Here $\frac{1}{\delta} \approx \tau$ and the results are qualitatively similar.

Extensions:


- ▶ to multiple workers $n > 1$
- ▶ here we assumed \mathbf{x}_t is not compressed. The same feedback-mechanism can be used to compress also the broadcast communication.
- ▶ In practice: most relevant are compressors that support efficient aggregation (all-reduce, all-gather).

Outlook


Optimization in Practice

Compression in Practice—PowerSGD [VKJ19]

- ▶ Low-rank approximation of weight matrix (power iteration)




- ▶ Efficient all-reduce



- ▶ with error-feedback
- ▶ Used for large-scale transformer training (DALL-E by OpenAI).

Adversarial Attacks (at inference time)



► Standard training: $\min_{\mathbf{x}} f(\mathbf{x}, \mathbf{a}_i)$

► Attacking:

$\nabla_{\mathbf{x}} f$ change **model**

$\nabla_{\mathbf{a}_i} f$ change **data**

$$\max_{\|\mathbf{a} - \mathbf{a}_i\| \leq \epsilon} f(\mathbf{x}, \mathbf{a})$$

► Algorithm: projected gradient descent

More info here

Other Aspects

- ▶ Robustness
 - ▶ Byzantine-robust training
- ▶ Privacy
 - ▶ Secure Multiparty Computation
 - ▶ Differential Privacy
 - ▶ Privacy/inference Attacks
- ▶ machine learning systems
 - ▶ decentralized
 - ▶ heterogeneous hardware
- ▶ Practical tricks
 - ▶ limited precision operations
 - ▶ number formats for DL
 - ▶ feature hashing
- ▶ ...

Thanks!

www.sstich.ch

Please reach out if you want to continue working on one of these (or other) topics.
(Master Thesis, HiWi and PhD positions available on a regular basis.)

Bibliography I



Dan Alistarh, Demjan Grubic, Jerry Li, Ryota Tomioka, and Milan Vojnovic.

QSGD: Communication-efficient SGD via gradient quantization and encoding.

In Advances in Neural Information Processing Systems 30 (NeurIPS), pages 1709–1720. Curran Associates, Inc., 2017.



Sebastian U. Stich, Jean-Baptiste Cordonnier, and Martin Jaggi.

Sparsified SGD with memory.

In Advances in Neural Information Processing Systems 31 (NeurIPS), pages 4452–4463. Curran Associates, Inc., 2018.



Sebastian U. Stich and Sai P. Karimireddy.

The error-feedback framework: Better rates for SGD with delayed gradients and compressed communication.

Journal of Machine Learning Research (JMLR), 2020.



Thijs Vogels, Sai Praneeth Karimireddy, and Martin Jaggi.

PowerSGD: Practical low-rank gradient compression for distributed optimization.

In Advances in Neural Information Processing Systems 32 (NeurIPS), pages 1626–1636. Curran Associates, Inc., 2019.