

Laxmi Charitable Trust's
Sheth L.U.J College of Arts & Sir M.V. College of Science and Commerce
Department of Information Technology (B.Sc.IT Semester IV)
MERN

Project

Roll No.: T038	Name: Akansha Pritam Ranade
Class: TYIT	Batch: 1
Date of Assignment: 03-10-2026	Date/Time of Submission: 03-10-2026

Create Database

Database Name

CampusBitesDB

Collection Name

menu

☐ Time-Series

Time-series collections efficiently store sequences of measurements over a period of time. [Learn More](#)

> **Additional preferences** (e.g. Custom collation, Clustered collections)

Cancel

Create Database

Insert Document

To collection CampusBitesDB.menu

VIEW > {}

```
1  [
2    { "itemName": "Paneer Frankie", "rate": 55, "type": "Kot
3    { "itemName": "Cheese Corn Toast", "rate": 45, "type": "
4    { "itemName": "Idli Vada Combo", "rate": 50, "type": "So
5    { "itemName": "Cold Coffee with Ice Cream", "rate": 50,
6    { "itemName": "Lemon Ice Tea", "rate": 30, "type": "Beve
7  ]
```

Cancel

Insert

```

PS D:\Mern\Akansha> npm init -y
Wrote to D:\Mern\Akansha\package.json:

{
  "name": "akansha",
  "version": "1.0.0",
  "description": "",
  "main": "index.js",
  "scripts": {
    "test": "echo \"Error: no test specified\" && exit 1"
  },
  "keywords": [],
  "author": "",
  "license": "ISC"
}

```

```

PS D:\Mern\Akansha> npm install express mongoose cors

added 88 packages, and audited 89 packages in 7s

30 packages are looking for funding
  run `npm fund` for details

found 0 vulnerabilities

```

[server.js](#)

```

const express = require("express");
const mongoose = require("mongoose");
const cors = require("cors");

```

```

const app = express();
const PORT = 5000;

```

```

app.use(cors());
app.use(express.json());

```

mongoose

```

.connect("mongodb://127.0.0.1:27017/CampusBitesDB")
.then(() => console.log("MongoDB Connected to CampusBitesDB"))
.catch((err) => console.error("Database connection failed:", err));

```

// 1. GET /food - Retrieve all food items

```

app.get("/food", async (req, res) => {
  try {
    const items = await mongoose.connection.db
      .collection("menu")
      .find()
      .toArray();
    res.status(200).json(items);
  } catch (error) {
    res.status(500).json({ error: "Failed to fetch menu items" });
  }
});

```

```
}  
});
```

```
// 2. POST /orders - Add student order
```

```
app.post("/orders", async (req, res) => {  
  try {  
    const { name, rollNo, stream, item, qty, price } = req.body;  
  
    const newBooking = {  
      studentName: name,  
      rollNumber: rollNo,  
      course: stream,  
      foodItem: item,  
      quantity: Number(qty),  
      totalAmount: Number(price) * Number(qty),  
      orderedAt: new Date().toLocaleTimeString([], { hour: "2-digit", minute: "2-digit" })  
    };  
  
    await mongoose.connection.db.collection("orders").insertOne(newBooking);  
    res.status(201).json({ message: "Order placed successfully!" });  
  } catch (error) {  
    res.status(500).json({ error: "Error placing order" });  
  }  
});
```

```
// 3. GET /orders - Retrieve all placed orders
```

```
app.get("/orders", async (req, res) => {  
  try {  
    const orderHistory = await mongoose.connection.db  
      .collection("orders")  
      .find()  
      .toArray();  
    res.status(200).json(orderHistory);  
  } catch (error) {  
    res.status(500).json({ error: "Failed to fetch orders" });  
  }  
});
```

```
app.listen(PORT, () => {  
  console.log(`Server live on http://localhost:${PORT}`);  
});
```

```
PS D:\Mern\Akansha> cd frontend
PS D:\Mern\Akansha\frontend> npm install

up to date, audited 144 packages in 2s

31 packages are looking for funding
  run `npm fund` for details

found 0 vulnerabilities

npm ERR! A complete log of this run can be found
PS D:\Mern\Akansha\frontend> npm install axios

added 25 packages, and audited 169 packages in 4

37 packages are looking for funding
  run `npm fund` for details

found 0 vulnerabilities
PS D:\Mern\Akansha\frontend> 
```

Code:

```
import { useEffect, useState } from "react";
import axios from "axios";
```

```
const SERVER_URL = "http://localhost:5000";
```

```
function App() {
  const [canteenMenu, setCanteenMenu] = useState([]);
  const [orderList, setOrderList] = useState([]);
```

```
  const [studentDetails, setStudentDetails] = useState({
    name: "",
    rollNo: "",
    stream: "",
    item: "",
    qty: 1
  });
```

```
  // GET: Fetch available items
```

```
  const loadMenu = () => {
    axios
      .get(`${SERVER_URL}/food`)
      .then((res) => {
        setCanteenMenu(res.data);
        if (res.data.length > 0 && !studentDetails.item) {
          setStudentDetails((prev) => ({ ...prev, item: res.data[0].itemName }));
        }
      })
      .catch((err) => console.error("Menu loading error:", err));
```

```

};

// GET: Fetch orders queue
const loadOrders = () => {
  axios
    .get(`${SERVER_URL}/orders`)
    .then((res) => setOrderList(res.data))
    .catch((err) => console.error("Orders loading error:", err));
};

useEffect(() => {
  loadMenu();
  loadOrders();
}, []);

const handleInputChange = (e) => {
  const { name, value } = e.target;
  setStudentDetails((prev) => ({ ...prev, [name]: value }));
};

// POST: Submit order
const submitOrder = (e) => {
  e.preventDefault();

  if (!studentDetails.name.trim() || !studentDetails.rollNo.trim() || !studentDetails.stream.trim()) {
    alert("Please fill in all student details.");
    return;
  }

  const matchedItem = canteenMenu.find((food) => food.itemName === studentDetails.item);
  const itemCost = matchedItem ? matchedItem.rate : 0;

  const payload = {
    ...studentDetails,
    price: itemCost
  };

  axios
    .post(`${SERVER_URL}/orders`, payload)
    .then((res) => {
      alert(res.data.message);
      setStudentDetails({
        name: "",
        rollNo: "",

```

```

        stream: studentDetails.stream,
        item: canteenMenu[0]?.itemName || "",
        qty: 1
    });
    loadOrders();
  })
  .catch((err) => console.error("Error submitting order:", err));
};

return (
  <div style={{ maxWidth: "850px", margin: "25px auto", padding: "10px", fontFamily: "Segoe
UI, sans-serif" }}>
    <header style={{ textAlign: "center", borderBottom: "2px solid #ea580c", paddingBottom:
"10px", marginBottom: "25px" }}>
      <h1 style={{ color: "#ea580c", margin: 0 }}>Campus Bites — Canteen Portal</h1>
      <p style={{ color: "#555", marginTop: "4px" }}>Quick Pre-Order & Token Generation</p>
    </header>

    <div style={{ display: "flex", gap: "20px", flexWrap: "wrap", marginBottom: "30px" }}>
      {/* Menu Section */}
      <section style={{ flex: "1 1 380px", border: "1px solid #fed7aa", borderRadius: "8px",
padding: "16px", backgroundColor: "#fffbeb" }}>
        <h2 style={{ marginTop: 0, color: "#9a3412" }}>Today's Menu</h2>
        <table style={{ width: "100%", borderCollapse: "collapse" }}>
          <thead>
            <tr style={{ borderBottom: "2px solid #fdb74", textAlign: "left" }}>
              <th style={{ padding: "8px" }}>Item</th>
              <th style={{ padding: "8px" }}>Category</th>
              <th style={{ padding: "8px" }}>Price</th>
            </tr>
          </thead>
          <tbody>
            {canteenMenu.map((item) => (
              <tr key={item._id} style={{ borderBottom: "1px solid #fde68a" }}>
                <td style={{ padding: "8px" }}>{item.itemName}</td>
                <td style={{ padding: "8px", color: "#666" }}>{item.type}</td>
                <td style={{ padding: "8px", fontWeight: "bold" }}>₹{item.rate}</td>
              </tr>
            ))}
          </tbody>
        </table>
      </section>

      {/* Form Section */}

```



```

<div>
  <label style={{ fontSize: "14px", fontWeight: 600 }}>Select Food</label>
  <select
    name="item"
    value={studentDetails.item}
    onChange={handleInputChange}
    style={{ width: "100%", padding: "8px", borderRadius: "4px", border: "1px solid #ccc" }}
  >
    {canteenMenu.map((food) => (
      <option key={food._id} value={food.itemName}>
        {food.itemName} (₹{food.rate})
      </option>
    ))}
  </select>
</div>

```

```

<div>
  <label style={{ fontSize: "14px", fontWeight: 600 }}>Quantity</label>
  <input
    type="number"
    min="1"
    max="5"
    name="qty"
    value={studentDetails.qty}
    onChange={handleInputChange}
    style={{ width: "100%", padding: "8px", borderRadius: "4px", border: "1px solid #ccc" }}
    required
  />
</div>

```

```

<button
  type="submit"
  style={{
    marginTop: "10px",
    padding: "10px",
    backgroundColor: "#ea580c",
    color: "white",
    border: "none",
    borderRadius: "5px",
    fontWeight: "bold",
    cursor: "pointer"
  }}
>

```



```

        Place Order
    </button>
</form>
</section>
</div>

```

```

{ /* Orders Table Section */
<section style={{ border: "1px solid #e2e8f0", borderRadius: "8px", padding: "16px" }}>
  <h2 style={{ marginTop: 0, color: "#1e293b" }}>Confirmed Order Queue</h2>
  <table style={{ width: "100%", borderCollapse: "collapse" }}>
    <thead>
      <tr style={{ backgroundColor: "#f1f5f9", textAlign: "left" }}>
        <th style={{ padding: "10px", border: "1px solid #cbd5e1" }}>Student Name</th>
        <th style={{ padding: "10px", border: "1px solid #cbd5e1" }}>Roll No</th>
        <th style={{ padding: "10px", border: "1px solid #cbd5e1" }}>Class</th>
        <th style={{ padding: "10px", border: "1px solid #cbd5e1" }}>Item</th>
        <th style={{ padding: "10px", border: "1px solid #cbd5e1" }}>Qty</th>
        <th style={{ padding: "10px", border: "1px solid #cbd5e1" }}>Total Cost</th>
        <th style={{ padding: "10px", border: "1px solid #cbd5e1" }}>Order Time</th>
      </tr>
    </thead>
    <tbody>
      {orderList.length === 0 ? (
        <tr>
          <td colSpan="7" style={{ textAlign: "center", padding: "14px" }}>
            No pre-orders recorded.
          </td>
        </tr>
      ) : (
        orderList.map((ord) => (
          <tr key={ord._id}>
            <td style={{ padding: "8px", border: "1px solid #cbd5e1" }}>{ord.studentName}</td>
            <td style={{ padding: "8px", border: "1px solid #cbd5e1" }}>{ord.rollNumber}</td>
            <td style={{ padding: "8px", border: "1px solid #cbd5e1" }}>{ord.course}</td>
            <td style={{ padding: "8px", border: "1px solid #cbd5e1" }}>{ord.foodItem}</td>
            <td style={{ padding: "8px", border: "1px solid #cbd5e1" }}>{ord.quantity}</td>
            <td style={{ padding: "8px", border: "1px solid #cbd5e1", fontWeight: "bold" }}>₹{ord.totalAmount}</td>
            <td style={{ padding: "8px", border: "1px solid #cbd5e1" }}>{ord.orderedAt}</td>
          </tr>
        ))
      )}
    </tbody>
  </table>

```

```

    </section>
  </div>
);
}

```

export default App;

```

found 0 vulnerabilities
PS D:\Mern\Akansha\frontend> npm run dev

> frontend@0.0.0 dev
> vite

11:48:20 pm [vite] (client) Re-optimizing dependencies because lockfile
has changed

VITE v8.3.2 ready in 544 ms
  ➔ Local:   http://localhost:5173/
  ➔ Network: use --host to expose
  ➔ press h + enter to show help

at Function._load (node:internal/modules/cjs/loader:1080:20)
at TracingChannel.traceSync (node:diagnostics_channel:322:3)
at wrapModuleLoad (node:internal/modules/cjs/loader:1080:20)
at Function.executeUserEntryPoint [as runMain] (node:internal/main/run_main_module:36:49)
s/run_main:171:5)
at node:internal/main/run_main_module:36:49 {
  code: 'MODULE_NOT_FOUND',
  requireStack: []
}

Node.js v22.19.0
PS D:\Mern\Akansha\frontend> cd ..
PS D:\Mern\Akansha> node server.js
Server live on http://localhost:5000
MongoDB Connected to CampusBitesDB

```

Campus Bites — Canteen Portal

Quick Pre-Order & Token Generation

Today's Menu

Item	Category	Price
Paneer Frankie	Rolls	₹55
Cheese Corn Toast	Snacks	₹45
Idli Vada Combo	South Indian	₹50
Cold Coffee with Ice Cream	Beverages	₹50
Lemon Ice Tea	Beverages	₹30

Order Form

Full Name

Akansha

Roll Number

38

Course / Class

B.sc.IT

Select Food

Paneer Frankie (₹55) ▼

Quantity

1

Place Order

Confirmed Order Queue

Student Name	Roll No	Class	Item	Qty	Total Cost	Order Time
No pre-orders recorded.						

localhost:5173 says

Order placed successfully!

OK

Confirmed Order Queue

Student Name	Roll No	Class	Item	Qty	Total Cost	Order Time
Akansha	38	B.sc.IT	Paneer Frankie	1	₹55	11:57 pm