

Quasar RAT Malware Analysis Report

Dynamic Analysis and SOC Portfolio Report

Analyst: Artamis Karrys

Environment: Isolated Windows virtual machine in UTM

Sample Focus: Suspected Quasar Remote Access Trojan

Report Date: June 4, 2026

Table of Contents

1. Executive Summary
2. Scope and Methodology
3. Analysis Environment
4. Sample Acquisition and Execution
5. Baseline State
6. Behavioral Analysis
7. Network Analysis
8. Persistence Analysis
9. Code Signing and File Identity
10. Indicators of Compromise
11. MITRE ATT&CK Mapping
12. Timeline of Key Events
13. Key Findings
14. Analyst Assessment
15. Conclusion
16. Appendix

Executive Summary

This report documents the dynamic analysis of a suspected Quasar Remote Access Trojan (RAT) executed inside an isolated Windows virtual machine. The purpose of the analysis was to identify execution behavior, persistence mechanisms, network communications, file artifacts, and indicators of compromise associated with the sample.

The investigation identified an unsigned executable named gfhgfgjgf.exe running from the user AppData\Roaming directory, creation of a suspicious scheduled task named hgfhjjhgj, repeated outbound TCP connection attempts to external infrastructure, and randomized artifact naming. These behaviors are consistent with remote access malware that attempts to persist across user logons and communicate with an external controller.

The strongest evidence supporting malicious classification is the scheduled task persistence mechanism that executes the payload from C:\Users\john\AppData\Roaming\ghghghfg\gfhgfgjgf.exe during user logon. Supporting evidence includes process enumeration, file metadata, digital signature validation, TCP connection analysis, and Wireshark endpoint/conversation data.

Scope and Methodology

The analysis was performed as a controlled malware lab exercise. The sample was detonated in a Windows VM while monitoring system, process, registry, filesystem, and network activity. The objective was not to attribute the malware to a specific actor, but to document observable behavior and extract defensible IOCs.

- Prepared an isolated Windows analysis environment.
- Captured baseline screenshots before execution.
- Executed the malware sample and monitored with Process Explorer, Process Monitor, TCPView, Wireshark, PowerShell, and Task Scheduler.
- Validated persistence using PowerShell task enumeration and exported scheduled task XML.
- Collected hash, file path, process ID, network destination, and signature status evidence.

Analysis Environment

The lab environment was organized with dedicated folders for evidence, exports, logs, samples, screenshots, and tools. This structure supports repeatable evidence handling and prevents collected artifacts from being scattered across the system like digital confetti, which is apparently humanity's default file-management strategy.




Figure 1. Malware lab directory structure. The MalwareLab directory contained separate folders for evidence, exports, logs, samples, screenshots, and tools.

Analyst note: This establishes the analysis workspace and shows that evidence was collected in a structured lab directory before detonation.




Figure 2. Fresh Windows VM baseline. The Windows VM was documented before malware execution.

Analyst note: This baseline shows the system state before detonation and helps distinguish malware-created artifacts from normal operating system files.




Figure 3. Analysis toolset prepared. Sysinternals and network-monitoring tools were staged before execution.

Analyst note: Process Explorer, TCPView, Process Monitor, and related tooling were available before running the sample, allowing runtime behavior to be captured immediately.

Sample Acquisition and Execution

The suspected Quasar sample was staged in the malware lab sample directory and executed within the isolated VM. The goal was to observe real runtime behavior while limiting the exposure of the host system and external environment.




Figure 4. Sample extraction directory. The sample was extracted into the MalwareLab sample path.

Analyst note: This screenshot documents the presence of the compressed sample and extracted executable used for dynamic analysis.




Figure 6. Windows Security baseline. Windows Security was reviewed before detonation.

Analyst note: The baseline records the security posture before execution and provides context for later Defender and security-related events.




Figure 7. Device security baseline. Device security settings were reviewed before detonation.

Analyst note: This provides additional baseline context for the virtualized Windows environment.




Figure 8. Scheduled Tasks baseline. Task Scheduler was reviewed before malware execution.

Analyst note: The baseline is important because a suspicious task named hgfhjhjg was later observed after detonation.




Figure 9. AppData Roaming baseline. The Roaming directory was checked before execution.

Analyst note: Only expected directories were visible before detonation. This later supports the finding that the ghghghfg directory and gfhgfgjf.exe payload location were suspicious.

Behavioral Analysis

After detonation, the sample produced process and persistence artifacts that were visible through Process Explorer, PowerShell, Process Monitor, and Task Scheduler. The most notable behavior was execution from a user-writable AppData path and creation of a scheduled task.




Figure 10. Process Explorer runtime activity. Process Explorer displayed active processes after detonation.

Analyst note: This view supported runtime triage by showing process activity, process hierarchy, loaded modules, and signature information.




Figure 11. Parent process identification. PowerShell confirmed the parent process ID for the suspicious process chain.

Analyst note: The output shows svchost.exe with the Schedule service context, which aligns with scheduled task execution behavior.

```
PS C:\Users\john> Get-ScheduledTask | Where-Object { $_.TaskPath -notlike "\Microsoft*" } | Select TaskName,TaskPath
```

TaskName	TaskPath
hgfhjjhgj	/
MicrosoftEdgeUpdateTaskMachineCore{F9214A84-8918-429C-A883-4564A8928318}	/
MicrosoftEdgeUpdateTaskMachineUA{E853A503-7A9D-4A4B-B0A7-ABEC2B25E872}	/
npcapwatchdog	/
OneDrive Reporting Task-S-1-5-21-2941031318-3638860368-3465996943-1001	/
OneDrive Standalone Update Task-S-1-5-21-2941031318-3638860368-3465996943-1001	/
OneDrive Startup Task-S-1-5-21-2941031318-3638860368-3465996943-1001	/
SoftLandingCreativeManagementTask	\SoftLanding\S-1-5-21-2941031318-...
SoftLandingDeferralTask-{bf6fc44b-d8b1-486b-b75a-5343e85d6f60}	\SoftLanding\S-1-5-21-2941031318-...
SoftLandingTriggerTask-128000000001615609-render-{0c4da4fd-93b8-4690-9936-b...	\SoftLanding\S-1-5-21-2941031318-...

Figure 12. Non-Microsoft scheduled task discovery. PowerShell listed scheduled tasks outside Microsoft paths, including hgfhjjhgj.

Analyst note: The randomized task name is suspicious and became one of the strongest persistence indicators in the report.




Figure 13. Process Monitor prepared for event capture. Process Monitor was available to capture file, registry, and process activity.

Analyst note: Procmon supports event-level artifact collection, although the report relies most heavily on task, process, and network artifacts.




Figure 14. Process Explorer suspicious process review. Process Explorer showed the suspicious executable among active processes.

Analyst note: The process was later correlated with file path, process ID, hash, and network connection evidence.

Network Analysis

Network analysis identified repeated outbound connection attempts from the infected VM to external IP addresses. The most notable destinations were 45.88.186.209 over TCP port 4782 and 207.246.91.177 over TCP port 443. The traffic pattern included SYN attempts and reset responses, indicating attempted communication even when a full command-and-control session was not established.




Figure 15. Malware process path confirmation. PowerShell showed process ID 4612 running from AppData\Roaming.

Analyst note: This establishes the process ID used for correlation with netstat and network-monitoring evidence.

```

PS C:\Users\john> Get-ScheduledTask -TaskName hgfhjjhgj | Format-List *

State                : Running
Actions              : {MSFT_TaskExecAction}
Author               : WIN-KGQKCHRT30B\john
Date                 : 2026-06-04T08:53:51
Description          :
Documentation        :
Principal            : MSFT_TaskPrincipal2
SecurityDescriptor   :
Settings             : MSFT_TaskSettings3
Source               :
TaskName             : hgfhjjhgj
TaskPath             : \
Triggers             : {MSFT_TaskLogonTrigger}
URI                  : \hgfhjjhgj
Version              :
PSComputerName       :
CimClass              : Root/Microsoft/Windows/TaskScheduler:MSFT_ScheduledTask
CimInstanceProperties : {Actions, Author, Date, Description...}
CimSystemProperties  : Microsoft.Management.Infrastructure.CimSystemProperties

```

Figure 16. Scheduled task full details. Get-ScheduledTask showed the suspicious task hgfhjjhgj in a running state.

Analyst note: The task was authored by the local user and configured with a logon trigger, making it a clear persistence artifact.

```

PS C:\Users\john> (Get-ScheduledTask -TaskName hgfhjjhgj).Actions

Id      :
Arguments :
Execute  : C:\Users\john\AppData\Roaming\ghghghfg\gfhgfgjgf.exe
WorkingDirectory :
PSComputerName :

PS C:\Users\john> |

```

Figure 17. Scheduled task action path. PowerShell confirmed the scheduled task action executes gfhgfgjgf.exe from AppData\Roaming.

Analyst note: This is the main smoking gun: the persistence mechanism directly launches the suspicious executable.

```

PS C:\Users\john> netstat -ano | findstr 4612
TCP    192.168.64.7:58081    45.88.186.209:4782    SYN_SENT    4612
PS C:\Users\john>

```

Figure 18. Netstat correlation to process ID. Netstat correlated PID 4612 with a connection to 45.88.186.209:4782.

Analyst note: This ties the suspicious process to outbound network behavior rather than leaving the network finding floating around like an orphaned packet.

```
PS C:\Users\john> Get-ChildItem "C:\Users\john\AppData\Roaming\ghghghfg" -Force

Directory: C:\Users\john\AppData\Roaming\ghghghfg

Mode                LastWriteTime         Length Name
----                -
-a-----         5/13/2024  10:09 AM        3265536 gfhgfgjgf.exe
```

Figure 19. Malware directory contents. The ghghghfg directory contained gfhgfgjgf.exe.


Analyst note: The randomized directory and executable names are consistent with malware staging in user-writable profile paths.

```
PS C:\Users\john> Get-FileHash "C:\Users\john\AppData\Roaming\ghghghfg\gfhgfgjgf.exe" -Algorithm SHA256

Algorithm      Hash
-----
SHA256         996E8D1AFC74090B75F936CA57B1570DE64DFF0BCDBFFA411F9F6ED814FC43F
Path
C:\Users\john\AppData\Roaming\ghghghfg\gfhgfgjgf.exe
```

Figure 20. SHA256 hash collection. PowerShell calculated the sample SHA256 hash.

Analyst note: Hashing uniquely identifies the sample and supports IOC sharing and threat-intelligence correlation.



Process Name	Process ID	Protocol	State	Local Address	Local Port	Remote Address
svchost.exe	7412	TCP	Established	WIN-KGQKCHRT30B	54552	150.171.110.195
msedge.exe	4104	TCP	Established	WIN-KGQKCHRT30B	54546	150.171.28.11
SystemSettings.exe	928	TCP	Established	WIN-KGQKCHRT30B	54547	20.1.248.118
SystemSettings.exe	928	TCP	Established	WIN-KGQKCHRT30B	54548	20.1.248.118
svchost.exe	3508	TCP	Established	WIN-KGQKCHRT30B	59595	20.59.87.226
svchost.exe	3508	TCP	Established	WIN-KGQKCHRT30B	49673	20.59.87.226
StartMenuExperience...	6068	TCP	Established	WIN-KGQKCHRT30B	49677	52.110.19.135
StartMenuExperience...	6068	TCP	Established	WIN-KGQKCHRT30B	49679	52.110.19.145
OneDriveStandaloneU...	3328	TCP	Established	WIN-KGQKCHRT30B	54554	52.123.129.14
[Time Wait]		TCP	Time Wait	WIN-KGQKCHRT30B	64304	52.159.108.190
smartscreen.exe	3648	TCP	Established	WIN-KGQKCHRT30B	54555	52.159.108.190
svchost.exe	7412	TCP	Established	WIN-KGQKCHRT30B	54553	a23-62-226-138.deploy.
msedge.exe	4104	TCP	Established	WIN-KGQKCHRT30B	58417	server-65-8-20-88.phx5l
System	4	TCP	Listen	WIN-KGQKCHRT30B	139	0.0.0.0
svchost.exe	3036	TCP	Listen	WIN-KGQKCHRT30B	5040	0.0.0.0
lsass.exe	912	TCP	Listen	WIN-KGQKCHRT30B	49664	0.0.0.0
wininit.exe	748	TCP	Listen	WIN-KGQKCHRT30B	49665	0.0.0.0
svchost.exe	1696	TCP	Listen	WIN-KGQKCHRT30B	49666	0.0.0.0
svchost.exe	1776	TCP	Listen	WIN-KGQKCHRT30B	49667	0.0.0.0
spoolsv.exe	2504	TCP	Listen	WIN-KGQKCHRT30B	49668	0.0.0.0
svchost.exe	924	TCP	Listen	WIN-KGQKCHRT30B	135	0.0.0.0
services.exe	892	TCP	Listen	WIN-KGQKCHRT30B	49672	0.0.0.0
System	4	TCP	Listen	WIN-KGQKCHRT30B	445	0.0.0.0
svchost.exe	8116	TCP	Listen	WIN-KGQKCHRT30B	7680	0.0.0.0
svchost.exe	924	TCPv6	Listen	WIN-KGQKCHRT30B	135	::
System	4	TCPv6	Listen	WIN-KGQKCHRT30B	445	::
svchost.exe	8116	TCPv6	Listen	WIN-KGQKCHRT30B	7680	::
OneDrive.Sync.Service...	8640	TCPv6	Listen	WIN-KGQKCHRT30B	42050	::
lsass.exe	912	TCPv6	Listen	WIN-KGQKCHRT30B	49664	::
wininit.exe	748	TCPv6	Listen	WIN-KGQKCHRT30B	49665	::
svchost.exe	1696	TCPv6	Listen	WIN-KGQKCHRT30B	49666	::

Endpoints: 68 Established: 12 Listening: 21 Time Wait: 1 Close Wait: 0 Update: 2 sec States: (All)

Figure 21. TCPView network overview. TCPView showed active and listening network connections during analysis.

Analyst note: TCPView provided quick process-to-network visibility and supported the network triage workflow.

Persistence Analysis

Persistence was confirmed through multiple independent artifacts: task enumeration, task action review, Task Scheduler GUI validation, and exported XML. The scheduled task hgfhjhgj was configured to execute at user login and launch the payload from the Roaming profile.

```
PS C:\Users\john> Get-Item "C:\Users\john\AppData\Roaming\ghghghfg\ghghghghfg.exe" | Select-Object Name,Length,CreationTime,LastWriteTime
```

Name	Length	CreationTime	LastWriteTime
ghghghghfg.exe	3265536	6/3/2026 5:47:30 PM	5/13/2024 10:09:04 AM

Figure 22. File metadata collection. PowerShell captured file length, creation time, and last write time for ghghghghfg.exe.

Analyst note: The file metadata supports the timeline and confirms the payload was present in AppData\Roaming.

```
PS C:\Users\john> Get-Process gfhgfgjgf | Select-Object Id,ProcessName,StartTime

Id ProcessName StartTime
--
4612 gfhgfgjgf 6/4/2026 8:53:34 AM
```

Figure 23. Process start time after logon. PowerShell confirmed process ID and start time for gfhgfgjgf.exe.

Analyst note: This supports the logon persistence finding by showing the payload running after the scheduled task was created.

```
PS C:\Users\john> Get-CimInstance Win32_Process -Filter "ProcessId=4612" | Select-Object ExecutablePath

ExecutablePath
-----
C:\Users\john\AppData\Roaming\ghghghfg\gfhgfgjgf.exe
```

Figure 24. Executable path revalidation. WMI confirmed the executable path for process ID 4612.

Analyst note: Revalidating the executable path through WMI reduces uncertainty and strengthens the evidence chain.




Figure 25. Screenshot evidence folder. The screenshot folder shows organized evidence collection.

Analyst note: This supports chain-of-documentation by showing that the investigation artifacts were saved systematically.




Figure 26. Task Scheduler GUI validation. Task Scheduler displayed the suspicious task hgfhjhgj.

Analyst note: GUI validation confirms the PowerShell findings and shows the task configured at the root task path.


```
PS C:\Users\john> Export-ScheduledTask -TaskName hgfhjjhgj
<?xml version="1.0" encoding="UTF-16"?>
<Task version="1.2" xmlns="http://schemas.microsoft.com/windows/2004/02/mit/task">
  <RegistrationInfo>
    <Date>2026-06-04T08:53:51</Date>
    <Author>WIN-HGQKCHRT30B\john</Author>
    <URI>\hgfhjjhgj</URI>
  </RegistrationInfo>
  <Principals>
    <Principal id="Author">
      <UserId>S-1-5-21-2941031318-3638860368-3465996943-1001</UserId>
      <LogonType>InteractiveToken</LogonType>
      <RunLevel>HighestAvailable</RunLevel>
    </Principal>
  </Principals>
  <Settings>
    <DisallowStartIfOnBatteries>true</DisallowStartIfOnBatteries>
    <StopIfGoingOnBatteries>true</StopIfGoingOnBatteries>
    <MultipleInstancesPolicy>IgnoreNew</MultipleInstancesPolicy>
    <IdleSettings>
      <Duration>PT10M</Duration>
      <WaitTimeout>PT1H</WaitTimeout>
      <StopOnIdleEnd>true</StopOnIdleEnd>
      <RestartOnIdle>false</RestartOnIdle>
    </IdleSettings>
  </Settings>
  <Triggers>
    <LogonTrigger>
      <StartBoundary>2026-06-04T08:53:00</StartBoundary>
    </LogonTrigger>
  </Triggers>
  <Actions Context="Author">
    <Exec>
      <Command>C:\Users\john\AppData\Roaming\ghghghfg\gfhgfgjgf.exe</Command>
    </Exec>
  </Actions>
</Task>
PS C:\Users\john> |
```

Figure 27. Exported scheduled task XML. Export-ScheduledTask output showed a logon trigger and command path to gfhgfgjgf.exe.

Analyst note: The XML directly confirms the persistence mechanism: at user login, Windows runs the payload from AppData\Roaming.

Code Signing and File Identity

Code signing verification was performed to determine whether the executable had a trusted publisher. The executable was not signed. While an unsigned executable alone is not proof of malware, unsigned code running from AppData\Roaming with scheduled-task persistence and suspicious network activity is highly suspicious.

```
PS C:\Users\john> Get-AuthenticodeSignature "C:\Users\john\AppData\Roaming\ghghghfg\gfhgfgjgf.exe"

Directory: C:\Users\john\AppData\Roaming\ghghghfg

SignerCertificate      Status      Path
-----
NotSigned              gfhgfgjgf.exe
```

Figure 28. Authenticode signature validation. Get-AuthenticodeSignature reported the executable status as NotSigned.

Analyst note: The lack of a trusted signature increases suspicion when combined with the execution path, randomized filename, persistence mechanism, and outbound connections.

Indicators of Compromise

Indicator Type	Value
Executable name	gfhgfgjgf.exe
Execution path	C:\Users\john\AppData\Roaming\ghghghfg\gfhgfgjgf.exe

Scheduled task	hgfhjjhgj
Observed process ID	4612
Remote IP	45.88.186.209
Remote IP	207.246.91.177
Observed ports	4782, 443
Persistence mechanism	Scheduled task at logon
Signature status	NotSigned
SHA256	996E8D1AFC74090B75F936CA57B1570DE64DFF0DBCDBFFA411F9F6ED814FC43F

MITRE ATT&CK Mapping

Technique	Tactic	Evidence from Analysis
T1053.005 - Scheduled Task	Persistence	Scheduled task hgfhjjhgj executed the payload at user logon.
T1547 - Boot or Logon Autostart Execution	Persistence	The payload was configured to run during user logon.
T1036 - Masquerading	Defense Evasion	Randomized names were used for the executable and task artifact.
T1071 - Application Layer Protocol	Command and Control	Outbound TCP communication attempts were observed to external infrastructure.
T1105 - Ingress Tool Transfer	Command and Control	The lab workflow involved a staged executable payload and potential malware delivery behavior.
T1027 - Obfuscated Files or Information	Defense Evasion	Randomized file and directory naming reduced immediate human readability.

Timeline of Key Events

Phase	Observed Artifact	Interpretation
Pre-execution	Baseline screenshots of security, scheduled tasks, Roaming folder, and tools	Known-good state documented before detonation.
Execution	gfhgfgjgf.exe observed running from AppData\Roaming	Suspicious user-profile execution path identified.
Persistence	Scheduled task hgfhjjhgj created with logon trigger	Malware configured to survive user logon events.
Network	TCP connection attempts to 45.88.186.209:4782 and 207.246.91.177:443	Potential command-and-control communication attempts.
Validation	Hash, signature status, task XML, and WMI process path collected	Artifacts support IOC extraction and report defensibility.

Key Findings

- The malware sample executed successfully inside the isolated analysis VM.
- The executable gfhgfgjgf.exe ran from C:\Users\john\AppData\Roaming\ghghghfg\.
- A suspicious scheduled task named hgfhjjhgj was created for logon-based persistence.
- The scheduled task action directly pointed to the suspicious AppData\Roaming executable.
- Network activity was observed to 45.88.186.209 over TCP port 4782 and 207.246.91.177 over TCP port 443.
- The executable was unsigned and used randomized naming conventions.
- The evidence is consistent with Remote Access Trojan behavior.

Analyst Assessment

The collected evidence supports classification of the sample as malicious. The strongest findings are the logon-triggered scheduled task, the execution path inside AppData\Roaming, the unsigned executable, and outbound network connection attempts. While the network traffic alone does not conclusively prove a successful command-and-control session, it is suspicious when correlated with persistence and payload execution artifacts.

From a SOC analyst perspective, this incident would justify containment of the affected host, preservation of the executable and scheduled task XML, blocking of observed IOCs where appropriate, and a hunt across other endpoints for the same task name, file path, executable hash, and remote IPs.


Conclusion

Dynamic analysis of the suspected Quasar RAT sample revealed execution from a user-writable Roaming profile directory, creation of scheduled-task persistence, suspicious outbound network communication attempts, randomized artifact naming, and lack of a trusted digital signature. These behaviors align with common remote access trojan tradecraft and support treating the sample as malicious.

The scheduled task hgfhjjhgj is the primary persistence artifact. It executed gfhgfgjgf.exe from C:\Users\john\AppData\Roaming\ghghghfg\ during user logon, providing a clear mechanism for continued execution after reboot or reauthentication. The combination of process, network, file, and persistence evidence makes this a defensible malware analysis finding.

Appendix - Additional Tooling Screenshots

The following screenshots document supporting tooling views captured during the analysis. These are retained for completeness and evidence traceability.



Process Name	Process ID	Protocol	State	Local Address	Local Port	Remote Address
svchost.exe	924	TCP	Listen	WIN-KGQKCHRT30B	135	0.0.0.0
System	4	TCP	Listen	WIN-KGQKCHRT30B	139	0.0.0.0
svchost.exe	5032	TCP	Listen	WIN-KGQKCHRT30B	5040	0.0.0.0
lsass.exe	912	TCP	Listen	WIN-KGQKCHRT30B	49664	0.0.0.0
wininit.exe	748	TCP	Listen	WIN-KGQKCHRT30B	49665	0.0.0.0
svchost.exe	1648	TCP	Listen	WIN-KGQKCHRT30B	49666	0.0.0.0
svchost.exe	1940	TCP	Listen	WIN-KGQKCHRT30B	49667	0.0.0.0
spoolsv.exe	3136	TCP	Listen	WIN-KGQKCHRT30B	49669	0.0.0.0
services.exe	892	TCP	Listen	WIN-KGQKCHRT30B	49670	0.0.0.0
svchost.exe	3684	TCP	Established	WIN-KGQKCHRT30B	49675	20.59.87.225
StartMenuExperience...	5536	TCP	Established	WIN-KGQKCHRT30B	49678	52.110.19.139
StartMenuExperience...	5536	TCP	Established	WIN-KGQKCHRT30B	49679	52.110.19.139
svchost.exe	3684	TCP	Established	WIN-KGQKCHRT30B	53124	20.59.87.225
[Time Wait]		TCP	Time Wait	WIN-KGQKCHRT30B	59152	13.91.96.185
smartscreen.exe	2328	TCP	Established	WIN-KGQKCHRT30B	59153	13.91.222.61
svchost.exe	6396	TCP	Established	WIN-KGQKCHRT30B	59154	72.153.5.129
svchost.exe	6396	TCP	Established	WIN-KGQKCHRT30B	59155	72.153.5.61
System	4	TCP	Listen	WIN-KGQKCHRT30B	445	0.0.0.0
svchost.exe	6396	TCP	Listen	WIN-KGQKCHRT30B	7680	0.0.0.0
svchost.exe	924	TCPv6	Listen	WIN-KGQKCHRT30B	135	::
System	4	TCPv6	Listen	WIN-KGQKCHRT30B	445	::
svchost.exe	6396	TCPv6	Listen	WIN-KGQKCHRT30B	7680	::
OneDrive.Sync.Service...	7712	TCPv6	Listen	WIN-KGQKCHRT30B	42050	::
lsass.exe	912	TCPv6	Listen	WIN-KGQKCHRT30B	49664	::
wininit.exe	748	TCPv6	Listen	WIN-KGQKCHRT30B	49665	::
svchost.exe	1648	TCPv6	Listen	WIN-KGQKCHRT30B	49666	::
svchost.exe	1940	TCPv6	Listen	WIN-KGQKCHRT30B	49667	::
spoolsv.exe	3136	TCPv6	Listen	WIN-KGQKCHRT30B	49669	::
services.exe	892	TCPv6	Listen	WIN-KGQKCHRT30B	49670	::
System	4	UDP		WIN-KGQKCHRT30B	137	*
System	4	UDP		WIN-KGQKCHRT30B	138	*

Endpoints: 57 Established: 7 Listening: 21 Time Wait: 1 Close Wait: 0 Update: 2 sec States: (All)

Figure 29. TCPView supporting screenshot. Additional TCPView evidence captured during the investigation.

Analyst note: This supplemental view supports the network-analysis workflow and shows broader connection context.




Figure 30. Process Monitor supporting screenshot. Additional Process Monitor evidence captured during the investigation.

Analyst note: This supplemental view documents that Procmon was available and configured for behavioral capture.




Figure 31. Autoruns supporting screenshot. Autoruns view of autostart locations.

Analyst note: Autoruns was used to review persistence-related locations and supplement scheduled-task analysis.