



AKA-CLAUDE-TOOLS · WHAT'S INSIDE · JUNE 2026

What's in the box.

A fresh Claude Code ships with almost no guardrails. **aka-claude-tools** adds fifteen pick-and-choose pieces that give it clean context, locked doors, and guarded exits.

15 additions

pick & choose

MIT

open-source

github.com/akasecurity/claude-tools

THE PREMISE

Powerful out of the box.
Bare out of the box.

Claude Code is a capable coding agent on day one, and it ships with the guardrails of a blank text editor.

- The kit adds **fifteen optional pieces**: nine on by default, six you opt in.
- Every one is **independent**. Take what you want, ignore the rest, delete any.
- **Open source**. Delete any piece in seconds.

Keep the model's desk clean.

`rtk-safe`

ON BY DEFAULT

Quietly rewrites chatty commands (giant file listings, logs) into compact summaries **before** they reach the model, saving its limited working memory. Invisible, and inert if you don't use `rtk`.

`statusline`

ON BY DEFAULT

A status bar showing your **context fill and rate-limit budget live**, so you know when to wrap a session before the model starts forgetting.

Safe defaults, day one.

secure-settings

ON BY DEFAULT

The settings a fresh install should already have: the agent **can't read your SSH keys, cloud credentials, .env files, or keychains**, and untrusted plugins don't auto-load.

One file turns a fresh, unguarded install into a clean, locked-down baseline.

Watch what leaves, and what runs.

leak-guard

ON BY DEFAULT

Inspects what the agent sends to the web (searches, fetches) and **blocks anything shaped like a secret** from leaving. Scanned locally. Nothing is uploaded to check it.

command-guard

ON BY DEFAULT

Watches shell commands: blocks **piping a random web script straight into your shell**, edits to your startup files, and credentials being shipped out.

Trim the chatter you didn't ask for.

Claude Code phones home with error reports, feedback, and surveys. The kit **silences those by default**, each an independent toggle you can flip back.

ON BY DEFAULT

- ✓ `error-reporting-off`
- ✓ `feedback-off`
- ✓ `feedback-survey-off`

OPT IN

- `telemetry-off`
- `autoupdater-off`

Telemetry and auto-update it leaves on, so **Remote Control keeps working** out of the box.

Check the work before it ships.

shell-audit

ON BY DEFAULT

An on-demand, read-only scan of your shell setup that flags **hardcoded credentials, sketchy startup hooks, and risky aliases** hiding in your dotfiles.

/wrap-up

OPT-IN

A clean end-of-session routine: it summarizes what changed, verifies, and **stages a commit for you to review, but never commits on its own.**

Three more, off until you want them.

secure-research

OPT-IN

Privacy-aware web research. Parallel researchers gather cited findings into a grounded report, routing sensitive topics through **your own search instance**. The everyday default.

secure-deep-research

OPT-IN

The heavier variant: adds **per-claim adversarial verification** before it synthesizes, for when correctness matters more than speed.

harness-pointer

OPT-IN

A small nudge that points the agent at the **right CLI for your environment**. Ships disabled. Turn it on only if you need it.

ALL FIFTEEN, AT A GLANCE

Nine on. Six you opt in.

ON BY DEFAULT

- ✓ `secure-settings`
- ✓ `leak-guard`
- ✓ `command-guard`
- ✓ `rtk-safe`
- ✓ `statusline`
- ✓ `shell-audit`
- ✓ `error-reporting-off`
- ✓ `feedback-off`
- ✓ `feedback-survey-off`

OPT IN

- `/wrap-up`
- `secure-research`
- `secure-deep-research`
- `harness-pointer`
- `telemetry-off`
- `autoupdater-off`

The nine I keep on by default. The other six you turn on by choice.

WHY A KIT, NOT A FRAMEWORK

Defaults a fresh install should already have.

This isn't a platform you adopt. It's the minimal, hardened starting point a coding agent should have: clean context, locked credentials, guarded egress.

- Each piece stands alone: **break one, the rest are fine.**
- Take any piece, drop it, or delete the whole profile in seconds.

GET IT

Add a clean slate to your setup.

Spin up a separate hardened profile, or install straight into your existing config. Your call. Two ways in, no developer chops required:

```
# hand it to your AI (recommended), no clone needed
"Set up aka-claude-tools from its GitHub repo:
 read the install guide and do it safely for me."

# prefer the terminal? clone it, then:
./install.sh --defaults
```



AKA **Security** · github.com/akasecurity