

# Zapocalypse Second Brain – User Manual

---

How to use the Obsidian LLM wiki as your primary project reference for day-to-day development.

---

## What It Is

A machine-maintained, interlinked wiki that gives any LLM (Claude or Gemini) complete project context without reading source code. Think of it as a compiled, cross-referenced version of `.claude/memory/` – optimised for targeted retrieval rather than full context loading.

**The core promise:** Ask Claude anything about architecture, agents, hooks, schemas, or project state – and it answers from the wiki, not from scanning files.

---

## Structure at a Glance

Obsidian Vault/Zapocalypse/

|                   |                                                          |
|-------------------|----------------------------------------------------------|
| ├ index.md        | ← Start here. Semantic lookup table + full TOC.          |
| ├ schema.md       | ← How the wiki works (for LLM maintainers)               |
| ├ log.md          | ← Chronological record of all ingests and changes        |
| ├ README.md       | ← Human-facing vault guide                               |
|                   |                                                          |
| ├ Sources/        | ← Immutable originals. Synced from repo. Never edit.     |
|                   |                                                          |
| ├ └ Memory/       | ← .claude/memory/ snapshots                              |
|                   |                                                          |
| ├ └ Rules/        | ← .claude/rules/ snapshots                               |
|                   |                                                          |
| ├ └ Docs/         | ← CLAUDE.md, GEMINI.md, V3 plans, market research        |
|                   |                                                          |
| ├ Wiki/           | ← LLM-maintained interlinked pages. The knowledge base.  |
|                   |                                                          |
| ├ └ Architecture/ | ← Stack, patterns (Fire-and-Forget, Hub-and-Spoke, etc.) |
|                   |                                                          |
| ├ └ Pipeline/     | ← Orchestrator + all 7 agents                            |
|                   |                                                          |
| ├ └ Data/         | ← Firestore schema, Zod schemas, Gemini client,          |

helpers

|   |                   |                                          |
|---|-------------------|------------------------------------------|
|   | — Hooks/          | ← All 15 React hooks                     |
|   | — Components/     | ← All UI components                      |
|   | — Pages/          | ← App pages + API routes                 |
|   | — Concepts/       | ← Cross-cutting design patterns          |
|   | — Decisions/      | ← Architectural decision records         |
|   | — Infrastructure/ | ← Deployment, env vars, endpoints        |
|   | — Project/        | ← Phase history, roadmap, current status |
|   | — _Health.md      | ← Live Dataview health dashboard         |
|   | — _Queries/       | ← Pre-baked Dataview lookups             |
|   |                   |                                          |
| — | Templates/        | ← Templater templates for new pages      |

---

## Day-to-Day Workflows

### 1. Asking an architecture question

**You:** "How does budget tracking work?"

**What Claude does (automatically, per Rule 1 in CLAUDE.md):**

1. Opens `index.md` → Semantic Lookup table → `Wiki/Concepts/Budget Protection Layers`
2. Reads that page (full code excerpts included)
3. Answers — no source file opened

You don't need to do anything differently. If you want to be explicit:

```
"Check the wiki for how X works"
```

---

### 2. Making a code change

**Before editing:** Claude reads the wiki page for context (e.g. `Wiki/Pipeline/Orchestrator` )

**After editing:** Claude finds the matching wiki page and marks it stale:

```
grep -rl "source_file: src/lib/pipeline/orchestrator.ts" "Obsidian Vault/"  
# Then sets status: stale in that page's frontmatter
```

The wiki-maintaining Claude refreshes it on next `/wiki-ingest` . You don't manage this manually.

---

### 3. Completing a phase

After merging a phase branch to `main`, run:

```
/phase-complete <N>
```

This automatically:

- Marks V3 phase checkboxes done in `phase_status.md`
- Updates `MEMORY.md` quick status
- Marks the three wiki project pages stale
- Appends a summary row to `Wiki/Project/Phase History.md`
- Prompts you to run the sync chain

Then complete the sync chain:

```
./scripts/sync-vault.sh    # Sync updated memory files into Sources/  
/wiki-ingest              # (in vault Claude session) Refresh stale pages
```

---

### 4. Syncing after any significant change

Run from the repo root whenever `.claude/memory/` or `src/docs/` changes:

```
./scripts/sync-vault.sh
```

Then in a Claude Code session opened inside `Obsidian Vault/Zapocalypse/`:

```
/wiki-ingest
```

The ingest is diff-based — it reads `git diff HEAD~1` to find changed sources and only updates affected pages. A full 78-page re-read never happens unless you do a full ingest.

#### **Preview before committing:**

```
/wiki-ingest dry-run
```

Prints what *would* change without editing anything.

---

### 5. Checking project status

```
/status
```

Reads `Wiki/Project/Current Status.md` first (canonical). Falls back to `.claude/memory/phase_status.md` only if the wiki page is stale.

---

## 6. Something is missing from the wiki

If Claude hits a question the wiki can't answer:

1. It falls back to `.claude/memory/` or source files and completes the task
2. Appends a gap entry to `Obsidian Vault/Zapocalypse/log.md` :  

```
## [YYYY-MM-DD] gap | <topic> | discovered during <task>  
<One sentence describing what's missing.>
```
3. Next `/wiki-ingest` picks up the gap and creates or updates the missing page

You can also file gaps manually — just open `log.md` and append the entry above.

---

## Slash Commands Reference

| Command                                | When to use                                                        |
|----------------------------------------|--------------------------------------------------------------------|
| <code>/status</code>                   | Start of every session — canonical phase + next work               |
| <code>/wiki-ingest</code>              | After <code>sync-vault.sh</code> — updates only changed wiki pages |
| <code>/wiki-ingest dry-run</code>      | Preview what would change without editing                          |
| <code>/check-budget</code>             | Before adding any agent or Gemini call                             |
| <code>/validate-sko</code>             | Before/after editing <code>src/lib/ai/schemas/sko.ts</code>        |
| <code>/phase-complete &lt;N&gt;</code> | After merging a phase branch to main                               |
| <code>/remember &lt;fact&gt;</code>    | Mid-session significant decision or constraint                     |

---

## Maintenance Schedule

| Trigger                             | Action                                                                                  |
|-------------------------------------|-----------------------------------------------------------------------------------------|
| After every <code>git commit</code> | <code>sync-vault.sh</code> → <code>/wiki-ingest</code> (checklist step 6)               |
| After every phase merge             | <code>/phase-complete N</code> → <code>sync-vault.sh</code> → <code>/wiki-ingest</code> |

---

| Trigger                                | Action                                                               |
|----------------------------------------|----------------------------------------------------------------------|
| Session start (log entry > 7 days old) | <code>/wiki-ingest</code> before answering any architecture question |
| Any time                               | <code>/status</code> to orient yourself                              |

**Rule of thumb:** If `log.md`'s most recent `ingest` entry is older than the latest commit to `.claude/memory/`, the wiki is stale. Run the sync chain.

## Health Check

Open `Obsidian Vault/Zapocalypse/Wiki/_Health.md` in Obsidian (requires Dataview plugin) to see:

- **Stale pages** — `status: stale`, need `/wiki-ingest`
- **Old pages** — `status: current` but not updated in 30+ days
- **Orphans** — pages with zero inbound links (may be unreachable)
- **Schema violations** — pages missing required frontmatter

Or via grep:

```
grep -rl "status: stale" "Obsidian Vault/Zapocalypse/Wiki/"
```

## Quick Navigation Cheat Sheet

| I want to know...               | Page                                                    |
|---------------------------------|---------------------------------------------------------|
| Pipeline flow end-to-end        | <code>Wiki/Pipeline/Pipeline Overview</code>            |
| What the SKO contains           | <code>Wiki/Data/Schema - SKO</code>                     |
| How budget protection works     | <code>Wiki/Concepts/Budget Protection Layers</code>     |
| How tone fingerprinting works   | <code>Wiki/Concepts/Additive Tone Fingerprinting</code> |
| How C2PA signing works          | <code>Wiki/Concepts/C2PA Signing</code>                 |
| All Firestore collection paths  | <code>Wiki/Data/Data Model Overview</code>              |
| How Gemini calls are structured | <code>Wiki/Data/Gemini Client</code>                    |
| CSS glass morphism tokens       | <code>Wiki/Concepts/Glass Morphism Theme</code>         |
| Current phase + next work       | <code>Wiki/Project/Current Status</code>                |

| I want to know...       | Page                                                      |
|-------------------------|-----------------------------------------------------------|
| Phases 6-8 scope        | <a href="#">Wiki/Project/Roadmap</a>                      |
| Deployment config       | <a href="#">Wiki/Infrastructure/Deployment</a>            |
| All env vars            | <a href="#">Wiki/Infrastructure/Environment Variables</a> |
| Why a decision was made | <a href="#">Wiki/Decisions/*</a>                          |

The full semantic lookup table with wikilinks lives in [index.md](#) → "Semantic Lookup".

---

## Key Principles

1. **Wiki first, source never** — if a wiki page exists, don't open the source file for context
2. **Gap → log → ingest** — missing knowledge flows through [log.md](#), not through ad-hoc file reads
3. **Stale is safe** — a stale page is better than no page; it still has old cross-references and won't cause errors
4. **Sync chain** — [code change](#) → [memory sync](#) → [sync-vault.sh](#) → [/wiki-ingest](#) is the full loop
5. **Sources/ are sacred** — never edit [Sources/](#); they're overwritten on every [sync-vault.sh](#) run