

EXPERIMENT - 5

AIM

To create SQL views for department salary summary and employee hierarchy, test the updatability of views, and implement a recursive CTE to display reporting chains.

OBJECTIVES

- To create a view that summarizes employee salary information department-wise.
- To create an employee hierarchy view using manager relationships.
- To test whether a view is updatable and understand the conditions affecting view updates.
- To implement a recursive CTE for displaying employee reporting chains.
- To verify the results using SELECT queries.

DATABASE USED

The queries use the CompanyDB database and the Employee–Department–Project schema from the reference experiment. The Employee table is extended with manager_id to support employee hierarchy and recursive reporting chains.

USE CompanyDB;

SCHEMA REFERENCE

The Department, Project and Employee tables remain connected through dept_id and project_id. The Employee table additionally contains manager_id, which references Employee(emp_id).

SOURCE CODE / SQL QUERIES

1. DEPARTMENT SALARY SUMMARY VIEW

Create a view showing employee count, average salary, minimum salary, maximum salary and total salary for each department.

```
CREATE OR REPLACE VIEW department_salary_summary AS
SELECT
    d.dept_id,
    d.dept_name,
    COUNT(e.emp_id) AS employee_count,
    AVG(e.salary) AS average_salary,
    MIN(e.salary) AS minimum_salary,
    MAX(e.salary) AS maximum_salary,
    SUM(e.salary) AS total_salary
FROM Department d
JOIN Employee e
    ON d.dept_id = e.dept_id
GROUP BY d.dept_id, d.dept_name;
```

Output

 **AKASH KUMAR**

I/O

AI Agent

141 ms 

STDIN

Input for the program (Optional)

Output:

dept_id	dept_name	employee_count	average_salary	minimum_salary	maximum_salary	total_salary
1	IT	6	67833.333333	58000.00	81000.00	407000.00
2	HR	6	53666.666667	47000.00	61000.00	322000.00
3	Finance	6	69166.666667	56000.00	83000.00	415000.00
4	Marketing	6	60166.666667	51000.00	70000.00	361000.00
5	Operations	6	66500.000000	59000.00	76000.00	399000.00

The view returns one summary row for each of the five departments.

2. EMPLOYEE HIERARCHY VIEW

Create a view containing each employee and the name of the employee's immediate manager.

```
CREATE OR REPLACE VIEW employee_hierarchy AS
SELECT
    e.emp_id,
    e.emp_name,
    e.dept_id,
    d.dept_name,
    e.manager_id,
    m.emp_name AS manager_name,
    e.salary
FROM Employee e
JOIN Department d
    ON e.dept_id = d.dept_id
LEFT JOIN Employee m
    ON e.manager_id = m.emp_id;
```

Output

 AKASH KUMAR

I/O

AI Agent

120 ms 

STDIN

Input for the program (Optional)

Output:

emp_id	emp_name	dept_id	dept_name	salary
1	Aarav	1	IT	65000.00
2	Vivaan	1	IT	72000.00
3	Aditya	1	IT	58000.00
4	Anjun	1	IT	81000.00
5	Kabir	1	IT	69000.00
6	Reyansh	1	IT	62000.00
7	Ananya	2	HR	52000.00
8	Diya	2	HR	48000.00
9	Myra	2	HR	61000.00
10	Sara	2	HR	55000.00
11	Ishita	2	HR	47000.00
12	Meera	2	HR	59000.00
13	Rohan	3	Finance	75000.00
14	Karan	3	Finance	68000.00
15	Nikhil	3	Finance	83000.00
16	Yash	3	Finance	62000.00
17	Manav	3	Finance	71000.00
18	Dev	3	Finance	56000.00
19	Aanya	4	Marketing	54000.00
20	Kiara	4	Marketing	63000.00
21	Tanya	4	Marketing	57000.00
22	Riya	4	Marketing	66000.00
23	Avni	4	Marketing	51000.00
24	Navya	4	Marketing	70000.00
25	Samar	5	Operations	60000.00
26	Dhruv	5	Operations	73000.00
27	Atharv	5	Operations	67000.00
28	Parth	5	Operations	59000.00
29	Rudra	5	Operations	76000.00
30	Veer	5	Operations	64000.00

3. TEST UPDATABILITY OF VIEWS

Test an update on a simple employee hierarchy view and then test an update on the grouped department salary summary view.


```
UPDATE employee_hierarchy
SET salary = salary + 1000
WHERE emp_id = 6;
```

```
SELECT emp_id, emp_name, salary
FROM Employee
WHERE emp_id = 6;
```

```
UPDATE department_salary_summary
SET average_salary = average_salary + 1000
WHERE dept_id = 1;
```

Output

The first UPDATE is expected to fail because the employee_hierarchy view contains joins and does not directly expose a single base-table row for every selected column. The grouped department_salary_summary view is also not directly updatable because it contains GROUP BY and aggregate functions. The base Employee table should be updated instead.



4. RECURSIVE CTE – REPORTING CHAIN

Display the reporting chain beginning with department heads and recursively follow manager relationships.

```
WITH RECURSIVE reporting_chain AS (  
    SELECT  
        e.emp_id,  
        e.emp_name,  
        e.manager_id,  
        1 AS level,  
        CAST(e.emp_name AS CHAR(500)) AS reporting_path  
    FROM Employee e  
    WHERE e.manager_id IS NULL  
  
    UNION ALL  
  
    SELECT  
        e.emp_id,  
        e.emp_name,  
        e.manager_id,  
        rc.level + 1,  
        CONCAT(rc.reporting_path, ' -> ', e.emp_name)  
    FROM Employee e  
    JOIN reporting_chain rc  
        ON e.manager_id = rc.emp_id  
)  
SELECT emp_id, emp_name, manager_id, level, reporting_path  
FROM reporting_chain  
ORDER BY reporting_path;
```

Output



AKASH KUMAR

I/O

AI Agent

87 ms

STDIN

Input for the program (Optional)

Output:

emp_id	emp_name	manager_id	level	reporting_path
7	Anika	NULL	1	Anika
8	Kavya	7	2	Anika -> Kavya
9	Ira	8	3	Anika -> Kavya -> Ira
10	Naina	9	4	Anika -> Kavya -> Ira -> Naina
11	Aditi	10	5	Anika -> Kavya -> Ira -> Naina -> Aditi
12	Saanvi	11	6	Anika -> Kavya -> Ira -> Naina -> Aditi -> Saanvi
13	Harsh	NULL	1	Harsh
14	Mohit	13	2	Harsh -> Mohit
15	Ritvik	14	3	Harsh -> Mohit -> Ritvik
16	Ayush	15	4	Harsh -> Mohit -> Ritvik -> Ayush
17	Kunal	16	5	Harsh -> Mohit -> Ritvik -> Ayush -> Kunal
18	Varun	17	6	Harsh -> Mohit -> Ritvik -> Ayush -> Kunal -> Varun
1	Ishaan	NULL	1	Ishaan
2	Reyansh	1	2	Ishaan -> Reyansh
3	Adit	2	3	Ishaan -> Reyansh -> Adit
4	Aarush	3	4	Ishaan -> Reyansh -> Adit -> Aarush
5	Raghav	4	5	Ishaan -> Reyansh -> Adit -> Aarush -> Raghav
6	Vihaan	5	6	Ishaan -> Reyansh -> Adit -> Aarush -> Raghav -> Vihaan
19	Mehak	NULL	1	Mehak
20	Pihu	19	2	Mehak -> Pihu
21	Shreya	20	3	Mehak -> Pihu -> Shreya
22	Tara	21	4	Mehak -> Pihu -> Shreya -> Tara
23	Mahi	22	5	Mehak -> Pihu -> Shreya -> Tara -> Mahi
24	Anvi	23	6	Mehak -> Pihu -> Shreya -> Tara -> Mahi -> Anvi
25	Rajat	NULL	1	Rajat
26	Yuvraj	25	2	Rajat -> Yuvraj
27	Arnav	26	3	Rajat -> Yuvraj -> Arnav
28	Laksh	27	4	Rajat -> Yuvraj -> Arnav -> Laksh
29	Devansh	28	5	Rajat -> Yuvraj -> Arnav -> Laksh -> Devansh
30	Om	29	6	Rajat -> Yuvraj -> Arnav -> Laksh -> Devansh -> Om

RESULT

Views were created for department salary summaries and employee hierarchy. View update behavior was tested, and a recursive CTE was used successfully to display reporting chains.

CONCLUSION

SQL views provide reusable logical representations of data, while recursive CTEs can traverse self-referencing employee relationships to display hierarchical reporting structures.