1. What is HTML?

- **Answer:** HTML (HyperText Markup Language) is the standard language used to create web pages. It organizes content such as headings, paragraphs, images, and links so browsers can display them correctly. It is a markup language, not a programming language, because it does not perform logic or calculations.

2. What are HTML tags?

- **Answer:** HTML tags are the **building blocks of HTML**. They are keywords **enclosed** in **angle brackets**, such as for a paragraph. Most tags come in pairs: an opening tag ( ) and a closing tag ( ), where the closing tag includes a forward slash. Tags tell the browser what type of content is inside them.

3. What is the purpose of the <!DOCTYPE html> declaration?

- **Answer:** The <!DOCTYPE html> declaration defines the document type and version of HTML being used. It ensures that the browser renders the page correctly according to the HTML5 standard.

4. What is the difference between block-level and inline elements?

- **Answer:** Block-level elements occupy the entire width available and start on a new line (e.g., , <h1>,). Inline elements, on the other hand, occupy only as much width as necessary and do not start on a new line (e.g., , <a>, <img>).

5. How do you create a hyperlink in HTML?

- **Answer:** A hyperlink is created using the <a> tag with the href attribute. For example:

```
<a href="https://www.example.com">Click here</a>
```

This creates a link that, when clicked, navigates to the specified URL.

6. What is the purpose of the alt attribute in <img> tags?

- **Answer:** The alt attribute provides alternative text for an image, which is displayed if the image cannot be loaded. It also improves accessibility for users using screen readers and is important for SEO.

7. What is the difference between <ul>, <ol>, and <li> tags?

- **Answer:** The <ul> tag defines an unordered list, the <ol> tag defines an ordered list, and the <li> tag defines a list item. For example:

```
<ul>
  <li>Item 1</li>
  <li>Item 2</li>
</ul>
<ol>
  <li>First</li>
  <li>Second</li>
```

```
</ol>
```

8. How do you create a table in HTML?

- **Answer:** A table is created using the <table> tag along with <tr> for table rows, <th> for table headers, and <td> for table data cells. For example:

```
<table>
  <tr>
    <th>Name</th>
    <th>Age</th>
  </tr>
  <tr>
    <td>John</td>
    <td>25</td>
  </tr>
</table>
```

9. What is a semantic element in HTML?

- **Answer:** Semantic elements clearly **describe their meaning** to both the browser and the developer to readable way. Examples include **<header>, <footer>, <article>, and <section>.** These elements improve accessibility and SEO by providing additional context about the content.

10. How do you create a form in HTML?

- **Answer:** A form is created using the <form> tag, which can contain various input elements like text fields, checkboxes, radio buttons, and submit buttons. For example:

```
<form action="/submit" method="POST">
  <label for="name">Name:</label>
  <input type="text" id="name" name="name">
  <input type="submit" value="Submit">
</form>
```

11. What is the difference between the id and class attributes?

- **Answer:** The id attribute is used **to uniquely identify a single HTML element**, while the class attribute can be used to apply the same style or **behavior to multiple elements**. The id must be **unique within a document**, whereas class can be **shared among elements**.

12. What is the purpose of the meta tag in HTML?

Answer: The meta tag provides metadata about the HTML document, such as character encoding, author, viewport settings, and keywords. Metadata is not displayed on the page but is essential for SEO and responsive design.

13. How do you embed a video in HTML?

- **Answer:** You can embed a video using the <video> tag with the src attribute or by nesting a <source> element. For example:

```
<video controls>
  <source src="video.mp4" type="video/mp4">
  Your browser does not support the video tag.
</video>
```

The controls attribute adds playback controls.

14. What are HTML entities, and why are they used?

- **Answer:**

  HTML entities **are special codes** used to **display reserved** or **special characters in HTML**.
  They are written using an **ampersand (&) and end with a semicolon (;)**.
  Entities are used because some characters (like <, >) are part of HTML syntax.
  If used directly, they may break the code or not display properly.
  So, entities help **safely show these characters in a webpage**.

15. What is the difference between section, article, and div tags?

- **Answer:**
  - <section>: A semantic element that represents a **thematic grouping of content**, **typically with a heading**. It is used to divide a page into **different sections**.
  - <article>: A semantic element for **self-contained**, **independent content** that could be **distributed or reused** (e.g., a blog post, news story).
  - : A generic, non-semantic container used for **grouping content for styling or layout purposes.**

16. How do you include JavaScript in an HTML document?

There are several ways:

1. Inline: Using the <script> tag directly in the HTML. This is rarely recommended for large blocks of code.
2. Internal: Placing JavaScript code between <script> tags in the <head> or at the end of the <body>.
3. External (Best Practice): Using the <script> tag with the src attribute to link to an external .js file.

17. What is the role of the viewport meta tag in responsive design?

- **Answer:** The viewport meta tag gives the browser instructions on how to control the page's dimensions and scaling. Example:

```
<meta name="viewport" content="width=device-width, initial-scale=1.0">
```

18. What is the difference between padding and margin in HTML/CSS?

Answer:

- Padding is the space between an element's content and its border.
- Margin is the space outside an element's border.
- Both are used to control layout and spacing in web design.

19. How do you create a dropdown list in HTML?

- **Answer:** A dropdown list is created using the <select> tag with nested <option> elements. For example:

```
<select name="options">
  <option value="1">Option 1</option>
  <option value="2">Option 2</option>
</select>
```

20. What are data attributes in HTML, and how are they used?

- **Answer:** Data attributes allow you to **store extra information on HTML elements**, which can be **accessed via JavaScript**. They are defined using the **data-* attribute**. For example:

```
<div data-user-id="123">User Information</div>
```

In JavaScript, you can access this attribute using:

javascript

Copy code

```
var userId = document.querySelector('div').dataset.userId;
```

These questions and answers cover a broad range of topics that are frequently asked in HTML interviews.

21. What is the purpose of the <head> element in an HTML document?

- **Answer:** The <head> element contains **meta-information about the HTML document**, such as the **title, character set, links to stylesheets, scripts, and meta tags for SEO and responsive design.** It does not contain any content that is directly visible on the webpage.

22. How do you create an ordered list and an unordered list in HTML?

- **Answer:**
    - An ordered list is created using the <ol> tag, and each item is wrapped in an <li> tag. The items are automatically numbered:

```
<ol>
  <li>First item</li>
  <li>Second item</li>
```

```
</ol>
```

- An unordered list is created using the <ul> tag, and each item is wrapped in an <li> tag. The items are usually displayed with bullet points:

```
<ul>
  <li>First item</li>
  <li>Second item</li>
</ul>
```

23. What is the difference between the src and href attributes?

- **Answer:**
  - The src attribute is used to specify the **source of embedded content**, such as images (<img>), scripts (<script>), and iframes (<iframe>).
  - The href attribute is used to define **a hyperlink to another page or resource**, typically within an <a> tag.

24. What are the differences between inline, block, and inline-block elements?

- **Answer:**
  - **Inline elements**: Take up only as much width as necessary and do not force a new line (e.g., , <a>, <img>).
  - **Block elements**: Take up the full width available and always start on a new line (e.g., , <p>, <h1>).
  - **Inline-block elements**: Behave like inline elements, but you can set width, height, padding, and margins just like block elements.

25. How do you create a hyperlink that opens in a new tab?

- **Answer:** To create a hyperlink that opens in a new tab, use the **target="_blank"** attribute in the <a> tag:

```
<a href="https://www.example.com" target="_blank">Visit Example</a>
```

26. What is the difference between localStorage and sessionStorage in HTML5?

- **Answer:**
  - **localStorage**: Stores data with **no expiration time**. The data is **not deleted when the browser is closed** and can be accessed even **after restarting the browser**.
  - **sessionStorage** : It data stores **temporarily** for a single session and is **cleared** when the **browser tab is closed**

27. Explain the concept of responsive web design and its importance.

- **Answer:** Responsive web design is an approach to web development that ensures web pages render well on various **devices and window sizes**, from **mobile phones to desktops**. It is important because it improves the user experience by making web content accessible and

usable on all devices. This is achieved using **flexible grids, layouts, images, and CSS media queries.**

28. How do you include external CSS and JavaScript files in an HTML document?

- **Answer:**
    - To include external CSS, use the <link> tag within the <head> section:

<link rel="stylesheet" href="styles.css">

    - To include external JavaScript, use the <script> tag, typically at the end of the <body> section:

<script src="script.js" defer></script>

29. What is the difference between defer and async attributes in a <script> tag?

- **Answer:**
    - **async**: async loads the JavaScript file **in parallel** with HTML parsing and executes it **immediately once loaded**.
    - **defer**: defer loads the script in parallel but executes it **only after HTML parsing is complete**.

30. How do you create a checkbox and a radio button in HTML?

- **Answer:**
    - **Checkbox**: An HTML input element (type="checkbox") that allows users to select **one or more options** from a set.

<input type="checkbox" id="option1" name="option1" value="Option1">

<label for="option1">Option 1</label>

    - **Radio Button**: An HTML input element (type="radio") that allows users to select **only one option** from a group of choices (same name attribute).

<input type="radio" id="choice1" name="choices" value="Choice1">

<label for="choice1">Choice 1</label>

<input type="radio" id="choice2" name="choices" value="Choice2">

<label for="choice2">Choice 2</label>

31. What are data lists in HTML, and how are they used?

Answer:

- In HTML, a <datalist> is used to provide a **list of predefined suggestions** for an <input> field.
- **Usage:** It is linked to an <input> using the list attribute, and shows dropdown suggestions as the user types.

```
<input list="browsers" name="browser">
<datalist id="browsers">
  <option value="Chrome">
  <option value="Firefox">
  <option value="Safari">
</datalist>
```

32. What is the purpose of the disabled attribute in form elements?

- **Answer:** The disabled attribute is used to make a form element **inactive**. A disabled element cannot be **focused, clicked, or edited**, and its value is **not included when the form is submitted**

```
<input type="text" disabled>
```

33. What is the purpose of the required attribute in form fields?

- **Answer:** The required attribute specifies that an input field must be filled out before submitting the form. It is a form validation feature.

```
<input type="text" required>
```

34. Explain the difference between GET and POST methods in form submission.

- **Answer:**
    - **GET method**: Data is sent in the URL as query parameters and is visible in the address bar. It is used for retrieving data and has no side effects.
    - **POST method**: Data is sent in the HTTP request body and is not visible in the URL. It is used when data may change the server state (like form submission).

35. What is the placeholder attribute in an input field?

- **Answer:** The placeholder attribute provides a short hint or instruction that is displayed inside an input field when it is empty. The text disappears when the user starts typing.

```
<input type="text" placeholder="Enter your name">
```

36. What is the difference between span and div elements?

- **Answer:**
    - is an inline element used for grouping and styling inline content without disrupting the flow of the document.
    - is a block-level element used for grouping and styling larger sections of content. It creates a new block, and subsequent content appears on a new line.

37. How do you create an HTML comment, and why are they used?

- **Answer:** HTML comments are created using <!-- comment -->. They are used to add notes or explanations in the code that are not displayed in the browser. Comments are useful for documentation and debugging.

```
<!-- This is a comment -->
```

38. How do you specify the language of an HTML document?

- **Answer:** The language of an HTML document is specified using the lang attribute in the <html> tag. This helps browsers and search engines understand the language of the content.

```
<html lang="en">
```

39. What is the purpose of the fieldset and legend elements in forms?

- **Answer:**
    - <fieldset> groups related elements in a form, visually and semantically. It creates a box around the grouped elements.
    - <legend> provides a caption or title for the <fieldset>.

```
<fieldset>
  <legend>Personal Information</legend>
  <label for="name">Name:</label>
  <input type="text" id="name" name="name">
</fieldset>
```

40. How do you include a favicon in an HTML document?

- **Answer:** A favicon is included using the <link> tag in the <head> section, pointing to the icon file.

```
<link rel="icon" href="favicon.ico" type="image/x-icon">
```