

Hardcoded SEO JSON-LD inventory

This document lists **every JSON-LD (Schema.org) block** that is still defined or driven from **code**, so the same shapes can be recreated in **Admin** → **Content** → **SEO · JSON-LD schemas** (`page_json_ld_schemas`).

Related code:

Area	Path
Schema builders	<code>src/lib/seo/schemaBuilders.js</code>
Merge code + DB	<code>src/lib/seo/resolvePageJsonLd.js</code>
Route keys	<code>src/lib/seo/pageSeoRoutes.js</code>
Course defaults	<code>src/lib/seo/coursePageJsonLdDefaults.js</code>
Admin UI	<code>src/components/AdminCms/PageJsonLdEditor.jsx</code>
DB table	<code>admin/db/page_json_ld.sql</code>

How rendering works today

```
flowchart TB
    subgraph layout [Root layout – every page]
        H1["Hardcoded: org-schema + website-schema"]
        H2["DB: global-head / global-footer"]
    end
    subgraph page [Per-route page component]
        D["Code defaults by script_id"]
        DB["DB rows for page_route_key"]
        M["mergePageJsonLdPlans – DB wins on same script_id"]
        R["resolveJsonLdFromPlan + runtime context"]
    end
    H1 --> HTML
    H2 --> HTML
    D --> M --> R --> HTML
    DB --> M
```

1. `layout.js` always injects **Organization** and **WebSite** scripts (`id="org-schema"` , `id="website-schema"`). These are **not** in `page_json_ld_schemas` unless you duplicate them under route `global` .
2. Each page calls `buildPageJsonLdForRoute({ routeKey, defaults, context })` .
3. **Code defaults** register expected `script_id` s and `schema_kind` s.
4. **DB rows** with the **same** `script_id` override or disable (`enabled: false`) a code default.
5. Kinds `breadcrumb` , `faq` , `course` , `organization` , `website` are built from **context** (live CMS/catalog data) unless `config` in DB overrides items.

After CMS publish: clear public cache / revalidate so Next.js picks up DB changes.

Tier 1 — Hardcoded in `layout.js` (all pages)

These run on **every** public page and are **not** managed by per-route `buildPageJsonLdForRoute` today.

HTML id	@type	Source file	Move to admin?
org-schema	Organization	src/app/ layout.js	Yes → route <code>global</code> , placement <code>global-head</code> , kind <code>organization</code> or <code>raw</code>
website-schema	WebSite	src/app/ layout.js	Yes → route <code>global</code> , placement <code>global-head</code> , kind <code>website</code> or <code>raw</code>

Organization (current hardcoded values)

Use env `NEXT_PUBLIC_SITE_URL` for production URLs (example below uses `https://www.aaftonline.com`).

Field	Value
name	AAFT Online
url	{SITE_URL}
logo	{SITE_URL}/images/aaft-logo.png (via <code>publicAssetUrl</code>)
description	AAFT Online offers industry-led creative and professional online diploma and certificate programs.
sameAs	https://www.instagram.com/aaftonline/
	https://www.youtube.com/@AAFTONLINE
	https://www.facebook.com/AAFTONLINE
	https://www.linkedin.com/company/aaft-online/

Admin entry (kind `organization`): route `global` , script_id `org-schema` , placement `global-head` , config:

```
{
  "organization": {
    "siteUrl": "https://www.aaftonline.com",
    "logoUrl": "https://www.aaftonline.com/images/aaft-logo.png",
    "sameAs": [
      "https://www.instagram.com/aaftonline/",
      "https://www.youtube.com/@AAFTONLINE",
      "https://www.facebook.com/AAFTONLINE",
      "https://www.linkedin.com/company/aaft-online/"
    ],
    "description": "AAFT Online offers industry-led creative and professional online diploma and certificate programs."
  }
}
```

Or kind `raw` with full JSON-LD object in `json_ld` (same fields as `generateOrganizationSchema` output).

WebSite (current hardcoded values)

Field	Value
@type	WebSite
url	{SITE_URL}

Admin entry (kind `website`): route `global` , script_id `website-schema` , placement `global-head` , config:

```
{ "siteUrl": "https://www.aaftonline.com" }
```

Note: To remove duplicate scripts after migrating to DB, you must later delete or gate the hardcoded blocks in `layout.js` (lines with `ORGANIZATION_SCHEMA` / `WEBSITE_SCHEMA`).

Tier 2 — Per-page code defaults (merge with DB)

Admin route picker uses `page_route_key` from `src/lib/seo/pageSeoRoutes.js`.

Static routes

<code>page_route_key</code>	Page path	Code source	Default <code>script_ids</code>	<code>schema_kind</code>	Runtime data source
<code>home</code>	<code>/</code>	<code>src/app/page.js</code>	<code>home-faq-schema</code> (if FAQs exist)	<code>faq</code>	<code>sections.faq</code> (home CMS)
<code>about</code>	<code>/about-us</code>	<code>src/app/about-us/page.jsx</code>	<code>about-breadcrumb-schema</code>	<code>breadcrumb</code>	Home → About us
			<code>about-faq-schema</code> (if items)	<code>faq</code>	About page FAQ CMS
<code>explore-course</code>	<code>/explore-course</code>	<code>src/app/explore-course/page.jsx</code>	<code>explore-course-breadcrumb-schema</code>	<code>breadcrumb</code>	Home → Explore Courses
<code>faqs</code>	<code>/faqs</code>	<code>src/app/faqs/page.jsx</code>	<code>faqs-breadcrumb-schema</code>	<code>breadcrumb</code>	Home → FAQs
			<code>faqs-faq-schema</code> (if entries)	<code>faq</code>	<code>faq_page_entries</code> table
<code>diploma-courses</code>	<code>/diploma-courses</code>	<code>src/app/diploma-courses/page.jsx</code>	<code>diploma-courses-breadcrumb-schema</code>	<code>breadcrumb</code>	Home → Diploma Courses
<code>press-release</code>	<code>/press-release</code>	<code>src/app/press-release/page.jsx</code>	<code>press-release-breadcrumb-schema</code>	<code>breadcrumb</code>	Home → Press Release
<code>global</code>	<code>*</code> (all pages)	<code>src/app/layout.js</code>	(none in code)	—	Optional extra head/footer via <code>global-head</code> / <code>global-footer</code>

Breadcrumb items to enter in admin (`config.items`)

Use absolute URLs with your production origin.

`explore-course`

```
{
  "items": [
    { "name": "Home", "url": "https://www.aaftonline.com" },
    { "name": "Explore Courses", "url": "https://www.aaftonline.com/explore-course" }
  ]
}
```

about

```
{
  "items": [
    { "name": "Home", "url": "https://www.aaftonline.com" },
    { "name": "About us", "url": "https://www.aaftonline.com/about-us" }
  ]
}
```

faqs

```
{
  "items": [
    { "name": "Home", "url": "https://www.aaftonline.com" },
    { "name": "FAQs", "url": "https://www.aaftonline.com/faqs" }
  ]
}
```

diploma-courses

```
{
  "items": [
    { "name": "Home", "url": "https://www.aaftonline.com" },
    { "name": "Diploma Courses", "url": "https://www.aaftonline.com/diploma-courses" }
  ]
}
```

press-release

```
{
  "items": [
    { "name": "Home", "url": "https://www.aaftonline.com" },
    { "name": "Press Release", "url": "https://www.aaftonline.com/press-release" }
  ]
}
```

FAQ schemas (`config.items` or live context)

For `home` , `about` , `faqs` : if you add a DB row with the **same** `script_id` as the code default and kind `faq` :

- Leave `config.items` **empty** → page still passes `faqItems` in **context** (recommended; stays in sync with CMS).
- Or set `config.items` explicitly:

```
{
  "items": [
    { "q": "Question text?", "a": "Answer text." }
  ]
}
```

Aliases accepted: `question` / `answer` instead of `q` / `a` .

Course routes (`course: {cmsCoursePageKey}`)

Each live course page uses `CourseMarketingPage.jsx` with three code defaults per course (`coursePageJsonLdDefaults`).

<code>page_route_key</code>	Public path	<code>schemaIdPrefix</code> (<code>script_id</code> prefix)	Default script IDs
<code>course:fashion</code>	<code>/diploma-in-fashion-design</code>	<code>fashion</code>	<code>fashion-breadcrumb-schema</code> , <code>fashion-course-schema</code> , <code>fashion-faq-schema</code>
<code>course:nutrition</code>	<code>/diploma-in-nutrition</code>	<code>nutrition</code>	<code>nutrition-*</code>
<code>course:music</code>	<code>/diploma-in-music-production-online</code>	<code>music</code>	<code>music-*</code>
<code>course:interior</code>	<code>/diploma-in-interior-design</code>	<code>interior</code>	<code>interior-*</code>
<code>course:animation</code>	<code>/diploma-in-animation-and-vfx</code>	<code>animation</code>	<code>animation-*</code>
<code>course:jewelry</code>	<code>/diploma-in-jewelry-design</code>	<code>jewelry</code>	<code>jewelry-*</code>
<code>course:event</code>	<code>/diploma-in-event-management</code>	<code>event</code>	<code>event-*</code>
<code>course:hospital</code>	<code>/diploma-in-hospital-management</code>	<code>hospital</code>	<code>hospital-*</code>
<code>course:travel-tourism</code>	<code>/diploma-in-travel-and-tourism</code>	<code>travel-tourism</code>	<code>travel-tourism-*</code>
<code>course:culinary-arts</code>	<code>/diploma-in-culinary-arts</code>	<code>culinary-arts</code>	<code>culinary-arts-*</code>
<code>course:real-estate-management</code>	<code>/diploma-in-real-estate</code>	<code>real-estate</code>	<code>real-estate-*</code>
<code>course:psychology</code>	<code>/diploma-in-psychology</code>	<code>psychology</code>	<code>psychology-*</code>
<code>course:hotel-management</code>	<code>/diploma-in-hotel-management</code>	<code>hotel-management</code>	<code>hotel-management-*</code>
<code>course:fashion-styling</code>	<code>/diploma-in-fashion-styling</code>	<code>fashion-styling</code>	<code>fashion-styling-*</code>
<code>course:ayurvedic-wellness</code>	<code>/diploma-in-ayurvedic-wellness</code>	<code>ayurvedic-wellness</code>	<code>ayurvedic-wellness-*</code>
<code>course:screenwriting</code>	<code>/diploma-in-screenwriting</code>	<code>screenwriting</code>	<code>screenwriting-*</code>
<code>course:naturopathy</code>	<code>/diploma-in-naturopathy</code>	<code>naturopathy</code>	<code>naturopathy-*</code>
<code>course:makeup</code>	<code>/diploma-in-makeup</code>	<code>makeup</code>	<code>makeup-*</code>

page_route_key	Public path	schemaIdPrefix (script_id prefix)	Default script IDs
course:podcasting-media	/diploma-in-Podcasting	podcasting	podcasting-*
course:ad-film-making	/ad-film-making-online	ad-film-making	ad-film-making-*
course:certificate-advertising-pr	/advertising-pr-corporate-communication	advertising-pr	advertising-pr-*
course:journalism	/the-ultimate-journalism	journalism	journalism-*
course:radio-jockey	/radio-jockey	radio-jockey	radio-jockey-*
course:online-dj-course	/certification-in-djing	certification-djing	certification-djing-*
course:photography-comprehensive	/professional-photography	professional-photography	professional-photography-*

Admin route key uses catalog `cms_id` (= `cmsCoursePageKey`), e.g. `course:fashion`, not always the same as `schemaIdPrefix`.

Course breadcrumb (code default pattern)

All courses use the same **structure** (middle crumb label is "Diploma Courses", URL is **explore-course**, not diploma-courses listing):

```
{
  "items": [
    { "name": "Home", "url": "https://www.aafonline.com" },
    { "name": "Diploma Courses", "url": "https://www.aafonline.com/explore-course" },
    { "name": "{Program display name}", "url": "https://www.aafonline.com{canonicalPath}" }
  ]
}
```

Override per course in admin with kind `breadcrumb` + matching `script_id` (e.g. `fashion-breadcrumb-schema`).

Course schema (`schema_kind: course`)

Built by `generateCourseSchema()` from **runtime context** in `CourseMarketingPage.jsx` (catalog + CMS). Fields:

Field	Source
<code>name</code>	Brochure card title or hero program name
<code>description</code>	Card subtitle or <code>courseSchemaDescriptionFallback</code> from registry
<code>url</code>	Canonical course URL
<code>image</code>	Hero image or default OG image
<code>aggregateRating.ratingValue</code>	Card <code>rating</code> (default <code>4.8</code>)
<code>aggregateRating.ratingCount</code>	Card <code>reviewCount</code> (default <code>840</code>)
<code>offers</code>	<code>{ @type: Offer, category: Paid, priceCurrency: INR }</code>

Field	Source
<code>totalHistoricalEnrollment</code>	Card <code>enrolled</code> (default <code>2400</code>)
<code>about</code>	Basic-info job titles or card <code>jobs</code>
<code>teaches</code>	Basic-info learn bullets or card <code>learn</code>
<code>educationalCredentialAwarded</code>	Diploma credential (name = program, url = page)
<code>coursePrerequisites</code>	Fixed string: no specific prerequisites
<code>hasCourseInstance</code>	Online, workload <code>P1Y</code>
<code>publisher</code> / <code>provider</code>	AAFT Online (fixed in builder)

Recommendation: Keep kind `course` in code (dynamic). Use DB only to **disable** (`enabled: false`) or add **extra** `raw` blocks. For a fully static course JSON-LD in admin, use kind `raw` and paste full JSON (will **not** auto-update when catalog changes).

Course FAQ (`{prefix}-faq-schema`)

- Source: course page **FAQ block** (`sections.coursePages[cmsKey].faq`), not site-wide home FAQ.
- Same Q/A as visible FAQ section when CMS is updated.
- Admin: kind `faq` , empty `config.items` → still uses live context unless you override items.

Tier 3 — Schema kind reference (admin)

<code>schema_kind</code>	Generated <code>@type</code>	<code>config</code> keys	<code>json_ld</code>
<code>raw</code>	(any)	optional <code>jsonLd</code>	Required full object
<code>breadcrumb</code>	<code>BreadcrumbList</code>	<code>items[]</code> with <code>name</code> + <code>url</code>	—
<code>faq</code>	<code>FAQPage</code>	<code>items[]</code> with <code>q</code> / <code>a</code> (or question/answer)	—
<code>course</code>	<code>Course</code>	—	— (uses page <code>context.course</code>)
<code>organization</code>	<code>Organization</code>	<code>organization</code> object	—
<code>website</code>	<code>WebSite</code>	<code>siteUrl</code>	—

Placements

<code>placement</code>	Where rendered
<code>page</code>	That route's page component only
<code>global-head</code>	Root layout (after hardcoded org/website)
<code>global-footer</code>	Root layout end of <code><body></code>

Migrating a code default into the backend

1. Open **Admin** → **Content** → **SEO · JSON-LD schemas**.

2. Select the `page_route_key` (e.g. `explore-course` , `course:fashion` , `global`).
3. Add a row:
4. **Script ID** — must match code default exactly to override (e.g. `explore-course-breadcrumb-schema`).
5. **Label** — admin-only note.
6. **Kind** — `breadcrumb` | `faq` | `raw` | etc.
7. **Placement** — usually `page` (or `global-head` for org/website).
8. **Enabled** — `false` to turn off a code default without deleting.
9. **Config / JSON-LD** — per kind above.
10. Save → clear CDN / revalidate site cache.

To **stop using code defaults entirely** for a route: add DB rows for every `script_id` you need, then (later) remove the `defaults` array from that page's `buildPageJsonLdForRoute` call.

Not JSON-LD (separate SEO)

These are `<meta>` / Open Graph via `createPageMetadata()` or `layout.js metadata` — **not** in `page_json_ld_schemas` :

Page	File	Notes
Home	<code>src/app/page.js</code>	title, description, canonical /
Explore	<code>src/app/explore-course/page.jsx</code>	
About	<code>src/app/about-us/page.jsx</code>	dynamic from CMS SEO band when present
FAQs	<code>src/app/faqs/page.jsx</code>	
Diploma listing	<code>src/app/diploma-courses/page.jsx</code>	
Press release	<code>src/app/press-release/page.jsx</code>	
Each course	<code>src/app/{canonical}/page.jsx</code> + registry <code>defaultTitle</code> / <code>defaultDescription</code>	
Legal	<code>privacy-policy</code> , <code>terms-conditions</code>	
Root defaults	<code>src/app/layout.js</code>	fallback title/description

Future work could add a `page_seo_meta` table; today only JSON-LD is admin-managed.

Quick checklist

- [] Migrate **global** Organization + WebSite to `global` / `global-head` (then remove layout hardcoding when ready).
- [] Confirm static breadcrumbs in admin for explore, about, faqs, diploma-courses, press-release (or leave code defaults).
- [] Home / about / faqs FAQ schemas — prefer live context; document overrides only if needed.
- [] Per-course: decide keep dynamic `course` + `faq` in code vs static `raw` in DB.
- [] Verify `script_id` matches table above when overriding.
- [] Revalidate production after bulk import.

Example: disable code FAQ on home only

Field	Value
<code>page_route_key</code>	<code>home</code>
<code>script_id</code>	<code>home-faq-schema</code>
<code>schema_kind</code>	<code>faq</code>
<code>enabled</code>	<code>false</code>
<code>placement</code>	<code>page</code>

Code default is suppressed; add a different `script_id` with kind `raw` if you replace it.