



National Textile University

Department of Computer Science

Subject:

Operating System

Submitted to:

Sir Nasir Mehmood

Submitted by:

Akasha Fatima

Reg. number:

23-NTU-CS-FL-1132

Semester:

5th - A

Home Tasks 10

Task_01: Exercise 1 – Hotel Room Occupancy Problem

Scenario: A hotel has N Rooms.

Only N people can take rooms at a time; others must wait outside.

One person can only take one room, and one room can only be taken by one person.

Tasks: 1. Use a counting semaphore initialized to N

2. Each person (thread) enters, stays for 1–3 seconds, leaves

3. Print: “Person X entered” “Person X left”

4. Show how many rooms are currently occupied


CODE:

```

1  /* Exercise 1 - Hotel Room Occupancy Problem
2  Scenario:
3  A hotel has N Rooms.
4  Only N people can take room at a time; others must wait outside.
5  One person can only take one room and one room can only be taken by one person.
6
7  Tasks:
8  1. Use a counting semaphore initialized to N
9  2. Each person (thread) enters, stays for 1-3 seconds, leaves
10 3. Print:
11    "Person X entered"
12    "Person X left"
13 4. Show how many rooms are currently occupied*/
14
15 #include <stdio.h>
16 #include <stdlib.h>
17 #include <pthread.h>
18 #include <semaphore.h>
19 #include <unistd.h>
20
21 #define Room_Numbers 5          // N rooms in a hotel
22 #define People_Numbers 10      // N people taking room at a time
23
24 sem_t room_Semaphore;          // Counting semaphore for rooms
25 int occupied_Rooms = 0;        // Counter for occupied rooms
26 pthread_mutex_t counter_Mutex; // Mutex for protecting the occupied_Rooms counter
27
28 void* person(void* arg) {
29     int person_ID = *((int*)arg);
30
31     sem_wait(&room_Semaphore); // Wait for a room to be available
32
33     // Critical section to update occupied rooms
34     pthread_mutex_lock(&counter_Mutex);
35     occupied_Rooms++;
36     printf("Person %d entered. Occupied Rooms: %d\n", person_ID, occupied_Rooms);
37     pthread_mutex_unlock(&counter_Mutex);
38
39     printf("Person %d is staying in the room...\n", person_ID);
40     sleep((rand() % 3) + 1); // Person staying in the room for 1-3 seconds
41
42     // Person leaves the room
43     pthread_mutex_lock(&counter_Mutex);
44     occupied_Rooms--;
45     printf("Person %d left. Occupied Rooms: %d\n", person_ID, occupied_Rooms);
46     pthread_mutex_unlock(&counter_Mutex);
47
48     sem_post(&room_Semaphore); // Signal that a room is now available
49
50     return NULL;
51 }
52
53 int main() {
54     pthread_t people[People_Numbers];
55     int person_IDs[People_Numbers];
56
57     sem_init(&room_Semaphore, 0, Room_Numbers); // Initialize semaphore with N rooms
58     pthread_mutex_init(&counter_Mutex, NULL); // Initialize mutex
59
60     for (int i = 0; i < People_Numbers; i++) { // Create threads representing each single person
61         person_IDs[i] = i + 1;
62         pthread_create(&people[i], NULL, person, &person_IDs[i]);
63     }
64
65     for (int i = 0; i < People_Numbers; i++) { // Wait for all threads to finish
66         pthread_join(people[i], NULL);
67     }
68
69     sem_destroy(&room_Semaphore); // Clean up
70     pthread_mutex_destroy(&counter_Mutex);
71
72     return 0;
73 }

```

Output:



```
akasha@DESKTOP-NOLGFR1:~/Operating-System-1132/Home_Tasks/Home_Tasks_10_1132$ gcc Task_01.c -o Task_01.out -pthread
akasha@DESKTOP-NOLGFR1:~/Operating-System-1132/Home_Tasks/Home_Tasks_10_1132$ ./Task_01.out
Person 3 entered. Occupied Rooms: 1
Person 3 is staying in the room...
Person 6 entered. Occupied Rooms: 2
Person 6 is staying in the room...
Person 2 entered. Occupied Rooms: 3
Person 2 is staying in the room...
Person 4 entered. Occupied Rooms: 4
Person 4 is staying in the room...
Person 7 entered. Occupied Rooms: 5
Person 7 is staying in the room...
Person 2 left. Occupied Rooms: 4
Person 8 entered. Occupied Rooms: 5
Person 8 is staying in the room...
Person 3 left. Occupied Rooms: 4
Person 6 left. Occupied Rooms: 3
Person 1 entered. Occupied Rooms: 4
Person 5 entered. Occupied Rooms: 5
Person 5 is staying in the room...
Person 1 is staying in the room...
Person 4 left. Occupied Rooms: 4
Person 9 entered. Occupied Rooms: 5
Person 9 is staying in the room...
Person 8 left. Occupied Rooms: 4
Person 10 entered. Occupied Rooms: 5
Person 10 is staying in the room...
Person 1 left. Occupied Rooms: 4
Person 7 left. Occupied Rooms: 3
Person 9 left. Occupied Rooms: 2
Person 5 left. Occupied Rooms: 1
Person 10 left. Occupied Rooms: 0
```

Task_02: Exercise 2 – Download Manager Simulation

Scenario: You have a download manager that can download max 3 files at a time.

Tasks: Create 8 download threads

Use a counting semaphore with value = 3

Each download takes random 1–5 seconds

Print messages for start/end of each download

CODE:

```

1  /*Exercise 2 - Download Manager Simulation
2  Scenario:
3  You have a download manager that can download max 3 files at a time.
4  Tasks:
5  Create 8 download threads
6  Use a counting semaphore with value = 3
7  Each download takes random 1-5 seconds
8  Print messages for start/end of each download*/
9
10 #include <stdio.h>
11 #include <stdlib.h>
12 #include <pthread.h>
13 #include <semaphore.h>
14 #include <unistd.h>
15
16 #define Max_Downloads 3 // Maximum concurrent downloads
17 #define Total_Files 8 // Total files to download
18
19 sem_t download_Semaphore; // Counting semaphore for downloads
20
21 void* download_file(void* arg) {
22     int file_ID = *((int*)arg);
23
24     sem_wait(&download_Semaphore); // Wait for a download slot to be available
25
26     printf("Download %d started.\n", file_ID);
27     sleep((rand() % 5) + 1); // Download time of files is between 1-5 seconds
28     printf("Download %d completed.\n", file_ID);
29
30     sem_post(&download_Semaphore); // Signal that a download slot is now available
31
32     return NULL;
33 }
34 int main() {
35     pthread_t downloads[Total_Files];
36     int file_IDs[Total_Files];
37
38     sem_init(&download_Semaphore, 0, Max_Downloads); // Initialize semaphore with max downloads
39
40     for (int i = 0; i < Total_Files; i++) { // Create threads for each file download
41         file_IDs[i] = i + 1;
42         pthread_create(&downloads[i], NULL, download_file, &file_IDs[i]);
43     }
44
45     for (int i = 0; i < Total_Files; i++) { // Wait for all download threads to finish
46         pthread_join(downloads[i], NULL);
47     }
48
49     sem_destroy(&download_Semaphore); // Clean up semaphore
50     return 0;
51 }

```

Output:

```
File Edit Selection View Go Run ... Home_Tasks_10_1132 [WSL: Ubuntu-24.04] bash - Home_Tasks_10_1132 + ... | ... X
EXPLORER PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS
HOME_TASKS_10_1132 [WSL: UBU...
  C Task_01.c U
  Task_01.out U
  C Task_02.c U
  Task_02.out
  akasha@DESKTOP-NOLGFR1:~/Operating-System-1132/Home_Tasks/Home_Tasks_10_1132$ gcc Task_02.c -o Task_02.out
  -pthread
  akasha@DESKTOP-NOLGFR1:~/Operating-System-1132/Home_Tasks/Home_Tasks_10_1132$ ./Task_02.out
  Download 1 started.
  Download 2 started.
  Download 3 started.
  Download 2 completed.
  Download 4 started.
  Download 3 completed.
  Download 5 started.
  Download 4 completed.
  Download 7 started.
  Download 1 completed.
  Download 6 started.
  Download 7 completed.
  Download 8 started.
  Download 6 completed.
  Download 5 completed.
  Download 8 completed.
  akasha@DESKTOP-NOLGFR1:~/Operating-System-1132/Home_Tasks/Home_Tasks_10_1132$
  > OUTLINE
  > TIMELINE
WSL: Ubuntu-24.04 main* 0 0 0 0 Ln 51, Col 2 Spaces: 4 UTF-8 LF C Linux 4:01 PM 12/4/2025
```

Task_03: Exercise 3 – Library Computer Lab Access

Scenario:

A university lab has K computers.

Students must wait until a computer becomes free.

Tasks:

Semaphore initialized to number of computers

Track who is using which computer using a shared array

Protect the array using a mutex


CODE:

```

1  /* Exercise 3 - Library Computer Lab Access
2  Scenario:
3  A university lab has K computers.
4  Students must wait until a computer becomes free.
5  Tasks:
6  Semaphore initialized to number of computers
7  Track who is using which computer using a shared array
8  Protect the array using a mutex */
9
10 #include <stdio.h>
11 #include <stdlib.h>
12 #include <pthread.h>
13 #include <semaphore.h>
14 #include <unistd.h>
15
16 #define Computer_Numbers 4      // K computers in the university lab
17 #define Student_Numbers 10     // Total number of students
18
19 sem_t computer_Semaphore;      // Counting semaphore for computers
20 pthread_mutex_t lab_Mutex;      // Mutex for protecting the computer usage array
21 int computer_Usage[Computer_Numbers]; // Array to track which student is using which computer
22
23 void* student(void* arg) {
24     int student_ID = *((int*)arg);
25     int assigned_Computer = -1;
26
27     sem_wait(&computer_Semaphore); // Wait for a computer to be available
28
29     // Critical section to assign a computer
30     pthread_mutex_lock(&lab_Mutex);
31     for (int i = 0; i < Computer_Numbers; i++) {
32         if (computer_Usage[i] == 0) { // If computer is free
33             computer_Usage[i] = student_ID; // Assign student to computer
34             assigned_Computer = i;
35             printf("Student %d is using Computer %d.\n", student_ID, assigned_Computer + 1);
36             break;
37         }
38     }
39     pthread_mutex_unlock(&lab_Mutex);
40
41     sleep((rand() % 3) + 1); // Time spent using the computer (1-3 seconds)
42
43     // Student leaves the computer
44     pthread_mutex_lock(&lab_Mutex);
45     computer_Usage[assigned_Computer] = 0; // Free the computer
46     printf("Student %d has left Computer %d.\n", student_ID, assigned_Computer + 1);
47     pthread_mutex_unlock(&lab_Mutex);
48
49     sem_post(&computer_Semaphore); // Signal that a computer is now available
50
51     return NULL;
52 }
53 int main() {
54     pthread_t students[Student_Numbers];
55     int student_IDs[Student_Numbers];
56
57     sem_init(&computer_Semaphore, 0, Computer_Numbers); // Initialize semaphore with number of computers
58     pthread_mutex_init(&lab_Mutex, NULL); // Initialize mutex
59
60     // Initialize computer usage array to 0 (all computers are free)
61     for (int i = 0; i < Computer_Numbers; i++) {
62         computer_Usage[i] = 0;
63     }
64
65     for (int i = 0; i < Student_Numbers; i++) { // Create threads representing each student
66         student_IDs[i] = i + 1;
67         pthread_create(&students[i], NULL, student, &student_IDs[i]);
68     }
69
70     for (int i = 0; i < Student_Numbers; i++) { // Wait for all student threads to finish
71         pthread_join(students[i], NULL);
72     }
73
74     sem_destroy(&computer_Semaphore); // Clean up
75     pthread_mutex_destroy(&lab_Mutex);
76
77     return 0;
78 }

```

Output:



```
akasha@DESKTOP-NOLGFR1:~/Operating-System-1132/Home_Tasks/Home_Tasks_10_1132$ gcc Task_03.c -o Task_03.out
akasha@DESKTOP-NOLGFR1:~/Operating-System-1132/Home_Tasks/Home_Tasks_10_1132$ ./Task_03.out
Student 1 is using Computer 1.
Student 5 is using Computer 2.
Student 2 is using Computer 3.
Student 7 is using Computer 4.
Student 2 has left Computer 3.
Student 8 is using Computer 3.
Student 1 has left Computer 1.
Student 5 has left Computer 2.
Student 4 is using Computer 1.
Student 3 is using Computer 2.
Student 7 has left Computer 4.
Student 6 is using Computer 4.
Student 6 has left Computer 4.
Student 10 is using Computer 4.
Student 8 has left Computer 3.
Student 3 has left Computer 2.
Student 4 has left Computer 1.
Student 9 is using Computer 1.
Student 10 has left Computer 4.
Student 9 has left Computer 1.
akasha@DESKTOP-NOLGFR1:~/Operating-System-1132/Home_Tasks/Home_Tasks_10_1132$
```

Task_04: Exercise 4 – Thread Pool / Worker Pool Simulation

Scenario:

A server has fixed number of worker threads.

More tasks arrive than workers available.

Task:

Simulate 10 tasks and 3 workers

Tasks “run” by sleeping for 1–2 seconds

Semaphore controls worker availability


CODE:


```

1  /* Exercise 4 - Thread Pool / Worker Pool Simulation
2  Scenario:
3  A server has fixed number of worker threads.
4  More tasks arrive than workers available.
5  Task:
6  Simulate 10 tasks and 3 workers
7  Tasks "run" by sleeping for 1-2 seconds
8  Semaphore controls worker availability */
9
10 #include <stdio.h>
11 #include <stdlib.h>
12 #include <pthread.h>
13 #include <semaphore.h>
14 #include <unistd.h>
15
16 #define Worker_Numbers 3          // Number of worker threads
17 #define Task_Numbers 10          // Total number of tasks arriving at the server
18
19 sem_t worker_Semaphore;          // Counting semaphore for controlling worker's availability
20
21 void* task(void* arg) {
22     int task_ID = *((int*)arg);
23
24     sem_wait(&worker_Semaphore); // Wait for a worker to be available
25
26     printf("Task %d is being processed by a worker...\n", task_ID);
27     sleep((rand() % 2) + 1);      // Task Sleeping time (1-2 seconds)
28     printf("Task %d has been completed by a worker.\n", task_ID);
29
30     sem_post(&worker_Semaphore); // Signal that a worker is now available
31
32     return NULL;
33 }
34
35 int main() {
36     pthread_t tasks[Task_Numbers];
37     int task_IDs[Task_Numbers];
38
39     sem_init(&worker_Semaphore, 0, Worker_Numbers); // Initialize semaphore with number of workers
40
41     for (int i = 0; i < Task_Numbers; i++) {          // Create threads representing each task
42         task_IDs[i] = i + 1;
43         pthread_create(&tasks[i], NULL, task, &task_IDs[i]);
44     }
45
46     for (int i = 0; i < Task_Numbers; i++) {          // Wait for all tasks to finish
47         pthread_join(tasks[i], NULL);
48     }
49
50     sem_destroy(&worker_Semaphore); // Clean up
51
52     return 0;
53 }

```

Output:



```
akasha@DESKTOP-NOLGFR1:~/Operating-System-1132/Home_Tasks/Home_Tasks_10_1132$ gcc Task_04.c -o Task_04.out -pthread
akasha@DESKTOP-NOLGFR1:~/Operating-System-1132/Home_Tasks/Home_Tasks_10_1132$ ./Task_04.out
Task 2 is being processed by a worker...
Task 1 is being processed by a worker...
Task 3 is being processed by a worker...
Task 1 has been completed by a worker.
Task 4 is being processed by a worker...
Task 2 has been completed by a worker.
Task 3 has been completed by a worker.
Task 6 is being processed by a worker...
Task 5 is being processed by a worker...
Task 4 has been completed by a worker.
Task 7 is being processed by a worker...
Task 6 has been completed by a worker.
Task 7 has been completed by a worker.
Task 8 is being processed by a worker...
Task 9 is being processed by a worker...
Task 5 has been completed by a worker.
Task 10 is being processed by a worker...
Task 8 has been completed by a worker.
Task 9 has been completed by a worker.
Task 10 has been completed by a worker.
akasha@DESKTOP-NOLGFR1:~/Operating-System-1132/Home_Tasks/Home_Tasks_10_1132$
```

Task_05: Exercise 5 – Car Wash Station

Scenario:

Car wash has two washing stations.

Tasks:

Use counting semaphore initialized to 2 (number of washing stations)

Car threads wait for availability

Cars take 3 seconds to wash


Track queue lengths (optional)

CODE:



```
1  /* Exercise 5 - Car Wash Station
2  Scenario:
3  Car wash has two washing stations.
4  Tasks:
5  Use counting semaphore initialized to 2 (number of washing stations)
6  Car threads wait for availability
7  Cars take 3 seconds to wash
8  Track queue lengths (optional */
9
10 #include <stdio.h>
11 #include <stdlib.h>
12 #include <pthread.h>
13 #include <semaphore.h>
14 #include <unistd.h>
15
16 #define Washing_Stations 2    // Number of washing stations
17 #define Car_Numbers 8        // Total number of cars
18
19 sem_t wash_Semaphore;        // Counting semaphore for washing stations
20 pthread_mutex_t queue_Mutex;  // Mutex for protecting the queue length counter
21 int queue_Length = 0;         // Counter for cars waiting in the queue
22
23 void* car(void* arg) {
24     int car_ID = *((int*)arg);
25
26     // Increment queue length
27     pthread_mutex_lock(&queue_Mutex);
28     queue_Length++;
29     printf("Car %d is waiting. ----- Queue Length: %d\n", car_ID, queue_Length);
30     pthread_mutex_unlock(&queue_Mutex);
31
32     sem_wait(&wash_Semaphore); // Wait for a washing station to be available
33
34     // Decrement queue length
35     pthread_mutex_lock(&queue_Mutex);
36     queue_Length--;
37     printf("Car %d is being washed. ----- Queue Length: %d\n", car_ID, queue_Length);
38     pthread_mutex_unlock(&queue_Mutex);
39
40     sleep(3);                  // Car's washing time (3 seconds)
41     printf("Car %d has been washed.\n", car_ID);
42
43     sem_post(&wash_Semaphore); // Signal that a washing station is now available
44
45     return NULL;
46 }
47 int main() {
48     pthread_t cars[Car_Numbers];
49     int car_IDs[Car_Numbers];
50     sem_init(&wash_Semaphore, 0, Washing_Stations); // Initialize semaphore with number of washing stations
51     pthread_mutex_init(&queue_Mutex, NULL);         // Initialize mutex
52
53     for (int i = 0; i < Car_Numbers; i++) {          // Create threads representing each car
54         car_IDs[i] = i + 1;
55         pthread_create(&cars[i], NULL, car, &car_IDs[i]);
56     }
57
58     for (int i = 0; i < Car_Numbers; i++) {          // Wait for all car threads to finish
59         pthread_join(cars[i], NULL);
60     }
61
62     sem_destroy(&wash_Semaphore); // Clean up semaphore
63     pthread_mutex_destroy(&queue_Mutex); // Clean up mutex
64
65     return 0;
66 }
```

Output:



```
akasha@DESKTOP-NOLGFR1:~/Operating-System-1132/Home_Tasks/Home_Tasks_10_1132$ gcc Task_05.c -o Task_05.out -pthread
akasha@DESKTOP-NOLGFR1:~/Operating-System-1132/Home_Tasks/Home_Tasks_10_1132$ ./Task_05.out
Car 1 is waiting. ----- Queue Length: 1
Car 1 is being washed. ----- Queue Length: 0
Car 2 is waiting. ----- Queue Length: 1
Car 2 is being washed. ----- Queue Length: 0
Car 3 is waiting. ----- Queue Length: 1
Car 4 is waiting. ----- Queue Length: 2
Car 5 is waiting. ----- Queue Length: 3
Car 6 is waiting. ----- Queue Length: 4
Car 7 is waiting. ----- Queue Length: 5
Car 8 is waiting. ----- Queue Length: 6
Car 1 has been washed.
Car 2 has been washed.
Car 4 is being washed. ----- Queue Length: 5
Car 3 is being washed. ----- Queue Length: 4
Car 4 has been washed.
Car 5 is being washed. ----- Queue Length: 3
Car 3 has been washed.
Car 6 is being washed. ----- Queue Length: 2
Car 5 has been washed.
Car 6 has been washed.
Car 7 is being washed. ----- Queue Length: 1
Car 8 is being washed. ----- Queue Length: 0
Car 7 has been washed.
Car 8 has been washed.
akasha@DESKTOP-NOLGFR1:~/Operating-System-1132/Home_Tasks/Home_Tasks_10_1132$
```

Task_06: Exercise 6 – Traffic Bridge Control (Single-Lane Bridge)

Scenario:

Only 3 cars are allowed on the bridge at once.

Tasks:

Semaphore for max cars

Mutex for printing

Add random crossing times

CODE:

```

1  /* Exercise 6 - Traffic Bridge Control (Single-Lane Bridge)
2  Scenario:
3  Only 3 cars are allowed on the bridge at once.
4  Tasks:
5  Semaphore for max cars
6  Mutex for printing
7  Add random crossing times */
8
9  #include <stdio.h>
10 #include <stdlib.h>
11 #include <pthread.h>
12 #include <semaphore.h>
13 #include <unistd.h>
14
15 #define Max_Cars_On_Bridge 3    // Maximum cars allowed on the bridge
16 #define Total_Cars 10         // Total number of cars arriving at the bridge
17
18 sem_t bridge_Semaphore;        // Counting semaphore for bridge
19 pthread_mutex_t print_Mutex;    // Mutex for protecting print statements
20
21 void* car(void* arg) {
22     int car_ID = *((int*)arg);
23
24     // Critical section for printing that car is approaching the bridge
25     pthread_mutex_lock(&print_Mutex);
26     printf("Car %d is approaching the bridge.\n", car_ID);
27     pthread_mutex_unlock(&print_Mutex);
28
29     sem_wait(&bridge_Semaphore); // Wait for a spot on the bridge
30
31     // Critical section for printing that car is crossing the bridge
32     pthread_mutex_lock(&print_Mutex);
33     printf("Car %d is crossing the bridge...\n", car_ID);
34     pthread_mutex_unlock(&print_Mutex);
35
36     sleep((rand() % 3) + 1);      // Car crossing time (1-3 seconds)
37
38     // Critical section for printing that car has crossed the bridge
39     pthread_mutex_lock(&print_Mutex);
40     printf("Car %d has crossed the bridge.\n", car_ID);
41     pthread_mutex_unlock(&print_Mutex);
42
43     sem_post(&bridge_Semaphore); // Signal that a spot on the bridge is now available
44
45     return NULL;
46 }
47
48 int main() {
49     pthread_t cars[Total_Cars];
50     int car_IDs[Total_Cars];
51     sem_init(&bridge_Semaphore, 0, Max_Cars_On_Bridge); // Initialize semaphore with max cars on bridge
52     pthread_mutex_init(&print_Mutex, NULL);             // Initialize mutex
53
54     for (int i = 0; i < Total_Cars; i++) {               // Create threads representing each car
55         car_IDs[i] = i + 1;
56         pthread_create(&cars[i], NULL, car, &car_IDs[i]);
57     }
58
59     for (int i = 0; i < Total_Cars; i++) {               // Wait for all car threads to finish
60         pthread_join(cars[i], NULL);
61     }
62
63     sem_destroy(&bridge_Semaphore); // Clean up
64     pthread_mutex_destroy(&print_Mutex);
65
66     return 0;
67 }

```

Output:

```
File Edit Selection View Go Run ... Home_Tasks_10_1132 [WSL: Ubuntu-24.04]
PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS bash - Home_Tasks_10_1132
akasha@DESKTOP-NOLGFR1:~/Operating-System-1132/Home_Tasks/Home_Tasks_10_1132$ gcc Task_06.c -o Task_06.out -pthread
akasha@DESKTOP-NOLGFR1:~/Operating-System-1132/Home_Tasks/Home_Tasks_10_1132$ ./Task_06.out
Car 1 is approaching the bridge.
Car 1 is crossing the bridge...
Car 2 is approaching the bridge.
Car 2 is crossing the bridge...
Car 3 is approaching the bridge.
Car 3 is crossing the bridge...
Car 4 is approaching the bridge.
Car 5 is approaching the bridge.
Car 6 is approaching the bridge.
Car 7 is approaching the bridge.
Car 8 is approaching the bridge.
Car 9 is approaching the bridge.
Car 10 is approaching the bridge.
Car 3 has crossed the bridge.
Car 4 is crossing the bridge...
Car 1 has crossed the bridge.
Car 2 has crossed the bridge.
Car 5 is crossing the bridge...
Car 6 is crossing the bridge...
Car 4 has crossed the bridge.
Car 7 is crossing the bridge...
Car 6 has crossed the bridge.
Car 8 is crossing the bridge...
Ln 38, Col 69 Spaces: 4 UTF-8 LF C Linux
Type here to search 7:50 PM 12/4/2025
```

```
File Edit Selection View Go Run ... Home_Tasks_10_1132 [WSL: Ubuntu-24.04]
PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS bash - Home_Tasks_10_1132
akasha@DESKTOP-NOLGFR1:~/Operating-System-1132/Home_Tasks/Home_Tasks_10_1132$ ./Task_06.out
Car 5 is approaching the bridge.
Car 6 is approaching the bridge.
Car 7 is approaching the bridge.
Car 8 is approaching the bridge.
Car 9 is approaching the bridge.
Car 10 is approaching the bridge.
Car 3 has crossed the bridge.
Car 4 is crossing the bridge...
Car 1 has crossed the bridge.
Car 2 has crossed the bridge.
Car 5 is crossing the bridge...
Car 6 is crossing the bridge...
Car 4 has crossed the bridge.
Car 7 is crossing the bridge...
Car 6 has crossed the bridge.
Car 8 is crossing the bridge...
Car 5 has crossed the bridge.
Car 9 is crossing the bridge...
Car 8 has crossed the bridge.
Car 10 is crossing the bridge...
Car 7 has crossed the bridge.
Car 9 has crossed the bridge.
Car 10 has crossed the bridge.
akasha@DESKTOP-NOLGFR1:~/Operating-System-1132/Home_Tasks/Home_Tasks_10_1132$
Ln 38, Col 69 Spaces: 4 UTF-8 LF C Linux
Type here to search 7:50 PM 12/4/2025
```