



Simulation Panel

Event List

Vis.	Time(sec)	Last Devi	At Devi	Type	Info
	0.000	--	PC0	ICMP	
	0.001	PC0	Switch0	ICMP	
	0.002	Switch0	PC1	ICMP	
	0.003	PC1	Switch0	ICMP	
	0.004	Switch0	PC0	ICMP	
	1.001	--	Switch0	STP	

Reset Simulation ☒ Constant Delay Captured to: 1.001 s

Play Controls: Back Auto Capture / Play Capture / Forward

Event List Filters - Visible Events

ACL Filter, ARP, BGP, CDP, DHCP, DNS, DTP, EIGRP, EIGRPv6, FTP, H.323, HSRP, HSRPv6, HTTP, HTTPS, ICMP, ICMPv6, IPsec, ISAKMP, LACP, NBP, NETFLOW, NTP, OSPF, OSPFv6, PAgg, POP3, RADIUS, RDP, RDPing, RTSP, SCCP, SMTP, SNMP, SSH, STP, SYSLOG, TACACS, TCP, TFTP, Telnet, UDP, VTP

Edit Filters Show All/None

Simulation

Scenario 0

New Delete

Fire	Last Stat	Source	Destination	Type	Color	Time	Period	Num	Edit	Delete
Success...		PC0	PC1	ICMP		0.000	N	0	(e...)	(delete)

Switch0

Physical Config CLI

IOS Command Line Interface

```

Switch#config
Configuring from terminal, memory, or network [terminal]?
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#int fa0/2
Switch(config-if)#switchport access vlan 10
Switch(config-if)#switchport mode access
Switch(config-if)#ex
Switch(config)#
Switch(config)#int fa0/3
Switch(config-if)#
Switch(config-if)#switchport access vlan 20
Switch(config-if)#switchport mode access
Switch(config-if)#ex
Switch(config)#
Switch(config)#int fa0/4
Switch(config-if)#
Switch(config-if)#switchport access vlan 10
Switch(config-if)#switchport mode access
Switch(config-if)#ex
Switch(config)#
Switch(config)#ex
Switch#
%SYS-5-CONFIG_I: Configured from console by console

Switch#
Switch#
Switch#show vlan brief
  
```

VLAN Name	Status	Ports
-----------	--------	-------

Copy Paste

Switch0

Physical Config CLI

IOS Command Line Interface

```
Switch>
Switch>
Switch>EN
Switch#config
Configuring from terminal, memory, or network [terminal]?
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#
Switch(config)#VLAN 10
Switch(config-vlan)#EX
Switch(config)#VLAN 20
Switch(config-vlan)#EX
Switch(config)#EX
Switch#
%SYS-5-CONFIG_I: Configured from console by console

Switch#SHOW VLAN BRIEF
```

VLAN Name	Status	Ports
1 default	active	Fa0/1, Fa0/2, Fa0/3, Fa0/4 Fa0/5, Fa0/6, Fa0/7, Fa0/8 Fa0/9, Fa0/10, Fa0/11, Fa0/12 Fa0/13, Fa0/14, Fa0/15, Fa0/16 Fa0/17, Fa0/18, Fa0/19, Fa0/20 Fa0/21, Fa0/22, Fa0/23, Fa0/24 Gig0/1, Gig0/2
10 VLAN0010	active	
20 VLAN0020	active	
1002 fddi-default	active	
1003 token-ring-default	active	

Copy Paste

Router1

Physical Config CLI

IOS Command Line Interface

```
Router#config
Configuring from terminal, memory, or network
[terminal]?
Enter configuration commands, one per line. End
with CNTL/Z.
Router(config)#
Router(config)#int gigabitEthernet0/0
Router(config-if)#no sh

Router(config-if)#
%LINK-5-CHANGED: Interface GigabitEthernet0/0,
changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface
GigabitEthernet0/0, changed state to up

Router(config-if)#int gigabitEthernet0/0
Router(config-if)#
```

Copy Paste