

Outline

The **outline** property in CSS is used to draw a line around an element, outside of the borders.

The primary use of `outline` is to indicate that an element has the **keyboard focus**

Property	Description	Accepted Values
<code>outline</code>	Shorthand property for setting the width, style, and color of an outline in one declaration.	Combines values for the three properties below.
<code>outline-style</code>	Specifies the appearance or pattern of the line. This is the most crucial property for visibility.	<code>solid</code> , <code>dotted</code> , <code>dashed</code> , <code>double</code> , <code>groove</code> , <code>ridge</code> , <code>none</code> .
<code>outline-width</code>	Specifies the thickness of the line.	Lengths (e.g., <code>5px</code>), or keywords (<code>thin</code> , <code>medium</code> , <code>thick</code>).
<code>outline-color</code> or <code>or</code>	Specifies the color of the outline.	Color values (e.g., <code>red</code> , <code>#007bff</code> , <code>rgba(...)</code>), or <code>invert</code> .

outline-off set	Specifies the distance between the element's border and the outline. (Does not affect layout size).	Lengths (e.g., 3px, -1px).
--------------------	---	----------------------------

```

<!DOCTYPE html>
<html>

<head>
  <style>
    p {
      border: 2px solid black;
      outline: green solid 10px;
      margin: auto;
      padding: 20px;
      text-align: center;
      border: red solid 2px;
      margin: 10px;
    }
  </style>
</head>

<body>
  <h2>CSS Outline</h2>
  <p>Lorem ipsum dolor sit amet consectetur adipisicing elit. Perferendis,
dolor.</p>
</body>
</html>
<!DOCTYPE html>
<html>

<head>
  <style>
    p {
      border: 2px solid black;
      outline: green solid 10px;
      margin: auto;

```

```

padding: 20px;
text-align: center;
border: red solid 2px;
margin: 10px;
}
</style>
</head>

<body>
  <h2>CSS Outline</h2>
  <p>Lorem ipsum dolor sit amet consectetur adipisicing elit. Perferendis,
dolor.</p>
</body>
</html>

```

Transition :

A CSS transition enables gradual changes in property values over a defined period, rather than applying them immediately.

It helps create smooth and natural effects for actions like hovering, color fading, and element movement.

Sub-Property	Description	Example Value
transition-property	Specifies which CSS property to animate (e.g., <code>opacity</code> , <code>background-color</code> , <code>transform</code>).	<code>width</code> , <code>all</code>
transition-duration	Specifies how long the transition should take.	<code>0.5s</code> , <code>500ms</code>

transition-timing-function	Specifies the speed curve of the transition (how it accelerates and decelerates).	ease, linear, ease-in-out
transition-delay	Specifies a delay before the transition starts.	1s, 250ms

Timing Functions

Function

Description

- linear** Constant speed from start to end.
- ease** Starts slow, speeds up, then slows down (default).
- ease-in** Starts slow, then speeds up.
- ease-out** Starts fast, then slows down.
- ease-in-out** Starts slow, speeds up, then slows again.

Example 1:

```
<!DOCTYPE html>
<html lang="en">

<head>
  <meta charset="UTF-8">
```

```

<title>Card Lift Transition</title>
<style>
    .card {
        width: 250px;
        height: 160px;
        background-color: #4a90e2;
        color: white;
        font-size: 18px;
        display: flex;
        justify-content: center;
        align-items: center;
        border-radius: 10px;
        margin: 40px auto;
        transition: transform 0.5s ease, box-shadow 0.5s ease;
    }

    .card:hover {
        transform: translateY(-10px);
        box-shadow: 0 15px 25px rgba(0, 0, 0, 0.3);
    }
</style>
</head>

<body>
    <h2>Card Lift Transition</h2>
    <div class="card">Hover Me</div>
</body>

</html>

```

Example2 :

```

<!DOCTYPE html>
<html lang="en">

<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>CSS Transition Example</title>
    <style>
        body {

```

```
        background-color: #f4f4f4;
        font-family: Arial, sans-serif;
        text-align: center;
        margin-top: 80px;
    }

    .card {
        width: 200px;
        height: 200px;
        background-color: #4a90e2;
        margin: auto;
        border-radius: 10px;
        box-shadow: 0 4px 10px rgba(0, 0, 0, 0.2);
        color: white;
        display: flex;
        align-items: center;
        justify-content: center;
        font-size: 18px;
        transition:
            background-color 0.8s ease,
            transform 0.6s ease-in-out,
            box-shadow 0.8s ease,
            border-radius 0.6s;
    }

    .card:hover {
        background-color: #50e3c2;
        transform: scale(1.1) rotate(5deg);
        box-shadow: 0 10px 25px rgba(0, 0, 0, 0.3);
        border-radius: 50%;
    }
</style>
</head>

<body>
    <h2>CSS Transition Demonstration</h2>
    <p>Hover over the box to see smooth transitions.</p>
    <div class="card">Hover Me</div>
</body>
</html>
```

Navigation Bar :

A **navigation bar** is a crucial UI element on a website that lists links to the main sections or pages, helping users navigate the site. They are essentially styled lists of hyperlinks.

Ways to create nav bar in css

1. Flexbox
2. Float
3. Inline-Block

Example: Using Flexbox

<!DOCTYPE html>

```
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Nav Bar - Flexbox</title>
  <style>
    .navbar-flex ul {
      list-style-type: none;
      margin: 0;
      padding: 0;
      background-color: #007bff;
      display: flex;
    }

    .navbar-flex li a {
      display: block;
      color: white;
      padding: 15px 20px;
      text-decoration: none;
      text-align: center;
      transition: background-color 0.3s;
    }

    .navbar-flex li a:hover {
      background-color: #0056b3;
    }
  </style>
</head>
```

```

<body>
  <nav class="navbar-flex">
    <ul>
      <li><a href="#">Home</a></li>
      <li><a href="#">Products</a></li>
      <li><a href="#">About</a></li>
      <li><a href="#">Contact</a></li>
    </ul>
  </nav>
</body>
</html>

```

Example2 : Using Float

```

<!DOCTYPE html>
<html>
<head>
  <style>
    body {
      margin: 0;
      padding: 0;
    }

    h2,p {
      margin: 10px;
    }

    ul {
      list-style-type: none;
      margin: 0;
      padding: 0;
      overflow: hidden;
      background-color: #333333;
    }

    ul li {
      float: left;
    }

    ul li a {
      display: block;
      color: white;
    }
  </style>

```



```

        text-align: center;
        padding: 14px 16px;
        text-decoration: none;
    }

    ul li a:hover {
        background-color: #111111;
    }
</style>
</head>
<body>
    <ul>
        <li><a href="#home">Home</a></li>
        <li><a href="#news">News</a></li>
        <li><a href="#contact">Contact</a></li>
        <li><a href="#about">About</a></li>
    </ul>
    <h2>Horizontal Navbar Using Float</h2>
</body>

</html>

```

Example 3 : Inline Block

```

<!DOCTYPE html>
<html lang="en">

<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Inline-Block Navigation Bar</title>
    <style>
        nav {
            background-color: #333;
            padding: 10px 0;
        }

        nav a {
            display: inline-block;
            color: white;
            text-decoration: none;
            padding: 12px 20px;
        }
    </style>

```

```
    nav a:hover {
      background-color: #2686df;
      border-radius: 5px;
    }
  </style>
</head>
<body>
  <nav>
    <a href="#">Home</a>
    <a href="#">About</a>
    <a href="#">Services</a>
    <a href="#">Portfolio</a>
    <a href="#">Contact</a>
  </nav>
</body>
</html>
```