

CKYC 2.0

Simplified Download APIs

Integration Guide — Individual and Legal Entity Records

API Integration Document

Covers: Initiate Download · Download · Resend OTP

1. Objective

This document describes three APIs that together replace the standard CKYC record lookup and download journey with a small, fixed set of calls: **Initiate Download**, **Download**, and **Resend OTP**. A Reporting Entity (RE) picks a consent mechanism once and integrates against these APIs instead of orchestrating a longer sequence of search, validation, and consent steps.

Both **Individual** and **Legal Entity** records are covered in this single document. Every request field, response field, and enum value the client needs is defined here.

API	Purpose	Applies to
Initiate Download	Locates the record — or accepts a known CKYC reference number directly — and opens the download journey, capturing consent in the same call	Individual, Legal
Download	Completes consent verification (where applicable) and retrieves the full KYC record	Individual, Legal
Resend OTP	Re-triggers an OTP that was sent by Initiate Download	Individual, Legal

1.1 Entity Types

customerType	Description
INDIVIDUAL	A natural person's KYC record. Supports all three consent mechanisms: <code>OTP</code> , <code>PHYSICAL</code> , <code>FACEAUTH</code> .
LEGAL	A legal entity's KYC record (company, LLP, etc.). Does not use the consent-type mechanism. Where OTP verification is required for a legal record, it happens automatically as part of the journey.

1.2 Consent Mechanisms (Individual only)

consentType	Description	Eligibility
OTP	A one-time password is sent to the mobile number and/or email on the record.	Requires a mobile number or email on the record
PHYSICAL	The customer signs a physical consent form, which is scanned and uploaded.	Always eligible — the only option when neither mobile nor email is on the record
FACEAUTH	The customer's live photograph is matched against the record.	Requires a mobile number or email on the record

Note: `consentType` is chosen upfront, on the first call. If the chosen mechanism is not eligible for the matched record, Initiate Download returns an error naming the eligible alternative (see Section 2.7).

2. Initiate Download

Locates a KYC record — by search criteria, or directly by a known CKYC reference number — and, unless only search results are requested, opens the download journey and captures consent in the same call.

API URL

```
POST https://{{URL}}/api/ckyc/v2/download/initiate
```

Replace `{{URL}}` with your assigned domain.

Authentication

Requires a unique `appId` and `appKey` issued to your organization.

Headers

Header	Mandatory	Description
<code>Content-Type</code>	Yes	<code>application/json</code>
<code>appId</code>	Yes	Application identifier issued to the client
<code>appKey</code>	Yes	Application key issued to the client
<code>transactionId</code>	No	Client-supplied identifier for tracking and logging. Echoed back in the response headers if present.

2.1 Request Parameters

Parameter	Type	Mandatory	Description
<code>customerType</code>	Enum	Yes	<code>INDIVIDUAL</code> , <code>LEGAL</code>
<code>ckycRefNo</code>	String	Optional	A known CKYC reference number, typically obtained from a prior search-only call (Section 2.3). When provided, <code>searchOption</code> and <code>searchCriteria</code> must be omitted and Search is skipped entirely.
<code>searchOption</code>	Enum	Required when <code>ckycRefNo</code> is not provided	See Section 2.2 for valid values per <code>customerType</code>
<code>searchCriteria</code>	Object	Required when <code>ckycRefNo</code> is not provided	Shape depends on <code>searchOption</code> . See Section 2.2.
<code>returnOnlySearchResponse</code>	Boolean	No (default <code>false</code>)	When <code>true</code> , only the record lookup runs. No download journey is opened and no consent step runs. Not applicable when <code>ckycRefNo</code> is supplied.
<code>consentType</code>	Enum	Required when <code>customerType</code> is <code>INDIVIDUAL</code> and <code>returnOnlySearchResponse</code> is not <code>true</code>	<code>OTP</code> , <code>PHYSICAL</code> , <code>FACEAUTH</code> . Must be omitted for <code>LEGAL</code> .
<code>authFactors</code>	Array of objects	Required when <code>consentType</code> is <code>PHYSICAL</code> or <code>FACEAUTH</code>	See Section 2.4

2.2 searchOption and searchCriteria Reference

Exactly one `searchOption` is used per call. Valid values by `customerType` :

customerType	Valid searchOption values
<code>INDIVIDUAL</code>	<code>OVD</code> , <code>CKYC</code> , <code>DEMOGRAPHIC</code> , <code>PHOTO</code> , <code>MOBILE</code> , <code>VC</code>
<code>LEGAL</code>	<code>OVD</code> , <code>DOI</code> , <code>MOBILE</code> , <code>CKYC</code>

Individual — OVD

`{ "ovdDetails": [ { "ovdNo", "ovdType", "fullName", "dob", "gender" } ] }` . Array — multiple documents can be searched in one call. PAN is searched as `ovdType: C` ; there is no separate PAN option.

Field	Type	Mandatory	Values
<code>ovdDetails[].ovdNo</code>	String	Yes	OVD number
<code>ovdDetails[].ovdType</code>	Enum	Yes	<code>A</code> Passport, <code>B</code> Voter ID, <code>C</code> PAN, <code>D</code> Driving Licence, <code>E</code> Aadhaar, <code>F</code> NREGA Job Card, <code>G</code> National Population Register Letter, <code>H</code> eKYC Authentication, <code>I</code> Offline Verification of Aadhaar, <code>J</code> Foreign

			government document, z Others
<code>ovdDetails[].fullName</code> , <code>.dob</code> (DD-MM-YYYY), <code>.gender</code>	String	Conditional	Needed for some ovdType values (e.g. Aadhaar), not others (e.g. PAN)

Individual — CKYC

`{ "ckycNo": "..." }`

Field	Type	Mandatory	Values
<code>ckycNo</code>	String	Yes	14-digit CKYC number

Individual — DEMOGRAPHIC

`{ "firstName", "middleName", "lastName", "gender", "dob", "relation", "relativeFirstName", "relativeMiddleName", "relativeLastName" }`

Field	Type	Mandatory	Values
<code>firstName</code>	String	Yes	
<code>middleName</code>	String	No	
<code>lastName</code>	String	Yes	
<code>gender</code>	String	Yes	
<code>dob</code>	String	Yes	Format DD-MM-YYYY
<code>relation</code>	String	Yes	Relationship to the relative named below
<code>relativeFirstName</code>	String	Yes	
<code>relativeMiddleName</code>	String	No	
<code>relativeLastName</code>	String	No	

Individual — PHOTO

`{ "firstName", "middleName", "lastName", "b64Photo" }`

Field	Type	Mandatory	Values
<code>firstName</code>	String	Yes	
<code>middleName</code>	String	No	
<code>lastName</code>	String	Yes	
<code>b64Photo</code>	String	Yes	Base64-encoded photograph

Individual — MOBILE

`{ "mobile": "..." }`

Field	Type	Mandatory	Values
<code>mobile</code>	String	Yes	Exactly 10 digits, must not start with 0. If more than 5 records share the number, the search is rejected — use a <code>ckycRefNo</code> once one is known (Section 2.3).

Individual — VC

`{ "ckycAlias": "..." }`

Field	Type	Mandatory	Values
<code>ckycAlias</code>	String	Yes	Format: <code>[FirstName].[LastName]</code> + last 3 digits of pincode + 2-character state code + 4-digit-plus-1-character unique code + <code>@ckyc</code> . Example: <code>Sandeep.sharma2727943242@ckyc</code> . Max 80 characters.

Legal — OVD

`{ "documentIds": [ { "id_type", "id_number" } ] }` . Array — multiple document IDs can be searched in one call.

Field	Type	Mandatory	Values
<code>documentIds[].id_type</code>	Enum	Yes	C PAN, 01 Registration Certificate (GSTIN), 02 Certificate of Incorporation (CIN), 04 LLP Identification Number (LLPIN)
<code>documentIds[].id_number</code>	String	Yes	ID number corresponding to <code>id_type</code>

Legal — DOI

`{ "constitution", "entityName", "doi" }` . Entity formation date search.

Field	Type	Mandatory	Values
<code>constitution</code>	String	Yes	Constitution type of the entity
<code>entityName</code>	String	Yes	
<code>doi</code>	String	Yes	Date of incorporation, DD-MM-YYYY

Legal — MOBILE

`{ "mobile": "..." }`

Field	Type	Mandatory	Values
<code>mobile</code>	String	Yes	10-digit mobile number registered against the entity

Legal — CKYC

`{ "ckycNo": "..." }`

Field	Type	Mandatory	Values
<code>ckycNo</code>	String	Yes	14-digit CKYC number

2.3 Locating One Record Among Several Matches

A search may return more than one matching record (for example, a `MOBILE` search where several people share a number). The search response carries `ckycRefNo` only — not `ckycNo` — so refining `searchCriteria` and searching again returns the same match set. To open a journey against one specific record:

- Call Initiate Download with `returnOnlySearchResponse: true` to get the full, unfiltered result list.
- Identify the desired record from `results[]` by its `ckycRefNo` .
- Call Initiate Download again, passing that `ckycRefNo` directly instead of `searchOption / searchCriteria` . This skips Search entirely and opens the journey against that exact record.

When `searchCriteria` is used without a `ckycRefNo` and multiple records match, the first result is used by default. `totalMatches` in the response reports how many records were found.

2.4 authFactors Reference

Required only when `consentType` is `PHYSICAL` or `FACEAUTH` . An array — more than one factor can be submitted per call.

authFactor	Companion field	Values
<code>DOB</code>	<code>authValue</code>	String, format DD-MM-YYYY
<code>RELATION</code>	<code>authFactorValueObj</code>	<code>{ "relationName", "firstName", "middleName", "lastName" }</code> . <code>relationName</code> is one of <code>Father</code> , <code>Mother</code> , <code>Spouse</code> .
<code>BIRTHYEARPINCODE</code>	<code>authFactorValueObj</code>	<code>{ "year", "pincode" }</code>

2.5 Sample Requests and Responses

Individual — OTP consent

```
{
  "customerType": "INDIVIDUAL",
  "searchOption": "CKYC",
  "searchCriteria": { "ckycNo": "11223344556677" },
  "consentType": "OTP"
}
```

```
{
  "success": true,
  "message": "Record matched, OTP triggered",
  "matchedRecord": {
    "fullName": "Manoranjan Kumar Dubey",
    "firstName": "Manoranjan", "middleName": "Kumar", "lastName": "Dubey",
    "gender": "M", "photo": "/9j/4/Z", "photoExt": ".jpg",
    "docSubmitted": [
      { "docName": "PAN", "docType": "C" },
      { "docName": "Driving Licence", "docType": "D" }
    ]
  }
}
```

```
    ],
    "lastUpdateDate": "2026-04-22T06:47:16.361035510Z",
    "mobile": "", "email": "",
    "ckycRefNo": "INRGPK99016315", "photoId": "34136",
    "status": "ACTIVE", "remark": "",
    "matchedOvdType": "C", "matchedOvdNumber": "AQAPD6079Q"
  },
  "totalMatches": 1,
  "downloadRefId": "a52bc817-1699-4f78-975d-8b2aa51cddf6",
  "consentCheck": false,
  "hasMobileNumber": true, "hasEmailAddress": true,
  "otpIdentifiers": {
    "MOBILE": "QOIS32-OTP-20260720T045812",
    "EMAIL": "EQIEQ9-OTP-20260720T045813"
  }
}
```

Individual — targeted directly by ckycRefNo (after a prior search-only call)

```
{
  "customerType": "INDIVIDUAL",
  "ckycRefNo": "INRGYY098765",
  "consentType": "OTP"
}
```

Individual — Physical consent

```
{
  "customerType": "INDIVIDUAL",
  "searchOption": "OVD",
  "searchCriteria": { "ovdDetails": [ { "ovdType": "C", "ovdNo": "AQAPD6079Q" } ] },
  "consentType": "PHYSICAL",
  "authFactors": [
    { "authFactor": "DOB", "authValue": "15-01-1973" },
    { "authFactor": "RELATION", "authFactorValueObj": { "relationName": "Father", "firstName": "THANG", "middleName": "", "lastName": "THANGHNUNA" },
    { "authFactor": "BIRTHYEARPINCODE", "authFactorValueObj": { "year": "1960", "pincode": "411045" } }
  ]
}
```

Individual — FaceAuth consent

```
{
  "customerType": "INDIVIDUAL",
  "searchOption": "MOBILE",
  "searchCriteria": { "mobile": "9999888877" },
  "consentType": "FACEAUTH",
  "authFactors": [ { "authFactor": "DOB", "authValue": "15-01-1973" } ]
}
```

Legal — OTP

```
{
  "customerType": "LEGAL",
  "searchOption": "CKYC",
  "searchCriteria": { "ckycNo": "98700000000439" }
}
```

```
{
  "success": true,
  "message": "Record matched, OTP triggered",
  "matchedRecord": {
    "name": "National Finance & Associates",
    "ckycRefNo": "LEPPQX46577348",
    "cin": "", "dateOfRegistration": "2017-02-13",
    "mobile": "97*****99", "email": "ad****08@yopmail.com",
    "status": "ACTIVE", "remark": "",
    "docSubmitted": [
      { "ckycNo": "98700000000439", "docCategory": "POI", "docId": "SEANIZALON3287522017", "docName": "Registration Certificate", "docType": "03" }
    ]
  },
  "totalMatches": 1,
  "downloadRefId": "f3e4d5c6-1234-4a5b-9c8d-7e6f5a4b3c2d",
  "consentCheck": false,
  "hasMobileNumber": true, "hasEmailAddress": true,
  "otpIdentifiers": { "MOBILE": "LGOTP1-20260817T091422" }
}
```

Legal — consent already on file

```
{
  "success": true,
  "message": "Record matched, consent already on file",
  "matchedRecord": { "name": "XYZ Logistics LLP", "ckycRefNo": "LGRGAA445566", "status": "ACTIVE" },
  "totalMatches": 1,
  "downloadRefId": "b2a1c9d8-5566-4e3f-8a9b-1c2d3e4f5a6b",
  "consentCheck": true,
  "hasMobileNumber": true, "hasEmailAddress": true,
  "otpIdentifiers": null
}
```

Search only (`returnOnlySearchResponse: true`)

```
{
  "customerType": "INDIVIDUAL",
  "searchOption": "MOBILE",
  "searchCriteria": { "mobile": "9999888877" },
  "returnOnlySearchResponse": true
}
```

```
{
  "success": true,
  "message": "2 individual entity records found",
  "results": [
    { "fullName": "Ramesh Kumar Sharma", "ckycRefNo": "INRGYY098765" },
    { "fullName": "Ramesh K Sharma", "ckycRefNo": "INRGYY098766" }
  ],
  "totalMatches": 2,
  "downloadRefId": null, "consentCheck": null,
  "hasMobileNumber": null, "hasEmailAddress": null, "otpIdentifiers": null
}
```

2.6 Response Field Reference

Field	Type	Description
success	Boolean	true / false
message	String	Human-readable result message
matchedRecord	Object	Full result for the matched record (absent when returnOnlySearchResponse is true ; see results[] instead)
results	Array	Present only in the search-only case — every matching record, unfiltered, same shape as matchedRecord
totalMatches	Integer	Total records found. Always 1 when ckycRefNo was supplied directly.
downloadRefId	String	Unique reference for this journey; required on Download and Resend OTP. null in the search-only case.
consentCheck	Boolean	true if valid consent already exists for this RE — Download can be called immediately with no consent fields
hasMobileNumber / hasEmailAddress	Boolean	Whether a mobile number / email is present on the matched record
otpIdentifiers	Object	{ "MOBILE": "...", "EMAIL": "..." } , present only when an OTP was triggered. Only the channel(s) actually used are present.

matchedRecord / results[] — Individual

Field	Type	Description
ckycRefNo	String	CKYC reference number — see prefix table below
fullName , firstName , middleName , lastName	String	Name fields as registered
gender	String	
photo	String (Base64)	KYC photograph
photoExt	String	Photo file extension
photoId	String	Photo identifier
mobile / email	String	Masked. Empty string if none on record.
docSubmitted	Array	Each entry: docName (label), docType (letter code, same enum as ovdType)
lastUpdateDate	String	Date the record was last updated

status	Enum	ACTIVE , INACTIVE , DEACTIVATED
remark	String	Additional remarks
matchedOvdType / matchedOvdNumber	String	OVD type/number the match was made on

matchedRecord / results[] — Legal

Field	Type	Description
ckycRefNo	String	CKYC reference number — see prefix table below
name	String	Entity name as registered
cin	String	Corporate Identification Number. Empty string if not applicable.
dateOfRegistration	String	
mobile / email	String	Masked
status	Enum	ACTIVE , INACTIVE , DEACTIVATED
remark	String	
docSubmitted	Array	Each entry: ckycNo , docCategory (POI / POA), docId , docName , docType (two-digit numeric code, e.g. 01 Registration Certificate, 03 PAN)

ckycRefNo Prefixes

Prefix	Account type
None	Normal account
S	Small account
L	Simplified Measures account
O	Aadhaar OTP-based e-KYC in non face-to-face mode
M	Minor account
X	Deceased — the record cannot be downloaded

2.7 Error Responses

```
{
  "success": false,
  "error": {
    "code": "CONSENT_NOT_ELIGIBLE",
    "message": "OTP not eligible. No mobile or email on file. Use PHYSICAL consent instead."
  }
}
```

HTTP Status	code	message
400	INVALID_REQUEST	A required field is missing, or a field fails format validation
400	INVALID_SEARCH_CRITERIA	Search criteria is invalid or insufficient for the given searchOption
400	TOO_MANY_MATCHES	More than 5 CKYC records are linked to this mobile number
401	UNAUTHORIZED	Missing or invalid appId / appKey
403	FORBIDDEN	appId is not authorized for this deployment
404	RECORD_NOT_FOUND	No matching record found for the given search criteria or ckycRefNo
422	CONSENT_NOT_ELIGIBLE	Chosen consentType is not eligible for this record; the eligible alternative is named
422	RECORD_DECEASED	Matched record is deceased (ckycRefNo prefix X) and cannot be downloaded
422	AUTH_FACTOR_MISMATCH	The auth factor supplied does not match what's registered on the record
429	RATE_LIMIT_EXCEEDED	Rate limit exceeded — retry after a delay
500	INTERNAL_ERROR	An unexpected error occurred
503	REGISTRY_UNAVAILABLE	The CKYC registry is temporarily unavailable

504	REGISTRY_TIMEOUT	The CKYC registry search timed out
-----	------------------	------------------------------------

3. Download

Completes consent (where applicable) and retrieves the full KYC record. Called once, immediately after Initiate Download.

API URL

```
POST https://{URL}}/api/ckyc/v2/download/complete
```

Headers

Header	Mandatory	Description
<code>Content-Type</code>	Yes	<code>application/json</code>
<code>appId</code>	Yes	Application identifier issued to the client
<code>appKey</code>	Yes	Application key issued to the client
<code>transactionId</code>	No	Client-supplied identifier for tracking

3.1 Request Parameters

Parameter	Type	Mandatory	Description
<code>customerType</code>	Enum	Yes	<code>INDIVIDUAL</code> , <code>LEGAL</code>
<code>downloadRefId</code>	String	Yes	From Initiate Download's response
<code>otp</code>	String	Required for OTP branch, with <code>otpIdentifier</code>	6-digit numeric string collected from the customer
<code>otpIdentifier</code>	String	Required for OTP branch, with <code>otp</code>	One value from Initiate Download's <code>otpIdentifiers</code> , for the channel the customer used
<code>consentDocument</code>	String	Required for Physical branch	Base64-encoded signed consent document, or a URL pointing to it (auto-detected)
<code>selfie</code>	String	Required for FaceAuth branch	Base64-encoded customer photograph, or a URL pointing to it (auto-detected)

Exactly one branch should be populated: `otp` with `otpIdentifier` , `consentDocument` , or `selfie` . None of them are needed when `consentCheck` was `true` on Initiate Download — only `customerType` and `downloadRefId` are required in that case.

3.2 Sample Requests

OTP branch

```
{
  "customerType": "INDIVIDUAL",
  "downloadRefId": "a52bc817-1699-4f78-975d-8b2aa51cddf6",
  "otp": "213456",
  "otpIdentifier": "QOIS32-OTP-20260720T045812"
}
```

Physical branch (Base64 or URL)

```
{ "customerType": "INDIVIDUAL", "downloadRefId": "8d99a754-...", "consentDocument": "bnkjvbjwv3213456" }
{ "customerType": "INDIVIDUAL", "downloadRefId": "8d99a754-...", "consentDocument": "https://client-storage.example.com/consent-docs/8d99a754.pdf" }
```

FaceAuth branch (Base64 or URL)

```
{ "customerType": "INDIVIDUAL", "downloadRefId": "c71fa321-...", "selfie": "iVBORw0KGgoAAAANS..." }
{ "customerType": "INDIVIDUAL", "downloadRefId": "c71fa321-...", "selfie": "https://client-storage.example.com/selfies/c71fa321.jpg" }
```

Direct-download branch (consent already on file)

```
{ "customerType": "LEGAL", "downloadRefId": "b2a1c9d8-5566-4e3f-8a9b-1c2d3e4f5a6b" }
```

3.3 Response Envelope

Identical shape across every branch.

Field	Type	Description
success	Boolean	
message	String	
downloadRefId	String	Echoed from the request
ckycNo	String	14-digit CKYC number of the downloaded record
status	String	Outcome of the request, e.g. KYC Record Found
timestamp	String	ISO 8601, UTC
data.searchResult	Object	Summary of the retrieved record — see 3.4
data.kycDetails	Object	Full record — see 3.5 (Individual) / 3.6 (Legal)

3.4 data.searchResult Field Reference

Field	Type	Description
status	Enum	ACTIVE , INACTIVE , DEACTIVATED
name	String	Full name (Individual) or entity name (Legal)
ckycNo	String	14-digit CKYC number
lastUpdatedOn	String	Date the record was last modified
confidenceLevel	String	e.g. Assured , Probable . Can be empty.
confidenceScore	Number	0 to 100
kycAccountType	Enum	NORMAL , SMALL , MINOR , AADHAR_EKYC
ckycAlias	String	alias@ckyc format. Can be empty.
prohibitedLists.nameReflectedIn	Array	Prohibited/sanction lists the name appears in. Empty if none.
entityType	String	Legal records only, e.g. LLP

3.5 data.kycDetails Field Reference — Individual

demographicDetails

Field	Type	Description
demographicDetails.nameDetails.title	String	Title prefix, e.g. Mr, Mrs, Ms, Dr
demographicDetails.nameDetails.firstName / .middleName / .lastName	String	Structured name
demographicDetails.nameDetails.photoAvailable	Boolean	Whether a photograph is attached to the record
demographicDetails.photo	String (Base64)	KYC photograph
demographicDetails.motherName.title / .firstName / .lastName	String	Mother's name
demographicDetails.fatherName.title / .firstName / .lastName	String	Father's name
demographicDetails.dob	String	Date of birth, DD-MM-YYYY
demographicDetails.isMinor	Boolean	True if the customer is a minor as per DOB
demographicDetails.gender	String	Gender code: M , F , T
demographicDetails.dobMatchingWithOVD	Boolean	True if DOB matches the OVD submitted
demographicDetails.nameMatchingWithOVD	Boolean	True if name matches the OVD submitted
demographicDetails.photoMatchingWithOVD	Boolean	True if photo matches the OVD
demographicDetails.genderMatchingWithOVD	Boolean	True if gender matches the OVD
demographicDetails.genderProvidedInOvd	Boolean	True if gender is provided in the OVD
demographicDetails.panCard.number	String	PAN number
demographicDetails.panCard.panVerified	Boolean	

demographicDetails.panCard.panImage	Boolean	Whether a PAN image is attached
demographicDetails.panCard.image	String (Base64)	PAN image, if attached
demographicDetails.panCard.description	String	
demographicDetails.residentialStatus.status	String	Residential status
demographicDetails.residentialStatus.supportedByDocument	Boolean	
demographicDetails.nationality.country	String	
demographicDetails.nationality.supportedByDocument	Boolean	
demographicDetails.differentlyAbled.status	Boolean	
demographicDetails.differentlyAbled.type	Enum	Blindness, Low Vision, Hearing Impairment, Locomotor Disability, Leprosy Cured, Cerebral Palsy, Intellectual Disability, Mental Illness, Muscular Dystrophy, Parkinson's Disease, Acid Attack Victim, Sickle Cell Disease, Haemophilia, Thalassemia, Speech and Language Disability, Multiple Sclerosis, Specific Learning Disabilities, Chronic Neurological Conditions, Autism Spectrum Disorder, Dwarfism, Other
demographicDetails.differentlyAbled.others	String	Free text, only when <code>type</code> is Other
demographicDetails.differentlyAbled.disabilityValidity	String	<code>Permanent</code> / <code>No</code>
demographicDetails.differentlyAbled.disabilityDate	String	DD-MM-YYYY
demographicDetails.differentlyAbled.udidNo	String	Disability certificate number
demographicDetails.differentlyAbled.differentlyAbledSupportedByDocument	Boolean	
demographicDetails.form60Flg	String	<code>Y</code> / <code>N</code>

proofOfIdentityAndAddress

Field	Type	Description
proofOfIdentityAndAddress.ovdDetails	Array of objects	One entry per OVD submitted — fields below
ovdDetails[] .ovdType	String	OVD type code
ovdDetails[] .idNoLast4Digits	String	Last 4 digits of the OVD number
ovdDetails[] .ovdCertifiedWithOriginal	Boolean	Certified against the original by an authorised official
ovdDetails[] .equivalentEDoc	Boolean	Submitted as a digitally signed equivalent e-document
ovdDetails[] .documentVerifiedFromDigilocker	Boolean	
ovdDetails[] .presenceOfOVDINRepository	Boolean	Present in the issuing repository (e.g. UIDAI)
ovdDetails[] .presenceOfOVDINRepositoryByRE	Boolean	Verified present in the repository by the RE
ovdDetails[] .drivingLicenseExpiryDate	String	DD-MM-YYYY, when <code>ovdType</code> = <code>D</code>
ovdDetails[] .passportExpiryDate	String	DD-MM-YYYY, when <code>ovdType</code> = <code>A</code>
ovdDetails[] .modeOfAadhaarVerification	String	
ovdDetails[] .modeOfAuthentication	String	Mode selected at the time the CKYC record was created
ovdDetails[] .ekycDataRecievedFromUidai	Boolean	
ovdDetails[] .offlineVerificationOfAadhaar	Boolean	
proofOfIdentityAndAddress.documents	Array of objects	One entry per uploaded document — fields below
documents[] .b64Doc	String (Base64)	Document file content
documents[] .docId	String	Document / OVD number
documents[] .docType	Enum	<code>01</code> Passport, <code>02</code> Voter ID, <code>03</code> PAN, <code>05</code> Aadhaar, <code>06</code> Driving Licence, <code>07</code> NREGA Job Card, <code>08</code> National Population Register Letter, <code>98</code> Other

<code>documents [].docName</code>	String	Original uploaded file name
<code>documents [].docCategory</code>	Enum	<code>POI</code> Proof of Identity, <code>POA</code> Proof of Address
<code>documents [].docDescription</code>	String	
<code>proofOfIdentityAndAddress.ovdNotAvailable</code>	Boolean	True when no OVD was submitted

addressDetails

Field	Type	Description
<code>addressDetails.sameAsPermanent</code>	Boolean	True if current address equals the OVD (permanent) address
<code>addressDetails.permanentAddress.addressLine1</code> / <code>.addressLine2</code> / <code>.addressLine3</code>	String	Address as per OVD
<code>addressDetails.permanentAddress.country</code> / <code>.state</code> / <code>.district</code> / <code>.cityTownVillage</code> / <code>.pinCode</code>	String	ISO country code; state/district per CKYCRR master; 6-digit PIN
<code>addressDetails.permanentAddress.digipin</code>	String	
<code>addressDetails.permanentAddress.addressSupportedWithDoc</code>	Boolean	
<code>addressDetails.permanentAddress.addressMatchWithDoc</code>	String	<code>Y</code> / <code>N</code>
<code>addressDetails.permanentAddress.proofOfAddress</code>	String	Proof-of-address document code
<code>addressDetails.currentAddress.addressLine1-3</code> , <code>.country</code> , <code>.state</code> , <code>.district</code> , <code>.cityTownVillage</code> , <code>.pinCode</code> , <code>.digipin</code> , <code>.proofOfAddress</code>	String	Same shape as <code>permanentAddress</code>
<code>addressDetails.currentAddress.addressMatchWithOvd</code>	String	Whether current address matches the OVD / deemed POA
<code>addressDetails.currentAddress.physicalVerficiationOfCurrAdd</code>	Boolean	Whether the current address has been physically verified
<code>addressDetails.currentAddress.geoTagged</code>	Boolean	Whether geo-tagging was carried out
<code>addressDetails.currentAddress.physicalVerificationByThirdParty</code>	Boolean	
<code>addressDetails.currentAddress.physicalVerificationByReOffical</code>	Boolean	Verified by the RE
<code>addressDetails.currentAddress.supportingDoc []</code>	Array	Additional supporting documents; same shape as <code>proofOfIdentityAndAddress.documents</code>
<code>addressDetails.currentAddress.addressProofDoc []</code>	Array	OVD-based address proof documents; same shape as above
<code>addressDetails.currentAddress.ovdDetails []</code>	Array	OVD details specific to the current address; same shape as <code>proofOfIdentityAndAddress.ovdDetails</code>
<code>addressDetails.currentAddress.nationalPoaDoc []</code>	Array	National POA documents for the current address; same shape as above

contactDetails, relatedPartyDetails, clientRERelationship, otherDetails

Field	Type	Description
<code>contactDetails.emailAddress</code>	String	Primary email, masked / blank in some flows
<code>contactDetails.countryCode</code>	String	Mobile country code, e.g. <code>+91</code>
<code>contactDetails.mobileNumber</code>	String	Primary mobile number, masked / blank in some flows
<code>contactDetails.mobileVerified</code> / <code>.emailVerified</code>	Boolean	
<code>contactDetails.mobileVerifiedThrough3Party</code>	String	<code>Y</code> / <code>N</code>
<code>relatedPartyDetails [].relation</code>	String	Relationship of the related party to the applicant
<code>relatedPartyDetails [].ckycNumber</code>	String	CKYC number of the related person
<code>relatedPartyDetails [].fullName</code>	String	Full name of the related person
<code>clientRERelationship.noOfTimesDownloaded</code>	Integer	Total number of times this record has been downloaded
<code>clientRERelationship.noOfTimesUpdated</code>	Integer	Total number of times this record has been updated
<code>otherDetails.modeOfKYC</code>	String	Mode of CKYC creation

<code>otherDetails.remark</code>	String	Remarks on the record
<code>docDetails</code>	Object	Reserved for future use. <code>null</code> when not populated.

3.6 data.kycDetails Field Reference — Legal

legalEntityDetails

Field	Type	Description
<code>legalEntityDetails.entityName</code>	String	
<code>legalEntityDetails.entityConstitution</code>	String	Constitution type code
<code>legalEntityDetails.listedCompany</code>	Boolean	
<code>legalEntityDetails.dateOfIncorporation</code>	String	DD-MM-YYYY
<code>legalEntityDetails.dateOfCommencementOfBusiness</code>	String	DD-MM-YYYY
<code>legalEntityDetails.placeOfIncorporation</code>	String	
<code>legalEntityDetails.countryOfIncorporation</code>	String	ISO country code
<code>legalEntityDetails.tinOrEquivalentIssuingCountry</code>	String	
<code>legalEntityDetails.pan.number</code>	String	PAN number
<code>legalEntityDetails.pan.panImage</code>	String (Base64)	
<code>legalEntityDetails.pan.panVerified</code>	Boolean	
<code>legalEntityDetails.pan.panDescription</code>	String	
<code>legalEntityDetails.pan.presenceOfOVDINRepository</code>	Boolean	
<code>legalEntityDetails.tinGstin.number</code>	String	TIN or 15-character GSTIN
<code>legalEntityDetails.tinGstin.tinGstImage</code>	String (Base64)	
<code>legalEntityDetails.tinGstin.tinGstDescription</code>	String	

proofOfIdentityAndAddress

Field	Type	Description
<code>proofOfIdentityAndAddress.ovdDetails</code>	Object (single, not an array)	Unlike Individual, Legal carries one OVD detail object
<code>ovdDetails.ovdType</code>	String	OVD type per CKYCRR Legal Entity master (Certificate of Incorporation, Registration Certificate, Trust Deed, Partnership Deed, etc.). May be blank.
<code>ovdDetails.ovdNumber</code>	String	OVD reference / registration number. Null if not provided.
<code>proofOfIdentityAndAddress.documents</code>	Array of objects	Same shape as Individual's: <code>b64Doc</code> , <code>docId</code> , <code>docType</code> , <code>docName</code> , <code>docCategory</code> (<code>POI</code> / <code>POA</code>), <code>docDescription</code>

addressDetails

Field	Type	Description
<code>addressDetails.sameAsPermanent</code>	Boolean	True if Principal Place of Business equals Registered Address
<code>addressDetails.registeredAddress.addressLine1</code> / <code>.addressLine2</code>	String	Registered office address (per Certificate of Incorporation)
<code>addressDetails.registeredAddress.country</code> / <code>.state</code> / <code>.district</code> / <code>.cityTownVillage</code> / <code>.pinCode</code>	String	
<code>addressDetails.registeredAddress.proofOfAddress</code>	String	
<code>addressDetails.registeredAddress.otherDocName</code>	String	
<code>addressDetails.principalPlaceOfBusiness.*</code>	—	Same field shape as <code>registeredAddress</code>
<code>addressDetails.documents</code>	Array of objects	Supporting POA documents for the entity address(es). Same shape as <code>proofOfIdentityAndAddress.documents</code> . Empty if none.

contactDetails, clientRERelationship, otherDetails

Field	Type	Description
contactDetails.emailAddress	String	
contactDetails.countryCode	String	
contactDetails.mobileNumber	String	
contactDetails.mobileVerified	Boolean	
clientRERelationship.noOfTimesDownloaded	Integer	Total number of times this record has been downloaded
clientRERelationship.noOfTimesUpdated	Integer	Total number of times this record has been updated
otherDetails.remark	String	
otherDetails.modeOfKYC	String	
docDetails	Object	Reserved for future use. <code>null</code> when not populated.

3.7 Sample Response — Individual

```
{
  "success": true, "message": "KYC data fetched successfully",
  "downloadRefId": "a52bc817-1699-4f78-975d-8b2aa51cd9f6",
  "ckycNo": "40052211470560", "status": "ACTIVE",
  "timestamp": "2026-08-01T13:20:59.610714717Z",
  "data": {
    "searchResult": {
      "status": "ACTIVE", "name": "RAM SHARMA", "ckycNo": "40052211470560",
      "lastUpdatedOn": "2024-06-18T20:36:53Z", "confidenceLevel": "", "confidenceScore": 0,
      "kycAccountType": "NORMAL", "ckycAlias": "", "prohibitedLists": { "nameReflectedIn": [] }
    },
    "kycDetails": {
      "demographicDetails": {
        "nameDetails": { "title": "Mr", "firstName": "RAM SHARMA", "lastName": "", "photoAvailable": true },
        "photo": "/9j/4AAQSkZ=",
        "motherName": { "title": "Mrs", "firstName": "VIDYA", "lastName": "" },
        "fatherName": { "title": "Mr", "firstName": "SHYAM", "lastName": "" },
        "dob": "26-01-2000", "isMinor": false, "gender": "M",
        "dobMatchingWithOVD": false, "nameMatchingWithOVD": false, "photoMatchingWithOVD": false,
        "genderMatchingWithOVD": false, "genderProvidedInOvd": false,
        "panCard": { "number": "ESEPM6716B", "panVerified": false, "panImage": false, "image": "", "description": "" },
        "residentialStatus": { "status": "", "supportedByDocument": false },
        "nationality": { "country": "", "supportedByDocument": false },
        "differentlyAble": { "status": false, "disabilityValidity": "No", "differentlyAbleSupportedByDocument": false },
        "form60Flg": "N"
      },
      "proofOfIdentityAndAddress": {
        "ovdDetails": [ { "ovdType": "E", "idNoLast4Digits": "5956" } ],
        "documents": [ { "b64Doc": "/9j/4A", "docId": "XXXXXXXXX5956", "docType": "04", "docName": "8061114021540_U.jpg", "docCategory": "POI", "docStatus": "Active" },
        "ovdNotAvailable": false
      },
      "addressDetails": {
        "sameAsPermanent": true,
        "permanentAddress": { "addressLine1": "LOHAR AALI BOUDH WASTI SAMOR GHODEGAON PUNE", "country": "IN", "state": "MH", "district": "229", "city": "Pune" }
      },
      "contactDetails": { "emailAddress": "manoranjana@example.com", "countryCode": "+91", "mobileNumber": "9131234289", "mobileVerified": true, "emailVerified": true },
      "relatedPartyDetails": [],
      "clientRERelationship": { "noOfTimesDownloaded": 1, "noOfTimesUpdated": 1 },
      "otherDetails": { "modeOfKYC": "", "remark": "" },
      "docDetails": null
    }
  }
}
```

3.8 Sample Response — Legal

```
{
  "success": true, "message": "KYC data fetched successfully",
  "downloadRefId": "b2a1c9d8-5566-4e3f-8a9b-1c2d3e4f5a6b",
  "ckycNo": "70041234053211", "status": "ACTIVE",
  "timestamp": "2026-08-01T18:04:44.505391144Z",
  "data": {
    "searchResult": {
      "status": "ACTIVE", "entityType": "Legal Entity", "name": "COMPANY LIMITED",
      "ckycNo": "70041234053211", "lastUpdatedOn": "2026-03-07T13:48:01Z",
      "prohibitedLists": { "nameReflectedIn": [] }
    },
    "kycDetails": {
      "legalEntityDetails": {
        "entityName": "COMPANY LIMITED", "entityConstitution": "D",

```

```

    "dateOfIncorporation": "05-01-2001", "dateOfCommencementOfBusiness": "05-01-2001",
    "placeOfIncorporation": "RAJASTHAN", "countryOfIncorporation": "IN",
    "pan": { "number": "FQWCI1125A", "panImage": "", "panVerified": false, "panDescription": "" },
    "tinGstin": { "number": "0001055", "tinGstImage": "" }
  },
  "proofOfIdentityAndAddress": {
    "documents": [
      { "b64Doc": "JVBE==", "docId": "ZZZZZS00333444", "docType": "19", "docName": "20223450916_U.pdf", "docCategory": "POI", "docDescription": "" },
      { "b64Doc": "/9j/4AAQSk", "docId": "0421012", "docType": "20", "docName": "654342345721_U.JPG", "docCategory": "POI", "docDescription": "" }
    ]
  },
  "addressDetails": {
    "sameAsPermanent": false,
    "registeredAddress": { "addressLine1": "TOWER NEAR CIRCLE", "addressLine2": "JAIPUR", "country": "IN", "state": "GJ", "district": "215", "cityTownVillage": "" },
    "principalPlaceOfBusiness": { "addressLine1": "BANDRA KURLA COMPLEX", "country": "IN", "state": "MH", "district": "722", "cityTownVillage": "" },
    "documents": []
  },
  "contactDetails": { "emailAddress": "example@company.com", "mobileNumber": "8867456668", "mobileVerified": true },
  "clientRERelationship": { "noOfTimesDownloaded": 3, "noOfTimesUpdated": 1 },
  "otherDetails": { "remark": "", "modeOfKYC": "" },
  "docDetails": null
}
}
}
```

3.9 Error Responses

HTTP Status	code	message
400	INVALID_REQUEST	Required field missing or fails validation
400	CONSENT_DOCUMENT_INVALID	<code>consentDocument</code> / <code>selfie</code> is neither valid Base64 nor a fetchable URL, or the URL timed out
401	UNAUTHORIZED	Missing or invalid <code>appId</code> / <code>appKey</code>
404	DOWNLOAD_REF_NOT_FOUND	<code>downloadRefId</code> is missing or unrecognized
409	JOURNEY_MISMATCH	The branch supplied does not match what this journey requires
422	OTP_INVALID	Invalid OTP entered; message includes remaining attempts
422	OTP_ATTEMPTS_EXHAUSTED	OTP validation unsuccessful across all 3 attempts; restart from Initiate Download
429	RATE_LIMIT_EXCEEDED	Rate limit exceeded
500	INTERNAL_ERROR	An unexpected error occurred

4. Resend OTP

Re-triggers an OTP previously sent by Initiate Download. Applies to both Individual and Legal OTP journeys.

API URL

POST `https://{{URL}}/api/ckyc/v2/download/resend-otp`

4.1 Request Parameters

Parameter	Type	Mandatory	Description
<code>customerType</code>	Enum	Yes	<code>INDIVIDUAL</code> , <code>LEGAL</code>
<code>downloadRefId</code>	String	Yes	From Initiate Download's response

4.2 Sample Request and Response

```
{ "customerType": "INDIVIDUAL", "downloadRefId": "a52bc817-1699-4f78-975d-8b2aa51cddf6" }
```

```
{ "status": true, "message": "OTP has been sent to the registered mobile number XXXXXX6045" }
```

Field	Type	Description
<code>status</code>	Boolean	
<code>message</code>	String	Human-readable result message

Resend is enabled only after 90 seconds have elapsed since the last OTP, and only while resend attempts remain (3 allowed in total, matching the 3 validation attempts on Download).

4.3 Error Responses

HTTP Status	code	message
404	<code>DOWNLOAD_REF_NOT_FOUND</code>	<code>downloadRefId</code> is missing or unrecognized
422	<code>RESEND_TOO_EARLY</code>	Resend is enabled only 90 seconds after the first OTP request
422	<code>RESEND_ATTEMPTS_EXHAUSTED</code>	All resend attempts have been used for this journey

CKYC 2.0 Simplified Download APIs — Integration Guide. All error responses share a common envelope: `{ "success": false, "error": { "code", "message" } }`.