

Webhook Reference

The complete list of webhook events across all CKYC 2.0 services, the scenario in which each one fires, and a sample payload for each.

Services and Events

Every webhook follows the same payload structure. You parse one shape regardless of which service or event fired, and branch on `eventName`.

Service	Events	Count
Upload	UPLOAD_APPROVED, UPLOAD_REJECTED, UPLOAD_PROBABLE_MATCH_FOUND, UPLOAD_PROBABLE_MATCH_RESOLVED, UPLOAD_CASE_RESUBMITTED, UPLOAD_CASE_EXPIRED	6
Update	UPDATE_APPROVED, UPDATE_REJECTED, UPDATE_CASE_RESUBMITTED, UPDATE_CASE_EXPIRED	4
Download	DOWNLOAD_COMPLETED	1
Fetch External RE Updates	EXTERNAL_UPDATES_FETCHED	1
Search	None. Search is fully synchronous and returns results in the API response.	0

Common Fields

These six fields are present on every event. Fields that do not apply to an event are sent as `null`, never omitted.

Field	Type	Description
<code>eventName</code>	String (Enum)	Identifies the event. The only field you need to branch on.
<code>occurredAt</code>	String (ISO 8601, UTC)	Time the event occurred.
<code>requestId</code>	String (UUID)	Identifier for the case. Every event raised on the same case carries the same value, so you can correlate them.
<code>appId</code>	String or null	Application that triggered the operation. <code>null</code> for scheduled events.
<code>transactionId</code>	String or null	Your own identifier, echoed back if you supplied one on the original request.
<code>data</code>	Object	Event specific content. Detailed per event below.

Upload

Upload creates a new CKYC record. CERSAI processes the submission asynchronously, so the outcome reaches you over a webhook rather than in the API response.

UPLOAD_APPROVED

Fires when CERSAI approves the record. This is the successful terminal outcome for an upload.

- Carries the newly generated CKYC number for the customer.

```
{
  "eventName": "UPLOAD_APPROVED",
  "occurredAt": "2026-08-17T09:14:22.118Z",
  "requestId": "ff51e048-425a-4f74-99dd-959f7f28d919",
  "appId": "2v78sp",
  "transactionId": "TXNUPL20260817001",
  "data": {
    "ackNo": "IN2509046927",
    "ckycNo": "98700000000245"
  }
}
```

UPLOAD_REJECTED

Fires when CERSAI rejects the record after submission.

- CERSAI does not return a field level reason, so the payload carries the acknowledgement number alone. The most common cause is an existing duplicate record for the customer.
- Validation failures caught before submission are returned to you as a 400 on the API response itself and do not raise a webhook.

```
{
  "eventName": "UPLOAD_REJECTED",
  "occurredAt": "2026-08-19T04:22:16.740Z",
  "requestId": "ff51e048-425a-4f74-99dd-959f7f28d919",
  "appId": "2v78sp",
  "transactionId": "TXNUPL20260817001",
  "data": {
    "ackNo": "IN2509046927"
  }
}
```

UPLOAD_PROBABLE_MATCH_FOUND

Fires when CERSAI finds one or more existing records that may belong to the same customer.

- Carries every candidate record CERSAI returned, with the criteria matched and the match confidence.
- `expiresAt` is CERSAI's deadline for submitting a decision. Unactioned cases are moved to the reject bucket after this point.

```
{
  "eventName": "UPLOAD_PROBABLE_MATCH_FOUND",
  "occurredAt": "2026-08-17T11:02:47.900Z",
  "requestId": "ff51e048-425a-4f74-99dd-959f7f28d919",
  "appId": "2v78sp",
  "transactionId": "TXNUPL20260817001",
  "data": {
    "ackNo": "IN2509046927",
    "expiresAt": "2026-08-27T11:02:47.900Z",
    "matches": [
      {
        "name": "Sandeep Sharma",
        "gender": "M",
        "ckycRefNo": "67893456789675",
        "mobile": "+91 89*****67",
        "email": "sa*****@gmail.com",
        "updatedAt": "20-03-2025",
        "submittedDocuments": ["Voter ID", "PAN Card", "Aadhaar"],
        "matchingCriteria": ["Name", "Date of Birth", "Gender", "Photo"],
        "matchingPercentage": "80%",
        "b64Photo": "/9j/4/Z"
      }
    ]
  }
}
```

UPLOAD_PROBABLE_MATCH_RESOLVED

Fires when A decision has been submitted to CERSAI for every candidate on a probable match case.

- **action** is **MATCH** or **NOMATCH**. Only one candidate on a case can be marked as a match.
- **resolutionMode** is **MANUAL** where a reviewer decided, or **AUTO** where the case was resolved automatically.
- **reviewer** carries the name and email address of the reviewer. It is **null** on an automatic resolution.
- **confidenceScore** is present on automatic resolutions only.
- The case returns to processing after this event.

```
{
  "eventName": "UPLOAD_PROBABLE_MATCH_RESOLVED",
  "occurredAt": "2026-08-18T06:20:11.005Z",
  "requestId": "ff51e048-425a-4f74-99dd-959f7f28d919",
  "appId": "2v78sp",
  "transactionId": "TXNUPL20260817001",
  "data": {
    "ackNo": "IN2509046927",
    "resolutionMode": "AUTO",
    "reviewer": null,
    "matchActions": [
      {
        "action": "MATCH",
        "ckycRefNo": "67893456789675",
        "confidenceScore": 92.4
      },
      {
        "action": "NOMATCH",
        "ckycRefNo": "67893456789680",
        "confidenceScore": 11.8
      }
    ]
  }
}
```

UPLOAD_CASE_RESUBMITTED

Fires when A reviewer corrects a rejected or flagged case and resubmits it to CERSAI.

- **payload** carries the complete upload record as resubmitted, giving you the latest copy of the customer's data.
- **reviewer** carries the name and email address of the reviewer who made the correction.
- The case returns to processing, so expect a further outcome event afterwards.

Abridged. The payload field carries the full upload request structure as submitted.

```
{
  "eventName": "UPLOAD_CASE_RESUBMITTED",
  "occurredAt": "2026-08-19T07:45:33.812Z",
  "requestId": "ff51e048-425a-4f74-99dd-959f7f28d919",
  "appId": "2v78sp",
  "transactionId": "TXNUPL20260817001",
  "data": {
    "ackNo": "IN2509046927",
    "reviewer": {
      "name": "Priya Nair",
      "email": "priya.nair@client.com"
    },
    "payload": {
      "searchKey": "SK_IND_TEST_001",
      "accountType": "NORMAL",
      "personalDetails": {
        "name": {
          "title": "Mr.",
          "firstName": "Rahul",
          "middleName": "Kumar",
          "lastName": "Sharma"
        },
        "dob": "15-08-1990",
        "isMinor": false,
        "gender": "M",
        "panDetails": { "number": "XXXXXXXXXX", "verified": true }
      },
      "photo": { "b64Content": "...", "contentType": "jpeg" },
      "identityProofs": [ ... ],
      "addressDetails": { ... },
      "contactDetails": { ... },
      "attestationDetails": { ... },
      "otherDetails": { "remarks": "" }
    }
  }
}
```

UPLOAD_CASE_EXPIRED

Fires when A case remains unresolved past its window and can no longer be actioned.

- Terminal state. No further events are raised for this case.
- `lastKnownStage` tells you the last event raised on the case before it expired.

```
{
  "eventName": "UPLOAD_CASE_EXPIRED",
  "occurredAt": "2026-08-27T00:05:00.000Z",
  "requestId": "ff51e048-425a-4f74-99dd-959f7f28d919",
  "appId": "2v78sp",
  "transactionId": "TXNUPL20260817001",
  "data": {
    "ackNo": "IN2509046927",
    "expiredAt": "2026-08-27T00:05:00.000Z",
    "lastKnownStage": "UPLOAD_PROBABLE_MATCH_FOUND"
  }
}
```

Update

Update modifies an existing CKYC record identified by CKYC number. There is no probable match stage, as the CKYC number identifies exactly one record.

UPDATE_APPROVED

Fires when CERSAI approves the update to the existing record.

```
{
  "eventName": "UPDATE_APPROVED",
  "occurredAt": "2026-08-17T10:41:09.442Z",
  "requestId": "b8d3f217-6c40-4e93-a1f7-70cc9d2e4b85",
  "appId": "2v78sp",
  "transactionId": "TXNUPD20260817001",
  "data": {
    "ackNo": "IN2509046944",
    "ckycNo": "98700000000245"
  }
}
```

UPDATE_REJECTED

Fires when CERSAI rejects the update after submission.

- As with Upload, no field level reason is returned, so the payload carries the acknowledgement number alone.
- Validation failures caught before submission are returned as a 400 on the API response and do not raise a webhook.

```
{
  "eventName": "UPDATE_REJECTED",
  "occurredAt": "2026-08-19T05:07:44.118Z",
  "requestId": "b8d3f217-6c40-4e93-a1f7-70cc9d2e4b85",
  "appId": "2v78sp",
  "transactionId": "TXNUPD20260817001",
  "data": {
    "ackNo": "IN2509046944"
  }
}
```

UPDATE_CASE_RESUBMITTED

Fires when A reviewer corrects a rejected update and resubmits it to CERSAI.

- payload carries every field being sent to CERSAI for this update. Update sends only changed fields, so this is a partial record by design.
- reviewer carries the name and email address of the reviewer who made the correction.

Abridged. The payload field carries every field being updated, as submitted.

```
{
  "eventName": "UPDATE_CASE_RESUBMITTED",
  "occurredAt": "2026-08-19T08:12:55.301Z",
  "requestId": "b8d3f217-6c40-4e93-a1f7-70cc9d2e4b85",
  "appId": "2v78sp",
  "transactionId": "TXNUPD20260817001",
  "data": {
    "ackNo": "IN2509046944",
    "reviewer": {
      "name": "Priya Nair",
      "email": "priya.nair@client.com"
    },
    "payload": {
      "ckycNo": "98700000000245",
      "addressDetails": {
        "currentAddress": {
          "line1": "FLAT 402 SHANTI RESIDENCY",
          "line2": "BANER",
          "countryCode": "IN",
          "state": "MH",
          "district": "229",
          "city": "Pune",
          "pinCode": "411045"
        }
      },
      "contactDetails": {
        "mobile": { "countryCode": "+91", "number": "9876543210" }
      }
    }
  }
}
```

UPDATE_CASE_EXPIRED

Fires when An update case remains unresolved past its retention window.

- Terminal state. No further events are raised for this case.

```
{
  "eventName": "UPDATE_CASE_EXPIRED",
  "occurredAt": "2026-09-16T00:05:00.000Z",
  "requestId": "b8d3f217-6c40-4e93-a1f7-70cc9d2e4b85",
  "appId": "2v78sp",
  "transactionId": "TXNUPD20260817001",
  "data": {
    "ackNo": "IN2509046944",
    "expiredAt": "2026-09-16T00:05:00.000Z",
    "lastKnownStage": "UPDATE_REJECTED"
  }
}
```


Download

Download retrieves a full KYC record from the registry. This webhook notifies you each time a record is retrieved through your deployment, including downloads performed by partners operating on your behalf.

DOWNLOAD_COMPLETED

Fires when A KYC record is successfully retrieved.

- Fires for both individual and legal records, and for every consent type.
- `appId` identifies which application performed the download, so you can distinguish partner activity from your own.
- Carries identifiers only. Call `/getFullResponse` with the `requestId` to retrieve the record itself.
- Does not fire on failed retrievals or on the earlier steps of the download journey.

```
{
  "eventName": "DOWNLOAD_COMPLETED",
  "occurredAt": "2026-08-17T09:14:22.118Z",
  "requestId": "ff51e048-425a-4f74-99dd-959f7f28d919",
  "appId": "2v78sp",
  "transactionId": "TXNDWL20260817001",
  "data": {
    "ckycNo": "98700000000245"
  }
}
```

Fetch External RE Updates

A scheduled job that tells you when another Reporting Entity has modified a CKYC record belonging to one of your customers. You do not call anything. The result is delivered to you on a fixed schedule.

EXTERNAL_UPDATES_FETCHED

Fires when A scheduled run completes successfully.

- `appId` and `transactionId` are always `null`, as no API call from you initiates this flow.
- Fires on every run, including runs where nothing changed. In that case `recordCount` is 0 and `records` is an empty array. You can treat this as a heartbeat.
- Tells you which records changed, not what the new data is. Call Download for a CKYC number if you want the updated record.

```
{
  "eventName": "EXTERNAL_UPDATES_FETCHED",
  "occurredAt": "2026-08-17T02:00:00.000Z",
  "requestId": "7c1e9d34-88ab-4f21-9c05-3ea61b2f7d10",
  "appId": null,
  "transactionId": null,
  "data": {
    "window": {
      "from": "10-08-2026",
      "to": "17-08-2026"
    },
    "recordCount": 2,
    "records": [
      {
        "ckycNo": "20234567891234",
        "updatedInfo": "Demographic Details Updated.",
        "updatedAt": "15-08-2026"
      },
      {
        "ckycNo": "20234567895678",
        "updatedInfo": "Address Details Updated",
        "updatedAt": "16-08-2026"
      }
    ]
  }
}
```

Sample payload for a run where nothing changed:

```
{
  "eventName": "EXTERNAL_UPDATES_FETCHED",
  "occurredAt": "2026-08-24T02:00:00.000Z",
  "requestId": "e2a70b91-4d55-4c8a-bb13-9f0c6alde338",
  "appId": null,
  "transactionId": null,
  "data": {
    "window": {
      "from": "17-08-2026",
      "to": "24-08-2026"
    },
    "recordCount": 0,
    "records": []
  }
}
```