

Slip 1: Write the HTML code for generating the form as shown below. Apply the internal CSS to following form to change the font size of the heading to 6pt and change the color to red and also change the background color to yellow.

Solution:

```
<html>
```

```
<head>
```

Project Management

Project Name project name

Assigned to Er Merry Petision

Start Date dd-mm-yyyY

End Date dd-nm-yyyy

Priority High Average Low

Description

Submit Clear

```
<title>slip 1</title>
```

```
<style>
```

```
body{background-color: yellow;}
```

```
table {background-color: turquoise;}
```

```
h3 {font-size: 6pt; color:red;}
```

```
</style>
```

```
</head>
```

```
<body>
```

```
<center>
```

```
<h3> Project Management </h3>
```

```
<table border="3" height="200px" width="400px">
```

```
<form name=form login><br>
```

```

<tr><td>Enter Project Name:</td><td><input type=text name=t1
placeholder=projectname><br><br></td></tr>

<tr><td>Assigned to:</td><td><select name="Names" id="nm" form="frmlogin">
<option value="ross">Ross Geller</option>
<option value="chuck">Chuck Bass</option>
<option value="rachel">Rachel Green </option>
<option value="dan">Dan James</option>
</select></td></tr>

<tr><td>Start Date:</td><td><input type="date" ></td></tr>

<tr><td>End Date:</td><td><input type="date"> </td></tr>

<tr><td>Priority:</td><br>
<td><input type=radio name=ck value="high">High<br>
<input type=radio name=ck value="avg">Average <br>
<input type=radio name=ck value="low">Low</td></tr>

<tr><td>Description:</td><td><input type=text name="dt"
value="description"></td></tr>

<tr><td><input type=submit value ="submit"></td>
<td><input type=reset value ="clear"></td></tr>

</table>

</center>

</body>

</html>

```

Slip 2: Create HTML5 page with following specifications

- i) Title should be about your City.
- ii) Color the background by Pink color.
- iii) Place your city name at the top of page in large text and in blue color.

iv) Add names of the landmarks in your city, each in different color, style and font

v) Add any image at the bottom. (Use inline CSS to format the web page)

Solution:

```
<html>

<head>

<title>PUNE</title>

<body style="background-color:Pink;">

<h3 style="font-size:100px; color:blue;"> PUNE</h3>

<ul>

<li style="color:brown; font-style: italic;">Dagadu Seth Ganpati Temple</li>

<li style="color:red; font-style: oblique;">Saras Baug Temple</li>

<li style="color:purple; font-style: italic;">Phoenix Market City Pune</li>

</ul>



</body>

</head>

</html>
```

Slip 3:

Write a program using html with following CSS specificationsi. The background colour of the company name should be in green.

ii. The text colour of the company name should be red.

iii. The heading should be large -with font "comic sans ms"

iv. The description of the company should be displayed in blue color in a paragraph.

```
<html>
```

```

<head>
<title>Accenture</title></head>
<body style="background-color:#4CBB17">
<h3 style="font-size:60px; color:red; font-style:Comic Sans MS "> Accenture</h3>
<p style=" color:blue; font-size:25px">Accenture plc is an Irish-American professional
services company based in Dublin,
specializing in information technology (IT) services and consulting.<br>
As of 2022,Accenture is considered
the largest consulting firm in the world by number of employees.<br>
Accenture is a $61.6-billion-in-annual-revenue technology and consulting company
incorporated in Dublin, Ireland.
Led by Chair & CEO Julie Sweet, who prior to her promotion in 2019 served as CEO of
Accentures business in North America,
the Fortune Global 500 information technology services company has supplemented its
growth
through high-profile acquisitions like that of ad agency Droga5.With 721,000 people
worldwide</p>
</html>

```

Slip4: Write a HTML code, which generate the following output

List of Books

```

<html>
<body>
<table border = 1>
<caption>list of book </caption>
<tr>
<td rowspan=2>item no </td>

```

```

<td rowspan=2>Item name </td>
<td colspan=2> price
<tr>
<td >Rs </td>
<td >paise</td>
</td>
</tr>
</tr>
<tr>
<td>1</td>
<td>programming in python </td>
<td>500</td><td>50</td>
</tr>
<tr>
<td>2</td>
<td>programming in java </td>
<td>345</td><td>00</td>
</tr>
</body>
</html>

```

Slip5: Create following Bootstrap Web Layout Design and change Title, add your personal information, educational information, job profile.

```

<html lang="en">
<head>
<title>NR Class</title>
<link rel="stylesheet" href="bootstrap.min.css">

```

```
</head>

<body>

<div class="jumbotron">

<center><h1>My First Bootstrap Page</h1></center>

<center><p>This is responsive</p></center>

</div>

<div class="row">

<div class="col-3 offset-1 bg-light">

<h4>Personal Information</h4>

<p>name</p>

</div>

<div class="col-3 offset-1 bg-light">

<h4>Educational Information</h4>

<p>name</p>

</div>

<div class="col-3 offset-1 bg-light">

<h4>Job Profile</h4>

<p>name</p>

</div>

</div>

</body>

</html>
```

Slip 6: Create following Bootstrap Web Layout Design and set Header background color Blue, add your College name, set Menu section background color green create menu About Us, In content section add college information, background color yellow, Footer section background color red, add address of college.

```
<html>

<head>

<link rel="stylesheet" href="bootstrap.min.css">

<title>NRC</title>

</head>

<body>

<div class="row ">

<div class="col-12 bg-primary">

<h3>header</h3>

</div>

</div>

<div class="row">

<div class="col-4 bg-info">

<h4>Menu</h4>

</div>

<div class="col-8 bg-warning ">

<p>this is collge information</p>

</div>

</div>

<div class="row">

<div class="col-12 bg-danger">

<h3>Footer</h3>

</div>

</div>

</body>

</html>
```

Slip7 Design HTML 5 Page Using CSS Which Displays the following Navigation Bar

Home Java HTML CSS

```
<html>

<head>

<title>Navigation Bar</title>

<style>

li {

}

display:inline;

</style>

</head>

<body style="font-size:40px">

<ul>

<li><a href="HOME.asp" style="color:white; backgroundcolor:grey;">HOME</a></li>

<li> <a href="JAVA.asp" style="color:blue; backgroundcolor:#D3D3D3;">Java</a></li>

<li><a href="HTML.asp" style="color:blue; backgroundcolor:#D3D3D3;">HTML</a></li>

<li><a href="CSS.asp" style="color:blue; backgroundcolor:#D3D3D3;">CSS</a></li>

</ul>

</body>

</html>
```

Slip8: Design an HTML form to accept two strings from the user. Write a PHP script for the following.

- Find whether the small string appears at the start of the large string.
- Find the position of the small string in the big string.
- Compare both the string for first n characters, also the comparison should not be case sensitive.

HTML FILE

```
<html>

<body>

<form action="slip_8.php" method="get">

enter first string:<input type="text" name="str1"><br>

enter second string:<input type="text" name="str2"><br>

<input type="submit" value="submit">

</form>

</body>

</html>
```

PHP FILE

```
<?php

Sa=$_GET["str1"];

$b=$_GET["str2"];

//$len1=strlen($a);

//$len2=strlen($b);

echo "Length Slen1 $len2";

Spos-strpos(Sa,$b);

if($pos==0)

}

echo"the small string appears at the start of the large string<br>";

else

}

echo"small string does not appear at the start of the large string<br>";

}

Sposstrpos(Sa,$b);
```

```

echo "the small string appears at $pos position<br>";
if(strcasecmp(Sa,$b)==0)
echo "Both Strings are equal<br>";
else if(strcasecmp($a,$b)>0)
echo "first string bigger<br>";
else
echo "second string is bigger<br>";
?>

```

Slip9: Write a PHP script for the following: Design a form having a text box and a drop down list containing any 3 separators(e.g. #, 1, %, @,! or comma) accept a strings from the user and also a separator.

- Split the string into separate words using the given separator.
- Replace all the occurrences of separator in the given string with some other separator.
- Find the last word in the given string.

HTML FILE

```

<html>

<body>

<form action="slip_9.php"method="get">

Enter a string:<input type="text" name="str1"><br>

choose a label

<select name="sep" id="sep">

<option value="#">#</option>

<option value="!">!</option>

<option value="@">@</option>

</select><br>

<input type="radio" name="op" value="a">Split The String Using The Seperator<br>

```

```
<input type="radio" name="op" value="b">Replace The Occurences Of The  
Seperator With Another Seperator<br>  
<input type="radio" name="op" value="c">Find The Last Word Of The String<br>  
<input type="submit" value="submit">  
</form>  
</body>  
</html>
```

PHP FILE

```
<?php  
$str=$_GET['str1'];  
$sep=$_GET['sep'];  
$op=$_GET['op'];  
//echo "$str $sep Sop";  
switch($op)  
{  
case 'a':$m=explode($sep,$str);  
foreach($m as $a){  
echo "$a<br>";  
}  
break:  
case 'b':  
?>  
$cnt=substr_count($str, $sep);  
$n=str_replace($sep,"!",Sstr, $cnt);  
echo "After changing separators<br>";  
echo $n;
```

```
break;
case 'c':$ar=explode(" ",$str);
Scnt=count($ar);
echo "This is the last word: ".$ar[$cnt-1];
break;
```

Slip10: Write a script to accept two integers(Use html form having 2 textboxes).Write a PHP script to,

- Find mod of the two numbers.
- Find the power of first number raised to the second.
- Find the sum of first n numbers (considering first number as n)
- Find the factorial of second number.

(Write a separate function for each of the above operations.)

HTML FILE

```
<html>
<head>
<title>Assignment 3 Q1</title>
</head>
<body>
<form action="slip10.php" value="GET">
Enter Two Numbers<br>
<input type="text" name="n1"><br><br>
<input type="text" name="n2"><br><br>
Select An Operation<br>
<input type="radio" name="op" value="mod">Mod Of The Two Numbers<br><br>
<input type="radio" name="op" value="power">Power Of The First Number Raised
To The Second<br><br>
```

```
<input type="radio" name="op" value="sum">The Sum Of First n Numbers<br><br>
```

```
<input type="radio" name="op" value="fact">Factorial Of The Second
```

```
Number<br><br>
```

```
<input type="submit" value="Submit">
```

```
</form>
```

```
</body>
```

```
</html>
```

PHP FILE

```
<?php
```

```
$n1=$_GET["n1"];
```

```
$n2=S_GET["n2"];
```

```
Sop=S_GET["op"];
```

```
function
```

```
}
```

```
mod($n1,$n2)
```

```
$n3=0;
```

```
if($n2!=0)
```

```
$n3=$n1%$n2;
```

```
return $n3;
```

```
}
```

```
function
```

```
}
```

```
power($n1,$n2)
```

```
$n3=1;
```

```
for($i=1;$i<=$n2;$i++)
```

```
$n3=$i*$nl;
```

```
return $n3;

function sum($n1)
{
    $n3=0;
    for($i=1;$i<=Sn1;$i++)
    {
        $n3=$n3+$i;
    }
    return $n3;
}

function fact($n2)
{
    $n3=1;
    for($i=1;$i<=$n2;$i++)
    {
        $n3=$n3*$i;
    }
}

return $n3;

switch($op)
case "mod": $result=mod($n1,$n2);
echo "Mod of $n1 and $n2 is $result.";
break;
case "power":$result=power($n1, Sn2);
echo "$n1 raised to $n2 is $result.";
break;
```

```

case "sum": $result=sum($n1);
echo "Sum of first $n1 number is $result.";
break;
case "fact":$result=fact($n2);
echo"Factorial of $n2 is $result.";
break:
}
?>

```

Slip11: Create a button with different style (Secondary, Primary, Success, Error, Info, Warning, Danger) using Bootstrap.

```

<html>
<head>
<link rel=stylesheet href="bootstrap.min.css">
</head>
<body>
<form >
<input type= button value="primary" class="btn btn-primary">
<input type= button value="warning" class="btn btn-warning">
<input type= button value="secondary" class="btn btn-Secondary">
<input type= button value="success" class="btn btn-success">
<input type= button value="info" class="btn btn-info">
<input type= button value="danger" class="btn btn-danger">
</body>
</html>

```

Slip12: Write a PHP script for the following: Design a form to accept two numbers from the

user. Give options to choose the arithmetic operation (use radio buttons). Display the result

on the next form. (Use the concept of function and default parameters. Use 'include' construct

or require statement)

PHP FILE

```
<?php
$x=$_POST['s1'];
$y=$_POST['s2'];
$op=$_POST['op'];
function add($x=4,$y=2)
$result=$x+$y;
echo"adition is $result";
function sub($x=4,$y=2)
$result=$x-$y;
echo"subtraction is $result";
}
switch ($op)
{
case"1": add($x,$y);
break;
case"2": sub($x,$y);
?>
break;
```

HTML FILE

```
<html>
```

```
<body>
<form action="slip12in.php"method="POST">
first number
<input type=text name=s2><br>
second number
<input type=text name=s1><br>
chose opration from below<br>
addition
<input type=radio value="1" name=op> <br>
subtraction
<input type=radio value="2" name=op> <br>
<input type= submit value="submit"><br>
</body>
</html>
```

PHP FILE

```
<?php
include'slip12.php';
?>
```

Slip13: Write a PHP script to create a chess board using CSS on table cells.

```
<html>
<head>
<head><title>NRC ChessBoard</title>
<style>
.clr1
background-color:black;
}
```

```
.clr2
background-color:white;
table
}
width:100%;
height:100%;
</style>
<?php
echo"<table border=1>":
for($i=1;$i<=8;$i++)
}
echo"<tr>";
if($i%2==0)
for($j=1;$j<=8;$j++)
}
if($j%2==1)
echo"<td class=clr2></td>";
else
echo"<td class=clr1></td>";
}
}
else
{
for($j=0;$j<8;$j++)
{
if($j%2==0)
```

```
echo"<td class=clr1></td>";
else
echo"<td class=clr2></td>";
}
}
echo "</tr>";
echo"</table>";
?>
</html>
```

Slip14: Create a container add row inside it and add 3 columns inside row using BootStrap.

```
<html>
<head>
<link rel="stylesheet" href="bootstrap.min.css">
</head>
<body>
<div class=container>
<div class="row bg-light" >
<div class="col-4">col1
</div>
<div class="col-4">col2
</div>
<div class="col-4">col3
</div>
</div>
</div>
</div>
</body>
```

</html>

Slip15: Design a form to accept string from the user and perform the following operations

- a. To select first 5 words from the string
- b. Convert the given string to lowercase and then to Title case.
- c. Pad the given string with "*" from left and right both the sides.
- d. Remove the leading whitespaces from the given string.
- e. Find the reverse of given string.

HTML FILE

<html>

<body>

<form action="Slip15.php" method=get>

Enter a String<input type-text name=t1>

<input type=radio name=op value=1>Select 5 words

<input type=radio name=op value=2>LowerCase

<input type=radio name=op value=3>Padding

<input type=radio name=op value=4>Remove Spaces

<input type=radio name=op value=5>Reverse

<input type submit value=submit>

</form>

</body>

</html>

PHP FILE

<?php

\$str=\$_GET['t1'];

\$ch=\$_GET['op'];

if(\$ch=1)

```
}  
  
}  
  
$ar=explode("", $str, 6);  
foreach($ar as $a)  
    echo "$a<br>";  
else if($ch=2)  
{  
    3  
    $str=strtolower($str);  
    echo $str;  
    $str=ucwords($str);  
    echo "<br>Sstr";  
else if($ch=3)  
{  
}  
$str=str_pad($str, 20, "*", STR_PAD_BOTH);  
echo $str;  
else if($ch=4)  
{  
    $str=trim($str);  
    echo $str;  
}  
else if($ch=5)  
{  
}  
}  
$str=strrev(Sstr);
```

```
echo $str;
```

```
?>
```

Slip16: Write a PHP script for the following: Design a form to accept the marks of 5 different subjects of a student, having serial number, subject name & marks out of 100. Display the result in the tabular format which will have total, percentage and grade. Use only

3 text boxes. (Use array of form parameters)

HTML FILE

```
<html>
```

```
<head>
```

```
<title> marksheet </title>
```

```
</head>
```

```
<body>
```

```
<form name = "string" action = "slip16.php" method = "get">
```

```
student id<input type = "text" name = "v1"/></br></br>
```

```
Subject name<input type = "text" name = "v2"/></br></br>
```

```
subject marks<input type = "text" name = "v3"/></br></br>
```

```
<button type = "submit"> display marklist </button>
```

```
</form>
```

```
</body>
```

```
</html>
```

PHP FILE

```
<?php
```

```
$a=$_GET['v1'];
```

```
$b=$_GET['v2'];
```

```
$c=$_GET['v3'];
```

```

Ssum=0;

echo "<h1> <center>Marksheet</center></h1>":

echo "<h3><center>student id:$a</h3><br>";

$d =explode(",",$b);

Se =explode(",",$c);

echo "<center><table border=2 width=50%>":

for($i=0;$i<=4;$i++)

}

echo "<tr>

<td>$d[$i]</td>

<td>$e[$i]</td>

</tr>";

$sum=Se[$i]+$sum;

$result=$sum/5;

echo "<tr><td>Total marks </td><td>$sum</td>";

echo"<tr><td>Percentage</td><td>$result</td></tr>";

echo "</center>"

>

```

Slip17: Write a PHP script to sort the following associative array:

```
array("Sagar"=>"31","Vicky"=>"41","Leena"=>"39","Ramesh"=>"40") in
```

- a) ascending order sort by Value
- b) ascending order sort by Key
- c) descending order sorting by Value
- d) descending order sorting by Key

```
<?php
```

```
Sa = array("Sagar"=>"31","Vicky"=>"41","Leena"=>"39","Ramesh"=>"40");
```

```
echo "sorting in ascending order by value<br>";
asort($a);
print_r($a);
echo "sorting in ascending order by key<br>";
ksort($a);
print_r($a);
echo "sorting in descending order by value<br>";
arsort($a);
print_r($a);
echo "sorting in descending order by key<br>";
krsort($a);
print_r($a);
```

Slip18: Write a menu driven program to perform the following operations on an associative array

- a. Reverse the order of each element's key-value pair.
- b. Traverse the element in an array in random order.
- c. Convert the array elements into individual variables.
- d. Display the elements of an array along with key.

HTML FILE

```
<html>
<head>
<title> String operations </title>
<body>
<form name = "String" action = "s18_q1.php" method = "get">
<h2> Select Operations</h2>
<input type = "radio" name = "s" value=1>Reverse the order</br></br>
```

```
<input type = "radio" name = "s" value=2>Traverse the element</br></br>
<input type = "radio" name = "s" value=3>Convert the array elements</br></br>
<input type = "radio" name = "s" value=4>Display the elements of an array along with
key.</br></br>
<input type=submit value=send>
</body>
</html>
```

PHP FILE

```
<?php
Sa = array("a"=>1,"b"=>21,"c"=> 56);
switch($_GET['s'])
case 1:
case 2:
case 3:
echo "Orginal Array is <br>";
print_r($a);
echo "reverse Array is <br>";
$c =array_reverse($a);
print_r($c);
break;
echo "Orginal Array is <br>";
print_r($a);
echo "traversing Array is <br>";
foreach(Sa as $v)
break;
echo "$v<br>";
```

```

echo " Original array is<br>";
print_r($a);
echo "elements into individual variables<br>":
$e = extract($a);
print_r($e);
break:
case 4:
echo " Original array is<br>";
print_r($a);
echo "key value pair is<br>";
foreach ($a as $k=>$v)
}
print_r("$k=>$v");
echo"<br>";
}
break;
default:
echo "Invalid choice!!";
?>

```

Slip19: Write a PHP script to accept 2 strings from the user, the first string should be a sentence and second can be a word.

- a. Delete a small part from first string after accepting position and number of characters to remove.
- b. Insert the given small string in the given big string at specified position without removing any characters from the big string.

c. Replace some characters/ words from given big string with the given small string at specified position.

HTML FILE

```
<html>

<form action=slip19.php method=get>

Enter a Sentence<input type=text name=t1><br>

Enter a word<input type=text name=t2><br>

Enter position<input type=text name=t3><br>

Enter number of characters to remove<input type=text name=t4><br>

<input type=submit value="Display Result">

</form>

</html>
```

PHP FILE

```
<?php

$st=$_GET['t1'];
$wd=$_GET['t2'];
Sps=$_GET['t3'];
Snr=$_GET['t4'];

$dup_st=$st;

$str=substr_replace($st,"", $ps, $nr);

echo "<br>$str<br>";

$str=substr_replace($st,$wd,Sps,0);

echo "<br>$str<br>";

$str=substr_replace($st,$wd,Sps,strlen($wd));

echo "<br>$str<br>";

?>
```

Slip20: Write a menu driven program to perform the following operations on associative arrays:

- a) Split an array into chunks
- b) Sort the array by values without changing the keys.
- c) Filter the even elements from an array.

HTML FILE

```
<html>

<body>

<form action="slip20.php" method="GET">

Enter Your Choice:<br>

<input type="radio" name="ch" value=1> Split an array into chunks<br>

<input type="radio" name="ch" value=2> Sort array by values without changing key
values <br>

<input type="radio" name="ch" value=3> Filter even elements from array <br>

<input type="submit" value="Submit">

</form>

</body>

</html>
```

PHP FILE

```
<?php

$choice=$_GET['ch'];

Sarr=array('a'=>1,'b'=>20,'c'=>13,'d'=>5,'e'=>18,'f'=>12,'g'=>7,'h'=>8,'i'=>15,'j'=>10);

switch($choice)

case 1:

case 2:

case 3:
```

```

print_r(array_chunk($arr,2));

break;

asort($arr);

echo "Array in ascending order:<br>";

print_r($arr);

break;

function even($var)

return $var%2==0?1:0;

}

$br=array_filter($arr,"even");

print_r($br);

break:

?>

```

Slip21: Create an array of 15 high temperatures, approximating the weather for a spring month, then find the average high temp, the five warmest high temps Display the result on the browser

```

<?php

$temp_array=range(31,45);

$tot_temp = 0;

$count = count($temp_array);

echo "Total temp values are: ".$count;

foreach($temp_array as $temp)

    $tot_temp += $temp;

$avg_high_temp = $tot_temp/$count;

echo "<br> Average Temperature is: ".$avg_high_temp."

```

.

```

sort($temp_array);
echo "<br> List of five lowest temperatures :";
$res1= array_slice($temp_array,0,5);
foreach($res1 as $high_temp)
{
echo "<br> $high_temp";
echo "<br> List of five highest temperatures :";
$res1= array_slice($temp_array,10);
foreach($res1 as $high_temp)
{
echo "<br> $high_temp";
?>

```

Slip22: Write a menu driven program to perform the following queue related operations

- a) Insert an element in queue
- b) Delete an element from queue
- c) Display the contents of queue

HTML FILE

```

<html>
<body>
<form method=get action="slip 23.php">
<input type=radio name=ch value=1> Insert in queue<br>
Enter No to insert<input type=text name=n1><br>
<input type=radio name=ch value=2> Delete in queue<br>
<input type=radio name=ch value=3> Display<br>
<input type=submit>
</form>

```

```
</body>
```

```
</html>
```

PHP FILE

```
<?php
```

```
$stk=array(1,2,3,4,5);
```

```
$ch=$_GET['ch'];
```

```
else if($ch=1)
```

```
}
```

```
echo "Insert element in queue <br>";
```

```
$n4=$_GET['n4'];
```

```
array_push($stk,$n4);//Insert element at last
```

```
print_r($stk);
```

```
}
```

```
else if($ch=2)
```

```
}
```

```
echo "Delete element from queue. <br>";
```

```
$res=array_shift($stk); //at beginning
```

```
echo "Deleted element is: ".$res;
```

```
else if($ch =3)
```

```
?>
```

```
echo "Given array is: <br>";
```

```
print_r($stk);
```

Slip23: Write a menu driven program to perform the following stack related operations:

a) Insert an element in stack

b) Delete an element from stack

c) Display the contents of stack

HTML FILE

```
<html>

<body>

<form method=get action="slip23.php">

<input type=radio name=ch value=1> Insert in stack<br>

Enter No to insert<input type=text name=n1><br>

<input type=radio name=ch value=2> Delete in stack<br>

<input type=radio name=ch value=3> Display<br>

<input type=submit>

</form>

</body>

</html>
```

PHP FILE

```
<?php

$stk=array(1,2,3,4,5);

$ch=$_GET['ch'];

if($ch=1)

}

echo "Insert element in stack <br>";

$n1=$_GET['n1'];

array_push($stk,$n1); //at end

print_r($stk);

else

}

if($ch=2)

echo "Delete element in stack <br>";
```

```

array_pop($stk);
print_r($stk);
}
else
}
if($ch=3)
echo"Given array is: <br>";
print_r($stk);
}
?>

```

Slip24: Write a PHP program to read two file names from user and append content of first file into second file.

HTML FILE

```

<html lang="en">
<head>
<title>NRC File Handling</title>
</head>
<body>
<form action="slip24.php" method="get">
Enter File name to read <input type="text" name="fname1">
Enter File name to write <input type="text" name="fname2">
<input type="submit" value="Copy">
</form>
</body>
</html>

```

PHP FILE (create 2 text file pf your choice name and use same)

```

<?php
$fname1=$_GET['fname1'];
$fname2=$_GET['fname2'];
$fp1=fopen($fname1,"r");
$fp2=fopen($fname2,"a");
$size=filesize($fname1);
$str=fread($fp1,$size);
fwrite($fp2,$str, $size);
echo "Append Successfull";
?>

```

Slip25: Write a menu driven program to perform various file operations. Accept filename from user.

- a) Display type of file.
- b) Display last modification time of file
- c) Display the size of file
- d) Delete the file

HTML FILE

```

<html lang="en">
<head>
<title>Document</title>
</head>
<body>
<form action="slip25.php" method="get">
Enter File name to read <input type="text" name="fname1"><br>
<input type="radio" name="op" value="1">Display Type of File<br>
<input type="radio" name="op" value="2">Display Modification Time<br>

```

```
<input type="radio" name="op" value="3">Display File Size<br>
<input type="radio" name="op" value="4">Delete File<br>
<input type="submit" value="Copy">
</form>
</body>
</html>
```

PHP FILE

```
<?php
$fp=$_GET['fname1'];
$op=$_GET['op'];
switch($op)
case 1:
echo basename($fp);
break;
case 2: $mtime=stat($fp);
echo Date("d/M/Y h:m:s",$mtime['mtime']);
break;
case 3:echo filesize($fp);
break;
case 4:unlink($fp);
echo "File deleted";
break;
}
?>
```

Slip 26: Consider the following entities and their relationship.

Doctor (doc_no, dname, address,city,area)

Hospital (hosp_no, hname, hcity)

Doctor-Hospital related with many-one

relationship. Create a RDB in 3NF for above and

solve the following.

Using above database write a script in PHP to print the Doctor visiting to the Hospital in Tabular format. Accept Hospital name from user.

(Use your database)

Solution

Html file

```
<html>

<form action=slip26.php method=get>

Enter Hospital Name<input type=text name=t1><br>

<input type=submit value="Display Doctors">

</form>

</html>
```

PHP File

```
<?php

$con=pg_connect("host=localhost user=postgres password=nrc dbname=slip26");

$cn=$_GET['t1'];

$rs=pg_query($con,"select * from doctor,hospital where hname='$cn' and hsno=hno");

while($row=pg_fetch_array($rs))

{

echo "Id:$row[0]

Pin:$row[4]<br>";

}

?>
```

Name:\$row[1] Address:\$row[2] City:\$row[3]

Slip27: Write a PHP program to read two file names from user and copy the content of first file into second file.

HTML FILE

```
<html lang="en">

<head>

<title>NRC File Handling</title>

</head>

<body>

<form action="slip27.php" method="get">

Enter File name to read <input type="text" name="fname1">

Enter File name to write <input type="text" name="fname2">

<input type="submit" value="Copy">

</form>

</body>

</html>
```

PHP FILE

```
<?php

$fname1=$_GET['fname1'];

$fname2=$_GET['fname2'];

$fp1=fopen($fname1,"r");

$fp2=fopen($fname2,"w");

$size=filesize($fname1);

$str=fread($fp1,$size);

fwrite($fp2,$str,$size);

echo "Append Successfull";
```

?>

Slip28: Write a program to read a flat file "student.dat", calculate the percentage and display the data from file in tabular format.(Student.dat file contains rollno, name, OS, WT, DS, Python, Java, CN)

Student.dat file

rollno name OS WT DS Python Java CN

1 Abd 30 30 25 23 20 45

2 xyz 32 33 24 25 25 45

PHP FILE

```
<?php
```

```
$fp=fopen("student.dat","r");
```

```
$ar=fscanf($fp,"%s%s%s%s%s%s%s%s",$rl,$nm,$os,$wt,$ds,$py,$jv,$cn);
```

```
echo "<table
```

```
border=1><tr><th>$rl</th><th>$nm</th><th>$os</th><th>$wt</th><th>$ds</th><t
```

```
h>$py</th><th>$jv</th><th>$cn</th><th>Percentage</tr>";
```

```
while(($ar=fscanf($fp,"%s%s%d%d%d%d%d",$rl,$nm,$os,$wt,$ds,$py,$jv,$cn))!=f
```

```
alse)
```

```
{
```

```
$total=$os+$wt+$ds+$py+$jv+$cn;
```

```
$per=$total/6;
```

```
echo
```

```
"<tr><th>$rl</th><th>$nm</th><th>$os</th><th>$wt</th><th>$ds</th><th>$py</t
```

```
h><th>$jv</th><th>$cn</th><td>$per</td></tr>";
```

```
}
```

```
echo "</table>";
```

```
?>
```

Slip29:

Consider the following entities and their relationships

Event (eno, title, date)

Committee (cno, name, head, from_time,to_time, status)

Event and Committee have many to many relationship. Write a php script to accept title of Event and modify status committee as working

HTML File

```
<html>

<form action=slip29.php method=get>

Enter Event Name:<input type=text name=t1><br>

<input type=submit value="Change Status">

</form>

</html>
```

PHP File

```
<?php

$con=pg_connect("host=localhost user=postgres password=nrc bname=practicals22");

//echo $con;

$en=$_GET['t1'];

$ws='Working';

$x=pg_query($con,"update comm_mem set cstatus='$ws' from event_comm,event

where comm_mem.cno=event_comm.cno and event_comm.eno=event.eno and

etitle='$en'");

if($x>0)

echo "Working status updated";

else

?>
```

```
echo "Status not updated";
```

Slip30:

Consider the following entities and their relationships

Student (Stud_id, name, class)

Competition (c_no, c_name, type)

Relationship between student and competition is many-many with attribute rank and year.

Create a RDB in 3NF for the above and solve the following. Using above database write a script in PHP to accept a competition name from user and display information of student who has secured 1st rank in that competition.

HTML File

```
<html>

<form action=slip30.php method=get>

Enter Comp. Name<input type=text name=t1><br>

<input type=submit value="Display Ranker">

</form>

</html>
```

PHP File

```
<?php

$con=pg_connect("host=localhost user=postgres password=nrc dbname=slip30");

$cn=$_GET['t1'];

$rs=pg_query($con,"select*fromstudent,competition,stu comp where cname='$cn' and
srnk=1 and id=sid and competition.cno=stud_comp.cno");

while($row=pg_fetch_array($rs){

echo "$row[0] $row[1] $row[2]<br>";

}??>
```