

PHP MySQL (Database Handling) – Smart Summary Guide

A concise guide to PHP MySQL functions with syntax and examples.

mysqli_connect()

Opens a new connection to the MySQL server.

```
$conn = mysqli_connect("localhost", "username", "password", "database");
```

mysqli_close()

Closes a previously opened database connection.

```
mysqli_close($conn);
```

mysqli_select_db()

Selects the default database.

```
mysqli_select_db($conn, "database");
```

mysqli_query()

Performs a query on the database.

```
$result = mysqli_query($conn, "SELECT * FROM users");
```

mysqli_fetch_assoc()

Fetches a result row as an associative array.

```
while($row = mysqli_fetch_assoc($result)) {  
    echo $row["name"];  
}
```

mysqli_fetch_array()

Fetches a result row as an associative or numeric array.

```
$row = mysqli_fetch_array($result);
```

mysqli_fetch_row()

Fetches a result row as a numeric array.

```
$row = mysqli_fetch_row($result);
```

mysqli_num_rows()

Returns the number of rows in a result set.

```
echo mysqli_num_rows($result);
```

mysqli_error()

Returns the last error description.

```
echo mysqli_error($conn);
```

mysqli_real_escape_string()

Escapes special characters in a string for use in SQL.

```
$safe = mysqli_real_escape_string($conn, $input);
```

mysqli_affected_rows()

Returns the number of affected rows in the previous operation.

```
echo mysqli_affected_rows($conn);
```

mysqli_insert_id()

Returns the ID of the last inserted row.

```
echo mysqli_insert_id($conn);
```

mysqli_prepare()

Prepares an SQL statement for execution.

```
$stmt = mysqli_prepare($conn, "INSERT INTO users(name) VALUES(?)");
```

mysqli_stmt_bind_param()

Binds variables to a prepared statement as parameters.

```
mysqli_stmt_bind_param($stmt, "s", $name);
```

mysqli_stmt_execute()

Executes a prepared statement.

```
mysqli_stmt_execute($stmt);
```

mysqli_stmt_close()

Closes a prepared statement.

```
mysqli_stmt_close($stmt);
```

mysqli_set_charset()

Sets the default client character set.

```
mysqli_set_charset($conn, "utf8");
```