PRODUCT DATA SHEET

Athen Marine Gear Oil Series

High-performance marine gear oil containing EP additives, suitable for all gears and bearings under severe pressure conditions.

Product Description

The Athen Marine Gear Oil series are premium quality extreme pressure gear oils with excellent load-carrying capacity, water Demulsibility, oxidation stability, and corrosion protection. These are blended from high-quality base stocks and sulphur-phosphorous type extreme pressure additive systems that give excellent load-carrying capability to protect shock loading and wear. The high thermo-oxidative stability of the oil helps resist high-temperature deposit formation and oil thickening. In addition, these oils also possess excellent water separation characteristics and resist foaming.

Features & Benefits

- Excellent load carrying capability protects gears against scuffing and wear and offers long equipment life and reduced maintenance costs.
- Excellent Demulsibility property enables trouble-free operation in conditions encountering water/ moisture.
- High thermo-oxidative stability helps resist deposit formation, provides enhanced system cleanliness and enables longer service intervals.
- Provides effective rust and corrosion protection to all gearbox components.

Applications

- These gear lubricants are recommended for use in circulatory or oil bath-enclosed industrial gearboxes operating under severe shock and heavy load conditions. These grades are most suitable for bevel, helical, or spur gears and must follow the manufacturer's recommendations
- They may also be used for the lubrication of some lightly loaded worm-type gear applications
- The viscosity selection of gear oil is based on the speed, operating temperature, and load or pressure applied through the system

PRODUCT DATA SHEET

Athen Marine

Athen Marine Gear Oil Series								
ISO Viscosity Grades		**68**	**100**	**150**	**220**	**320**	**460**	**680**
Performance Level Meets/Exceeds the specifications								
AIST (formerly U.S. Steel) 224		✓	✓	✓	✓	✓	✓	✓
ANSI/AGMA 9005-F16-AntiScuff		✓	✓	✓	✓	✓	✓	✓
David Brown S1.53.101 (5E)		✓	✓	✓	✓	✓	✓	✓
DIN 51517/3 CLP		✓	✓	✓	✓	✓	✓	✓
Fives Cincinnati		P-63	P-76	P-77	P-74	P-59	P-35	P-34
ISO 12925-1 CKC/CKD		✓	✓	✓	✓	✓	✓	✓
ZF - TE-ML 04H(VG100&VG150), TE-ML 04F(VG220)			✓	✓	✓			
Typical Properties								
Test Parameters	**ASTM Method**	**Typical**						
Viscosity @ 40 °C, cSt	D 445	68	100	150	220	320	460	680
Viscosity Index	D 2270	100	97	97	97	97	95	90
Flash Point, °C	D 92	230	230	230	240	240	240	280
Pour Point, °C	D 97	-21	-21	-21	-15	-15	-15	-9
Density 15°C, Kg/l	D 1298	Report	Report	Report	Report	Report	Report	Report
Rust Test	D 665A/B	Pass	Pass	Pass	Pass	Pass	Pass	Pass
Copper Corrosion	D 130	1b	1b	1b	1b	1b	1b	1b
4 Ball weld load, kg	D 2783	250	250	250	250	250	250	250

"Data provided in this PDS is based on standard tests under laboratory conditions and is indicative only. Minor variations which do not affect product performance are expected in normal manufacturing. This product should not be used for any purpose other than those expressly set out in this PDS"