PRODUCT DATA SHEET

Athen Marine SYN PAO SERIES

A high-performance marine synthetic gear oil suitable for all gear and bearing applications, providing excellent resistance to oxidation, hydrolysis, and rust formation.

Product Description

- Advanced lubricant properties such as viscosity characteristics, low pour point and good air and water separation capabilities
- Excellent anti-wear, extreme pressure and load-carrying properties leading to savings in both maintenance time and costs
- Substantially extended lubricant life, Excellent thermal and oxidative stability, and proven superior performance across a wide temperature range and at high temperatures.

Features & Benefits

- High-performance additives provide EP protection, protecting components against scuffing and wear
- Premium shear stability, ensuring that the viscosity is retained throughout the fluid lifetime
- Good low-temperature fluidity, superior to a standard SAE 90 product, allowing fast circulation during cold-weather start-up
- Reliable oxidation stability, preventing oil thickening during service and formation of harmful varnish and deposits.
- Compatible with a wide variety of elastomer materials, preventing loss of fluid due to seal deterioration, and good rust protection

Applications

- Heavy-duty marines enclose gears such as bow thrusters and purifiers and bearing and circulation systems where high temperatures are encountered
- Industrial enclosed gearboxes operate under severe conditions like high loads, extreme temperatures, and wide temperature ranges.
- Severe heavy-duty gearboxes with a high risk of micro pitting wear and bearing and circulation systems where high temperatures are encountered.

Athen Marine Gear SYN PAO Series										
Performance Level Meets/Exceeds the specifications										
DIN 51517 part 3 CLP, AGMA 9005-E02, ISO 6743-6 CKD, CINCINNATI MILACRON, AIST 224, and DAVID BROWN										
ISO Viscosity Grades		**46**	**68**	**100**	**150**	**220**	**320**	**460**	**680**	**1000**
Test Parameters	**ASTM Method**	**Typical Properties**								
Viscosity @ 40 ºC, cSt	D 445	46	68	100	150	220	320	460	680	1000
Viscosity Index	D 2270	160	160	160	162	165	165	165	170	170
Flash Point, ºC	D 92	230	240	250	270	270	270	270	270	270
Pour Point, ºC	D 97	-42	-42	-42	-39	-39	-36	-36	-36	-36
Density @ 15ºC, Kg/l	D 1298	0.85	0.86	0.86	0.86	0.86	0.87	0.87	0.87	0.87
Rust Test	D 665A/B	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass
Copper Corrosion	D 130	1b	1b	1b	1b	1b	1b	1b	1b	1b
FZG Gear Failure Load (A/8.3/90)	D 5182	>12	>12	>12	>12	>12	>12	>12	>12	>12

"Data provided in this PDS is based on standard tests under laboratory conditions and is indicative only. Minor variations that do not affect product performance are expected in normal manufacturing. This product should not be used for any purpose other than those expressly set out in this PDS"