

Security Incident Report

Classification: TLP:AMBER — Internal Use / Client Deliverable **Prepared by:** Chayan

Panchal Contact: chayanpanchal11@gmail.com | [phone redacted] **Report Date:** July 19, 2026

Environment: corp.local (Active Directory domain) **Hosts in Scope:** PURPLE.corp.local, IIS.corp.local, DC01.corp.local **Primary Evidence Source:** Elastic SIEM (Sysmon / Windows Security / Task Scheduler / Service Control Manager event logs)

INCIDENT 1 — Malicious Document Execution to Domain Controller Compromise

1. Executive Summary

Incident Title: Multi-Stage Intrusion Involving Malicious Document Execution, C2 Communication, Active Directory Discovery, Process Injection, UAC Bypass, Kerberoasting, Lateral Movement, and Domain Controller Persistence

Severity: Critical

Status: Contained / Under Remediation (pending eradication confirmation)

Summary:

An intrusion originated when a user on host **PURPLE.corp.local** (`Marty.Mcfly`) opened a malicious Microsoft Word document. The document spawned a PowerShell process that established outbound communication with attacker-controlled infrastructure at **18.207.78.25**, then downloaded and executed the Active Directory reconnaissance tool **SharpHound** to enumerate the domain via LDAP. The attacker escalated privileges locally on PURPLE by injecting shellcode into `explorer.exe` and abusing the **ms-settings registry hijack** technique to bypass User Account Control (UAC). A scheduled task (`ExplorerUpdater`) was registered for persistence on PURPLE.

Using information gathered during discovery, the attacker performed **Kerberoasting** against the `iis_svc` service account, obtaining a crackable RC4-encrypted service ticket. This credential material was used — via a remote service execution (`488e74c.exe`) over `ADMIN$` — to move laterally onto **IIS.corp.local**, where the attacker conducted internal port scanning (SSH/22, Kerberos/88, RDP/3389, WinRM/5985) to identify further pivot points, including the domain controller.

The attacker subsequently authenticated to **DC01.corp.local** using a **Pass-the-Ticket** technique as the `John.Snow` account, installed a malicious Windows service (`ServicesUpdater`), running `C:\ProgramData\Services.exe` for persistence, and accessed

the memory of `lsass.exe` using a disguised/renamed credential-dumping tool — placing the entire domain's credential material at risk.

Business Impact: Full domain compromise. The attacker achieved SYSTEM-level persistence on the domain controller and had the capability to extract all domain credentials (including KRBTGT), which would enable Golden Ticket attacks and long-term, difficult-to-remediate access to the environment.

Root Cause: User execution of a malicious document (initial access vector consistent with a phishing or drive-by delivery mechanism; delivery channel was not directly observed in the available log sources and is noted as an evidence gap).

Key Recommendation Highlights (*Impact/Response sections excluded from this report per scope; noted here only as headline items for stakeholder awareness*):

- Reset credentials for `Marty.Mcfly`, `iis_svc`, `John.Snow`, and — given DC01 compromise — rotate the **KRBTGT** account twice.
- Rebuild PURPLE, IIS, and DC01 from known-good baselines; do not trust-in-place a compromised domain controller.
- Enable AMSI/script-block logging and restrict Office macro execution via GPO.

2. Technical Analysis

2.1 Methodology

Analysis was performed using Elastic SIEM against Sysmon (`Microsoft-Windows-Sysmon/Operational`), Windows Security Auditing, Task Scheduler, and Service Control Manager event logs. Investigation followed a process-lineage approach: each pivot began from a previously confirmed malicious PID/host and expanded outward (parent/child process relationships, file writes, registry writes, network connections, and authentication events) to avoid false-positive noise from legitimate system activity.

2.2 Cyber Kill Chain Mapping

Kill Chain Phase	Observed Activity
Reconnaissance	Not directly observed in available logs (pre-compromise OSINT/targeting is assumed but not evidenced)
Weaponization	Malicious Microsoft Word document built to spawn PowerShell on open
Delivery	Delivery mechanism not captured in available log sources (evidence gap — likely email/phishing based on file type)

Kill Chain Phase	Observed Activity
Exploitation	User-driven execution: opening the document triggered PowerShell execution
Installation	SharpHound.exe dropped to disk; scheduled task <code>ExplorerUpdater</code> and service <code>ServicesUpdater</code> installed for persistence
Command & Control	Outbound communication from PowerShell to <code>18.207.78.25</code>
Actions on Objectives	Discovery (<code>whoami</code> , LDAP/SharpHound enumeration), process injection, UAC bypass, Kerberoasting, lateral movement, internal port scanning, Pass-the-Ticket, credential dumping

The remainder of this section details each phase step by step, including data source, exact SIEM query, tool/command observed, and analytic reasoning.

2.3 Exploitation & Initial Execution

Objective: Determine the process spawned as a result of the user opening the malicious document.

- **Data Source:** Sysmon Event ID 1 (Process Creation)
- **SIEM Query:** `winlog.event_id:1 AND winlog.event_data.ParentProcessId:"4760"`
- **Reasoning:** Sysmon Event ID 1 records parent/child process relationships. `winword.exe` (PID 4760) was the process that opened the malicious document; filtering on its PID as parent isolates anything Word directly spawned — abnormal for a legitimate document.
- **Finding:** `winword.exe` (PID 4760) spawned `powershell.exe` (PID 4900).
- **Assessment:** A Word document spawning PowerShell is not expected in normal business use and is a strong indicator of macro-based (or OLE/embedded-object) malicious document execution — MITRE ATT&CK **T1204.002 (User Execution: Malicious File)** leading into **T1059.001 (PowerShell)**.

Artifact	Value
Process	powershell.exe
PID	4900
Parent	winword.exe (PID 4760)
MD5 (of PID)	b9cfe8b6042cf759dc4c0cccb27a6737

2.4 Command and Control

Objective: Identify the external infrastructure contacted by the malicious PowerShell process.

- **Data Source:** Sysmon Event ID 1 (CommandLine field)
- **SIEM Query:** winlog.event_id:1 AND winlog.event_data.ParentProcessId:"4760" (reviewing winlog.event_data.CommandLine on the resulting PowerShell event)
- **Reasoning:** Malicious PowerShell one-liners commonly embed a download/callback URL or IP directly in the command line. Reviewing the full command line of PID 4900 was the fastest path to identifying C2 infrastructure without needing separate Sysmon Event ID 3 network-connection correlation.
- **Finding:** The PowerShell command line referenced 18.207.78.25 as the callback/download address.
- **Assessment:** Confirms outbound C2 channel establishment — MITRE ATT&CK T1071 (Application Layer Protocol) / T1105 (Ingress Tool Transfer).

Artifact	Value
C2 IP	18.207.78.25
MD5 (of IP)	7db1b7f90edc5a9c413fa94dfa9f2a99

2.5 Installation — Tool Drop

Objective: Identify the executable written to disk by the malicious PowerShell process.

- **Data Source:** Sysmon Event ID 11 (File Create)

- **SIEM Query (initial, broad):** `winlog.event_id:11 AND winlog.event_data.TargetFilename:*.exe`
- **SIEM Query (refined):** `winlog.event_id:11 AND winlog.event_data.TargetFilename:*.exe AND winlog.event_data.ProcessId:"4900"`
- **Reasoning:** The initial broad query returned excessive noise from routine executable creation across the environment. Pivoting to the confirmed malicious PID (4900) as the creating process reduced the result set to attacker-attributable activity only.
- **Finding:** PowerShell wrote `C:\Users\Marty.Mcfly\AppData\Local\SharpHound.exe` to disk.
- **Assessment:** SharpHound is a legitimate, publicly available BloodHound data-collection tool commonly abused for Active Directory attack-path enumeration — MITRE ATT&CK T1592 / T1087 / T1482 (Domain Trust Discovery) staging.

Artifact	Value
File Path	<code>C:\Users\Marty.Mcfly\AppData\Local\SharpHound.exe</code>
MD5 (of path)	<code>fba38d3957a65ebda92cd0b57d5d43e2</code>

2.6 Discovery — Host Enumeration

Objective: Identify commands executed by the malicious process for local reconnaissance.

- **Data Source:** Sysmon Event ID 1 (Process Creation)
- **SIEM Query:** `winlog.event_id:1 AND winlog.event_data.ProcessId:"4900"`
- **Reasoning:** Rather than reviewing all host activity, filtering directly on the malicious PowerShell PID isolates only processes it spawned.
- **Finding:** PowerShell spawned `cmd.exe` running `C:\Windows\system32\cmd.exe /C whoami /all`.
- **Assessment:** Classic post-exploitation privilege/context enumeration — MITRE ATT&CK T1033 (System Owner/User Discovery) and T1069 (Permission Groups Discovery).

Artifact	Value
Command	<code>C:\Windows\system32\cmd.exe /C whoami /all</code>
MD5 (of command)	<code>ab2b9a2f98d3e770d19cebc1e6f4c33a</code>

2.7 Discovery — Active Directory Enumeration (LDAP)

Objective: Identify the process responsible for the bulk of LDAP query activity.

- **Data Source:** `SilkService Collector` provider (LDAP-specific telemetry)
- **SIEM Query:** `winlog.provider_name:"SilkService Collector"`
- **Reasoning:** Having already identified SharpHound.exe as dropped to disk (Section 2.5), and knowing SharpHound's primary function is LDAP-based AD enumeration, this provider was queried to confirm the correlation between the dropped binary and observed LDAP traffic volume.
- **Finding:** `SharpHound.exe` (PID 6904) generated the majority of LDAP events.
- **Assessment:** Confirms active BloodHound-style collection of AD objects, group memberships, ACLs, and trust relationships — MITRE ATT&CK **T1087.002 (Domain Account Discovery)** / **T1482**.

Artifact	Value
Process	<code>SharpHound.exe</code>
PID	6904
MD5 (of PID)	<code>0db2e204010400f5c506620adcd1ae68</code>

2.8 Defense Evasion — Process Injection (Detailed Scrutiny)

Objective: Identify the process injection event, its origin, destination, and technique characteristics.

- **Data Source:** Sysmon Event ID 8 (CreateRemoteThread); corroborated with Event IDs 12/13/14 (Registry object create/modify) on the target PID
- **SIEM Query (primary):** `winlog.event_id:8`
- **SIEM Query (corroboration):** `winlog.event_data.ProcessId:"5276" AND (winlog.event_id:12 OR winlog.event_id:13 OR winlog.event_id:14)`
- **Reasoning:** Event ID 8 is Sysmon's dedicated telemetry for remote thread creation across process boundaries — the primary indicator of classic DLL/shellcode injection. Corroborating with subsequent registry activity from the same PID validated that `explorer.exe` was genuinely acting maliciously post-injection, not simply the passive target of a benign remote thread.

Origin (Source) Process: The injecting process is the malicious PowerShell lineage (PID 4900 chain) — consistent with the tool responsible for all preceding staged activity (C2 callback, SharpHound drop, discovery commands).

Destination (Target) Process:

Artifact	Value
Target Process	explorer.exe
Target PID	5276
MD5 (of PID)	ed383ec94720d62a939bfb6bdd98f50c

Sacrificial Process Assessment: Based on the available evidence, explorer.exe PID 5276 appears to be the **pre-existing, legitimately running user shell process** rather than a newly spawned "sacrificial" process created solely to host injected code. No corresponding Sysmon Event ID 1 (Process Creation) for a fresh explorer.exe launch immediately preceding the Event ID 8 injection was identified in the investigation diary — if a sacrificial/suspended process had been created for this purpose (as in classic **T1055.012 Process Hollowing**), a new process-creation event tied to the attacker's process tree would be expected. The pattern observed — an existing trusted process receiving a remote thread — is more consistent with **T1055.001/T1055 (DLL/Process Injection via CreateRemoteThread)** into a live process, used here to (a) continue execution under a trusted, allow-listed binary and (b) stage the subsequent registry-based UAC bypass from a process less likely to draw scrutiny than powershell.exe.

Note on evidence gap: This assessment is based on the absence of a Process Hollowing indicator (no suspended-process creation, no NtUnmapViewOfSection-style memory unmapping event captured) rather than a definitive negative; if raw Sysmon XML or full command-line/memory forensics become available, this should be re-validated.

MITRE ATT&CK Mapping: T1055 (Process Injection) → sub-technique consistent with T1055 (generic CreateRemoteThread), not T1055.012 (Process Hollowing), based on available telemetry.

2.9 Defense Evasion — UAC Bypass

Objective: Identify the registry-based technique used to bypass UAC following process injection.

- **Data Source:** Sysmon Event ID 13 (Registry Value Set)

- **SIEM Query (primary):** `winlog.event_id:13 AND winlog.event_data.TargetObject:*ms-settings*`
- **SIEM Query (pivot):** `winlog.event_id:1 AND winlog.event_data.ProcessId:"5860"` (parent of `reg.exe` PID 6984)
- **Reasoning:** The `ms-settings` protocol handler is a well-documented UAC bypass abuse vector (fodhelper/computerdefaults-style hijacks). The query targeted registry writes under that key namespace. Two results were returned; the first (PID 4136) contained an encoded PowerShell payload but the second (PID 6984, `reg.exe`) had no inline details, requiring a pivot to its parent process (PID 5860) to recover the full command chain and confirm the exact registry path modified.
- **Finding:** Registry key `HKCU\Software\Classes\ms-settings\Shell\Open\Command` was modified to hijack the auto-elevating `ms-settings` handler, allowing arbitrary command execution without a UAC prompt.
- **Assessment:** MITRE ATT&CK **T1548.002 (Abuse Elevation Control Mechanism: Bypass User Account Control)**.

Artifact	Value
Registry Path	<code>HKCU\Software\Classes\ms-settings\Shell\Open\Command</code>
MD5 (of path)	<code>0707bf208083fc5006187107e08e1605</code>

2.10 Persistence — PURPLE Host

Objective: Identify the persistence mechanism established on PURPLE.

- **Data Source:** Microsoft-Windows-TaskScheduler operational log
- **SIEM Query:** `winlog.event_id:"106" AND winlog.provider_name:"Microsoft-Windows-TaskScheduler"`
- **Tool/Artifact Reviewed:** Raw scheduled task definition at `C:\Windows\System32\Tasks\ExplorerUpdater` (execution action not present in the Elastic-indexed Event ID 106 record; required direct review of the task XML)
- **Reasoning:** Event ID 106 marks scheduled task registration and is a reliable indicator of Task Scheduler-based persistence (**T1053.005**). Because Elastic's indexed event did not include the task's execution action, the underlying task file was inspected directly to recover the command executed on trigger.
- **Finding:** A scheduled task named `ExplorerUpdater` was registered under the **SYSTEM** context, configured to execute `C:\Users\Marty.Mcfly\AppData\Local\explorer.exe`.

- **Assessment:** SYSTEM-context scheduled task execution of a binary masquerading as `explorer.exe` from a user-writable path represents both persistence and privilege escalation — MITRE ATT&CK **T1053.005 (Scheduled Task)**.

Artifact	Value
Task Name	ExplorerUpdater
MD5 (of task name)	e407ec194a21a8d5531975c6c845bee1
Execution Command	C:\Users\Marty.Mcfly\AppData\Local\explorer.exe
MD5 (of command)	4e9714461cb35071daf8d905cc348631

2.11 Credential Access — Kerberoasting

Objective: Identify the service account targeted for offline credential cracking.

- **Data Source:** Windows Security Event ID 4769 (Kerberos Service Ticket Request)
- **SIEM Query:** `winlog.event_id:4769` refined with `winlog.event_data.TicketEncryptionType:"0x17"`
- **Reasoning:** Event ID 4769 logs every Kerberos service ticket request. Filtering to encryption type `0x17` (RC4-HMAC) isolates requests for weakly encrypted tickets — the hallmark of Kerberoasting, since attackers deliberately request RC4 tickets to enable faster offline password cracking versus AES.
- **Finding:** A ticket was requested for user `Marty.Mcfly@CORP.LOCAL` targeting service `iis_svc`, using RC4 (`0x17`) encryption.
- **Assessment:** MITRE ATT&CK **T1558.003 (Kerberoasting)**. This is the pivot point that ultimately enabled lateral movement to the IIS host.

Artifact	Value
Targeted Service Account	iis_svc
MD5 (of account name)	182999696be22eec4adaa2b343762c1e

Objective: Identify the process and remote execution chain used to reach IIS.corp.local.

- **Data Source:** Sysmon Event ID 1 (Process Creation), correlated with named-pipe telemetry on the IIS host
- **Reasoning:** Following the Kerberoasting event, pipe-connection activity on the IIS host was correlated in time with a `rundl132.exe` process creation whose parent command line referenced remote execution via `ADMIN$` — consistent with a PsExec-style or Service Control Manager-based remote execution technique using the compromised `iis_svc`-associated access.
- **Finding:**
 - Process: `rundl132.exe`, PID **4680**, running as `NT AUTHORITY\SYSTEM`, ParentProcessId 3972
 - Parent Command Line: `\\10.100.0.24\ADMIN$\488e74c.exe`
- **Assessment:** MITRE ATT&CK **T1021.002 (SMB/Windows Admin Shares)** combined with **T1569.002 (Service Execution)** — a binary was staged to the `ADMIN$` share of the IIS host from source `10.100.0.24` and executed as a service, consistent with tools like PsExec/Impacket `psexec.py`.

Artifact	Value
Process	<code>rundl132.exe</code>
PID	4680
MD5 (of PID)	<code>4f5c422f4d49a5a807eda27434231040</code>
Parent Command Line	<code>\\10.100.0.24\ADMIN\$\488e74c.exe</code>
MD5 (of parent command line)	<code>000e52699c0f5b843546dd2e7bd9eb0a</code>

2.13 Discovery — Internal Port Scanning from IIS

Objective: Identify the process responsible for internal network scanning from the newly compromised IIS host.

- **Data Source:** Sysmon Event ID 3 (Network Connection)
- **SIEM Query:** `host.name:"IIS.corp.local" AND winlog.event_id:3`
- **Reasoning:** Event ID 3 captures outbound/inbound network connections per process. Reviewing connection volume and port diversity from IIS host processes surfaced

anomalous multi-port, multi-host connection behavior.

- **Finding:** `C:\Windows\System32\svchost.exe` (PID 2964) connected to multiple hosts across ports **22 (SSH)**, **88 (Kerberos)**, **3389 (RDP)**, and **5985 (WinRM)**.
- **Assessment:** Reconnaissance to identify additional pivotable services/hosts, including — critically — Kerberos (88) traffic indicative of domain controller identification. MITRE ATT&CK **T1046 (Network Service Discovery)**.

Artifact	Value
Process	<code>svchost.exe</code>
PID	2964
MD5 (of PID)	<code>60ad83801910ec976590f69f638e0d6d</code>
Ports Scanned	22, 88, 3389, 5985

2.14 Lateral Movement — Pass-the-Ticket to DC01

Objective: Identify the account used to authenticate to the domain controller.

- **Data Source:** Windows Security Event ID 4624 (Successful Logon), Logon Type 3 (Network)
- **SIEM Query:** `host.name:"DC01.corp.local" AND winlog.event_id:4624 AND winlog.event_data.LogonType:"3" AND winlog.event_data.IpAddress:"10.100.0.24"`
- **Reasoning:** The same source IP identified in the IIS lateral-movement stage (`10.100.0.24`) was used as a pivot filter against DC01's logon events. Type-3 (network) logons were targeted since Pass-the-Ticket authentication manifests as a network logon rather than an interactive one. Machine-account logons (`*$`) were excluded to isolate genuine user-account activity.
- **Finding:** Domain user `John.Snow` authenticated to DC01 from `10.100.0.24` during the relevant window.
- **Assessment:** No corresponding interactive logon, RDP session, or credential-entry event was expected/needed for this technique — the absence of such an event, combined with ticket-based Kerberos authentication from an already-compromised host, supports **T1550.003 (Pass the Ticket)** rather than legitimate password-based authentication.

Artifact	Value
Account	John.Snow
MD5 (of account name)	dc4cb0ef633ac400fd5792a4c3d3b460

2.15 Persistence — DC01 (Domain Controller)

Objective: Identify the persistence mechanism installed on the domain controller.

- **Data Source:** System log, Service Control Manager (Event ID 7045 — New Service Installed)
- **SIEM Query:** `host.name:"DC01.corp.local" AND winlog.event_id:"7045"`
- **Reasoning:** Event ID 7045 logs every new Windows service installation — a common persistence and lateral-movement enabler on domain controllers. Two results were returned and had to be differentiated: one was the transient service used purely to execute the lateral-movement binary (`6470517.exe`) via (`ADMIN$`), the other was a durable, auto-start persistence mechanism.
- **Finding:**
 - Service Name: `ServicesUpdater`
 - Service File: `C:\ProgramData\Services.exe`
 - Start Type: Auto Start
 - Account: LocalSystem
- **Assessment:** An auto-start, LocalSystem-context service on a domain controller represents the highest-severity persistence found in this incident, granting the attacker SYSTEM-level access to DC01 on every reboot. MITRE ATT&CK T1543.003 (Create or Modify System Process: Windows Service).

Artifact	Value
Persistence Executable Path	C:\ProgramData\Services.exe
MD5 (of path)	34935037d90c765badc359c602889685

2.16 Credential Access — LSASS Memory Access on DC01

Objective: Identify the process used to harvest credentials from memory on the domain

controller.

- **Data Source:** Sysmon Event ID 10 (Process Access)
- **SIEM Query:** `host.name:"DC01.corp.local" AND winlog.event_id:10 AND winlog.event_data.TargetImage:"*lsass.exe"`
- **Reasoning:** Credential-dumping utilities (e.g., Mimikatz, comsvcs.dll MiniDump abuse, renamed dumping tools) require direct memory access to `lsass.exe`. Filtering Event ID 10 to `lsass.exe` as the `TargetImage` isolates any process requesting handle access consistent with credential extraction, regardless of the source binary's on-disk name.
- **Finding:** A single Process Access event was returned with `SourceImage` = `svchost.exe`, accessing `lsass.exe` — inconsistent with legitimate `svchost.exe` behavior and indicative of a renamed or masquerading credential-dumping tool (a genuine Windows `svchost.exe` does not request the access rights typically requested by dumping tools against LSASS).
- **Assessment:** MITRE ATT&CK T1003.001 (OS Credential Dumping: LSASS Memory), combined with T1036.005 (Masquerading: Match Legitimate Name or Location). This represents the most severe finding in the incident: potential exposure of all domain account credential material, including the KRBTGT account hash, from the domain controller itself.

Artifact	Value
Source Process (masquerading)	svchost.exe
Target Process	lsass.exe
PID	Identified and validated during investigation (submitted/accepted in original case tracking)

3. Consolidated Attack Chain

```
User opens malicious document
|
winword.exe (PID 4760)
|
powershell.exe (PID 4900) ---> C2: 18.207.78.25
|
```

```

drops SharpHound.exe -----> cmd.exe "whoami /all"
|
SharpHound.exe (PID 6904) ---> LDAP enumeration (AD discovery)
|
Process Injection -----> explorer.exe (PID 5276)
|
UAC Bypass -----> HKCU\...\ms-settings\Shell\Open\Command
|
Persistence (PURPLE) -----> Scheduled Task "ExplorerUpdater"
|
Kerberoasting -----> iis_svc
|
Lateral Movement -----> rundll32.exe on IIS.corp.local (via
ADMIN$\488e74c.exe)
|
Internal Port Scan -----> svchost.exe (22, 88, 3389, 5985)
|
Pass-the-Ticket -----> John.Snow @ DC01.corp.local
|
Persistence (DC01) -----> Service "ServicesUpdater"
(C:\ProgramData\Services.exe)
|
Credential Dumping -----> svchost.exe --> lsass.exe (DC01)

```

4. Indicators of Compromise (IOC) Summary

Type	Indicator	Host
IP	18.207.78.25	PURPLE (C2)
File	C:\Users\Marty.Mcfly\AppData\Local\SharpHound.exe	PURPLE
File	C:\Users\Marty.Mcfly\AppData\Local\explorer.exe	PURPLE
File	C:\ProgramData\Services.exe	DC01
File	\\10.100.0.24\ADMIN\$\488e74c.exe	IIS
Registry Key	HKCU\Software\Classes\ms- settings\Shell\Open\Command	PURPLE
Scheduled Task	ExplorerUpdater	PURPLE

Type	Indicator	Host
Service	ServicesUpdater	DC01
Account (compromised)	Marty.Mcfly, iis_svc, John.Snow	Domain- wide
Source IP (lateral movement)	10.100.0.24	IIS, DC01

5. MITRE ATT&CK Technique Summary

Tactic	Technique	ID
Initial Access	User Execution: Malicious File	T1204.002
Execution	PowerShell	T1059.001
Command and Control	Application Layer Protocol / Ingress Tool Transfer	T1071 / T1105
Discovery	System Owner/User Discovery	T1033
Discovery	Domain Account / Trust Discovery	T1087.002 / T1482
Defense Evasion	Process Injection	T1055
Defense Evasion	Bypass UAC	T1548.002
Persistence	Scheduled Task	T1053.005
Persistence	Windows Service	T1543.003
Credential Access	Kerberoasting	T1558.003
Credential Access	Pass the Ticket	T1550.003
Credential Access	LSASS Memory Dumping	T1003.001
Defense Evasion	Masquerading	T1036.005
Discovery	Network Service Discovery	T1046
Lateral Movement	SMB/Windows Admin Shares	T1021.002
Execution	Service Execution	T1569.002

End of Report