


Performance

Metrics


First Contentful Paint	2.8 s	First Meaningful Paint	2.8 s
▲ Speed Index	6.0 s	▲ First CPU Idle	9.9 s
▲ Time to Interactive	10.8 s	▲ Max Potential First Input Delay	870 ms

View Trace

Values are estimated and may vary. The performance score is based only on these metrics.



Opportunities — These suggestions can help your page load faster. They don't directly affect the Performance score.

Opportunity	Estimated Savings
▲ Serve images in next-gen formats	1.94 s ^
Image formats like JPEG 2000, JPEG XR, and WebP often provide better compression than PNG or JPEG, which means faster downloads and less data consumption. Learn more .	
<input type="checkbox"/> Show 3rd-party resources (0)	
URL	Size Potential Savings
 /images/texture.png (todolistme.net)	129 KB 89 KB
Remove unused CSS	0.32 s ^

Remove dead rules from stylesheets and defer the loading of CSS not used for above-the-fold content to reduce unnecessary bytes consumed by network activity. [Learn more.](#)

☒ Show 3rd-party resources (1)

URL	Size	Potential Savings
...smoothness/jquery-ui.css (code.jquery.com)	6 KB	6 KB
/css/style_g.css (todolistme.net)	7 KB	3 KB

Preconnect to required origins 0.3 s ^

Consider adding preconnect or dns-prefetch resource hints to establish early connections to important third-party origins. [Learn more.](#)

URL	Potential Savings
https://connect.facebook.net	300 ms

Minify JavaScript 0.22 s ^

Minifying JavaScript files can reduce payload sizes and script parse time. [Learn more.](#)

☒ Show 3rd-party resources (1)

URL	Size	Potential Savings
...1.12.1/jquery-ui.js (code.jquery.com)	122 KB	44 KB

Diagnostics — More information about the performance of your application. These numbers don't [directly affect](#) the Performance score.

▲ Minimize main-thread work — 39.3 s ^

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this.

Category	Time Spent
Script Evaluation	20,804 ms
Other	11,048 ms
Rendering	5,922 ms
Script Parsing & Compilation	506 ms
Style & Layout	479 ms
Parse HTML & CSS	304 ms
Garbage Collection	195 ms

▲ Ensure text remains visible during webfont load ^

Leverage the font-display CSS feature to ensure text is user-visible while webfonts are loading. [Learn more.](#)

☒ Show 3rd-party resources (2)

URL	Potential Savings
...v10/KtkxAKiDZ....woff2 (fonts.gstatic.com)	40 ms
...v10/MwQ5bhbm2....woff2 (fonts.gstatic.com)	40 ms

▲ Reduce JavaScript execution time — 21.2 s



Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. [Learn more](#).

☒ Show 3rd-party resources (12)

URL	Total CPU Time	Script Evaluation	Script Parse
Other	20,219 ms	2,754 ms	7 ms
...current/osd.js?cb=%2Fr20100101 (www.googletagservices.com)	8,566 ms	8,421 ms	78 ms
/javascript/javascript_e.js (todolistme.net)	3,960 ms	3,946 ms	3 ms
/jquery-2.2.4.min.js (code.jquery.com)	980 ms	865 ms	12 ms
...r20190131/show_ads_impl.js (pagead2.googlesyndication.com)	896 ms	724 ms	76 ms
/js/plusone.js (apis.google.com)	803 ms	775 ms	8 ms
/en_US/all.js?hash=735bc15...&ua=modern_es6 (connect.facebook.net)	713 ms	609 ms	74 ms
...rs=AGLTcCOaA.../cb=gapi.loaded_0 (apis.google.com)	703 ms	678 ms	24 ms
/widgets.js (platform.twitter.com)	645 ms	565 ms	31 ms
...js/adsbygoogle.js (pagead2.googlesyndication.com)	445 ms	410 ms	27 ms
/pagead/show_ads.js (pagead2.googlesyndication.com)	362 ms	239 ms	55 ms
/ga.js (www.google-analytics.com)	359 ms	317 ms	7 ms
...rs=AGLTcCOaA.../cb=gapi.loaded_1 (apis.google.com)	345 ms	333 ms	11 ms
...1.12.1/jquery-ui.js (code.jquery.com)	149 ms	95 ms	54 ms

▲ Serve static assets with an efficient cache policy — 29 resources found



A long cache lifetime can speed up repeat visits to your page. [Learn more](#).

☒ Show 3rd-party resources (3)

URL	Cache TTL	Size
/images/texture.png (todolistme.net)	None	129 KB
/javascript/javascript_e.js (todolistme.net)	None	10 KB
/javascript/lists.js (todolistme.net)	None	10 KB
/css/style_g.css (todolistme.net)	None	7 KB
/images/tick.png (todolistme.net)	None	6 KB

URL	Cache TTL	Size
/javascript/lib.js (todolistme.net)	None	2 KB
/images/undo.png (todolistme.net)	None	2 KB
/images/top_sync_waiting.png (todolistme.net)	None	1 KB
/images/top_sync.png (todolistme.net)	None	1 KB
/images/top_sync_on.png (todolistme.net)	None	1 KB
/images/top_sync_error.png (todolistme.net)	None	1 KB
/images/purge.png (todolistme.net)	None	1 KB
/images/arrow_down.png (todolistme.net)	None	1 KB
/images/arrow_up.png (todolistme.net)	None	1 KB
/images/top_new_window.png (todolistme.net)	None	1 KB
/images/top_not_saved.png (todolistme.net)	None	1 KB
/images/print.png (todolistme.net)	None	1 KB
/images/top_saved.png (todolistme.net)	None	1 KB
/images/category_down.png (todolistme.net)	None	1 KB
/images/category_up.png (todolistme.net)	None	1 KB
/images/addlist.png (todolistme.net)	None	1 KB
/images/info.png (todolistme.net)	None	1 KB
/images/adddivider.png (todolistme.net)	None	1 KB
/images/copy.png (todolistme.net)	None	0 KB
/images/sort_order.png (todolistme.net)	None	0 KB
/images/delete.gif (todolistme.net)	None	0 KB
/en_US/all.js (connect.facebook.net)	20 m	2 KB
/widgets.js (platform.twitter.com)	30 m	29 KB
/ga.js (www.google-analytics.com)	2 h	17 KB

Minimize Critical Requests Depth — 11 chains found



The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load.

[Learn more.](#)

Maximum critical path latency: **1,140 ms**

Initial Navigation

http://todolistme.net

/css?family=Abel|Architects+Daughter (fonts.googleapis.com) - **40 ms, 0.85 KB**

...smoothness/jquery-ui.css (code.jquery.com) - **290 ms, 6.32 KB**

/css/style_g.css (todolistme.net) - **170 ms, 7.22 KB**

/pagead/show_ads.js (pagead2.googlesyndication.com) - 80 ms, 29.29 KB

/widgets.js (platform.twitter.com) - 40 ms, 28.65 KB

/en_US/all.js (connect.facebook.net)

 /en_US/all.js (connect.facebook.net) - 110 ms, 2.24 KB

/jquery-2.2.4.min.js (code.jquery.com) - 460 ms, 34.44 KB

...1.12.1/jquery-ui.js (code.jquery.com) - 130 ms, 121.96 KB

/javascript/lists.js (todolistme.net) - 220 ms, 9.87 KB

/javascript/lib.js (todolistme.net) - 210 ms, 1.7 KB

/javascript/javascript_e.js (todolistme.net) - 220 ms, 10.05 KB

Keep request counts low and transfer sizes small — 63 requests • 777 KB

To set budgets for the quantity and size of page resources, add a budget.json file. [Learn more.](#)

Resource Type	Requests	Transfer Size
Total	63	777 KB
Script	19	573 KB
Image	26	159 KB
Font	2	23 KB
Stylesheet	3	14 KB
Document	10	8 KB
Media	0	0 KB
Other	3	0 KB
Third-party	36	592 KB

Third-Party Usage — 6 Third-Parties Found

Third-party code can significantly impact load performance. Limit the number of redundant third-party providers and try to load third-party code after your page has primarily finished loading. [Learn more.](#)

Third-Party	Size	Main Thread Time
Google/DoubleClick Ads	187 KB	10,270 ms
Other Google APIs/SDKs	101 KB	1,851 ms
jQuery CDN	170 KB	1,129 ms
Facebook	60 KB	730 ms
Twitter	32 KB	683 ms
Google Analytics	17 KB	359 ms

Passed audits (13)

Eliminate render-blocking resources — Potential savings of 0 ms

Resources are blocking the first paint of your page. Consider delivering critical JS/CSS inline and deferring all non-critical JS/styles. [Learn more](#).

☒ Show 3rd-party resources (2)

URL	Size	Potential Savings
/css?family=Abel Architects+Daughter (fonts.googleapis.com)	1 KB	620 ms
...smoothness/jquery-ui.css (code.jquery.com)	6 KB	810 ms
/css/style_g.css (todolistme.net)	7 KB	350 ms


Properly size images ^

Serve images that are appropriately-sized to save cellular data and improve load time. [Learn more](#).

Defer offscreen images — Potential savings of 7 KB ^

Consider lazy-loading offscreen and hidden images after all critical resources have finished loading to lower time to interactive. [Learn more](#).

☒ Show 3rd-party resources (1)

URL	Size	Potential Savings
 ...images/ui-icons_222222_256x240.png (code.jquery.com)	7 KB	7 KB

Minify CSS ^

Minifying CSS files can reduce network payload sizes. [Learn more](#).

Efficiently encode images ^

Optimized images load faster and consume less cellular data. [Learn more](#).

Enable text compression ^

Text-based resources should be served with compression (gzip, deflate or brotli) to minimize total network bytes. [Learn more](#).

Server response times are low (TTFB) — Root document took 300 ms ^

Time To First Byte identifies the time at which your server sends a response. [Learn more](#).

Avoid multiple page redirects ^

Redirects introduce additional delays before the page can be loaded. [Learn more](#).

Preload key requests ^

Consider using <link rel=preload> to prioritize fetching resources that are currently requested later in page load. [Learn more](#).

Use video formats for animated content ^

Large GIFs are inefficient for delivering animated content. Consider using MPEG4/WebM videos for animations and PNG/WebP for static images instead of GIF to save network bytes. [Learn more](#)

Avoids enormous network payloads — **Total size was 774 KB** ^

Large network payloads cost users real money and are highly correlated with long load times. [Learn more](#).

☒ Show 3rd-party resources (9)

URL	Size
/images/texture.png (todolistme.net)	129 KB
...1.12.1/jquery-ui.js (code.jquery.com)	122 KB
...r20190131/show_ads_impl.js (pagead2.googlesyndication.com)	90 KB
/en_US/all.js?hash=735bc15...&ua=modern_es6 (connect.facebook.net)	57 KB
...rs=AGLTcCOaA.../cb=gapi.loaded_0 (apis.google.com)	49 KB
...js/adsbygoogle.js (pagead2.googlesyndication.com)	38 KB
/jquery-2.2.4.min.js (code.jquery.com)	34 KB
...rs=AGLTcCOaA.../cb=gapi.loaded_1 (apis.google.com)	34 KB
/pagead/show_ads.js (pagead2.googlesyndication.com)	29 KB
...current/osd.js?cb=%2Fr20100101 (www.googletagervices.com)	29 KB

Avoids an excessive DOM size — **365 elements** ^

Browser engineers recommend pages contain fewer than ~1,500 DOM elements. The sweet spot is a tree depth < 32 elements and fewer than 60 children/parent element. A large DOM can increase memory usage, cause longer [style calculations](#), and produce costly [layout reflows](#). [Learn more](#).

Statistic	Element	Value
Total DOM Elements		365
Maximum DOM Depth		13
Maximum Child Elements	<body>	17

User Timing marks and measures ^

Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. [Learn more](#).



Accessibility

These checks highlight opportunities to [improve the accessibility of your web app](#). Only a subset of accessibility issues can be automatically detected so manual testing is also encouraged.

Contrast — These are opportunities to improve the legibility of your content.

▲ Background and foreground colors do not have a sufficient contrast ratio.

^

Low-contrast text is difficult or impossible for many users to read. [Learn more.](#)

Failing Elements

- a#sort0.current
- a#sort1
- a#sort2
- a#sort3
- h3#tomorrowtitle.ui-droppable
- h3#latertitle.ui-droppable
- p
- a
- a
- a
- a
- a
- a
- a
- a

Best practices — These items highlight common accessibility best practices.

▲ [id] attributes on the page are not unique

^

The value of an id attribute must be unique to prevent other instances from being overlooked by assistive technologies. [Learn more.](#)

Failing Elements

- span#later_number

Names and labels — These are opportunities to improve the semantics of the controls in your application. This may enhance the experience for users of assistive technology, like a screen reader.

▲ <frame> or <iframe> elements do not have a title

^

Screen reader users rely on frame titles to describe the contents of frames. [Learn more.](#)

Failing Elements

Failing Elements

```

iframe
<iframe width="300" height="250" frameborder="0" marginwidth="0" marginheight="0"
vspace="0" hspace="0" allowtransparency="true" scrolling="no" allowfullscreen="true"
onload="var
i=this.id,s=window.google_iframe_oncopy,H=s&&s.handlers,h=H&&H[i],w=this.c
ontentWindow,d;try{d=w.document}catch(e){}if(h&&d&&
(!d.body||!d.body.firstChild)){if(h.call){setTimeout(h,0)}else if(h.match)
{try{h=s.upd(h,i)}catch(e){}w.location.replace(h)}}" id="aswift_0" name="aswift_0"
style="left:0;position:absolute;top:0;border:0px;width:300px;height:250px;">

iframe#IO_1577718575857

```

▲ Image elements do not have [alt] attributes ^

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. [Learn more](#).

Failing Elements

```

img#logotick
img
img
img
img

```

▲ Form elements do not have associated labels ^

Labels ensure that form controls are announced properly by assistive technologies, like screen readers. [Learn more](#).

Failing Elements

```

input
input
input
input
input
input
input#newtodo.newtodonormal

```

Internationalization and localization — These are opportunities to improve the interpretation of your content by users in different locales.

▲ <html> element does not have a [lang] attribute ^

If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not

announce the page's text correctly. [Learn more](#).

Failing Elements

html

Additional items to manually check (11) — These items address areas which an automated testing tool cannot cover. [Learn more](#) in our guide on [conducting an accessibility review](#).

The page has a logical tab order



Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. [Learn more](#).

Interactive controls are keyboard focusable



Custom interactive controls are keyboard focusable and display a focus indicator. [Learn more](#).

Interactive elements indicate their purpose and state



Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. [Learn more](#).

The user's focus is directed to new content added to the page



If new content, such as a dialog, is added to the page, the user's focus is directed to it. [Learn more](#).

User focus is not accidentally trapped in a region



A user can tab into and out of any control or region without accidentally trapping their focus. [Learn more](#).

Custom controls have associated labels



Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. [Learn more](#).

Custom controls have ARIA roles



Custom interactive controls have appropriate ARIA roles. [Learn more](#).

Visual order on the page follows DOM order



DOM order matches the visual order, improving navigation for assistive technology. [Learn more](#).

Offscreen content is hidden from assistive technology



Offscreen content is hidden with display: none or aria-hidden=true. [Learn more](#).

Headings don't skip levels



Headings are used to create an outline for the page and heading levels are not skipped. [Learn more](#).

HTML5 landmark elements are used to improve navigation



Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. [Learn more](#).

Passed audits (6)



The page contains a heading, skip link, or landmark region



Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. [Learn more.](#)

Document has a `<title>` element ^

The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more.](#)

Links have a discernible name ^

Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. [Learn more.](#)

Lists contain only `` elements and script supporting elements (`<script>` and `<template>`). ^

Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. [Learn more.](#)

List items (``) are contained within `` or `` parent elements ^

Screen readers require list items (``) to be contained within a parent `` or `` to be announced properly. [Learn more.](#)

No element has a `[tabindex]` value greater than 0 ^

A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. [Learn more.](#)

Not applicable (23) ^

`[accesskey]` values are unique ^

Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. [Learn more.](#)

`[aria-*) attributes match their roles ^`

Each ARIA `role` supports a specific subset of `aria-*)` attributes. Mismatching these invalidates the `aria-*)` attributes. [Learn more.](#)

`[role]`s have all required `[aria-*) attributes ^`

Some ARIA roles have required attributes that describe the state of the element to screen readers. [Learn more.](#)

Elements with `[role]` that require specific children `[role]`s, are present ^

Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. [Learn more.](#)

`[role]`s are contained by their required parent element ^

Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. [Learn more.](#)

`[role]` values are valid ^

ARIA roles must have valid values in order to perform their intended accessibility functions. [Learn more.](#)

`[aria-*) attributes have valid values ^`

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. [Learn more.](#)

`[aria-*) attributes are valid and not misspelled ^`

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. [Learn more.](#)

`<audio>` elements contain a `<track>` element with `[kind="captions"]` ^

Captions make audio elements usable for deaf or hearing-impaired users, providing critical information such as who is talking, what they're saying, and other non-speech information. [Learn more.](#)

Buttons have an accessible name ^

When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. [Learn more.](#)

`<dl>`'s contain only properly-ordered `<dt>` and `<dd>` groups, `<script>` or `<template>` elements. ^

When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. [Learn more.](#)

Definition list items are wrapped in `<dl>` elements ^

Definition list items (``<dt>`` and ``<dd>``) must be wrapped in a parent ``<dl>`` element to ensure that screen readers can properly announce them. [Learn more.](#)

`<html>` element has a valid value for its `[lang]` attribute ^

Specifying a valid [BCP 47 language](#) helps screen readers announce text properly. [Learn more.](#)

`<input type="image">` elements have `[alt]` text ^

When an image is being used as an ``<input>`` button, providing alternative text can help screen reader users understand the purpose of the button. [Learn more.](#)

Presentational `<table>` elements avoid using `<th>`, `<caption>` or the `[summary]` attribute. ^

A table being used for layout purposes should not include data elements, such as the `th` or `caption` elements or the `summary` attribute, because this can create a confusing experience for screen reader users. [Learn more.](#)

The document does not use `<meta http-equiv="refresh">` ^

Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. [Learn more.](#)

`[user-scalable="no"]` is not used in the `<meta name="viewport">` element and the `[maximum-scale]` attribute is not less than 5. ^

Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. [Learn more.](#)

`<object>` elements have `[alt]` text ^

Screen readers cannot translate non-text content. Adding alt text to ``<object>`` elements helps screen readers convey meaning to users. [Learn more.](#)

Cells in a `<table>` element that use the `[headers]` attribute only refer to other cells of that same table. ^

Screen readers have features to make navigating tables easier. Ensuring ``<td>`` cells using the ``[headers]`` attribute only refer to other cells in the same table may improve the experience for screen reader users. [Learn more.](#)

`<th>` elements and elements with `[role="columnheader"/"rowheader"]` have data cells they describe. ^

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. [Learn more.](#)

[lang] attributes have a valid value ^

Specifying a valid [BCP 47 language](#) on elements helps ensure that text is pronounced correctly by a screen reader. [Learn more.](#)

<video> elements contain a <track> element with [kind="captions"] ^

When a video provides a caption it is easier for deaf and hearing impaired users to access its information. [Learn more.](#)

<video> elements contain a <track> element with [kind="description"] ^

Audio descriptions provide relevant information for videos that dialogue cannot, such as facial expressions and scenes. [Learn more.](#)



Best Practices

▲ Does not use HTTPS — 40 insecure requests found ^

All sites should be protected with HTTPS, even ones that don't handle sensitive data. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. [Learn more.](#)

☒ Show 3rd-party resources (13)

Insecure URL

http://todolistme.net

/css?family=Abel|Architects+Daughter (fonts.googleapis.com)

...smoothness/jquery-ui.css (code.jquery.com)

/css/style_g.css (todolistme.net)

/images/tick.png (todolistme.net)

/images/top_not_saved.png (todolistme.net)

/images/top_sync.png (todolistme.net)

/images/top_new_window.png (todolistme.net)

/images/adddivider.png (todolistme.net)

/images/addlist.png (todolistme.net)

/images/info.png (todolistme.net)

/pagead/show_ads.js (pagead2.googlesyndication.com)

/images/print.png (todolistme.net)

/images/sort_order.png (todolistme.net)

/images/purge.png (todolistme.net)

Insecure URL

- /images/arrow_down.png (todolistme.net)
- /widgets.js (platform.twitter.com)
- /en_US/all.js (connect.facebook.net)
- /images/undo.png (todolistme.net)
- /jquery-2.2.4.min.js (code.jquery.com)
- ...1.12.1/jquery-ui.js (code.jquery.com)
- /javascript/lists.js (todolistme.net)
- /javascript/lib.js (todolistme.net)
- /javascript/javascript_e.js (todolistme.net)
- /ga.js (www.google-analytics.com)
- /images/texture.png (todolistme.net)
- ...v10/KtkxAKiDZ....woff2 (fonts.gstatic.com)
- ...v10/MwQ5bhbm2....woff2 (fonts.gstatic.com)
- /__utm.gif?utmwv=... (www.google-analytics.com)
- /images/top_sync_on.png (todolistme.net)
- /images/top_sync_error.png (todolistme.net)
- /images/top_sync_waiting.png (todolistme.net)
- /images/arrow_up.png (todolistme.net)
- /images/category_up.png (todolistme.net)
- /images/category_down.png (todolistme.net)
- ...images/ui-bg_flat_75_ffffff_40x100.png (code.jquery.com)
- ...images/ui-icons_222222_256x240.png (code.jquery.com)
- /images/top_saved.png (todolistme.net)
- /images/copy.png (todolistme.net)
- /images/delete.gif (todolistme.net)

▲ Does not use HTTP/2 for all of its resources — 27 requests not served via HTTP/2 ^

HTTP/2 offers many benefits over HTTP/1.1, including binary headers, multiplexing, and server push. [Learn more.](#)

☐ Show 3rd party resources (0)

URL	Protocol
http://todolistme.net	http/1.1
/css/style_g.css (todolistme.net)	http/1.1
/images/tick.png (todolistme.net)	http/1.1
/images/top_not_saved.png (todolistme.net)	http/1.1

URL	Protocol
/images/top_sync.png (todolistme.net)	http/1.1
/images/top_new_window.png (todolistme.net)	http/1.1
/images/adddivider.png (todolistme.net)	http/1.1
/images/addlist.png (todolistme.net)	http/1.1
/images/info.png (todolistme.net)	http/1.1
/images/print.png (todolistme.net)	http/1.1
/images/sort_order.png (todolistme.net)	http/1.1
/images/purge.png (todolistme.net)	http/1.1
/images/arrow_down.png (todolistme.net)	http/1.1
/images/undo.png (todolistme.net)	http/1.1
/javascript/lists.js (todolistme.net)	http/1.1
/javascript/lib.js (todolistme.net)	http/1.1
/javascript/javascript_e.js (todolistme.net)	http/1.1
/images/texture.png (todolistme.net)	http/1.1
/images/top_sync_on.png (todolistme.net)	http/1.1
/images/top_sync_error.png (todolistme.net)	http/1.1
/images/top_sync_waiting.png (todolistme.net)	http/1.1
/images/arrow_up.png (todolistme.net)	http/1.1
/images/category_up.png (todolistme.net)	http/1.1
/images/category_down.png (todolistme.net)	http/1.1
/images/top_saved.png (todolistme.net)	http/1.1
/images/copy.png (todolistme.net)	http/1.1
/images/delete.gif (todolistme.net)	http/1.1

▲ Uses document.write()

^

For users on slow connections, external scripts dynamically injected via `document.write()` can delay page load by tens of seconds. [Learn more](#).

☒ Show 3rd-party resources (3)

URL	Location
/pagead/show_ads.js (pagead2.googlesyndication.com)	line: 46
/pagead/show_ads.js (pagead2.googlesyndication.com)	line: 112
...js/adsbygoogle.js (pagead2.googlesyndication.com)	line: 143

▲ Includes front-end JavaScript libraries with known security vulnerabilities — 2 vulnerabilities detected

^

Some third-party scripts may contain known security vulnerabilities that are easily identified and exploited by attackers. [Learn more.](#)

Library Version	Vulnerability Count	Highest Severity
jQuery@2.2.4	2	Medium

Passed audits (11)

Avoids Application Cache

Application Cache is deprecated. [Learn more.](#)

Uses passive listeners to improve scrolling performance

Consider marking your touch and wheel event listeners as `passive` to improve your page's scroll performance. [Learn more.](#)

Links to cross-origin destinations are safe

Add `rel="noopener"` or `rel="noreferrer"` to any external links to improve performance and prevent security vulnerabilities. [Learn more.](#)

Avoids requesting the geolocation permission on page load

Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. [Learn more.](#)

Page has the HTML doctype

Specifying a doctype prevents the browser from switching to quirks-mode. Read more on the [MDN Web Docs page](#)

Detected JavaScript libraries

All front-end JavaScript libraries detected on the page.

Name	Version
jQuery	2.2.4
jQuery UI	1.12.1

Avoids requesting the notification permission on page load

Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. [Learn more.](#)

Avoids deprecated APIs

Deprecated APIs will eventually be removed from the browser. [Learn more.](#)

Allows users to paste into password fields

Preventing password pasting undermines good security policy. [Learn more.](#)

No browser errors logged to the console

Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns.

Displays images with correct aspect ratio



Image display dimensions should match natural aspect ratio. [Learn more.](#)



SEO

These checks ensure that your page is optimized for search engine results ranking. There are additional factors Lighthouse does not check that may affect your search ranking. [Learn more.](#)

Mobile Friendly — Make sure your pages are mobile friendly so users don't have to pinch or zoom in order to read the content pages. [Learn more.](#)

▲ Does not have a `<meta name="viewport">` tag with width or initial-scale **No viewport meta tag found**



Add a viewport meta tag to optimize your app for mobile screens. [Learn more.](#)

▲ Document doesn't use legible font sizes



Text is illegible because there's no viewport meta tag optimized for mobile screens.

Font sizes less than 12px are too small to be legible and require mobile visitors to "pinch to zoom" in order to read. Strive to have >60% of page text ≥12px. [Learn more.](#)

▲ Tap targets are not sized appropriately



Tap targets are too small because there's no viewport meta tag optimized for mobile screens

Interactive elements like buttons and links should be large enough (48x48px), and have enough space around them, to be easy enough to tap without overlapping onto other elements. [Learn more.](#)

Content Best Practices — Format your HTML in a way that enables crawlers to better understand your app's content.

▲ Image elements do not have `[alt]` attributes



Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. [Learn more.](#)

Failing Elements

img#logotick

img

img

img

img

Additional items to manually check (1) — Run these additional validators on your site to check additional SEO best practices.



Structured data is valid



Run the [Structured Data Testing Tool](#) and the [Structured Data Linter](#) to validate structured data. [Learn more.](#)

Passed audits (7)



Document has a <title> element



The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more.](#)

Document has a meta description



Meta descriptions may be included in search results to concisely summarize page content. [Learn more.](#)

Page has successful HTTP status code



Pages with unsuccessful HTTP status codes may not be indexed properly. [Learn more.](#)

Links have descriptive text



Descriptive link text helps search engines understand your content. [Learn more.](#)

Page isn't blocked from indexing



Search engines are unable to include your pages in search results if they don't have permission to crawl them. [Learn more.](#)

Document has a valid hreflang



hreflang links tell search engines what version of a page they should list in search results for a given language or region. [Learn more.](#)

Document avoids plugins



Search engines can't index plugin content, and many devices restrict plugins or don't support them. [Learn more.](#)

Not applicable (2)



robots.txt is valid



If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed.

Document has a valid rel=canonical



Canonical links suggest which URL to show in search results. [Learn more.](#)

Runtime Settings

URL

<http://todolistme.net/>

Fetch time

Dec 30, 2019, 3:08 PM GMT

Device	Emulated Nexus 5X
Network throttling	150 ms TCP RTT, 1,638.4 Kbps throughput (Simulated)
CPU throttling	4x slowdown (Simulated)
User agent (host)	Mozilla/5.0 (X11; Linux x86_64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/78.0.3904.108 Safari/537.36
User agent (network)	Mozilla/5.0 (Linux; Android 6.0.1; Nexus 5 Build/MRA58N) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/74.0.3694.0 Mobile Safari/537.36 Chrome-Lighthouse
CPU/Memory Power	395

Generated by **Lighthouse** 5.2.0 | [File an issue](#)