



Performance

Metrics



First Contentful Paint	2.3 s	First Meaningful Paint	2.5 s
Speed Index	3.8 s	First CPU Idle	4.3 s
Time to Interactive	4.4 s	▲ Max Potential First Input Delay	330 ms

View Trace

Values are estimated and may vary. The performance score is based only on these metrics.



Opportunities — These suggestions can help your page load faster. They don't directly affect the Performance score.

Opportunity	Estimated Savings
Preconnect to required origins	0.47 s ^
Consider adding preconnect or dns-prefetch resource hints to establish early connections to important third-party origins. Learn more.	
URL	Potential Savings
https://accounts.google.com	470 ms
https://ssl.google-analytics.com	300 ms
https://apis.google.com	300 ms
Properly size images	0.4 s ^

Serve images that are appropriately-sized to save cellular data and improve load time. [Learn more.](#)

☐ Show 3rd-party resources (0)

URL	Size	Potential Savings
 /images/tick.png (todolistme.net)	6 KB	5 KB

Remove unused CSS 0.4 s ^

Remove dead rules from stylesheets and defer the loading of CSS not used for above-the-fold content to reduce unnecessary bytes consumed by network activity. [Learn more.](#)

☐ Show 3rd-party resources (0)

URL	Size	Potential Savings
/css/style_g.css (todolistme.net)	7 KB	4 KB

Serve images in next-gen formats 0.4 s ^

Image formats like JPEG 2000, JPEG XR, and WebP often provide better compression than PNG or JPEG, which means faster downloads and less data consumption. [Learn more.](#)

☐ Show 3rd-party resources (0)

URL	Size	Potential Savings
 /images/texture.png (todolistme.net)	129 KB	89 KB

Diagnostics — More information about the performance of your application. These numbers don't [directly affect](#) the Performance score.

▲ Serve static assets with an efficient cache policy — 18 resources found ^

A long cache lifetime can speed up repeat visits to your page. [Learn more.](#)

☒ Show 3rd-party resources (1)

URL	Cache TTL	Size
/images/texture.png (todolistme.net)	None	130 KB
/javascript/javascript_e.js (todolistme.net)	None	10 KB
/javascript/lists.js (todolistme.net)	None	10 KB
/css/style_g.css (todolistme.net)	None	7 KB
/images/tick.png (todolistme.net)	None	6 KB
/images/undo.png (todolistme.net)	None	2 KB
/javascript/lib.js (todolistme.net)	None	1 KB
/images/top_sync.png (todolistme.net)	None	1 KB

URL	Cache TTL	Size
/images/purge.png (todolistme.net)	None	1 KB
/images/arrow_down.png (todolistme.net)	None	1 KB
/images/top_new_window.png (todolistme.net)	None	1 KB
/images/print.png (todolistme.net)	None	1 KB
/images/top_not_saved.png (todolistme.net)	None	1 KB
/images/addlist.png (todolistme.net)	None	0 KB
/images/info.png (todolistme.net)	None	0 KB
/images/adddivider.png (todolistme.net)	None	0 KB
/images/sort_order.png (todolistme.net)	None	0 KB
/ga.js (ssl.google-analytics.com)	2 h	17 KB

Minimize main-thread work — 2.5 s

^

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this.

Category	Time Spent
Other	931 ms
Script Evaluation	845 ms
Rendering	202 ms
Style & Layout	187 ms
Parse HTML & CSS	161 ms
Script Parsing & Compilation	125 ms
Garbage Collection	14 ms

Minimize Critical Requests Depth — 11 chains found

^

The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. [Learn more](#).

Maximum critical path latency: 1,980 ms

Initial Navigation

- https://todolistme.net
 - /css/style_g.css (todolistme.net) - 240 ms, 7.03 KB
 - /javascript/lists.js (todolistme.net) - 460 ms, 9.65 KB
 - /javascript/lib.js (todolistme.net) - 260 ms, 1.45 KB
 - /javascript/javascript_e.js (todolistme.net) - 520 ms, 9.86 KB
 - /css?family=Abel|Architects+Daughter (fonts.googleapis.com) - 0 ms, 0 KB
 - ...smoothness/jquery-ui.css (code.jquery.com) - 0 ms, 0 KB

/pagead/show_ads.js (pagead2.googlesyndication.com) - 0 ms, 0 KB

/widgets.js (platform.twitter.com) - 0 ms, 0 KB

/en_US/all.js (connect.facebook.net) - 0 ms, 0 KB

/jquery-2.2.4.min.js (code.jquery.com) - 0 ms, 0 KB

...1.12.1/jquery-ui.js (code.jquery.com) - 0 ms, 0 KB

Keep request counts low and transfer sizes small — 32 requests • 295 KB ^

To set budgets for the quantity and size of page resources, add a budget.json file. [Learn more.](#)

Resource Type	Requests	Transfer Size
Total	32	295 KB
Image	14	143 KB
Script	12	139 KB
Stylesheet	3	7 KB
Document	3	5 KB
Media	0	0 KB
Font	0	0 KB
Other	0	0 KB
Third-party	14	120 KB

Third-Party Usage — 6 Third-Parties Found ^

Third-party code can significantly impact load performance. Limit the number of redundant third-party providers and try to load third-party code after your page has primarily finished loading. [Learn more.](#)

Third-Party	Size	Main Thread Time
Other Google APIs/SDKs	102 KB	554 ms
Google Analytics	17 KB	321 ms
jQuery CDN	0 KB	0 ms
Google/DoubleClick Ads	0 KB	0 ms
Twitter	0 KB	0 ms
Facebook	0 KB	0 ms

Passed audits (15) ^

Eliminate render-blocking resources ^

Resources are blocking the first paint of your page. Consider delivering critical JS/CSS inline and deferring all non-critical JS/styles. [Learn more.](#)

Defer offscreen images ^

Consider lazy-loading offscreen and hidden images after all critical resources have finished loading to lower time to interactive. [Learn more](#).

Minify CSS ^

Minifying CSS files can reduce network payload sizes. [Learn more](#).

Minify JavaScript ^

Minifying JavaScript files can reduce payload sizes and script parse time. [Learn more](#).

Efficiently encode images ^

Optimized images load faster and consume less cellular data. [Learn more](#).

Enable text compression ^

Text-based resources should be served with compression (gzip, deflate or brotli) to minimize total network bytes. [Learn more](#).

Server response times are low (TTFB) — Root document took 340 ms ^

Time To First Byte identifies the time at which your server sends a response. [Learn more](#).

Avoid multiple page redirects ^

Redirects introduce additional delays before the page can be loaded. [Learn more](#).

Preload key requests ^

Consider using <link rel=preload> to prioritize fetching resources that are currently requested later in page load. [Learn more](#).

Use video formats for animated content ^

Large GIFs are inefficient for delivering animated content. Consider using MPEG4/WebM videos for animations and PNG/WebP for static images instead of GIF to save network bytes. [Learn more](#)

Avoids enormous network payloads — Total size was 294 KB ^

Large network payloads cost users real money and are highly correlated with long load times. [Learn more](#).

☒ Show 3rd-party resources (4)

URL	Size
/images/texture.png (todolistme.net)	130 KB
...rs=AGLTcCOaA.../cb=gapi.loaded_0 (apis.google.com)	49 KB
...rs=AGLTcCOaA.../cb=gapi.loaded_1 (apis.google.com)	34 KB
/js/plusone.js (apis.google.com)	19 KB
/ga.js (ssl.google-analytics.com)	17 KB
/javascript/javascript_e.js (todolistme.net)	10 KB
/javascript/lists.js (todolistme.net)	10 KB
/css/style_g.css (todolistme.net)	7 KB
/images/tick.png (todolistme.net)	6 KB

URL

https://todolistme.net

Size4 KB

Avoids an excessive DOM size — 177 elements

Browser engineers recommend pages contain fewer than ~1,500 DOM elements. The sweet spot is a tree depth < 32 elements and fewer than 60 children/parent element. A large DOM can increase memory usage, cause longer [style calculations](#), and produce costly [layout reflows](#). [Learn more](#).

Statistic	Element	Value
Total DOM Elements		177
Maximum DOM Depth		10
Maximum Child Elements	<body>	12

User Timing marks and measures

Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. [Learn more](#).

JavaScript execution time — 0.9 s

Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. [Learn more](#).

Show 3rd-party resources (4)

URL	Total CPU Time	Script Evaluation	Script Parse
Other	1,517 ms	20 ms	5 ms
/ga.js (ssl.google-analytics.com)	321 ms	309 ms	12 ms
/js/plusone.js (apis.google.com)	198 ms	188 ms	8 ms
...rs=AGLTcCOaA.../cb=gapi.loaded_0 (apis.google.com)	180 ms	129 ms	51 ms
...rs=AGLTcCOaA.../cb=gapi.loaded_1 (apis.google.com)	176 ms	163 ms	11 ms

All text remains visible during webfont loads

Leverage the font-display CSS feature to ensure text is user-visible while webfonts are loading. [Learn more](#).



Accessibility

These checks highlight opportunities to [improve the accessibility of your web app](#). Only a subset of accessibility issues can be automatically detected so manual testing is also encouraged.

Contrast — These are opportunities to improve the legibility of your content.

- ▲

Background and foreground colors do not have a sufficient contrast ratio.

^

Low-contrast text is difficult or impossible for many users to read. [Learn more.](#)

Failing Elements

- h3
- a#sort0
- a#sort1
- a#sort2
- a#sort3
- h3#tomorrowtitle
- h3#latertitle
- p
- a.twitter-share-button
- p
- a
- a
- a
- a
- a
- a
- a

Best practices — These items highlight common accessibility best practices.

- ▲

[id] attributes on the page are not unique

^

The value of an id attribute must be unique to prevent other instances from being overlooked by assistive technologies. [Learn more.](#)

Failing Elements

- span#later_number

Names and labels — These are opportunities to improve the semantics of the controls in your application. This may enhance the experience for users of assistive technology, like a screen reader.

- ▲

<frame> or <iframe> elements do not have a title

^

Screen reader users rely on frame titles to describe the contents of frames. [Learn more.](#)

Failing Elements

iframe#IO_1577538289944

▲ Image elements do not have [alt] attributes ^

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. [Learn more.](#)

Failing Elements

img#logotick
img
img
img#sortbutton
img
img

Internationalization and localization — These are opportunities to improve the interpretation of your content by users in different locales.

▲ <html> element does not have a [lang] attribute ^

If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. [Learn more.](#)

Failing Elements

html

Additional items to manually check (11) — These items address areas which an automated testing tool cannot cover. Learn more in our guide on [conducting an accessibility review.](#) ^

The page has a logical tab order ^

Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. [Learn more.](#)

Interactive controls are keyboard focusable ^

Custom interactive controls are keyboard focusable and display a focus indicator. [Learn more.](#)

Interactive elements indicate their purpose and state ^

Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. [Learn more.](#)

The user's focus is directed to new content added to the page ^

If new content, such as a dialog, is added to the page, the user's focus is directed to it. [Learn more.](#)

User focus is not accidentally trapped in a region



A user can tab into and out of any control or region without accidentally trapping their focus. [Learn more.](#)

Custom controls have associated labels



Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. [Learn more.](#)

Custom controls have ARIA roles



Custom interactive controls have appropriate ARIA roles. [Learn more.](#)

Visual order on the page follows DOM order



DOM order matches the visual order, improving navigation for assistive technology. [Learn more.](#)

Offscreen content is hidden from assistive technology



Offscreen content is hidden with display: none or aria-hidden=true. [Learn more.](#)

Headings don't skip levels



Headings are used to create an outline for the page and heading levels are not skipped. [Learn more.](#)

HTML5 landmark elements are used to improve navigation



Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. [Learn more.](#)

Passed audits (4)



The page contains a heading, skip link, or landmark region



Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. [Learn more.](#)

Document has a <title> element



The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more.](#)

Links have a discernible name



Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. [Learn more.](#)

No element has a [tabindex] value greater than 0



A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. [Learn more.](#)

Not applicable (26)



[accesskey] values are unique



Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. [Learn more.](#)

[aria-*] attributes match their roles



Each ARIA `role` supports a specific subset of `aria-*` attributes. Mismatching these invalidates the `aria-*` attributes. [Learn more](#).

[role]s have all required [aria-*] attributes ^

Some ARIA roles have required attributes that describe the state of the element to screen readers. [Learn more](#).

Elements with [role] that require specific children [role]s, are present ^

Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. [Learn more](#).

[role]s are contained by their required parent element ^

Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. [Learn more](#).

[role] values are valid ^

ARIA roles must have valid values in order to perform their intended accessibility functions. [Learn more](#).

[aria-*] attributes have valid values ^

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. [Learn more](#).

[aria-*] attributes are valid and not misspelled ^

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. [Learn more](#).

<audio> elements contain a <track> element with [kind="captions"] ^

Captions make audio elements usable for deaf or hearing-impaired users, providing critical information such as who is talking, what they're saying, and other non-speech information. [Learn more](#).

Buttons have an accessible name ^

When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. [Learn more](#).

<dl>s contain only properly-ordered <dt> and <dd> groups, <script> or <template> elements. ^

When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. [Learn more](#).

Definition list items are wrapped in <dl> elements ^

Definition list items (`<dt>` and `<dd>`) must be wrapped in a parent `<dl>` element to ensure that screen readers can properly announce them. [Learn more](#).

<html> element has a valid value for its [lang] attribute ^

Specifying a valid [BCP 47 language](#) helps screen readers announce text properly. [Learn more](#).

<input type="image"> elements have [alt] text ^

When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. [Learn more](#).

Form elements have associated labels ^

Labels ensure that form controls are announced properly by assistive technologies, like screen readers. [Learn more](#).

Presentational <table> elements avoid using <th>, <caption> or the [summary] attribute. ^

A table being used for layout purposes should not include data elements, such as the `th` or `caption` elements or the `summary` attribute, because this can create a confusing experience for screen reader users. [Learn more.](#)

Lists contain only `` elements and script supporting elements (`<script>` and `<template>`). ^

Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. [Learn more.](#)

List items (``) are contained within `` or `` parent elements ^

Screen readers require list items (``) to be contained within a parent `` or `` to be announced properly. [Learn more.](#)

The document does not use `<meta http-equiv="refresh">` ^

Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. [Learn more.](#)

`[user-scalable="no"]` is not used in the `<meta name="viewport">` element and the `[maximum-scale]` attribute is not less than 5. ^

Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. [Learn more.](#)

`<object>` elements have `[alt]` text ^

Screen readers cannot translate non-text content. Adding alt text to `<object>` elements helps screen readers convey meaning to users. [Learn more.](#)

Cells in a `<table>` element that use the `[headers]` attribute only refer to other cells of that same table. ^

Screen readers have features to make navigating tables easier. Ensuring `<td>` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. [Learn more.](#)

`<th>` elements and elements with `[role="columnheader"/"rowheader"]` have data cells they describe. ^

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. [Learn more.](#)

`[lang]` attributes have a valid value ^

Specifying a valid [BCP 47 language](#) on elements helps ensure that text is pronounced correctly by a screen reader. [Learn more.](#)

`<video>` elements contain a `<track>` element with `[kind="captions"]` ^

When a video provides a caption it is easier for deaf and hearing impaired users to access its information. [Learn more.](#)

`<video>` elements contain a `<track>` element with `[kind="description"]` ^

Audio descriptions provide relevant information for videos that dialogue cannot, such as facial expressions and scenes. [Learn more.](#)

Best Practices

▲ Does not use HTTPS — 7 insecure requests found



All sites should be protected with HTTPS, even ones that don't handle sensitive data. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. [Learn more.](#)

☒ Show 3rd-party resources (7)

Insecure URL

- /css?family=Abel|Architects+Daughter (fonts.googleapis.com)
- ...smoothness/jquery-ui.css (code.jquery.com)
- /pagead/show_ads.js (pagead2.googlesyndication.com)
- /widgets.js (platform.twitter.com)
- /en_US/all.js (connect.facebook.net)
- /jquery-2.2.4.min.js (code.jquery.com)
- ...1.12.1/jquery-ui.js (code.jquery.com)

▲ Browser errors were logged to the console



Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns.

☐ Show 3rd-party resources (0)

URL	Description
https://todolistme.net	Mixed Content: The page at 'https://todolistme.net/' was loaded over HTTPS, but requested an insecure stylesheet 'http://fonts.googleapis.com/css?family=Abel Architects+Daughter'. This request has been blocked; the content must be served over HTTPS.
https://todolistme.net	Mixed Content: The page at 'https://todolistme.net/' was loaded over HTTPS, but requested an insecure stylesheet 'http://code.jquery.com/ui/1.10.3/themes/smoothness/jquery-ui.css'. This request has been blocked; the content must be served over HTTPS.
https://todolistme.net	Mixed Content: The page at 'https://todolistme.net/' was loaded over HTTPS, but requested an insecure script 'http://pagead2.googlesyndication.com/pagead/show_ads.js'. This request has been blocked; the content must be served over HTTPS.
https://todolistme.net	Mixed Content: The page at 'https://todolistme.net/' was loaded over HTTPS, but requested an insecure script 'http://platform.twitter.com/widgets.js'. This request has been blocked; the content must be served over HTTPS.
https://todolistme.net	Mixed Content: The page at 'https://todolistme.net/' was loaded over HTTPS, but requested an insecure script 'http://connect.facebook.net/en_US/all.js'. This request has been blocked; the content must be served over HTTPS.
https://todolistme.net	Mixed Content: The page at 'https://todolistme.net/' was loaded over HTTPS, but requested an insecure script 'http://code.jquery.com/jquery-2.2.4.min.js'. This request has been blocked; the content must be served over HTTPS.
https://todolistme.net	Mixed Content: The page at 'https://todolistme.net/' was loaded over HTTPS, but requested an insecure script 'http://code.jquery.com/ui/1.12.1/jquery-ui.js'. This request has been blocked; the content must be served over HTTPS.

URL	Description
https://todolistme.net	Mixed Content: The page at 'https://todolistme.net/' was loaded over HTTPS, but requested an insecure stylesheet 'http://fonts.googleapis.com/css?family=Abel Architects+Daughter'. This request has been blocked; the content must be served over HTTPS.
https://todolistme.net	Mixed Content: The page at 'https://todolistme.net/' was loaded over HTTPS, but requested an insecure stylesheet 'http://code.jquery.com/ui/1.10.3/themes/smoothness/jquery-ui.css'. This request has been blocked; the content must be served over HTTPS.
/javascript/javascript_e.js (todolistme.net)	ReferenceError: \$ is not defined at new UndoAgent (https://todolistme.net/javascript/javascript_e.js:6:5068) at https://todolistme.net/javascript/javascript_e.js:6:163
/javascript/javascript_e.js (todolistme.net)	ReferenceError: \$ is not defined at launch (https://todolistme.net/javascript/javascript_e.js:6:31489) at https://todolistme.net/:254:2

Passed audits (13)

Avoids Application Cache	^
Application Cache is deprecated. Learn more.	
Uses HTTP/2 for its own resources	^
HTTP/2 offers many benefits over HTTP/1.1, including binary headers, multiplexing, and server push. Learn more.	
Uses passive listeners to improve scrolling performance	^
Consider marking your touch and wheel event listeners as `passive` to improve your page's scroll performance. Learn more.	
Avoids document.write()	^
For users on slow connections, external scripts dynamically injected via `document.write()` can delay page load by tens of seconds. Learn more.	
Links to cross-origin destinations are safe	^
Add `rel="noopener"` or `rel="noreferrer"` to any external links to improve performance and prevent security vulnerabilities. Learn more.	
Avoids requesting the geolocation permission on page load	^
Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. Learn more.	
Page has the HTML doctype	^
Specifying a doctype prevents the browser from switching to quirks-mode. Read more on the MDN Web Docs page	
Avoids front-end JavaScript libraries with known security vulnerabilities	^
Some third-party scripts may contain known security vulnerabilities that are easily identified and exploited by attackers. Learn more.	
Detected JavaScript libraries	^
All front-end JavaScript libraries detected on the page.	
Avoids requesting the notification permission on page load	^

Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. [Learn more.](#)

Avoids deprecated APIs ^

Deprecated APIs will eventually be removed from the browser. [Learn more.](#)

Allows users to paste into password fields ^

Preventing password pasting undermines good security policy. [Learn more.](#)

Displays images with correct aspect ratio ^

Image display dimensions should match natural aspect ratio. [Learn more.](#)



SEO

These checks ensure that your page is optimized for search engine results ranking. There are additional factors Lighthouse does not check that may affect your search ranking. [Learn more.](#)

Mobile Friendly — Make sure your pages are mobile friendly so users don't have to pinch or zoom in order to read the content pages. [Learn more.](#)

▲ Does not have a <meta name="viewport"> tag with width or initial-scale **No viewport meta tag found** ^

Add a viewport meta tag to optimize your app for mobile screens. [Learn more.](#)

Content Best Practices — Format your HTML in a way that enables crawlers to better understand your app's content.

▲ Image elements do not have [alt] attributes ^

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. [Learn more.](#)

Failing Elements

img#logotick

img

img

img#sortbutton

img

img

Additional items to manually check (1) — Run these additional validators on your site to check additional SEO best practices. ^

Structured data is valid



Run the [Structured Data Testing Tool](#) and the [Structured Data Linter](#) to validate structured data. [Learn more.](#)

Passed audits (7)



Document has a <title> element



The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more.](#)

Document has a meta description



Meta descriptions may be included in search results to concisely summarize page content. [Learn more.](#)

Page has successful HTTP status code



Pages with unsuccessful HTTP status codes may not be indexed properly. [Learn more.](#)

Links have descriptive text



Descriptive link text helps search engines understand your content. [Learn more.](#)

Page isn't blocked from indexing



Search engines are unable to include your pages in search results if they don't have permission to crawl them. [Learn more.](#)

Document has a valid hreflang



hreflang links tell search engines what version of a page they should list in search results for a given language or region. [Learn more.](#)

Document avoids plugins



Search engines can't index plugin content, and many devices restrict plugins or don't support them. [Learn more.](#)

Not applicable (4)



robots.txt is valid



If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed.

Document has a valid rel=canonical



Canonical links suggest which URL to show in search results. [Learn more.](#)

Document uses legible font sizes



Font sizes less than 12px are too small to be legible and require mobile visitors to "pinch to zoom" in order to read. Strive to have >60% of page text ≥12px. [Learn more.](#)

Tap targets are sized appropriately



Interactive elements like buttons and links should be large enough (48x48px), and have enough space around them, to be easy enough to tap without overlapping onto other elements. [Learn more.](#)

Runtime Settings

URL	https://todolistme.net/
Fetch time	Dec 28, 2019, 1:04 PM GMT
Device	Emulated Desktop
Network throttling	150 ms TCP RTT, 1,638.4 Kbps throughput (Simulated)
CPU throttling	4x slowdown (Simulated)
User agent (host)	Mozilla/5.0 (X11; Linux x86_64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/78.0.3904.108 Safari/537.36
User agent (network)	Mozilla/5.0 (Macintosh; Intel Mac OS X 10_13_6) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/74.0.3694.0 Safari/537.36 Chrome-Lighthouse
CPU/Memory Power	430

Generated by **Lighthouse** 5.2.0 | [File an issue](#)