



Course > Module 0: Fundamentals (bootcamps) > Assignment: Notebook 4 (Due: 9/25/17 at 11:59 UTC) > Sample solutions

Sample solutions

[Bookmark this page](#)

part0 (Score: 12.0 / 12.0)

1. Test cell (Score: 1.0 / 1.0)
2. Test cell (Score: 3.0 / 3.0)
3. Test cell (Score: 4.0 / 4.0)
4. Test cell (Score: 2.0 / 2.0)
5. Test cell (Score: 2.0 / 2.0)

Important note! Before you turn in this lab notebook, make sure everything runs as expected:

- First, **restart the kernel** -- in the menubar, select Kernel→Restart.
- Then **run all cells** -- in the menubar, select Cell→Run All.

Make sure you fill in any place that says YOUR CODE HERE or "YOUR ANSWER HERE."

Part 0: Representing numbers as strings

The following exercises are designed to reinforce your understanding of how we can view the encoding of a number as string of digits in a given base.

If you are interested in exploring this topic in more depth, see the "[Floating-Point Arithmetic](https://docs.python.org/3/tutorial/floatingpoint.html)" section (<https://docs.python.org/3/tutorial/floatingpoint.html>) of the Python documentation.

Integers as strings

Consider the string of digits:

```
'16180339887'
```

If you are told this string is for a decimal number, meaning the base of its digits is ten (10), then its value is given by

$$\llbracket 16180339887 \rrbracket_{10} = (1 \times 10^{10}) + (6 \times 10^9) + (1 \times 10^8) + \dots + (8 \times 10^1) + (7 \times 10^0) = 16,180,339,887.$$

Similarly, consider the following string of digits:

```
'100111010'
```

If you are told this string is for a binary number, meaning its base is two (2), then its value is

$$\llbracket 100111010 \rrbracket_2 = (1 \times 2^9) + (1 \times 2^6) + \dots + (1 \times 2^1).$$

(What is this value?)

And in general, the value of a string of $d + 1$ digits in base b is,

$$\llbracket s_d s_{d-1} \dots s_1 s_0 \rrbracket_b = \sum_{i=0}^d s_i \times b^i.$$

Bases greater than ten (10). Observe that when the base is at most ten, the digits are the usual decimal digits, 0, 1, 2, ..., 9. What happens when the base is greater than ten? For this notebook, suppose we are interested in bases that are at most 36; then, we will adopt the convention of using lowercase Roman letters, a, b, c, ..., z for "digits" whose values correspond to 10, 11, 12, ..., 35.

Before moving on to that exercise, run the following code cell. It has three functions, which are used in some of the testing code. Given a base, one checks whether a single-character input string is a valid digit; and the other returns a list of all valid string digits. (The third one simply prints the valid digit list, given a base.) If you want some additional practice reading code, you might inspect these functions.

```
In [1]: def is_valid_strdigit(c, base=2):
        if type(c) is not str: return False # Reject non-string digits
        if (type(base) is not int) or (base < 2) or (base > 36): return False # Reject non-integer bases outside 2-36
        if base < 2 or base > 36: return False # Reject bases outside 2-36
        if len(c) != 1: return False # Reject anything that is not a single character
        if '0' <= c <= str(min(base-1, 9)): return True # Numerical digits for bases up to 10
        if base > 10 and 0 <= ord(c) - ord('a') < base-10: return True # Letter digits for bases > 10
        return False # Reject everything else

    def valid_strdigits(base=2):
        POSSIBLE_DIGITS = '0123456789abcdefghijklmnopqrstuvwxyz'
        return [c for c in POSSIBLE_DIGITS if is_valid_strdigit(c, base)]

    def print_valid_strdigits(base=2):
        valid_list = valid_strdigits(base)
        if not valid_list:
            msg = '(none)'
        else:
            msg = ', '.join([c for c in valid_list])
        print('The valid base ' + str(base) + ' digits: ' + msg)

    # Quick demo:
    print_valid_strdigits(6)
    print_valid_strdigits(16)
    print_valid_strdigits(23)

    The valid base 6 digits: 0, 1, 2, 3, 4, 5
    The valid base 16 digits: 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, a, b, c, d, e, f
    The valid base 23 digits: 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, a, b, c, d, e, f, g, h, i, j, k, l, m
```

Exercise 0 (1 point). Write a function, `eval_strint(s, base)`, which given a string of digits `s` and a base `base`, returns its value as an integer.

That is, this function essentially implements the mathematical object, $[[s]]_b$, which would convert a string `s` to its numerical value, assuming its digits are given in base `b`. For example:

```
eval_strint('100111010', base=2) == 314
```

Hint: Python makes this exercise very easy. Search Python's online documentation for information about the `int()` constructor to see how you can apply it to solve this problem. (You have encountered this constructor already, in Lab/Notebook 2.)

In [2]: Student's answer

(Top)

```
def eval_strint(s, base=2):
    assert type(s) is str
    assert 2 <= base <= 36
    return int(s, base)
```

In [3]: Grade cell: eval_strint_test

Score: 1.0 / 1.0 (Top)

```
# Test: `eval_strint_test`

def check_eval_strint(s, v, base=2):
    v_s = eval_strint(s, base)
    msg = "'{}' -> {}".format(s, v_s)
    print(msg)
    assert v_s == v, "Results do not match expected solution."

# Test 0: From the videos
check_eval_strint('16180339887', 16180339887, base=10)

# Test 1: Also from the videos
check_eval_strint('100111010', 314, base=2)

# Test 2
check_eval_strint('a205b064', 2718281828, base=16)

print ("\n(Passed!)")

'16180339887' -> 16180339887
'100111010' -> 314
'a205b064' -> 2718281828

(Passed!)
```

Fractional values

Recall that we can extend the basic string representation to include a fractional part by interpreting digits to the right of the "fractional point" (i.e., "the dot") as having negative indices. For instance,

$$\llbracket 3.14 \rrbracket_{10} = (3 \times 10^0) + (1 \times 10^{-1}) + (4 \times 10^{-2}).$$

Or, in general,

$$\llbracket s_d s_{d-1} \cdots s_1 s_0 \cdot s_{-1} s_{-2} \cdots s_{-r} \rrbracket_b = \sum_{i=-r}^d s_i \times b^i.$$

Exercise 1 (3 points). Suppose a string of digits s in base $base$ contains up to one fractional point. Complete the function, `eval_strfrac(s, base)`, so that it returns its corresponding floating-point value. Your function should *always* return a value of type float, even if the input happens to correspond to an exact integer.

Examples:

```
eval_strfrac('3.14', base=10) ~= 3.14
eval_strfrac('100.101', base=2) == 4.625
```

Because of potential floating-point roundoff errors, as explained in the videos, conversions based on the general polynomial formula given previously will not be exact. The testing code will include a built-in tolerance to account for such errors.

In [4]: Student's answer

(Top)

```
def is_valid_strfrac(s, base=2):
    return all([is_valid_strdigit(c, base) for c in s if c != '.']) \
           and (len([c for c in s if c == '.']) <= 1)

def eval_strfrac(s, base=2):
    assert is_valid_strfrac(s, base), "'{}' contains invalid digits for a base-{} number.".format(s, base)

    s_parts = s.split('.')
    assert len(s_parts) <= 2

    value_int = eval_strint(s_parts[0], base)
    if len(s_parts) == 2:
        r = len(s_parts[1])
```

```

        value_frac = eval_strint(s_parts[1], base) * (float(base) ** (-r))
    else:
        value_frac = 0
    return float(value_int) + value_frac

```

In [5]: Grade cell: eval_strfrac_test

Score: 3.0 / 3.0 (Top)

```

# Test: `eval_strfrac_test`

def check_eval_strfrac(s, v_true, base=2, tol=1e-7):
    v_you = eval_strfrac(s, base)
    assert type(v_you) is float, "Your function did not return a `float` as instructed."
    "
    delta_v = v_you - v_true
    msg = "[{}]_{{{}}} ~= {}: You computed {}, which differs by {}".format(s, base, v_
true,
                                                                    v_you, delt
a_v)
    print(msg)
    assert abs(delta_v) <= tol, "Difference exceeds expected tolerance."

# Test cases from the video
check_eval_strfrac('3.14', 3.14, base=10)
check_eval_strfrac('100.101', 4.625, base=2)
check_eval_strfrac('11.0010001111', 3.1396484375, base=2)

# A hex test case
check_eval_strfrac('f.a', 15.625, base=16)

# Random test cases
def check_random_strfrac():
    from random import randint
    b = randint(2, 36) # base
    d = randint(0, 5) # leading digits
    r = randint(0, 5) # trailing digits
    v_true = 0.0
    s = ''
    possible_digits = valid_strdigits(b)
    for i in range(-r, d+1):
        v_i = randint(0, b-1)
        s_i = possible_digits[v_i]

        v_true += v_i * (b**i)
        s = s_i + s
        if i == -1:
            s = '.' + s
    check_eval_strfrac(s, v_true, base=b)

for _ in range(10):
    check_random_strfrac()

print("\n(Passed!)")

```

```

[3.14]_{10} ~= 3.14: You computed 3.14, which differs by 0.0.
[100.101]_{2} ~= 4.625: You computed 4.625, which differs by 0.0.
[11.0010001111]_{2} ~= 3.1396484375: You computed 3.1396484375, which differs by 0.0.
[f.a]_{16} ~= 15.625: You computed 15.625, which differs by 0.0.
[fcq]_{32} ~= 15770.0: You computed 15770.0, which differs by 0.0.
[115bq.o]_{31} ~= 958484.7741935484: You computed 958484.7741935484, which differs by 0.0.
.
[053.23887]_{9} ~= 48.27157106809599: You computed 48.27157106809599, which differs by 0.0.
[59d4j6.e24k]_{22} ~= 28017248.6409569: You computed 28017248.6409569, which differs by 0.0.
[142475.6]_{10} ~= 142475.6: You computed 142475.6, which differs by 0.0.
[lm61]_{28} ~= 478409.0: You computed 478409.0, which differs by 0.0.
[7.556o]_{27} ~= 7.192393887562307: You computed 7.192393887562307, which differs by 0.0.
[j8]_{27} ~= 521.0: You computed 521.0, which differs by 0.0.
[89a8]_{13} ~= 19235.0: You computed 19235.0, which differs by 0.0.
[0iskk]_{30} ~= 511820.0: You computed 511820.0, which differs by 0.0.

```

(Passed:)

Floating-point encodings

Recall that a floating-point encoding or format is a normalized scientific notation consisting of a *base*, a *sign*, a fractional *significand* or *mantissa*, and a signed integer *exponent*. Conceptually, think of it as a tuple of the form, $(\pm, \llbracket s \rrbracket_b, x)$, where b is the digit base (e.g., decimal, binary); \pm is the sign bit; s is the significand encoded as a base b string; and x is the exponent. For simplicity, let's assume that only the significand s is encoded in base b and treat x as an integer value. Mathematically, the value of this tuple is $\pm \llbracket s \rrbracket_b \times b^x$.

IEEE double-precision. For instance, Python, R, and MATLAB, by default, store their floating-point values in a standard tuple representation known as *IEEE double-precision format*. It's a 64-bit binary encoding having the following components:

- The most significant bit indicates the sign of the value.
- The significand is a 53-bit string with an *implicit* leading one. That is, if the bit string representation of s is $s_0.s_1s_2\cdots s_d$, then $s_0 = 1$ always and is never stored explicitly. That also means $d = 52$.
- The exponent is an 11-bit string and is treated as a signed integer in the range $[-1022, 1023]$.

Thus, the smallest positive value in this format $2^{-1022} \approx 2.23 \times 10^{-308}$, and the smallest positive value greater than 1 is $1 + \epsilon$, where $\epsilon = 2^{-52} \approx 2.22 \times 10^{-16}$ is known as *machine epsilon* (in this case, for double-precision).

Special values. You might have noticed that the exponent is slightly asymmetric. Part of the reason is that the IEEE floating-point encoding can also represent several kinds of special values, such as infinities and an odd bird called "not-a-number" or NaN. This latter value, which you may have seen if you have used any standard statistical packages, can be used to encode certain kinds of floating-point exceptions that result when, for instance, you try to divide zero by zero.

If you are familiar with languages like C, C++, or Java, then IEEE double-precision format is the same as the `double` primitive type. The other common format is single-precision, which is `float` in those same languages.

Inspecting a floating-point number in Python. Python provides support for looking at floating-point values directly! Given any floating-point variable, v (that is, `type(v) is float`), the method `v.hex()` returns a string representation of its encoding. It's easiest to see by example, so run the following code cell:

```
In [6]: def print_fp_hex(v):
        assert type(v) is float
        print("v = {} ==> v.hex() == '{}'.format(v, v.hex()))

print_fp_hex(0.0)
print_fp_hex(1.0)
print_fp_hex(16.0625)
print_fp_hex(-0.1)

v = 0.0 ==> v.hex() == '0x0.0p+0'
v = 1.0 ==> v.hex() == '0x1.0000000000000p+0'
v = 16.0625 ==> v.hex() == '0x1.0100000000000p+4'
v = -0.1 ==> v.hex() == '-0x1.9999999999999p-4'
```

Observe that the format has these properties:

- If v is negative, the first character of the string is `'-'`.
- The next two characters are always `'0x'`.
- Following that, the next characters up to but excluding the character `'p'` is a fractional string of hexadecimal (base-16) digits. In other words, this substring corresponds to the significand encoded in base-16.
- The `'p'` character separates the significand from the exponent. The exponent follows, as a signed integer (`'+'` or `'-'` prefix). Its implied base is two (2)---**not** base-16, even though the significand is.

Thus, to convert this string back into the floating-point value, you could do the following:

- Record the sign as a value, `v_sign`, which is either `+1` or `-1`.
- Convert the significand into a fractional value, `v_signif`, assuming base-16 digits.
- Extract the exponent as a signed integer value, `v_exp`.
- Compute the final value as `v_sign * v_signif * (2.0**v_exp)`.

```
In [7]: # Recall: v = 16.0625 ==> v.hex() == '0x1.010000000000p+4'
print((+1.0) * eval_strfrac('1.010000000000', base=16) * (2**4))

16.0625
```

- `s_sign` is a string representing the sign bit, encoded as either a '+' or '-' character;
- `s_signif` is the significand, which should be a string of 54 bits having the form, `x.xxx...x`, where there are (at most) 53 `x` bits (0 or 1 values);
- `v_exp` is the value of the exponent and should be an *integer*.

[illegible]

(Top)

Score: 4.0 / 4.0 (Top)

Page 6 of 17

[illegible]

Exercise 3 (3 points). Suppose you are given a floating-point value in a base given by `base` and in the form of the tuple, `(sign, significand, exponent)`, where

- `sign` is either the character '+' if the value is positive and '-' otherwise;
- `significand` is a *string* representation in base-base;
- `exponent` is an *integer* representing the exponent value.

Complete the function,

```
def eval_fp(sign, significand, exponent, base):
    ...
```

so that it converts the tuple into a numerical value (of type `float`) and returns it.

In [10]: Student's answer [\(Top\)](#)

```
def eval_fp(sign, significand, exponent, base=2):
    assert sign in ['+', '-'], "Sign bit must be '+' or '-', not '{}'.format(sign)
    assert is_valid_strfrac(significand, base), "Invalid significand for base-{:}: '{}'.format(base, significand)
    assert type(exponent) is int

    v_sign = 1.0 if sign == '+' else -1.0
    v_significand = eval_strfrac(significand, base)
    return v_sign * v_significand * (base ** exponent)
```

In [11]: Grade cell: eval fp test Score: 2.0 / 2.0 (Top)

```
# Test: `eval_fp_test`

def check_eval_fp(sign, significand, exponent, v_true, base=2, tol=1e-7):
    v_you = eval_fp(sign, significand, exponent, base)
    delta_v = v_you - v_true
    msg = "('{}', ['{}']_{{{}}}, {}) ~= {}: You computed {}, which differs by {}".format(
        sign, significand, base, exponent, v_true, v_you, delta_v)
    print(msg)
    assert abs(delta_v) <= tol, "Difference exceeds expected tolerance."

# Test 0: From the videos
check_eval_fp('+', '1.25000', -1, 0.125, base=10)

# Test 1: Random floating-point binary values
def gen_rand_fp_bin():
    from random import random, randint
    v_sign = 1.0 if (random() < 0.5) else -1.0
```

```

v_sign = 1 if random() < 0.5 else -1.0
v_mag = random() * (10**randint(-5, 5))
v = v_sign * v_mag
s_sign, s_bin, s_exp = fp_bin(v)
return v, s_sign, s_bin, s_exp

for _ in range(5):
    (v_true, sign, significand, exponent) = gen_rand_fp_bin()
    check_eval_fp(sign, significand, exponent, v_true, base=2)

```

```

('+', ['1.25000']_10, -1) ~= 0.125: You computed 0.125, which differs by 0.0.
('+', ['1.111110111111001011000010001100111101010010011000101']_2, -12) ~= 0.000486349
2373439855: You computed 0.0004863492373439855, which differs by 0.0.
('+', ['1.0010110110000100110000011101011010010111001100001110']_2, -4) ~= 0.0736129352
384973: You computed 0.0736129352384973, which differs by 0.0.
('-', ['1.011101001111110000000111111110101101101010111111100']_2, -14) ~= -8.89264337
8185372e-05: You computed -8.892643378185372e-05, which differs by 0.0.
('+', ['1.001001011000000010101101100100101100001000010100000']_2, 4) ~= 18.3439166895
2651: You computed 18.34391668952651, which differs by 0.0.
('+', ['1.1100010011110110001011000111101110110100010010101101']_2, 5) ~= 56.6202020325
0845: You computed 56.62020203250845, which differs by 0.0.

```

Exercise 4 (2 points). Suppose you are given two binary floating-point values, u and v , in the tuple form given above. That is, $u == (u_sign, u_signif, u_exp)$ and $v == (v_sign, v_signif, v_exp)$, where the base for both u and v is two (2). Complete the function `add_fp_bin(u, v, signif_bits)`, so that it returns the sum of these two values with the resulting significand *truncated* to `signif_bits` digits.

Note 0: Assume that `signif_bits` includes the leading 1. For instance, suppose `signif_bits == 4`. Then the significand will have the form, `1.xxx`.

Note 1: You may assume that `u_signif` and `v_signif` use `signif_bits` bits (including the leading 1). Furthermore, you may assume each uses far fewer bits than the underlying native floating-point type (`float`) does, so that you can use native floating-point to compute intermediate values.

Hint: The test cell above defines a function, `fp_bin(v)`, which you can use to convert a Python native floating-point value (i.e., `type(v) is float`) into a binary tuple representation.

In [12]: Student's answer

(Top)

```

def add_fp_bin(u, v, signif_bits):
    u_sign, u_signif, u_exp = u
    v_sign, v_signif, v_exp = v

    # You may assume normalized inputs at the given precision, `signif_bits`.
    assert u_signif[:2] == '1.' and len(u_signif) == (signif_bits+1)
    assert v_signif[:2] == '1.' and len(v_signif) == (signif_bits+1)

    u_value = eval_fp(u_sign, u_signif, u_exp, base=2)
    v_value = eval_fp(v_sign, v_signif, v_exp, base=2)
    w_value = u_value + v_value
    w_sign, w_signif, w_exp = fp_bin(w_value)
    w_signif = w_signif[:signif_bits+1] # May need to truncate
    return (w_sign, w_signif, w_exp)

```

In [13]: Grade cell: add_fp_bin_test

Score: 2.0 / 2.0 (Top)

```

# Test: `add_fp_bin_test`

def check_add_fp_bin(u, v, signif_bits, w_true):
    w_you = add_fp_bin(u, v, signif_bits)
    msg = "{} + {} == {}: You produced {}".format(u, v, w_true, w_you)
    print(msg)
    assert w_you == w_true, "Results do not match."

u = ('+', '1.010010', 0)
v = ('-', '1.000000', -2)
w_true = ('+', '1.000010', 0)

```



```

"""_"""
check_add_fp_bin(u, v, 7, w_true)

u = ('+', '1.00000', 0)
v = ('+', '1.00000', -5)
w_true = ('+', '1.00001', 0)
check_add_fp_bin(u, v, 6, w_true)

u = ('+', '1.00000', 0)
v = ('-', '1.00000', -5)
w_true = ('+', '1.11110', -1)
check_add_fp_bin(u, v, 6, w_true)

u = ('+', '1.00000', 0)
v = ('+', '1.00000', -6)
w_true = ('+', '1.00000', 0)
check_add_fp_bin(u, v, 6, w_true)

u = ('+', '1.00000', 0)
v = ('-', '1.00000', -6)
w_true = ('+', '1.11111', -1)
check_add_fp_bin(u, v, 6, w_true)

print("\n(Passed!)")

```

```

('+', '1.010010', 0) + ('-', '1.000000', -2) == ('+', '1.000010', 0): You produced ('+', '1.000010', 0).
('+', '1.00000', 0) + ('+', '1.00000', -5) == ('+', '1.00001', 0): You produced ('+', '1.00001', 0).
('+', '1.00000', 0) + ('-', '1.00000', -5) == ('+', '1.11110', -1): You produced ('+', '1.11110', -1).
('+', '1.00000', 0) + ('+', '1.00000', -6) == ('+', '1.00000', 0): You produced ('+', '1.00000', 0).
('+', '1.00000', 0) + ('-', '1.00000', -6) == ('+', '1.11111', -1): You produced ('+', '1.11111', -1).

(Passed!)

```

Done! You've reached the end of part0. Be sure to save and submit your work. Once you are satisfied, move on to part1.

part1 (Score: 5.0 / 5.0)

1. Test cell (Score: 2.0 / 2.0)
2. Written response (Score: 0.0 / 0.0)
3. Test cell (Score: 3.0 / 3.0)

Important note! Before you turn in this lab notebook, make sure everything runs as expected:

- First, **restart the kernel** -- in the menubar, select Kernel→Restart.
- Then **run all cells** -- in the menubar, select Cell→Run All.

Make sure you fill in any place that says YOUR CODE HERE or "YOUR ANSWER HERE."

Floating-point arithmetic

As a data analyst, you will be concerned primarily with *numerical programs* in which the bulk of the computational work involves floating-point computation. This notebook guides you through some of the most fundamental concepts in how computers store real numbers, so you can be smarter about your number crunching.

WYSInnWYG, or "what you see is not necessarily what you get."

One important consequence of a binary format is that when you print values in base ten, what you see may not be what you get! For instance, try running the code below.

This code invokes Python's `decimal` (<https://docs.python.org/3/library/decimal.html>) package, which implements base-10 floating-point arithmetic in software.

```
In [1]: from decimal import Decimal
        ?Decimal # Asks for a help page on the Decimal() constructor
```

```
In [2]: x = 1.0 + 2.0**(-52)

        print(x)
        print(Decimal(x)) # What does this do?

        print(Decimal(0.1) - Decimal('0.1')) # Why does the output appear as it does?

1.000000000000000002
1.000000000000000002220446049250313080847263336181640625
5.551115123125782702118158340E-18
```

Aside: If you ever need true decimal storage with no loss of precision (e.g., an accounting application), turn to the `decimal` package. Just be warned it might be slower. See the following experiment for a practical demonstration.

```
In [3]: from random import random

        NUM_TRIALS = 2500000

        print("Native arithmetic:")
        A_native = [random() for _ in range(NUM_TRIALS)]
        B_native = [random() for _ in range(NUM_TRIALS)]
        %timeit [a+b for a, b in zip(A_native, B_native)]

        print("\nDecimal package:")
        A_decimal = [Decimal(a) for a in A_native]
        B_decimal = [Decimal(b) for b in B_native]
        %timeit [a+b for a, b in zip(A_decimal, B_decimal)]

Native arithmetic:

1 loop, best of 3: 385 ms per loop

Decimal package:

1 loop, best of 3: 1.09 s per loop
```

The same and not the same. Consider the following two program fragments:

Program 1:

```
s = a - b
t = s + b
```

Program 2:

```
s = a + b
t = s - b
```

Let $a = 1.0$ and $b = \epsilon_d/2 \approx 1.11 \times 10^{-16}$, i.e., machine epsilon for IEEE-754 double-precision. Recall that we do not expect these programs to return the same value; let's run some Python code to see.

Note: The IEEE standard guarantees that given two finite-precision floating-point values, the result of applying any binary operator to them is the same as if the operator were applied in infinite-precision and then rounded back to finite-precision. The precise nature of rounding can be controlled by so-called *rounding modes*; the default rounding mode is "round-half-to-even" (<http://en.wikipedia.org/wiki/Rounding>)."

```
In [4]: a = 1.0
        b = 2.**(-53) # == $epsilon_d$ / 2.0

        s1 = a - b
        t1 = s1 + b

        s2 = a + b
        t2 = s2 - b

        print("s1:", s1.hex())
        print("t1:", t1.hex())
        print("\n")
        print("s2:", s2.hex())
        print("t2:", t2.hex())

        print("")
        print(t1, "vs.", t2)
        print("(t1 == t2) == {}".format(t1 == t2))

s1: 0x1.fffffffffffffp-1
t1: 0x1.000000000000p+0

s2: 0x1.000000000000p+0
t2: 0x1.fffffffffffffp-1

1.0 vs. 0.9999999999999999
(t1 == t2) == False
```

By the way, the NumPy/SciPy package, which we will cover later in the semester, allows you to determine machine epsilon in a portable way. Just note this fact for now.

Here is an example of printing machine epsilon for both single-precision and double-precision values.

```
In [5]: import numpy as np

        EPS_S = np.finfo (np.float32).eps
        EPS_D = np.finfo (float).eps

        print("Single-precision machine epsilon:", float(EPS_S).hex(), "~", EPS_S)
        print("Double-precision machine epsilon:", float(EPS_D).hex(), "~", EPS_D)

Single-precision machine epsilon: 0x1.000000000000p-23 ~ 1.19209e-07
Double-precision machine epsilon: 0x1.000000000000p-52 ~ 2.22044604925e-16
```

Analyzing floating-point programs

Let's say someone devises an algorithm to compute $f(x)$. For a given value x , let's suppose this algorithm produces the value $\text{alg}(x)$. One important question might be, is that output "good" or "bad?"

Forward stability. One way to show that the algorithm is good is to show that

$$|\text{alg}(x) - f(x)|$$

is "small" for all x of interest to your application. What is small depends on context. In any case, if you can show it then you can claim that the algorithm is *forward stable*.

Backward stability. Sometimes it is not easy to show forward stability directly. In such cases, you can also try a different technique, which is to show that the algorithm is, instead, *backward stable*.

In particular, $\text{alg}(x)$ is a *backward stable algorithm* to compute $f(x)$ if, for all x , there exists a "small" Δx such that

$$\text{alg}(x) = f(x + \Delta x).$$

In other words, if you can show that the algorithm produces the exact answer to a slightly different input problem (meaning Δx is small, again in a context-dependent sense), then you can claim that the algorithm is backward stable.

Round-off errors. You already know that numerical values can only be represented finitely, which introduces round-off error. Thus, at the very least we should hope that a scheme to compute $f(x)$ is as insensitive to round-off errors as possible. In other words, given that there will be round-off errors, if you can prove that $\text{alg}(x)$ is either forward or backward stable, then that will give you some measure of confidence that your algorithm is good.

Here is the "standard model" of round-off error. Start by assuming that every scalar floating-point operation incurs some bounded error. That is, let $a \odot b$ be the exact mathematical result of some operation on the inputs, a and b , and let $\text{fl}(a \odot b)$ be the *computed* value, after rounding in finite-precision. The standard model says that

$$\text{fl}(a \odot b) \equiv (a \odot b)(1 + \delta),$$

where $|\delta| \leq \epsilon$, machine epsilon.

Let's apply these concepts on an example.

Example: Computing a sum

Let $x \equiv (x_0, \dots, x_{n-1})$ be a collection of input data values. Suppose we wish to compute their sum.

The exact mathematical result is

$$f(x) \equiv \sum_{i=0}^{n-1} x_i.$$

Given x , let's also denote its exact sum by the synonym $s_{n-1} \equiv f(x)$.

Now consider the following Python program to compute its sum:

```
In [6]: def alg_sum(x): # x == x[:n]
        s = 0.
        for x_i in x: # x_0, x_1, \ldots, x_{n-1}
            s += x_i
        return s
```

In exact arithmetic, meaning without any rounding errors, this program would compute the exact sum. (See also the note below.) However, you know that finite arithmetic means there will be some rounding error after each addition.

Let δ_i denote the (unknown) error at iteration i . Then, assuming the collection x represents the input values exactly, you can show that $\text{alg_sum}(x)$ computes \hat{s}_{n-1} where

$$\hat{s}_{n-1} \approx s_{n-1} + \sum_{i=0}^{n-1} s_i \delta_i,$$

that is, the exact sum *plus* a perturbation, which is the second term (the sum). The question, then, is under what conditions will this sum will be small?

Using a *backward error analysis*, you can show that

$$\hat{s}_{n-1} \approx \sum_{i=0}^{n-1} x_i (1 + \Delta_i) = f(x + \Delta),$$

where $\Delta \equiv (\Delta_0, \Delta_1, \dots, \Delta_{n-1})$. In other words, the computed sum is the exact solution to a slightly different problem, $x + \Delta$.

To complete the analysis, you can at last show that

$$|\Delta_i| \leq (n - i)\epsilon,$$

where ϵ is machine precision. Thus, as long as $n\epsilon \ll 1$, then the algorithm is backward stable and you should expect the computed result to be close to the true result. Interpreted differently, as long as you are summing $n \ll \frac{1}{\epsilon}$ values, then you needn't worry about the accuracy of the computed result compared to the true result:

```
In [7]: print("Single-precision: 1/epsilon_s ~= {:.1f} million".format(1e-6 / EPS_S))
        print("Double-precision: 1/epsilon_d ~= {:.1f} quadrillion".format(1e-15 / EPS_D))

Single-precision: 1/epsilon_s ~= 8.4 million
Double-precision: 1/epsilon_d ~= 4.5 quadrillion
```

Based on this result, you can probably surmise why double-precision is usually the default in many languages.

In the case of this summation, we can quantify not just the *backward error* (i.e., Δ_i) but also the *forward error*. In that case, it turns out that

$$|s_{n-1}^{\hat{}} - s_{n-1}| \lesssim n\epsilon \|x\|_1.$$

Note: Analysis in exact arithmetic. We claimed above that `alg_sum()` is correct *in exact arithmetic*, i.e., in the absence of round-off error. You probably have a good sense of that just reading the code.

However, if you wanted to argue about its correctness more formally, you might do so as follows using the technique of [proof by induction](https://en.wikipedia.org/wiki/Mathematical_induction) (https://en.wikipedia.org/wiki/Mathematical_induction). When your loops are more complicated and you want to prove that they are correct, you can often adapt this technique to your problem.

First, assume that the `for` loop enumerates each element `p[i]` in order from `i=0` to `n-1`, where `n=len(p)`. That is, assume `p_i` is `p[i]`.

Let $p_k \equiv p[k]$ be the k -th element of `p[:]`. Let $s_i \equiv \sum_{k=0}^i p_k$; in other words, s_i is the *exact* mathematical sum of `p[:i+1]`. Thus, s_{n-1} is the exact sum of `p[:]`.

Let $s_{-1}^{\hat{}}$ denote the initial value of the variable `s`, which is 0. For any $i \geq 0$, let $s_i^{\hat{}}$ denote the *computed* value of the variable `s` immediately after the execution of line 4, where $i = i$. When $i = i = 0$, $s_0^{\hat{}} = s_{-1}^{\hat{}} + p_0 = p_0$, which is the exact sum of `p[:1]`. Thus, $s_0^{\hat{}} = s_0$.

Now suppose that $s_{i-1}^{\hat{}} = s_{i-1}$. When $i = i$, we want to show that $s_i^{\hat{}} = s_i$. After line 4 executes, $s_i^{\hat{}} = s_{i-1}^{\hat{}} + p_i = s_{i-1} + p_i = s_i$. Thus, the computed value $s_i^{\hat{}}$ is the exact sum s_i .

If $i = n$, then, at line 5, the value `s` is $s_{n-1}^{\hat{}} = s_{n-1}$, and thus the program must in line 5 return the exact sum.

A numerical experiment: Summation

Let's do an experiment to verify that these bounds hold.

Exercise 0 (2 points). In the code cell below, we've defined a list,

```
N = [10, 100, 1000, 10000, 100000, 1000000, 10000000, 100000000]
```

- Take each entry `N[i]` to be a problem size.
- Let `t[:len(N)]` be a list, which will hold computed sums.
- For each `N[i]`, run an experiment where you sum a list of values `x[:N[i]]` using `alg_sum()`. Store the computed sum in `t[i]`.

In [8]: Student's answer

(Top)

```
N = [10, 100, 1000, 10000, 100000, 1000000, 10000000, 100000000]

# Initialize an array t of size len(N) to all zeroes.
t = [0.0] * len(N)

# Your code should do the experiment described above for
# each problem size N[i], and store the computed sum in t[i].

x = [0.1] * max(N)
```

```
t = [alg_sum(x[0:n]) for n in N]
print(t)
```

```
[0.9999999999999999, 9.999999999999998, 99.99999999999986, 1000.0000000001588, 10000.000000
018848, 100000.00000133288, 999999.9998389754]
```

In [9]: Grade cell: experiment_results

Score: 2.0 / 2.0 (Top)

```
# Test: `experiment_results`
import pandas as pd
from IPython.display import display

import matplotlib.pyplot as plt
%matplotlib inline

s = [1., 10., 100., 1000., 10000., 100000., 1000000.] # exact sums
t_minus_s_rel = [(t_i - s_i) / s_i for s_i, t_i in zip(s, t)]
rel_err_computed = [abs(r) for r in t_minus_s_rel]
rel_err_bound = [ni*EPS_D for ni in N]

# Plot of the relative error bound
plt.loglog(N, rel_err_computed, 'b*', N, rel_err_bound, 'r--')

print("Relative errors in the computed result:")
display(pd.DataFrame({'n': N, 'rel_err': rel_err_computed, 'rel_err_bound': [n*EPS_D
for n in N]}))


assert all([abs(r) <= n*EPS_D for r, n in zip(t_minus_s_rel, N)])

print("\n(Passed!)")
```

Relative errors in the computed result:

	n	rel_err	rel_err_bound
0	10	1.110223e-16	2.220446e-15
1	100	1.953993e-15	2.220446e-14
2	1000	1.406875e-14	2.220446e-13
3	10000	1.588205e-13	2.220446e-12
4	100000	1.884837e-12	2.220446e-11
5	1000000	1.332883e-11	2.220446e-10
6	10000000	1.610246e-10	2.220446e-09

(Passed!)



Computing dot products

Let x and y be two vectors of length n , and denote their dot product by $f(x, y) \equiv x^T y$.

Now suppose we store the values of x and y *exactly* in two Python arrays, $x[0:n]$ and $y[0:n]$. Further suppose we compute their dot product by the program, `alg_dot()`.

```
In [10]: def alg_dot (x, y):
          p = [xi*yi for (xi, yi) in zip (x, y)]
          s = alg_sum (p)
          return s
```

Exercise 1 (OPTIONAL -- 0 points, not graded or collected). Show under what conditions `alg_dot()` is backward stable.

Hint. Let (x_k, y_k) denote the exact values of the corresponding inputs, $(x[k], y[k])$. Then the true dot product, $x^T y = \sum_{l=0}^{n-1} x_l y_l$. Next, let \hat{p}_k denote the k -th computed product, i.e., $\hat{p}_k \equiv x_k y_k (1 + \gamma_k)$, where γ_k is the k -th round-off error and $|\gamma_k| \leq \epsilon$. Then apply the results for `alg_sum()` to analyze `alg_dot()`.

Student's answer

Score: 0.0 / 0.0 (Top)

Answer. Following the hint, `alg_sum` will compute s_{n-1}^{\wedge} on the *computed* inputs, $\{\hat{p}_k\}$. Thus,

$$\begin{aligned} s_{n-1}^{\wedge} &\approx \sum_{l=0}^{n-1} \hat{p}_l (1 + \Delta_l) \\ &= \sum_{l=0}^{n-1} x_l y_l (1 + \gamma_l) (1 + \Delta_l) \\ &= \sum_{l=0}^{n-1} x_l y_l (1 + \gamma_l + \Delta_l + \gamma_l \Delta_l). \end{aligned}$$

Mathematically, this appears to be the exact dot product to an input in which x is exact and y is perturbed (or vice-versa). To argue that `alg_dot` is backward stable, we need to establish under what conditions the perturbation, $|\gamma_l + \Delta_l + \gamma_l \Delta_l|$, is "small." Since $|\gamma_l| \leq \epsilon$ and $|\Delta_l| \leq n\epsilon$,

$$|\gamma_l + \Delta_l + \gamma_l \Delta_l| \leq |\gamma_l| + |\Delta_l| + |\gamma_l| \cdot |\Delta_l| \leq (n+1)\epsilon + \mathcal{O}(n\epsilon^2) \approx (n+1)\epsilon.$$

More accurate summation

Suppose you wish to compute the sum, $s = x_0 + x_1 + x_2 + x_3$. Let's say you use the "standard algorithm," which accumulates the terms one-by-one from left-to-right, as done by `alg_sum()` above.

For the standard algorithm, let the i -th addition incur a roundoff error, δ_i . Then our usual error analysis would reveal that the absolute error in the computed sum, s^{\wedge} , is approximately:

$$s^{\wedge} - s \approx x_0(\delta_0 + \delta_1 + \delta_2 + \delta_3) + x_1(\delta_1 + \delta_2 + \delta_3) + x_2(\delta_2 + \delta_3) + x_3\delta_3.$$

And since $|\delta_i| \leq \epsilon$, you would bound the absolute value of the error by,

$$|s^{\wedge} - s| \lesssim (4|x_0| + 3|x_1| + 2|x_2| + 1|x_3|)\epsilon.$$

Notice that $|x_0|$ is multiplied by 4, $|x_1|$ by 3, and so on.

In general, if there are n values to sum, the $|x_i|$ term will be multiplied by $n - i$.

Exercise 2 (3 points). Based on the preceding observation, implement a new summation function, `alg_sum_accurate(x)` that computes a more accurate sum than `alg_sum()`.

In [11]: Student's answer

(Top)

```
def alg_sum_accurate(x):
    assert type(x) is list
    x_sorted = sorted(x, key=abs)
    return sum(x_sorted)
```

In [12]: Grade cell: alg_sum_accurate_test

Score: 3.0 / 3.0 (Top)

```
# Test: `alg_sum_accurate_test`
from math import exp
from numpy.random import lognormal

print("Generating non-uniform random values...")
N = [10, 10000, 100000000]
x = [lognormal(-10.0, 10.0) for _ in range(max(N))]
print("Range of input values: [{}, {}].format(min(x), max(x))

print("Computing the 'exact' sum. May be slow so please wait...")
x_exact = [Decimal(x_i) for x_i in x]
s_exact = [float(sum(x_exact[:n])) for n in N]
print("==>", s_exact)

print("Running alg_sum()...")
s_alg = [alg_sum(x[:n]) for n in N]
print("==>", s_alg)

print("Running alg_sum_accurate()...")
s_acc = [alg_sum_accurate(x[:n]) for n in N]
print("==>", s_acc)

print("Summary of relative errors:")
ds_alg = [abs(s_a - s_e) / s_e for s_a, s_e in zip(s_alg, s_exact)]
ds_acc = [abs(s_a - s_e) / s_e for s_a, s_e in zip(s_acc, s_exact)]
display(pd.DataFrame({'n': N,
                      'rel_err(alg_sum)': ds_alg,
                      'rel_err(alg_sum_accurate)': ds_acc}))

assert all([r_acc < r_alg for r_acc, r_alg in zip(ds_acc[1:], ds_alg[1:])]), \
        "The 'accurate' algorithm appears to be less accurate than the conventional one!"

print("\n(Passed!)")
```

Generating non-uniform random values...

Range of input values: [2.6435384868703784e-28, 5.219348712549726e+19]

Computing the 'exact' sum. May be slow so please wait...

==> [1.6543314740870991, 115344247820.34613, 1.027106740306605e+20]

Running alg_sum()...

==> [1.6543314740870994, 115344247820.34462, 1.0271067403042505e+20]

Running alg_sum_accurate()...


==> [1.6543314740870994, 115344247820.34613, 1.027106740306605e+20]

Summary of relative errors:

	n	rel_err(alg_sum)	rel_err(alg_sum_accurate)
0	10	1.342201e-16	1.342201e-16
1	10000	1.309662e-14	0.000000e+00
2	10000000	2.292405e-12	0.000000e+00

(Passed!)

© All Rights Reserved



© 2012–2017 edX Inc. All rights reserved except
where noted. EdX, Open edX and the edX and Open
edX logos are registered trademarks or trademarks of
edX Inc. | 粤ICP备17044299号-2

