

Recap

EXPLORATORY DATA ANALYSIS (EDA)



Q1: The syntax `df.shape` returns a tuple representing ____ of the dataset.

- A. correlation and variance**
- B. mean and median**
- C. number of rows and columns**
- D. size in memory**





Q1: The syntax `df.shape` returns a tuple representing ____ of the dataset.

- A. correlation and variance**
- B. mean and median**
- C. number of rows and columns**
- D. size in memory**





Q2: To check the percentage of missing values column-wise, we use `df.isnull().mean()`, which gives us values between ____ and ____.

- A. 1 and 100**
- B. 0 and 1**
- C. -1 and 1**
- D. 0 and 100**



Q2: To check the percentage of missing values column-wise, we use `df.isnull().mean()`, which gives us values between ____ and ____.

- A. 1 and 100**
- B. 0 and 1**
- C. -1 and 1**
- D. 0 and 100**



Q3: The line

`df = df.drop(columns=null_percent[null_percent > 0.3].index)` is used to remove columns with more than ____% missing values.

- A. 3
- B. 10
- C. 30
- D. 50



Q3: The line

`df = df.drop(columns=null_percent[null_percent > 0.3].index)` is used to remove columns with more than ____% missing values.

- A. 3
- B. 10
- C. 30
- D. 50



Q4: To examine the summary statistics of numerical features, the code `df[num_cols].describe().T[:5]` is used. The `.T` stands for ____.

- A. table format**
- B. trimming values**
- C. transpose**
- D. top values**



Q4: To examine the summary statistics of numerical features, the code `df[num_cols].describe().T[:5]` is used. The `.T` stands for ____.

- A. table format
- B. trimming values
- C. transpose**
- D. top values



Q5: The function `sns.boxplot()` is used to detect ____ and visualize distribution characteristics.

- A. duplicates**
- B. outliers**
- C. nulls**
- D. categories**



Q5: The function `sns.boxplot()` is used to detect ____ and visualize distribution characteristics.

- A. duplicates
- B. outliers**
- C. nulls
- D. categories





Q6: A histogram with KDE (Kernel Density Estimation) is plotted using `sns.histplot(df['SalePrice'], kde=True)`. The KDE line helps to understand the ____ of the data.

- A. completeness**
- B. sparsity**
- C. central tendency**
- D. probability density**



Q6: A histogram with KDE (Kernel Density Estimation) is plotted using `sns.histplot(df['SalePrice'], kde=True)`. The KDE line helps to understand the ____ of the data.

- A. completeness
- B. sparsity
- C. central tendency
- D. probability density**





Q7: The `df.select_dtypes(include='object')` line is used to select ____ features in the dataset.

- A. numerical**
- B. categorical**
- C. Boolean**
- D. missing**



Q7: The `df.select_dtypes(include='object')` line is used to select ____ features in the dataset.

- A. numerical
- B. categorical**
- C. Boolean
- D. missing



Q8: The correlation matrix is created using `df.corr(numeric_only=True)`. Setting `numeric_only=True` ensures that only ____ data types are used in the computation.

- A. float and bool
- B. object and float
- C. int and float
- D. datetime and object



Q8: The correlation matrix is created using `df.corr(numeric_only=True)`. Setting `numeric_only=True` ensures that only ____ data types are used in the computation.

- A. float and bool
- B. object and float
- C. int and float**
- D. datetime and object



Q9: The `sns.heatmap()` function with `annot=True` overlays ____ on the heatmap cells.

- A. feature names**
- B. colors**
- C. correlation values**
- D. histogram bars**





Q9: The `sns.heatmap()` function with `annot=True` overlays ____ on the heatmap cells.

- A. feature names
- B. colors
- C. correlation values
- D. histogram bars





Q10: In the context of EDA, the main reason to remove columns with high null percentages is to avoid ____ during model training.

- A. faster execution**
- B. better styling**
- C. bias and error**
- D. overfitting**



Q10: In the context of EDA, the main reason to remove columns with high null percentages is to avoid ____ during model training.

- A. faster execution**
- B. better styling**
- C. bias and error**
- D. overfitting**

Knowledge Test Day 3

REGULARIZATION + DEEP LEARNING OVERVIEW



Q1. Overfitting occurs when a model performs well on training data but poorly on test data because it ____ the training patterns.

- A. ignores**
- B. generalizes**
- C. memorizes**
- D. transforms**





Q1. Overfitting occurs when a model performs well on training data but poorly on test data because it ____ the training patterns.

- A. ignores**
- B. generalizes**
- C. memorizes**
- D. transforms**



Q2. Underfitting typically happens when the model is too ____ to capture the underlying structure of the data.

- A. large**
- B. simple**
- C. complex**
- D. deep**





Q2. Underfitting typically happens when the model is too ____ to capture the underlying structure of the data.

- A. large**
- B. simple**
- C. complex**
- D. deep**





Q3. One of the key goals of L1 and L2 regularization is to prevent ____ by penalizing large weights.

- A. optimization**
- B. dropout**
- C. overfitting**
- D. training**





Q3. One of the key goals of L1 and L2 regularization is to prevent ____ by penalizing large weights.

- A. optimization**
- B. dropout**
- C. overfitting**
- D. training**



Q4. L1 regularization encourages ____ by forcing some weights to become exactly zero.

- A. sparsity**
- B. overfitting**
- C. weight duplication**
- D. normalization**



Q4. L1 regularization encourages ____ by forcing some weights to become exactly zero.

- A. sparsity**
- B. overfitting**
- C. weight duplication**
- D. normalization**



Q5. In L2 regularization, the penalty added to the loss function is proportional to the ____ of the weights.

- A. mean**
- B. square**
- C. absolute value**
- D. maximum**



Q5. In L2 regularization, the penalty added to the loss function is proportional to the ____ of the weights.

- A. mean**
- B. square**
- C. absolute value**
- D. maximum**



Q6. A neural network consists of input, hidden, and output layers where each neuron computes a weighted sum followed by a(n) ____ function.

- A. loss**
- B. dropout**
- C. activation**
- D. optimizer**



Q6. A neural network consists of input, hidden, and output layers where each neuron computes a weighted sum followed by a(n) ____ function.

- A. loss**
- B. dropout**
- C. activation**
- D. optimizer**



Q7. In deep learning, the term “deep” refers to the presence of ____ layers in the network.

- A. very wide**
- B. many hidden**
- C. few output**
- D. multiple input**





Q7. In deep learning, the term “deep” refers to the presence of ____ layers in the network.

- A. very wide**
- B. many hidden**
- C. few output**
- D. multiple input**





Q8. Regularization is typically added to the model's ____ function to constrain the learning process.

- A. activation**
- B. loss**
- C. dropout**
- D. optimizer**





Q8. Regularization is typically added to the model's ____ function to constrain the learning process.

- A. activation**
- B. loss**
- C. dropout**
- D. optimizer**





Q9. A key indicator of overfitting is when training accuracy is high, but ____ accuracy is low.

- A. validation**
- B. learning rate**
- C. training**
- D. test loss**





Q9. A key indicator of overfitting is when training accuracy is high, but ____ accuracy is low.

- A. validation**
- B. learning rate**
- C. training**
- D. test loss**





Q10. One benefit of using dropout layers in neural networks is that they prevent co-adaptation of neurons by randomly ____ some during training.

- A. scaling**
- B. deleting**
- C. updating**
- D. deactivating**