UNIT – III


DEADLOCKS: System model, deadlock characterization, deadlock prevention, avoidance, detection and recovery from deadlock. **(T1: Ch-7)**

MEMORY MANAGEMENT: Memory management strategies-Swapping, contiguous memory allocation, paging, structure of the page table, segmentation, virtual-memory management-demand paging, page-replacement algorithms, allocation of frames, thrashing. (**T1: Ch-8, 9**)

What is a Deadlock?

In a multiprogramming environment, several processes may compete for a finite number of resources. A process requests resources; if the resources are not available at that time, the process enters a waiting state. Sometimes, awaiting process is never again able to change state, because the resources it has requested are held by other waiting processes. This situation is called a **deadlock**.

Deadlocks are a set of blocked processes each holding a resource and waiting to acquire a resource held by another process.



System Model

System consists of a finite number of resources to be distributed among a number of competing processes. The resources may be partitioned into several types (or classes), each consisting of some number of identical instances. CPU cycles, files, and I/O devices (such as printers and DVD drives) are examples of resource types. If a system has two CPUs, then the

resource type *CPU* has two instances. Similarly, the resource type *printer* may have five instances.

A process must request a resource before using it and must release there source after using it. A process may request as many resources as it requires to carry out its designated task. Obviously, the number of resources requested may not exceed the total number of resources available in the system. In other words, a process cannot request three printers if the system has only two. Under the normal mode of operation, a process may utilize a resource in only the following sequence:

1. **Request**. The process requests the resource. If the request cannot be granted immediately (for example, if the resource is being used by another process), then the requesting process must wait until it can acquire there source.
2. **Use**. The process can operate on the resource (for example, if the resource is a printer, the process can print on the printer).
3. **Release**. The process releases the resource.

The request and release of resources may be system calls like request() and release() device, open() and close() file, and allocate() and free() memory system calls.

Deadlocks may also involve different resource types. For example, consider a system with one printer and one DVD drive. Suppose that process *Pi* is holding the DVD and process *Pj* is holding the printer. If *Pi* requests the printer and *Pj* requests the DVD drive, a deadlock occurs.

Deadlock Characterization

In a deadlock, processes never finish executing, and system resources are tied up, preventing other jobs from starting.


Necessary Conditions

A deadlock situation can arise if the following four conditions hold simultaneously in a system:

1. **Mutual exclusion**. At least one resource must be held in a non-sharable mode; that is, only one process at a time can use the resource. If another process requests that resource, the requesting process must be delayed until the resource has been released.
2. **Hold and wait**. A process must be holding at least one resource and waiting to acquire additional resources that are currently being held by other processes.

3. **No preemption**. Resources cannot be preempted; that is, a resource can be released only voluntarily by the process holding it, after that process has completed its task.

4. **Circular wait**. A set *{P*0, *P*1, ..., *Pn}* of waiting processes must exist such that *P*0 is waiting for a resource held by *P*1, *P*1 is waiting for a resource held by *P*2, ..., *Pn*−1 is waiting for a resource held by *Pn*, and *Pn* is waiting for a resource held by *P*0.



State diagram of circular wait condition

We emphasize that all four conditions must hold for a deadlock to occur. The circular-wait condition implies the hold-and-wait condition, so the four conditions are not completely independent.

Resource-Allocation Graph

Deadlocks can be described more precisely in terms of a directed graph called a **system resource-allocation graph**. This graph consists of a set of vertices *V* and a set of edges *E*. The set of vertices *V* is partitioned into two different types of nodes: *P* = *{P*1, *P*2, ..., *Pn}*, the set consisting of all the active processes in the system, and *R* = *{R*1, *R*2, ..., *Rm}*, the set consisting of all resource types in the system.

A directed edge from process *Pi* to resource type *Rj* is denoted by *Pi* → *Rj* ;it signifies that process *Pi* has requested an instance of resource type *Rj* and is currently waiting for that resource. A directed edge from resource type *Rj*to process *Pi* is denoted by *Rj* → *Pi* ; it signifies that an instance of resource type *Rj* has been allocated to process *Pi* . A directed edge *Pi* → *Rj* is called a **request edge**; a directed edge *Rj* → *Pi* is called an **assignment edge**.

Pictorially, we represent each process *Pi* as a circle and each resource type *Rj* as a rectangle. Since resource type *Rj* may have more than one instance, were present each such instance as a dot within the rectangle. Note that a request edge points to only the rectangle *Rj* , whereas an assignment edge must also designate one of the dots in the rectangle. When

process *Pi* requests an instance of resource type *Rj*, a request edge is inserted in the resource-allocation graph. When this request can be fulfilled, the request edge is ***instantaneously*** transformed to an assignment edge. When the process no longer needs access to the resource, it releases the resource. As a result, the assignment edge is deleted.

The resource-allocation graph shown in Figure 7.1 depicts the following situation.

The sets *P, R,* and *E*:

◦*P* = {*P*1, *P*2, *P*3}




Figure 7.1 Resource-allocation graph.

R = {*R*1, *R*2, *R*3, *R*4}

◦*E* = {*P*1 → *R*1, *P*2 → *R*3, *R*1 → *P*2, *R*2 → *P*2, *R*2 → *P*1, *R*3 → *P*3}

• Resource instances:

◦One instance of resource type *R*1

◦Two instances of resource type *R*2

◦One instance of resource type *R*3

◦Three instances of resource type *R*4

• Process states:

◦Process *P*1 is holding an instance of resource type *R*2 and is waiting for an instance of resource type *R*1.

◦Process *P*2 is holding an instance of *R*1 and an instance of *R*2 and is waiting for an instance of *R*3.

◦Process *P*3 is holding an instance of *R*3.

Given the definition of a resource-allocation graph, it can be shown that, if the graph contains no cycles, then no process in the system is deadlocked. If the graph does contain a cycle, then a deadlock may exist.

If each resource type has exactly one instance, then a cycle implies that a deadlock has occurred. If the cycle involves only a set of resource types, each of which has only a single instance, then a deadlock has occurred. Each process involved in the cycle is deadlocked. In this case, a cycle in the graph is both a necessary and a sufficient condition for the existence of deadlock.

If each resource type has several instances, then a cycle does not necessarily imply that a deadlock has occurred. In this case, a cycle in the graph is a necessary but not a sufficient condition for the existence of deadlock.

To illustrate this concept, we return to the resource-allocation graph depicted in Figure 7.1. Suppose that process $P3$ requests an instance of resource type $R2$. Since no resource instance is currently available, we add a request edge$P3 \rightarrow R2$ to the graph (Figure 7.2). At this point, two minimal cycles exist in the system:




Figure 7.2 Resource-allocation graph with a deadlock.

$P1 \rightarrow R1 \rightarrow P2 \rightarrow R3 \rightarrow P3 \rightarrow R2 \rightarrow P1$

$P2 \rightarrow R3 \rightarrow P3 \rightarrow R2 \rightarrow P2$

Processes $P1$, $P2$, and $P3$ are deadlocked. Process $P2$ is waiting for the resource$R3$, which is held by process $P3$. Process $P3$ is waiting for either process $P1$ or process $P2$ to release resource $R2$. In addition, process $P1$ is waiting for process$P2$ to release resource $R1$.

Now consider the resource-allocation graph in Figure 7.3. In this example, we also have a cycle:

$P1 \rightarrow R1 \rightarrow P3 \rightarrow R2 \rightarrow P1$




Figure 7.3 Resource-allocation graph with a cycle but no deadlock.


However, there is no deadlock. Observe that process *P*4 may release its instance of resource type *R*2. That resource can then be allocated to *P*3, breaking the cycle. In summary, if a resource-allocation graph does not have a cycle, then the system is ***not*** in a deadlocked state. If there is a cycle, then the system may or may not be in a deadlocked state. This observation is important when we deal with the deadlock problem.

Resource Allocation Graph


The resource allocation graph is the pictorial representation of the state of a system. As its name suggests, the resource allocation graph is the complete information about all the processes which are holding some resources or waiting for some resources.

It also contains the information about all the instances of all the resources whether they are available or being used by the processes. In Resource allocation graph, the process is represented by a Circle while the Resource is represented by a rectangle.

Vertices are mainly of two types, Resource and process. Each of them will be represented by a different shape. Circle represents process while rectangle represents resource. A resource can have more than one instance. Each instance will be represented by a dot inside the rectangle.



Edges in RAG are also of two types, one represents assignment and other represents the wait of a process for a resource. The above image shows each of them. A resource is shown as assigned to a process if the tail of the arrow is attached to an instance to the resource and the head is attached to a process. A process is shown as waiting for a resource if the tail of an arrow is attached to the process while the head is pointing towards the resource.




Example

Let's consider 3 processes P1, P2 and P3, and two types of resources R1 and R2. The resources are having 1 instance each.


According to the graph, R1 is being used by P1, P2 is holding R2 and waiting for R1, P3 is waiting for R1 as well as R2.

The graph is deadlock free since no cycle is being formed in the graph.



Deadlock Detection using RAG

If a cycle is being formed in a Resource allocation graph where all the resources have the single instance then the system is deadlocked. In Case of Resource allocation graph with multi-instanced resource types, Cycle is a necessary condition of deadlock but not the sufficient condition. The following example contains three processes P1, P2, P3 and three resources R2, R2, R3. All the resources are having single instances each.



If we analyze the graph then we can find out that there is a cycle formed in the graph since the system is satisfying all the four conditions of deadlock.

Allocation Matrix

Allocation matrix can be formed by using the Resource allocation graph of a system. In Allocation matrix, an entry will be made for each of the resource assigned. For Example, in the following matrix, en entry is being made in front of P1 and below R3 since R3 is assigned to P1.

Process	R1	R2	R3
P1	0	0	1

P2	1	0	0
P3	0	1	0

Request Matrix

In request matrix, an entry will be made for each of the resource requested. As in the following example, P1 needs R1 therefore an entry is being made in front of P1 and below R1.


Process	R1	R2	R3
P1	1	0	0
P2	0	1	0
P3	0	0	1

Avial = (0,0,0)

Neither we are having any resource available in the system nor a process going to release. Each of the process needs at least single resource to complete therefore they will continuously be holding each one of them. We cannot fulfill the demand of at least one process using the available resources therefore the system is deadlocked as determined earlier when we detected a cycle in the graph.

Deadlock Detection and Recovery

In this approach, The OS doesn't apply any mechanism to avoid or prevent the deadlocks. Therefore the system considers that the deadlock will definitely occur. In order to get rid of deadlocks, The OS periodically checks the system for any deadlock. In case, it finds any of the deadlock then the OS will recover the system using some recovery techniques. The main task of the OS is detecting the deadlocks. The OS can detect the deadlocks with the help of Resource allocation graph.



In single instanced resource types, if a cycle is being formed in the system then there will definitely be a deadlock. On the other hand, in multiple instanced resource type graph, detecting a cycle is not just enough. We have to apply the safety algorithm on the system by converting the resource allocation graph into the allocation matrix and request matrix. In order to recover the system from deadlocks, either OS considers resources or processes.

For Resource

Preempt the resource

We can snatch one of the resources from the owner of the resource (process) and give it to the other process with the expectation that it will complete the execution and will release this resource sooner. Well, choosing a resource which will be snatched is going to be a bit difficult.

Rollback to a safe state

System passes through various states to get into the deadlock state. The operating system can rollback the system to the previous safe state. For this purpose, OS needs to implement check pointing at every state. The moment, we get into deadlock, we will rollback all the allocations to get into the previous safe state.


For Process

Kill a process

Killing a process can solve our problem but the bigger concern is to decide which process to kill. Generally, Operating system kills a process which has done least amount of work until now.

Kill all process

This is not a suggestible approach but can be implemented if the problem becomes very serious. Killing all process will lead to inefficiency in the system because all the processes will execute again from starting.



Methods for Handling Deadlocks

Generally speaking, we can deal with the deadlock problem in one of three ways:

- We can use a protocol to prevent or avoid deadlocks, ensuring that the system will ***never*** enter a deadlocked state.
- We can allow the system to enter a deadlocked state, detect it, and recover.
- We can ignore the problem altogether and pretend that deadlocks never occur in the system.

The third solution is the one used by most operating systems, including Linux and Windows. It is then up to the application developer to write programs that handle deadlocks.

To ensure that deadlocks never occur, the system can use either a deadlock prevention or a deadlock-avoidance scheme. **Deadlock prevention** provides a set of methods to ensure that at least one of the necessary conditions (Section7.2.1) cannot hold. These methods prevent deadlocks by constraining how requests for resources can be made.

Deadlock avoidance requires that the operating system be given additional information in advance concerning which resources a process will request and use during its lifetime. With this additional knowledge, the operating system can decide for each request whether or not the process should wait. To decide whether the current request can be satisfied or must be delayed, the system must consider the resources currently available, the resources currently allocated to each process, and the future requests and releases of each process.

If a system does not employ either a deadlock-prevention or a deadlock avoidance algorithm, then a deadlock situation may arise. In this environment, the system can provide an algorithm that examines the state of the system to determine whether a deadlock has occurred and an algorithm to recover from the deadlock.

Deadlock Prevention

For a deadlock to occur, each of the four necessary conditions must hold. By ensuring that at least one of these conditions cannot hold, we can *prevent* the occurrence of a deadlock.

Deadlock Prevention

If we simulate deadlock with a table which is standing on its four legs then we can also simulate four legs with the four conditions which when occurs simultaneously, cause the deadlock.

However, if we break one of the legs of the table then the table will fall definitely. The same happens with deadlock, if we can be able to violate one of the four necessary conditions and don't let them occur together then we can prevent the deadlock.

Let's see how we can prevent each of the conditions.


1. Mutual Exclusion

Mutual section from the resource point of view is the fact that a resource can never be used by more than one process simultaneously which is fair enough but that is the main reason behind the deadlock. If a resource could have been used by more than one process at the same time then the process would have never been waiting for any resource.

However, if we can be able to violate resources behaving in the mutually exclusive manner then the deadlock can be prevented.

Spooling

For a device like printer, spooling can work. There is a memory associated with the printer which stores jobs from each of the process into it. Later, Printer collects all the jobs and print each one of them according to FCFS. By using this mechanism, the process doesn't have to wait for the printer and it can continue whatever it was doing. Later, it collects the output when it is produced.



Although, Spooling can be an effective approach to violate mutual exclusion but it suffers from two kinds of problems.

1. This cannot be applied to every resource.
2. After some point of time, there may arise a race condition between the processes to get space in that spool.

We cannot force a resource to be used by more than one process at the same time since it will not be fair enough and some serious problems may arise in the performance. Therefore, we cannot violate mutual exclusion for a process practically.

2. Hold and Wait

Hold and wait condition lies when a process holds a resource and waiting for some other resource to complete its task. Deadlock occurs because there can be more than one process which are holding one resource and waiting for other in the cyclic order.

However, we have to find out some mechanism by which a process either doesn't hold any resource or doesn't wait. That means, a process must be assigned all the necessary resources before the execution starts. A process must not wait for any resource once the execution has been started.

!(Hold and wait) = !hold or !wait (negation of hold and wait is, either you don't hold or you don't wait)

This can be implemented practically if a process declares all the resources initially. However, this sounds very practical but can't be done in the computer system because a process can't determine necessary resources initially. Process is the set of instructions which are executed by the CPU. Each of the instruction may demand multiple resources at the multiple times. The need cannot be fixed by the OS.

The problem with the approach is:

1. Practically not possible.
2. Possibility of getting starved will be increases due to the fact that some process may hold a resource for a very long time.

3. No Preemption

Deadlock arises due to the fact that a process can't be stopped once it starts. However, if we take the resource away from the process which is causing deadlock then we can prevent deadlock.

This is not a good approach at all since if we take a resource away which is being used by the process then all the work which it has done till now can become inconsistent. Consider a printer is being used by any process. If we take the printer away from that process and assign it to some other process then all the data which has been printed can become inconsistent and ineffective and also the fact that the process can't start printing again from where it has left which causes performance inefficiency.

4. Circular Wait

To violate circular wait, we can assign a priority number to each of the resource. A process can't request for a lesser priority resource. This ensures that not a single process can request a resource which is being utilized by some other process and no cycle will be formed.

Condition	Approach	Is Practically Possible?
Mutual Exclusion	Spooling	✗
Hold and Wait	Request for all the resources initially	✗
No Preemption	Snatch all the resources	✗
Circular Wait	Assign priority to each resources and order resources numerically	✓

Among all the methods, violating Circular wait is the only approach that can be implemented practically.

Deadlock Avoidance

An alternative method for avoiding deadlocks is to require additional information about how resources are to be requested. In this the system consider the resources currently available, the resources currently allocated to each process, and the future requests and releases of each process. A deadlock-avoidance algorithm dynamically examines the resource-allocation state to ensure that a circular-wait condition can never exist. The resource-allocation state is defined by the number of available and allocated resources and the maximum demands of the processes.

Deadlock avoidance algorithms:

1) Resource-Allocation-Graph Algorithm
2) Banker's Algorithm

Safe State

A state is safe if the system can allocate resources to each process (up to its maximum) in some order and still avoid a deadlock. More formally, a system is in a safe state only if there exists a safe sequence. A sequence of processes<P1, P2, ..., Pn > is a safe sequence for the current allocation state if, for each Pi , the resource requests that Pi can still make can be satisfied by the currently available resources plus the resources held by all P j ,with j < i. In this situation, if the resources that Pi needs are not immediately available, then Pi can wait until all P j have finished. When they have finished, Pi can obtain all of its needed resources, complete its designated task, return its allocated resources, and terminate. When Pi terminates, Pi +1 can obtain its needed resources, and so on. If no such sequence exists, then the system state is said to be unsafe.

Deadlock avoidance

In deadlock avoidance, the request for any resource will be granted if the resulting state of the system doesn't cause deadlock in the system. The state of the system will continuously be checked for safe and unsafe states. In order to avoid deadlocks, the process must tell OS, the maximum number of resources a process can request to complete its execution.

The simplest and most useful approach states that the process should declare the maximum number of resources of each type it may ever need. The Deadlock avoidance algorithm examines the resource allocations so that there can never be a circular wait condition.

Safe and Unsafe States

The resource allocation state of a system can be defined by the instances of available and allocated resources, and the maximum instance of the resources demanded by the processes.

A state of a system recorded at some random time is shown below.

Resources Assigned

Process	Type 1	Type 2	Type 3	Type 4
A	3	0	2	2
B	0	0	1	1
C	1	1	1	0
D	2	1	4	0

Resources still needed

Process	Type 1	Type 2	Type 3	Type 4
A	1	1	0	0
B	0	1	1	2
C	1	2	1	0
D	2	1	1	2

1. E = (7 6 8 4)
2. P = (6 2 8 3)
3. A = (1 4 0 1)

Above tables and vector E, P and A describes the resource allocation state of a system. There are 4 processes and 4 types of the resources in a system. Table 1 shows the instances of each resource assigned to each process. Table 2 shows the instances of the resources, each process still needs. Vector E is the representation of total instances of each resource in the system.

Vector P represents the instances of resources that have been assigned to processes. Vector A represents the number of resources that are not in use. A state of the system is called safe if the system can allocate all the resources requested by all the processes without entering into deadlock. If the system cannot fulfill the request of all processes then the state of the system is called unsafe. The key of Deadlock avoidance approach is when the request is made for resources then the request must only be approved in the case if the resulting state is also a safe state.

What is Banker's Algorithm?

Banker's algorithm is a **deadlock avoidance algorithm**. It is named so because this algorithm is used in banking systems to determine whether a loan can be granted or not.

Consider there are n account holders in a bank and the sum of the money in all of their accounts is S. Every time a loan has to be granted by the bank, it subtracts the **loan amount** from the **total money** the bank has. Then it checks if that difference is greater than S. It is done because, only then, the bank would have enough money even if all the n account holders draw all their money at once.

Banker's algorithm works in a similar way in computers.

Whenever a new process is created, it must specify the maximum instances of each resource type that it needs, exactly.

Let us assume that there are n processes and m resource types. Some data structures that are used to implement the banker's algorithm are:

1. Available

It is an **array** of length m. It represents the number of available resources of each type. If Available[j] = k, then there are k instances available, of resource type R(j).

2. Max

It is an n x m matrix which represents the maximum number of instances of each resource that a process can request. If Max[i][j] = k, then the process P(i) can request atmost k instances of resource type R(j).

3. Allocation

It is an n x m matrix which represents the number of resources of each type currently allocated to each process. If Allocation[i][j] = k, then process P(i) is currently allocated k instances of resource type R(j).

4. Need

It is an n x m matrix which indicates the remaining resource needs of each process. If Need[i][j] = k, then process P(i) may need k more instances of resource type R(j) to complete its task.

```
Need[i][j] = Max[i][j] - Allocation [i][j]
```

Resource Request Algorithm

This describes the behavior of the system when a process makes a resource request in the form of a request matrix. The steps are:

1. If number of requested instances of each resource is less than the need (which was declared previously by the process), go to step 2.
2. If number of requested instances of each resource type is less than the available resources of each type, go to step 3. If not, the process has to wait because sufficient resources are not available yet.
3. Now, assume that the resources have been allocated. Accordingly do,

```
Available = Available - Requesti
Allocation(i) = Allocation(i) + Request(i)
Need(i) = Need(i) - Request(i)
```

This step is done because the system needs to assume that resources have been allocated. So there will be less resources available after allocation. The number of allocated instances will increase. The need of the resources by the process will reduce. That's what is represented by the above three operations.

After completing the above three steps, check if the system is in safe state by applying the safety algorithm. If it is in safe state, proceed to allocate the requested resources. Else, the process has to wait longer.

Safety Algorithm

1. Let Work and Finish be vectors of length **m** and **n**, respectively. Initially,
2. Work = Available
3. Finish[i] =false for i = 0, 1, ... , n - 1.

   This means, initially, no process has finished and the number of available resources is represented by the **Available** array.
4. Find an index **i** such that both
5. Finish[i] ==false
6. Needi <= Work

   If there is no such i present, then proceed to step 4.

   It means, we need to find an unfinished process whose need can be satisfied by the available resources. If no such process exists, just go to step 4.
7. Perform the following:
8. Work = Work + Allocation;
9. Finish[i] = true;

   Go to step 2.

   When an unfinished process is found, then the resources are allocated and the process is marked finished. And then, the loop is repeated to check the same for all other processes.
10. If Finish[i] == true for all i, then the system is in a safe state.

    That means if all processes are finished, then the system is in safe state.

Example:

Considering a system with five processes P_0 through P_4 and three resources types A, B, C. Resource type A has 10 instances, B has 5 instances and type C has 7 instances. Suppose at time t_0 following snapshot of the system has been taken:

Process	Allocation	Max	Available
	A B C	A B C	A B C
P_0	0 1 0	7 5 3	3 3 2
P_1	2 0 0	3 2 2	
P_2	3 0 2	9 0 2	
P_3	2 1 1	2 2 2	
P_4	0 0 2	4 3 3	

Question1. What will be the content of the Need matrix?


Need [i, j] = Max [i, j] – Allocation [i, j]


So, the content of Need Matrix is:


Process	Need		
	A	B	C
P_0	7	4	3
P_1	1	2	2
P_2	6	0	0
P_3	0	1	1
P_4	4	3	1


Question2. Is the system in safe state? If Yes, then what is the safe sequence?


Applying the Safety algorithm on the given system,






































The safe sequence is P_1, P_3, P_4, P_0, P_2

Question3. What will happen if process P_1 requests one additional instance of resource type A and two instances of resource type C?

$Request_1$ = (A B C) 1, 0, 2

To decide whether the request is granted we use Resource Request algorithm

Step 1: $Request_1$ (1, 0, 2) < $Need_1$ (1, 2, 2) ✔

Step 2: $Request_1$ (1, 0, 2) < Available (3, 3, 2) ✔

Step 3:


$Available = Available - Request_1$

$Allocation_1 = Allocation_1 + Request_1$

$Need_1 = Need_1 - Request_1$

Process	Allocation	Need	Available
	A B C	A B C	A B C
P_0	0 1 0	7 4 3	2 3 0
P_1	3 0 2	0 2 0	
P_2	3 0 2	6 0 0	
P_3	2 1 1	0 1 1	
P_4	0 0 2	4 3 1	

We must determine whether this new system state is safe. To do so, we again execute Safety algorithm on the above data structures.



Hence the new system state is safe, so we can immediately grant the request for process $\mathbf{P_1}$.

Example2

Assuming that the system distinguishes between four types of resources, (A, B, C and D), the following is an example of how those resources could be distributed. *Note that this example shows the system at an instant before a new request for resources arrives. Also, the types and number of resources are abstracted. Real systems, for example, would deal with much larger quantities of each resource.*

Total resources in system:

A B C D

6 5 7 6

Available system resources are:

A B C D

3 1 1 2

Processes (currently allocated resources):

A B C D

P1 1 2 2 1

P2 1 0 3 3

P3 1 2 1 0

Processes (maximum resources):

A B C D

P1 3 3 2 2

P2 1 2 3 4

P3 1 3 5 0

Need= maximum resources - currently allocated resources

Processes (need resources):

A B C D

P1 2 1 0 1

P2 0 2 0 1

P3 0 1 4 0

Deadlock Detection

If deadlock prevention and avoidance are not done properly, as deadlock may occur and only things left to do is to detect the recover from the deadlock.

If all resource types has only single instance, then we can use a graph called wait-for-graph, which is a variant of resource allocation graph. Here, vertices represent processes and a directed edge from P1 to P2 indicate that P1 is waiting for a resource held by P2. Like in the case of resource allocation graph, a cycle in a wait-for-graph indicate a deadlock. So the system can maintain a wait-for-graph and check for cycles periodically to detect any deadlocks.




Figure 7.9 (a) Resource-allocation graph. (b) Corresponding wait-for graph.

The wait-for-graph is not much useful if there are multiple instances for a resource, as a cycle may not imply a deadlock. In such a case, we can use an algorithm similar to Banker's algorithm to detect deadlock. We can see if further allocations can be made on not based on