# XAI


**I.XAI** : Explainable Artificial Intelligence (XAI) is a branch of Artificial Intelligence (AI) that develops methods and techniques to make AI models transparent, understandable, and interpretable. It explains how an AI model makes decisions and why it produces a particular prediction, enabling humans to understand and trust AI systems.

**Need for XAI**

- Makes AI decisions transparent.
- Improves user trust and confidence.
- Helps identify errors and bias in AI models.
- Supports debugging and model improvement.
- Ensures ethical and responsible AI.

## II. Black Box Problem:

A Black Box Model is an AI model whose inputs and outputs are visible, but its internal reasoning process is hidden or not easily interpretable.




**1. Lack of Transparency:** The internal decision-making process of complex AI models is hidden, making it difficult for users to understand how and why a prediction was made.

Example: An AI system rejects a loan application but does not explain which factors (income, credit score, or repayment history) influenced the decision.

**2. Lack of Trust:** Users are less likely to trust AI systems if they cannot understand or verify the reasoning behind the predictions.

Example: Passengers may hesitate to trust an autonomous vehicle if it suddenly brakes without explaining the reason.

**3. Difficult Debugging:** When an AI model makes incorrect predictions, it is difficult for developers to identify the source of the error because the internal reasoning is not visible.

Example: A medical AI incorrectly diagnoses a patient, but doctors cannot determine which input features caused the mistake.

**4. Bias and Unfairness:** AI models trained on biased data may produce unfair or discriminatory decisions. Without explanations, these hidden biases are difficult to detect.

Example: A recruitment AI may reject qualified candidates because it has learned biased patterns from historical hiring data.

**5. Regulatory and Legal Challenges:** Many governments and regulatory bodies require AI systems to provide explanations for important decisions, particularly in healthcare, finance, and public services.

Example: A bank using AI for loan approval may be required to explain why a customer's application was rejected.

## III. Goals of XAI :

**Explainability** is the overall objective of XAI.
**Interpretability** identifies which features influenced the decision.
**Understandability** ensures explanations are easy for humans to understand.
**Comprehensibility** ensures explanations are complete, meaningful, and useful.
**Transparency** reveals how the AI system works and the information it uses.

| Goal | Meaning | Key Question | Autonomous Vehicle Example |
|---|---|---|---|
| **Explainability** | Explains why the AI made a decision | Why was the decision made? | "Emergency braking because a pedestrian was detected ahead." |
| **Interpretability** | Explains which features influenced the decision | Which factors influenced the decision? | Pedestrian (60%), speed (25%), wet road (15%). |
| **Understandability** | Makes explanations easy to understand | Can users easily understand it? | "The car slowed because a cyclist crossed the road." |
| **Comprehensibility** | Provides complete and meaningful explanations | Is the explanation complete and useful? | Dashboard shows distance, speed, road condition, and braking decision. |
| **Transparency** | Reveals model, data, and decision process | How does the AI system work? | Shows sensors, model type, training data, and limitations. |


**Stakeholders:**

| Stakeholder | Need for Explanation |
|---|---|
| 1.Data Scientists / Developers | Need explanations to understand why a model produces specific predictions. |
| 2. Domain Experts | Need to verify whether AI decisions are consistent with real-world knowledge and practices. |
| 3. End Users | Need simple and understandable reasons behind AI decisions before trusting and acting on them. |
| 4. Regulators / Auditors | Need transparency to check whether AI systems follow laws, ethical guidelines, and fairness requirements. |
| 5.Business / Management | Need explanations to understand risks, justify AI-driven decisions, and make strategic choices. |


## IV. History:

The goal of making AI systems understandable and trustworthy has evolved through different stages.


1. **Porphyrian Trees (3rd Century)**
    - One of the earliest knowledge representation methods based on hierarchical classification and logical reasoning.
    - It represented concepts by breaking general categories into specific subcategories.
    - *Example:* Classification of living things into animals, plants, mammals, birds, and humans.




2. **Expert Systems (1970s–1980s)**
    - AI systems used human expert knowledge encoded as IF–THEN rules.
    - Decisions could be easily explained by tracing the rules followed.
    - *Example:* Medical diagnosis systems explaining disease prediction using symptoms and rules.





3. **Case-Based Reasoning and Bayesian Networks (1980s–1990s)**
    - Case-Based Reasoning (CBR) solved new problems by comparing them with previous experiences.





**4.Bayesian Networks (1980s–1990s)**

- Used probability theory and graphical models to represent uncertain knowledge and cause–effect relationships.
- Helped explain decisions by showing dependencies between different factors.
- **Example:** Accident risk prediction using relationships among rain, wet roads, vehicle speed, and accident probability.



**5.Neural Networks and Modern XAI (1980s–Present)**

- Neural networks achieved high accuracy by learning complex patterns from data.
- However, their internal decision-making became difficult to understand, creating the **black-box problem**.




## V Purpose of XAI:

**1. Informativeness**

- Meaning: Explanations should provide relevant and useful information about the AI decision.
- Purpose: Helps users understand the important factors influencing the output.
- Example: The autonomous car identifies that pedestrian location, speed, and obstacle distance influenced braking.

**2. Trustworthiness**

- Meaning: Explanations should be reliable, truthful, and consistent with the actual model behavior.
- Purpose: Builds confidence among users.
- Example: The vehicle should provide the real reason for stopping rather than a misleading explanation.

**3. Fairness**

- Meaning: AI decisions should be unbiased and equally reliable for all users.
- Purpose: Prevents discrimination caused by biased data or algorithms.
- Example**:** A self-driving car should detect pedestrians accurately regardless of age, gender, clothing, or skin tone.

**4. Transparency**

- Meaning: Makes the AI model, data usage, and decision-making process understandable.
- Purpose: Allows users and developers to know how the system works.
- Example: The vehicle system reveals that camera input, LiDAR data, and speed information were used for decision-making.

**5. Causality**

- Meaning: Explains actual cause-and-effect relationships rather than only statistical correlations.
- Purpose: Helps understand what factors truly caused the decision.
- Example:“The vehicle stopped because an obstacle was detected in the driving path,” rather than simply saying “stopping is associated with low speed.”

**6. Transferability**

- Meaning: Explanations should remain useful across different environments, situations, and domains.
- Purpose: Enables reuse of explanation methods.
- Example: An explanation method developed for autonomous cars can be adapted for medical diagnosis or smart grid applications.

**7. Reliability**

- Meaning: Explanations should remain consistent when similar inputs are provided.
- Purpose: Ensures stable and dependable AI behavior.

- Example: If the same road condition occurs repeatedly, the autonomous vehicle should provide similar reasoning for braking.

**8. Accessibility**

- Meaning: Explanations should be easy to understand by the target users.
- Purpose: Makes AI understandable for non-technical users.
- Example: Instead of saying *"*CNN detected high-confidence object classification," the car explains: "A person was detected crossing the road."

**9. Privacy**

- Meaning: Explanations should protect sensitive information while providing useful insights.
- Purpose: Prevents disclosure of confidential data.
- Example: A medical AI system should explain disease prediction without revealing a patient's private information.

## VI. Societal Impact:

The societal impact of Explainable AI (XAI) refers to how AI systems influence people, organizations, and society by ensuring that AI decisions are trustworthy, fair, and responsible.

1. **Fairness and Bias Reduction:** XAI identifies hidden biases in AI models and data, helping to reduce discrimination and ensure fair decisions.
   Example: Detecting bias in AI-based recruitment or loan approval systems.
2. **Safety and Reliability:** XAI explains AI behavior and detects possible errors or unsafe decisions before they cause harm.
   Example: Autonomous vehicles use XAI to understand why an object or pedestrian was not detected.
3. **Verifiability:** XAI allows users and developers to verify whether an AI system works correctly and follows expected rules.
   Example: Medical AI systems can be checked to ensure safe and reliable diagnosis recommendations.
4. **Accountability and Transparency:** XAI provides reasons behind AI decisions, making organizations responsible for AI outcomes.
   Example: A bank can explain why a loan application was rejected based on specific factors.

## VII. Types of Explanations in Explainable AI:

Explainable AI (XAI) provides different types of explanations to make AI model decisions understandable, transparent, and trustworthy for humans. The major types of explanations are:

**1. Local Explanations:**

- Local explanations describe why an AI model made a particular decision for a specific individual case.
- They focus on the contribution of input features for one prediction.
- Useful for understanding individual decisions.

Example (Loan Approval):A bank AI model rejects a loan application because:

- High debt-to-income ratio
- Low credit score
- Short credit history

The explanation tells the applicant the specific reasons behind rejection.

**2. Global Explanations:**

- Global explanations describe the overall behavior and decision-making process of the AI model.
- They identify the most important features influencing predictions across the entire dataset.
- Helps developers and regulators understand model behavior.

Example (Loan Approval):For all loan applicants, the model considers:

- Credit score
- Income level
- Debt-to-income ratio

as the major factors affecting loan decisions.

**3. Counterfactual Explanations:**

- Counterfactual explanations show what changes in input values would change the AI decision.
- They answer the question: “What should be different to get another outcome?”

Example: A loan is rejected because income is ₹4 lakh.The explanation may state:
"If your income were increased to ₹6 lakh, your loan would likely be approved."

**4. What-if Explanations:**

- What-if explanations allow users to explore how changing different inputs affects the prediction.
- They help users understand possible scenarios before making decisions.

Example:

- Increasing income to ₹6 lakh → Loan approved
- Reducing EMI burden by ₹5,000 → Loan approved
- Increasing loan amount to ₹12 lakh → Loan may be rejected

**5. Contrastive Explanations:**

- Contrastive explanations compare a given decision with a similar case having a different outcome.
- They explain why one person was rejected while another similar person was approved.

**Example:** A similar applicant received approval because:

- Higher credit score (720 vs 620)
- Higher income (₹6.5 lakh vs ₹4 lakh)
- Lower debt ratio (30% vs 55%)

**6. Example-Based Explanations:**

- Example-based explanations use similar past cases to justify the current prediction.
- They explain decisions by referring to previous examples stored in the dataset.

Example: "Previous applicants with similar income, credit score, and debt levels were also rejected due to high financial risk.

## VIII. Trade offs:

In Explainable AI (XAI), improving one aspect of an AI system often reduces the performance of another. These are known as trade-offs. The three major trade-offs are:

**1. Completeness vs Interpretability**

- Completeness means the explanation captures the full complexity of the AI model and usually provides higher accuracy.
- Interpretability means the explanation is simple and easy for humans to understand.
- Trade-off: Highly accurate deep learning models are difficult to interpret, while simpler models are easier to understand but may have lower accuracy.

Example: A deep learning model detects cancer with 95% accuracy, whereas a decision tree is easier to understand but achieves only 75% accuracy.

**2. Efficacy vs Privacy**

- Efficacy means explanations are detailed and useful.
- Privacy protects sensitive information in the training data.
- Trade-off: More detailed explanations may reveal confidential information, while stronger privacy protection reduces the detail of explanations.

Example: In healthcare, explaining why a patient is at high risk may expose sensitive medical information.

**3. Human Understandability vs Accuracy**

- Human Understandability means explanations are simple and understandable.
- Accuracy refers to the predictive performance of the AI model.
- Trade-off: Simplifying explanations makes them easier to understand but may not represent the complete decision-making process, reducing accuracy.

Example: A simple rule like "High debt-to-income ratio caused loan rejection" is easy to understand but ignores other factors considered by the AI model.

## IX. Taxonomy of Explainable AI:

The taxonomy of Explainable AI (XAI) classifies explanation methods based on where the explanation is generated (Scope), when it is generated (Stage), and how it relates to the AI model (Model). This taxonomy helps users select the most suitable explanation technique for different AI applications.

**1. Scope-Based Taxonomy**

Scope refers to the level at which explanations are generated.

a) Global Explanation

- Explains the overall behavior of the AI model.
- Helps understand how the model makes predictions for the entire dataset.
- Mainly used by researchers and developers.

Example:

In a loan approval system, feature importance shows that credit score, income, and debt-to-income ratio are the most influential factors.

b) Local Explanation

- Explains the prediction made for a specific instance.
- Shows why the model produced a particular output.

Example:

A loan application is rejected because of:

- High debt-to-income ratio
- Low credit score
- Short credit history

**2. Stage-Based Taxonomy**

Stage indicates when explanations are generated during the AI pipeline.

a) Pre-model Explainability

- Applied before model training.
- Improves data quality and transparency.
- Includes:
    - Data preprocessing
    - Feature engineering
    - Data visualization
    - Feature selection

Example: Removing missing values and selecting important customer features before training a fraud detection model.

b) Intrinsic Explainability

- The model is interpretable by design.
- Explanations are available while the model is being built.
- Uses simple and transparent models.

Examples:

- Linear Regression
- Decision Trees
- Rule-based Systems

c) Post-hoc Explainability

- Applied after the model has made predictions.
- Used for complex black-box models such as Deep Neural Networks.
- Explains predictions without changing the model.

Examples:

- SHAP
- LIME
- Counterfactual Explanations

**3. Model-Based Taxonomy**

This taxonomy describes the relationship between explanation methods and AI models.

a) Model-Specific Methods

- Designed for a particular type of AI model.
- Utilize the internal structure of that model.
- Usually provide more accurate explanations.

Examples:

- Decision Trees
- Rule Lists
- Linear Regression coefficients

b) Model-Agnostic Methods

- Can explain any machine learning model, regardless of its architecture.
- Treat the model as a black box.

Examples:

- SHAP
- LIME
- Anchors

# Pre-model Interpretability and Explainability

**Pre-model interpretability** focuses on understanding, analyzing, and preparing the data before any machine learning model is trained**.** It ensures that the data and features are meaningful, transparent, and suitable for building an interpretable AI model.

**1. Data Science Process and Exploratory Data Analysis (EDA)**

EDA is the first step in understanding the dataset before model development.

**Activities include:**

- Collecting and understanding the dataset.
- Handling missing values and duplicate records.
- Detecting and removing outliers.
- Visualizing data using histograms, box plots, scatter plots, and heatmaps.
- Identifying relationships and correlations among features.
- Understanding data distribution and class imbalance.

**Benefits:**

- Improves data quality.
- Detects errors and inconsistencies early.
- Provides insights into important variables.

- Reduces bias in the dataset.

**Example:**
In a loan approval dataset, EDA may reveal that credit score and income strongly influence loan approval, while some features contain many missing values and should be cleaned.

**2. Feature Engineering**
Feature engineering involves creating, selecting, and transforming input variables to improve both model performance and interpretability.


**Activities include:**
- Feature selection (choosing relevant features).
- Feature extraction (combining existing features into new ones).
- Feature transformation (normalization, scaling, encoding categorical variables).
- Removing redundant or highly correlated features.

**Benefits:**
- Reduces model complexity.
- Improves prediction accuracy.
- Makes feature contributions easier to explain.
- Enhances transparency of the model.

**Example:**
Instead of using Monthly Income and Monthly Expenses separately, a new feature called Debt-to-Income Ratio can be created, which is more meaningful and easier to interpret for loan approval decisions.

# I. Exploratory Data Analysis (EDA)

Exploratory Data Analysis (EDA) can be defined as a collection of statistical techniques and visualization representations to get more insights from the data.




**EDA Challenges for Explainability:**

Pre-model interpretability involves understanding and preparing the data before model training. During this stage, several challenges arise that affect data analysis, visualization, and the performance of Explainable AI (XAI).

**1. High Dimensionality:**

- Real-world datasets often contain hundreds or thousands of features.
- As the number of features increases, computational cost and memory usage also increase.
- Visualizing high-dimensional data becomes difficult because reducing dimensions may result in loss of important information.

**Example:** A healthcare dataset with 500 patient attributes is difficult to visualize and interpret directly.

**2. Mixed Data Types (Heterogeneity)**

- Datasets usually contain different types of features, such as:

    - Numerical (Age, Salary)
    - Categorical (Gender, City)
    - Ordinal (Education Level)
    - Boolean (Yes/No)
- Applying statistical analysis and visualization to mixed data types is challenging and often requires different preprocessing methods.

**Example:** A bank loan dataset contains income (continuous), occupation (categorical), and credit rating (ordinal), requiring different encoding and analysis techniques.

**3. Missing Values and Outliers**

- Real-world datasets often contain missing values due to incomplete data collection.
- They may also contain outliers, which are abnormal or erroneous observations.
- If not handled properly, they can reduce model accuracy and produce misleading explanations.

**Example:** A customer's annual income recorded as ₹5 crore instead of ₹5 lakh is an outlier that can distort analysis.

**4. Anonymity and Privacy**

- Many datasets contain sensitive or confidential information, such as medical records or financial details.
- Data privacy regulations require that personal information be protected before analysis.
- Removing or masking sensitive information may reduce the amount of information available for interpretation.

**Example:** A hospital dataset removes patient names and IDs to protect privacy before performing data analysis.

**5. Large Data Volume**

- Modern datasets may contain millions or billions of records.
- Traditional data analysis techniques become slow and memory-intensive.
- Efficient methods such as sampling, aggregation, approximation, and distributed computing are often required.

**Example:** An e-commerce company analyzes billions of customer transactions using sampled data instead of the entire dataset.

## Benefits of Exploratory Data Analysis (EDA):

- **Detect and manage outliers** through outlier and distribution analysis, improving model accuracy and robustness.
- **Identify patterns in missing data** and support effective imputation strategies to enhance data quality.
- **Reduce dimensionality** for easier visualization while revealing both local and global data patterns using multivariate visualization techniques.
- **Understand relationships and correlations** among features to uncover dependencies and support local and global pattern analysis.
- **Validate expert hypotheses** by exploring whether the observed data supports expected patterns or assumptions.
- **Evaluate newly engineered features** by examining their interactions with existing features and assessing their contribution to the dataset.

**EDA Taxonomy:** One of the simplest and most widely used ways to classify EDA is based on:

1. **Number of variables analysed** (Univariate or Multivariate)
2. **Method of analysis** (Graphical or Non-Graphical)

These two criteria result in four categories of EDA.

**1. Non-Graphical Univariate Analysis**

- Analyzes one variable at a time using summary statistics.
- Provides information about the central tendency and spread of the data.

**Techniques:**

- Mean , Median, Mode , Variance, Standard Deviation, Frequency Distribution etc

**Example:** Marks of 5 students 10, 20, 20, 30, 40

Mean = 24, median = 20, mode=20, Variance = 104, Standard Deviation = 10.20 ,

Frequency distribution = 10:1, 20:2, 30:1, 40:1


**2. Graphical Univariate Analysis**

- Analyzes one variable visually to understand its distribution.
- Helps identify skewness, outliers, and data patterns.

**Techniques:**

- Histogram , Bar Chart , Pie Chart, Box Plot, Density Plot

**Example:** A histogram showing the distribution of students' examination marks.





**3. Non-Graphical Multivariate Analysis**

- Studies the relationship between two or more variables using statistical methods.
- Helps identify dependencies and associations among variables.

**Techniques:**

- Correlation Analysis, Covariance, Cross-tabulation, Contingency Tables

**Example:**





## 4. Graphical Multivariate Analysis

- Uses visualizations to understand relationships among multiple variables.
- Useful for identifying clusters, trends, and feature interactions.

**Techniques:**

- Scatter Plot , Heatmap , Pair Plot, Bubble Chart, Parallel Coordinates Plot etc

**Example:**



**EDA and Time Series Data :** The process of analysing data collected over time to understand its characteristics, identify patterns, and prepare it for forecasting or predictive modelling. Unlike normal EDA, time is the most important variable, and the order of observations must be preserved.

**Key Components of Time Series EDA**

1. **Trend Analysis**
   - Identifies the long-term increase or decrease in data over time.
   - **Example:** Electricity demand gradually increases every year.
2. **Seasonality Analysis**
   - Detects repeating patterns at regular intervals (daily, weekly, monthly, or yearly).
   - **Example:** Higher electricity consumption during summer months.
3. **Cyclical Patterns**
   - Identifies fluctuations occurring over longer, irregular periods due to economic or environmental factors.
   - **Example:** Reduction in industrial power demand during an economic recession.
4. **Outlier and Missing Value Detection**
   - Finds abnormal values and missing observations that may affect forecasting accuracy.
   - **Example:** Sudden spike in electricity usage due to a festival or sensor malfunction.

**Common EDA Techniques for Time Series:**

- Line plots
- Moving averages
- Time series decomposition (Trend, Seasonal, Residual)
- Autocorrelation (ACF) and Partial Autocorrelation (PACF)
- Rolling mean and rolling standard deviation

## EDA and Natural Language Processing:

Exploratory Data Analysis (EDA) in Natural Language Processing (NLP) is the process of analyzing and understanding text data before training an NLP model. It helps identify patterns, data quality issues, class imbalance, vocabulary characteristics, and potential bias, leading to better model performance and explainability.

**1. Text-Specific EDA**

- **Word Frequency Counts:** Identify the most frequently occurring words in the corpus.
- **Word Clouds:** Visually display the most important or frequent words.
- **N-gram Analysis:** Analyze common sequences of words (e.g., bigrams and trigrams) to understand context and language patterns.


**2. Document-Level Statistics**


- **Text Length Distribution:** Measures the number of words or characters in each document.
- **Vocabulary Size:** Determines the number of unique words in the dataset.
- **Sentiment Distribution:** Examines the proportion of positive, negative, and neutral texts.


**Example:** For a **movie review dataset**:

a) Dataset Overview

| Category | No. of Reviews | Percentage |
|---|---|---|
| Positive | 600 | 60% |
| Negative | 400 | 40% |
| Total | 1000 | 100% |




Insights from EDA

- 60% reviews are positive and 40% are negative.
- Most reviews contain between 20-60 words.
- Common positive words: good, great, excellent.
- Common negative words: bad, boring, waste.




## EDA and Computer Vision:

Exploratory Data Analysis (EDA) for Computer Vision is the process of analyzing image datasets before training a deep learning or machine learning model. It helps understand image characteristics, detect data quality issues, and improve model performance and explainability.

**1. Image-Specific EDA**

- Analyze the class distribution across different image categories.
- Study image size and aspect ratio statistics to ensure consistency.

**Example:** Checking whether a dataset contains an equal number of cat and dog images.

**2. Pixel Intensity and Channel Statistics**

- Plot pixel intensity histograms to understand brightness and contrast.
- Compute channel-wise statistics (RGB) such as mean and standard deviation for image normalization.

**Example:** Measuring the average Red, Green, and Blue values in satellite images.

**3. Visual Inspection**

- Display sample images from each class to detect:
  - Incorrect labels
  - Blurred or corrupted images
  - Dataset bias

**Example:** A dog image mistakenly labeled as a cat can be identified and corrected.

**4. Duplicate Image Detection**

- Identify duplicate or near-duplicate images that may appear in both training and testing datasets.
- Prevents data leakage, which can lead to overly optimistic model performance.

EDA for image data helps to:


- Detect class imbalance.
- Identify labeling errors and dataset bias.
- Standardize image size and quality.
- Prevent data leakage caused by duplicate images.
- Improve the accuracy and explainability of computer vision models.

**Example:** for sample data set


a) Dataset Overview

| Class | No. of Images | Percentage |
|---|---|---|
| Cat | 600 | 60% |
| Dog | 400 | 40% |
| Total | 1000 | 100% |


b) Class Distribution (Bar Chart)




c) Image Size Distribution (Histogram)





d) Average Brightness Distribution (Histogram)




# II. Feature Engineering

**Feature Engineering** is the process of creating, selecting, transforming, and reducing input features to improve the performance, interpretability, and explainability of machine learning models. It converts raw data into meaningful features that help models make accurate and transparent predictions.

## FEATURE ENGINEERING PROCESS




**Advantages of Feature Engineering:** Feature engineering plays a vital role in improving the performance and explainability of machine learning models. Its major advantages are:

**1. Reduces Model Complexity and Improves Interpretability**

- Feature selection and dimensionality reduction remove irrelevant and redundant features.
- Simpler models have fewer feature interactions, making them easier to understand and explain.
- Noise caused by unnecessary features is reduced, leading to better prediction accuracy.

**Example:** Selecting only **Credit Score, Income, and Debt-to-Income Ratio** instead of 50 customer attributes makes a loan approval model easier to interpret.

**2. Improves Computational Efficiency**

- A smaller number of features requires less storage space and memory.
- Reduces model training and prediction time.

- Makes hyperparameter tuning and automated model selection faster and more efficient.

**Example:** Reducing a dataset from **500 features to 50 features** significantly decreases training time.

**3. Reduces Overfitting**

- Removing irrelevant features prevents the model from learning noise in the training data.
- Improves the model's ability to generalize to unseen data.
- Analyzing feature distributions between training and test data helps identify the causes of poor model performance.

**Example:** Removing random or highly correlated features improves the accuracy of a fraud detection model on new transactions.

## Taxonomy and Tools:

**1. Transformation**

Transformation converts feature values into a suitable form for machine learning algorithms.

**Common Techniques**

- **Scaling:** Brings features to a common range (e.g., 0–1 or -1 to 1).
- **Normalization:** Adjusts values so they have comparable magnitudes.
- **Log Transformation:** Reduces skewness in highly skewed data.
- **Power Transformation:** Makes data more normally distributed.

**Example:** Scaling salary values from ₹10,000–₹1,00,000 to a range of 0–1.

**2. Encoding**

Encoding converts **categorical variables** into numerical values that machine learning models can process.

**Common Techniques**

- **One-Hot Encoding:** Creates separate binary columns for each category.
- **Ordinal Encoding:** Assigns ordered numerical values to categories.
- **Target Encoding:** Replaces categories with the average value of the target variable.

**Example:**
Gender:

- Male → 1, Female → 0 (Ordinal)

or

Colour: Red → (1,0,0), Blue → (0,1,0), Green → (0,0,1) (One-Hot Encoding)

**3. Feature Construction**

Feature construction creates **new informative features** from existing variables.

**Common Techniques**

- **Interaction Terms:** Combine two or more features.
- **Polynomial Features:** Create squared or higher-order terms.
- **Domain-Driven Ratios:** Construct meaningful ratios based on domain knowledge.

**Example:**

- Debt-to-Income Ratio = Loan Amount / Annual Income
- $Age^2$ as a polynomial feature.

**4. Feature Selection and Dimensionality Reduction**

These techniques reduce the number of features while retaining the most useful information.

**Feature Selection Methods**

- **Filter Methods:** Select features using statistical tests (e.g., correlation, chi-square).
- **Wrapper Methods:** Evaluate different feature subsets using model performance.
- **Embedded Methods:** Perform feature selection during model training (e.g., LASSO, Decision Trees).

**Dimensionality Reduction Techniques**

- **PCA (Principal Component Analysis):** Reduces features while preserving maximum variance.
- **t-SNE (t-Distributed Stochastic Neighbor Embedding):** Projects high-dimensional data into lower dimensions for visualization.

**Example:** Reducing 100 customer features to 20 principal components using PCA.

**Tools Used for Feature Engineering**

- **Scikit-learn:** Scaling, encoding, feature selection, and PCA.
- **Featuretools:** Automated feature engineering.
- **Pandas:** Data cleaning and feature creation.
- **category_encoders:** Advanced encoding techniques for categorical variables.

**Advantages**

- Improves model accuracy and efficiency.
- Reduces computational cost.
- Prevents overfitting.
- Makes models more interpretable and explainable.
- Enhances the quality of input features.

## Short answer questions

1. Define Explainable Artificial Intelligence (XAI).
2. What is the Black Box Problem?
3. List the goals of XAI.
4. What is the purpose of Explainable AI?
5. State any four societal impacts of XAI.
6. List the different types of explanations in XAI.
7. What are the major trade-offs in XAI?
8. What is meant by XAI taxonomy?
9. Define Exploratory Data Analysis (EDA).
10. What is Feature Engineering?

## Long answer questions

1. Explain the goals of Explainable AI.
2. Describe the brief history of Explainable AI.
3. Explain the purpose of XAI.
4. Explain the societal impact of Explainable AI.
5. Differentiate Local and Global explanations.
6. Explain the trade-offs involved in Explainable AI.
7. A bank rejects a customer's loan application using AI. Explain how XAI can solve the Black Box Problem.
8. Apply Exploratory Data Analysis (EDA) techniques to prepare a time series dataset for forecasting.
9. Explain how Exploratory Data Analysis (EDA) prepares text data for Natural Language Processing (NLP) applications.
10. A company wants to build an AI-based image classification system. Explain how EDA can be used to prepare the image dataset before model training
11. A recruitment AI shows gender bias. Explain how XAI can identify and reduce the bias.
12. Compare two trade-offs in XAI and recommend which is more suitable for a healthcare application.
13. Classify different XAI techniques using the Scope-, Stage-, and Model-based taxonomy.
14. Given a raw customer dataset with missing values and outliers, explain how EDA prepares the data before model training.
15. Design a Feature Engineering pipeline for a loan approval dataset using transformation, encoding, feature construction, and feature selection.