EXECUTIVE SECURITY REPORT

Consolidated VAPT Findings

This report combines uploaded scanner outputs into a single review-ready document with normalized severity levels, tool attribution, and OWASP mapping where available.

TOTAL FINDINGS	REPORT TYPE	COVERAGE
154	HTML + PDF	Multi-tool ingestion

Severity Summary

High-level distribution of normalized findings across all uploaded reports.

CRITICAL	HIGH	MEDIUM	LOW
2	2	19	131

Detailed Findings

Each record below shows the normalized severity, originating tool, mapped OWASP category, and remediation detail when present.

prismjs: DOM Clobbering vulnerability within the Prism library's prism-autoloader plugin

Medium | Tool: Trivy | OWASP: Unknown

Description	Prism (aka PrismJS) through 1.29.0 allows DOM Clobbering (with resultant XSS for untrusted input that contains HTML but does not directly contain JavaScript), because document.currentScript lookup can be shadowed by attacker-injected HTML elements.
Remediation	1.30.0
Reference	CVE-2024-53382

prismjs: DOM Clobbering vulnerability within the Prism library's prism-autoloader plugin

Medium | Tool: Trivy | OWASP: Unknown

Description	Prism (aka PrismJS) through 1.29.0 allows DOM Clobbering (with resultant XSS for untrusted input that contains HTML but does not directly contain JavaScript), because document.currentScript lookup can be shadowed by attacker-injected HTML elements.
Remediation	1.30.0
Reference	CVE-2024-53382

Prototype pollution in swiper

Critical | Tool: Trivy | OWASP: Unknown

Description

Swiper is a free and mobile touch slider with hardware accelerated transitions and native behavior. Versions 6.5.1 through 12.1.1 have a Prototype pollution vulnerability. The vulnerability resides in line 94 of shared/utils.mjs, where the indexOf() function is used to check whether user provided input contain forbidden strings. Despite a previous fix that attempted to mitigate prototype pollution by checking whether user input contained a forbidden key, it is still possible to pollute Object.prototype via a crafted input using Array.prototype. The exploit works across Windows and Linux and on Node and Bun runtimes. Any application that processes attacker-controlled input using this package may be affected by the following: Authentication Bypass, Denial of Service and RCE. This issue is fixed in version 12.1.2.

Remediation

12.1.2

Reference

CVE-2026-27212

Prototype pollution in swiper

Critical | Tool: Trivy | OWASP: Unknown

Description

Swiper is a free and mobile touch slider with hardware accelerated transitions and native behavior. Versions 6.5.1 through 12.1.1 have a Prototype pollution vulnerability. The vulnerability resides in line 94 of shared/utils.mjs, where the indexOf() function is used to check whether user provided input contain forbidden strings. Despite a previous fix that attempted to mitigate prototype pollution by checking whether user input contained a forbidden key, it is still possible to pollute Object.prototype via a crafted input using Array.prototype. The exploit works across Windows and Linux and on Node and Bun runtimes. Any application that processes attacker-controlled input using this package may be affected by the following: Authentication Bypass, Denial of Service and RCE. This issue is fixed in version 12.1.2.

Remediation

12.1.2

Reference

CVE-2026-27212

cryptography: Cryptography: Buffer overflow via non-contiguous buffer in API

Medium | Tool: Trivy | OWASP: Unknown

Description

cryptography is a package designed to expose cryptographic primitives and recipes to Python developers. From 45.0.0 to before 46.0.7, if a non-contiguous buffer was passed to APIs which accepted Python buffers (e.g. Hash.update()), this could lead to buffer overflows. This vulnerability is fixed in 46.0.7.

Remediation

46.0.7

Reference

CVE-2026-39892

python-cryptography: Cryptography: Security bypass due to improper DNS name constraint validation

Low | Tool: Trivy | OWASP: Unknown

Description

cryptography is a package designed to expose cryptographic primitives and recipes to Python developers. Prior to version 46.0.6, DNS name constraints were only validated against SANs within child certificates, and not the "peer name" presented during each validation. Consequently, cryptography would allow a peer named bar.example.com to validate against a wildcard leaf certificate for *.example.com, even if the leaf's parent certificate (or upwards) contained an excluded subtree constraint for bar.example.com. This issue has been patched in version 46.0.6.

Remediation

46.0.6

Reference

CVE-2026-34073

langchain: path traversal in legacy load_prompt functions in langchain-core

High | Tool: Trivy | OWASP: Unknown

Description

LangChain is a framework for building agents and LLM-powered applications. Prior to version 1.2.22, multiple functions in langchain_core.prompts.loading read files from paths embedded in deserialized config dicts without validating against directory traversal or absolute path injection. When an application passes user-influenced prompt configurations to load_prompt() or load_prompt_from_config(), an attacker can read arbitrary files on the host filesystem, constrained only by file-extension checks (.txt for templates, .json/.yaml for examples). This issue has been patched in version 1.2.22.

Remediation

1.2.22

Reference

CVE-2026-34070

langchain: SSRF via image_url token counting in ChatOpenAI.get_num_tokens_from_messages

Low | Tool: Trivy | OWASP: Unknown

Description

LangChain is a framework for building agents and LLM-powered applications. Prior to 1.2.11, the ChatOpenAI.get_num_tokens_from_messages() method fetches arbitrary image_url values without validation when computing token counts for vision-enabled models. This allows attackers to trigger Server-Side Request Forgery (SSRF) attacks by providing malicious image URLs in user input. This vulnerability is fixed in 1.2.11.

Remediation

1.2.11

Reference

CVE-2026-26013

LangGraph checkpoint loading has unsafe msgpack deserialization

Medium | Tool: Trivy | OWASP: Unknown

Description

LangGraph SQLite Checkpoint is an implementation of LangGraph CheckpointSaver that uses SQLite DB (both sync and async, via aiosqlite). In version 1.0.9 and prior, LangGraph checkpointers can load msgpack-encoded checkpoints that reconstruct Python objects during deserialization. If an attacker can modify checkpoint data in the backing store (for example, after a database compromise or other privileged write access to the persistence layer), they can potentially supply a crafted payload that triggers unsafe object reconstruction when the checkpoint is loaded. No known patch is public.

Remediation

1.0.10

Reference

CVE-2026-28277

LangGraph Checkpoint affected by RCE in "json" mode of JsonPlusSerializer

High | Tool: Trivy | OWASP: Unknown

Description

LangGraph SQLite Checkpoint is an implementation of LangGraph CheckpointSaver that uses SQLite DB (both sync and async, via aiosqlite). In versions 2.1.2 and below, the JsonPlusSerializer (used as the default serialization protocol for all checkpointing) contains a Remote Code Execution (RCE) vulnerability when deserializing payloads saved in the "json" serialization mode. By default, the serializer attempts to use "msgpack" for serialization. However, prior to version 3.0 of the checkpointer library, if illegal Unicode surrogate values caused serialization to fail, it would fall back to using the "json" mode. This issue is fixed in version 3.0.0.

Remediation

3.0.0

Reference

CVE-2025-64439

langgraph-checkpoint: LangGraph Checkpoint: Remote Code Execution via insecure deserialization in caching layer

Medium | Tool: Trivy | OWASP: Unknown

Description

LangGraph Checkpoint defines the base interface for LangGraph checkpointers. Prior to version 4.0.0, a Remote Code Execution vulnerability exists in LangGraph's caching layer when applications enable cache backends that inherit from `BaseCache` and opt nodes into caching via `CachePolicy`. Prior to `langgraph-checkpoint` 4.0.0, `BaseCache` defaults to `JsonPlusSerializer(pickle_fallback=True)`. When msgpack serialization fails, cached values can be deserialized via `pickle.loads(...)`. Caching is not enabled by default. Applications are affected only when the application explicitly enables a cache backend (for example by passing `cache=...` to `StateGraph.compile(...)` or otherwise configuring a `BaseCache` implementation), one or more nodes opt into caching via `CachePolicy`, and the attacker can write to the cache backend (for example a network-accessible Redis instance with weak/no auth, shared cache infrastructure reachable by other tenants/services, or a writable SQLite cache file). An attacker must be able to write attacker-controlled bytes into the cache backend such that the LangGraph process later reads and deserializes them. This typically requires write access to a networked cache (for example a network-accessible Redis instance with weak/no auth or shared cache infrastructure reachable by other tenants/services) or write access to local cache storage (for example a writable SQLite cache file via permissive file permissions or a shared writable volume). Because exploitation requires write access to the cache storage layer, this is a post-compromise / post-access escalation vector. LangGraph Checkpoint 4.0.0 patches the issue.

Remediation

4.0.0

Reference

CVE-2026-27794

pip: pip missing checks on symbolic link extraction

Medium | Tool: Trivy | OWASP: Unknown

Description

When extracting a tar archive pip may not check symbolic links point into the extraction directory if the tarfile module doesn't implement PEP 706. Note that upgrading pip to a "fixed" version for this vulnerability doesn't fix all known vulnerabilities that are remediated by using a Python version that implements PEP 706. Note that this is a vulnerability in pip's fallback implementation of tar extraction for Python versions that don't implement PEP 706 and therefore are not secure to all vulnerabilities in the Python 'tarfile' module. If you're using a Python version that implements PEP 706 then pip doesn't use the "vulnerable" fallback code. Mitigations include upgrading to a version of pip that includes the fix, upgrading to a Python version that implements PEP 706 (Python >=3.9.17, >=3.10.12, >=3.11.4, or >=3.12), applying the linked patch, or inspecting source distributions (sdists) before installation as is already a best-practice.

Remediation

25.3

Reference

CVE-2025-8869

pip: pip: Information disclosure via path traversal when installing crafted wheel archives

Low | Tool: Trivy | OWASP: Unknown

Description

When pip is installing and extracting a maliciously crafted wheel archive, files may be extracted outside the installation directory. The path traversal is limited to prefixes of the installation directory, thus isn't able to inject or overwrite executable files in typical situations.

Remediation

26.0

Reference

CVE-2026-1703

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./audit/signals.py:192)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./audit/utils.py:20)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

django_mark_safe

Medium | Tool: Bandit | OWASP: Unknown

Description	Potential XSS on mark_safe function. (./gmc_rfq/claims_analytics.py:34)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b703_django_mark_safe.html
Reference	B703

blacklist

Medium | Tool: Bandit | OWASP: Unknown

Description	Use of mark_safe() may expose cross-site scripting vulnerabilities and should be reviewed. (./gmc_rfq/claims_analytics.py:34)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b308-mark-safe
Reference	B308

django_mark_safe

Medium | Tool: Bandit | OWASP: Unknown

Description	Potential XSS on mark_safe function. (./gmc_rfq/claims_analytics.py:45)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b703_django_mark_safe.html
Reference	B703

blacklist

Medium | Tool: Bandit | OWASP: Unknown

Description	Use of mark_safe() may expose cross-site scripting vulnerabilities and should be reviewed. (./gmc_rfq/claims_analytics.py:45)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b308-mark-safe
Reference	B308

django_mark_safe

Medium | Tool: Bandit | OWASP: Unknown

Description	Potential XSS on mark_safe function. (./gmc_rfq/claims_analytics.py:801)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b703_django_mark_safe.html
Reference	B703

blacklist

Medium | Tool: Bandit | OWASP: Unknown

Description	Use of mark_safe() may expose cross-site scripting vulnerabilities and should be reviewed. (./gmc_rfq/claims_analytics.py:801)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b308-mark-safe
Reference	B308

django_mark_safe

Medium | Tool: Bandit | OWASP: Unknown

Description	Potential XSS on mark_safe function. (./gmc_rfq/claims_analytics.py:926)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b703_django_mark_safe.html
Reference	B703

blacklist

Medium | Tool: Bandit | OWASP: Unknown

Description	Use of mark_safe() may expose cross-site scripting vulnerabilities and should be reviewed. (./gmc_rfq/claims_analytics.py:926)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b308-mark-safe
Reference	B308

django_mark_safe

Medium | Tool: Bandit | OWASP: Unknown

Description	Potential XSS on mark_safe function. (./gmc_rfq/claims_analytics.py:949)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b703_django_mark_safe.html
Reference	B703

blacklist

Medium | Tool: Bandit | OWASP: Unknown

Description	Use of mark_safe() may expose cross-site scripting vulnerabilities and should be reviewed. (./gmc_rfq/claims_analytics.py:949)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b308-mark-safe
Reference	B308

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: '1' (./gmc_rfq/excel_column_matcher.py:377)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: '2' (./gmc_rfq/excel_column_matcher.py:397)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: '3' (./gmc_rfq/excel_column_matcher.py:426)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: '3' (./gmc_rfq/excel_column_matcher.py:438)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: '4' (./gmc_rfq/excel_column_matcher.py:466)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: 'NBHIUAT@6$' (./gmc_rfq/management/commands/create_uat_users.py:10)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./gmc_rfq/management/commands/create_uat_users.py:90)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: 'Reqdas@6$' (./gmc_rfq/management/commands/step4.py:24)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: 'Reqdas@6$' (./gmc_rfq/management/commands/step4.py:34)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: 'Reqdas@6$' (./gmc_rfq/management/commands/step4.py:44)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: 'Reqdas@6$' (./gmc_rfq/management/commands/step4.py:55)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: 'Reqdas@6$' (./gmc_rfq/management/commands/step4.py:66)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: 'Reqdas@6$' (./gmc_rfq/management/commands/step4.py:76)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: 'Reqdas@6$' (./gmc_rfq/management/commands/step4.py:87)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

hardcoded_password_funcarg

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: 'Reqdas@6$' (./gmc_rfq/management/commands/step4.py:126)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b106_hardcoded_password_funcarg.html
Reference	B106

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./gmc_rfq/preprocessing/date_normalizer.py:545)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: '' (./gmc_rfq/split_quote_utils.py:367)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

django_mark_safe

Medium | Tool: Bandit | OWASP: Unknown

Description	Potential XSS on mark_safe function. (./gmc_rfq/templatetags/custom_filters.py:176)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b703_django_mark_safe.html
Reference	B703

blacklist

Medium | Tool: Bandit | OWASP: Unknown

Description	Use of mark_safe() may expose cross-site scripting vulnerabilities and should be reviewed. (./gmc_rfq/templatetags/custom_filters.py:176)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b308-mark-safe
Reference	B308

blacklist

Medium | Tool: Bandit | OWASP: Unknown

Description	Use of mark_safe() may expose cross-site scripting vulnerabilities and should be reviewed. (./gmc_rfq/templatetags/custom_filters.py:178)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b308-mark-safe
Reference	B308

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./gmc_rfq/utils.py:86)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./gmc_rfq/utils.py:121)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./gmc_rfq/utils.py:3626)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./gmc_rfq/utils.py:3632)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./gmc_rfq/views.py:190)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./gmc_rfq/views.py:2783)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./gmc_rfq/views.py:4167)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./gmc_rfq/views.py:7525)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./gmc_rfq/workflow.py:4195)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./gmc_rfq/workflow.py:4200)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./insurance_apis/services/orchestrator.py:473)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./insurance_apis/views/premiums.py:978)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./intelligence/agents/addon_mapper.py:194)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./intelligence/agents/demographic_parser.py:303)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./intelligence/agents/demographic_parser.py:315)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_continue

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Continue detected. (./intelligence/agents/demographic_parser.py:342)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b112_try_except_continue.html
Reference	B112

try_except_continue

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Continue detected. (./intelligence/agents/demographic_parser.py:519)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b112_try_except_continue.html
Reference	B112

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./intelligence/parsers/document_classifier.py:369)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./intelligence/parsers/document_classifier.py:633)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./intelligence/parsers/email_parser.py:79)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./intelligence/parsers/email_parser.py:87)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Consider possible security implications associated with the subprocess module. (./intelligence/setup.py:12)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_imports.html#b404-import-subprocess
Reference	B404

subprocess_without_shell_equals_true

Low | Tool: Bandit | OWASP: Unknown

Description	subprocess call - check for execution of untrusted input. (./intelligence/setup.py:28)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b603_subprocess_without_shell_equals_true.html
Reference	B603

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./masters/api_views.py:43)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./masters/views.py:543)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./product_configuration/api_views.py:1650)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./product_configuration/endorsement_views.py:354)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description Try, Except, Pass detected. (./product_configuration/endorsement_views.py:505)

Remediation https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html

Reference B110

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:219)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:220)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:220)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:220)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:221)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:222)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:223)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:236)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:240)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:245)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:247)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:250)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:252)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:253)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:254)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:270)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:281)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:282)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:291)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:296)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:297)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:339)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:345)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:346)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:347)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:348)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:349)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:350)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:351)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:352)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:353)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:361)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:362)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:363)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:364)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:365)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:366)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:368)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:408)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:410)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:412)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:426)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:460)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:469)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:523)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:552)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:552)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:556)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:559)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:562)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:565)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:596)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:596)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:600)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:603)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:607)

Remediation https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random

Reference B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:610)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./product_configuration/management/commands/generate_test_rfqs.py:613)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./product_configuration/pricing_engine.py:2730)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./product_configuration/pricing_engine.py:5302)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./product_configuration/quote_generation.py:1737)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Consider possible security implications associated with the subprocess module. (./product_configuration/views.py:23)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_imports.html#b404-import-subprocess
Reference	B404

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./product_configuration/views.py:1373)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./product_configuration/views_bulk_import.py:178)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./product_configuration/views_management.py:312)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./tars/decorators.py:149)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./tars/middleware/login_ratelimit.py:46)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: 'local' (./tars/settings.py:27)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: 'Reqdas@6$' (./uat_runner.py:51)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: 'Reqdas@6$' (./uat_runner.py:55)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: 'Reqdas@6$' (./uat_runner.py:59)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./uat_runner.py:115)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

try_except_pass

Low | Tool: Bandit | OWASP: Unknown

Description	Try, Except, Pass detected. (./uat_runner.py:153)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b110_try_except_pass.html
Reference	B110

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: '+' (./uat_runner.py:168)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: '92D050' (./uat_runner.py:1217)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: '0' (./uat_runner.py:1263)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: '0' (./uat_runner.py:1340)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./user_management/management/commands/assign_zones_randomly.py:58)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./user_management/management/commands/assign_zones_randomly.py:59)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

blacklist

Low | Tool: Bandit | OWASP: Unknown

Description	Standard pseudo-random generators are not suitable for security/cryptographic purposes. (./user_management/models.py:279)
Remediation	https://bandit.readthedocs.io/en/1.9.4/blacklists/blacklist_calls.html#b311-random
Reference	B311

hardcoded_password_string

Low | Tool: Bandit | OWASP: Unknown

Description	Possible hardcoded password: 'NBHIUAT@6$' (./user_management/views.py:2162)
Remediation	https://bandit.readthedocs.io/en/1.9.4/plugins/b105_hardcoded_password_string.html
Reference	B105