Gautam Solar Private Limited

Document No.	GSPL/IPQC/IPC/0
Issue Date	01/12/2024
Rev. No./Rev.Da	01/30-08-2025

IPQC Check Sheet

Date :- 19/12m Shif 1 Po.no.:-

Sr.No.	Stag	Chec	Quantum	Samp	Freq	Acceptanc o	Monitoring Result	Remarks
1	Shop	Temp	once	per	Temp. 25±		Time 8:15 24.8°C	
		Humi	once	per	RH ≤60%		Time 8:15 40%	
2	Glas	Glas	once	per	As Per PO		2376×1128×2.0mm	
3	EVA/App		once	per	Glass Bro		OK	
		EVA/	once	per	As per ap		EP304	
5	Cell	EVA/	once	per	As per Sp		2378×1125×0.70mm	
		EVA/	once	per	Not allow		Mfg: 26-12-2025	
4	Eva/	Sold	Once	per	As per sp		130■	
		Cell	once	per	Refer Pro		25.70% Solar Space	
6	Tabb	Cell	once	per	Refer Pro		182.35×91.88MM	
		Cell	once	per	Free From		OK	
		Clea	once	per	No unwant		Claen	
		Veri	once	per	ATW Str		ATW STRINGER - oK	
		Cell	once	per	Both side		Ok	
		Veri	once	Mont	ATW Str		ATW Temp - All OK	
		Visu	once	1 St	TS Visu			

TS01A	TS01B	TS02A	TS02B	TS03A	TS03B	TS04A	TS04B
OK	OK	Ok	Ok	oK	Ok	OK	Ok

EL I	once	1 St	TS EL C				

TS01A	TS01B	TS02A	TS02B	TS03A	TS03B	TS04A	TS04B
OK	O.K	OK	OK	OK	Ok	OK	ok

	once	1 St	Refer Pro				
Stri							

TS01A	TS01B	TS02A	TS02B	TS03A	TS03B	TS04A	TS04B
1163	1162	1163	1164	1164	1163	1163	1163

Cel							

TS01A	TS01B	TS02A	TS02B	TS03A	TS03B	TS04A	TS04B
0.78	0.9	0.80	0.80	0.74	0.74	0.81	0.80

		Veri	2 ce	per	Peel Stre	Ribbon peel strength O.K					
					Refer Pro						
		Stri	once	per		1.5 MM					
						TOP: 11.52mm					
						Bottom: 10.62 Mm					
						Sides: 12.11 MM					
		Sold	once	per	≥2N	Busbar peel test OK					
		Term	once	per	132 Cel	132 Cell module					
					Refer M	3.15 mm					
		Sold	Ever	per	No Dry/Po		OK oK O.K				
		Top	Ever	per	Creepage		T-12.35/B-11.24				
		Veri	once	per	Specifi	Ok					
		Qual	Ever	per	Taping sh		OK				
9	EVA	Posi	Ever	per	Should no		ok OK ok OK				
		EVA	once	per	EVA	EP304					
		EVA	once	per	As per Sp	2378×1125×0.70mm					
		EVA	once	per	Not allow	26-12-2025					
10	Back	Glas	once	Per	As per PO	2376×1128×2.0mm					
		No.	once	Per	3 hole wi	3 holes 12.11mm 12.06mm 12.07mm					
11	Auto	Visu	5 pi	per	No crack	OK OK OK					

					Pre EL			
						S.No	GS04770T40172614719	
						S.No	GS0477OT40172614725	
					Pre EL	S.No	GS04770TG0172614721	
						S.No	GS0477OTG0172614722	
						S.No	GSO4770T40172614724	
13	Stri	clea	once	per	Rework St	Clean and Wet		
14	Modu	Sold	once	per	400±30°C	Time: 8:15 418		
		Meth	once	per	As per Wl	manual		
		Clea	once	per	Rework St	Clean & Wet		
15	Lami	Sold	once	per	400±30°C	Time: 8:15 426		
		Moni	once	per	Process	O.K		
		Clea	once	24h	Diaphragm	Claen		
		Peel	All	All	E/G ≥60N/	Refer Document GSPL/IPQC/QC/001		
		Gel			75to 95%	Refer Document GSPL/IPQC/QC/001		

		Trim	5 pi	per	Excess la						
16	Auto	Visu	5 pi	per	Check Tap	ok OK oK					
						S.No.	GS04770TG0172614677				
						S.No.	GS04770TG0172614689				
18	90°	Visu	5 pi	per	Post La	S.No.	GS04770TG0172614620				
						S.No.	GS0477OTG0172614662				
						S.No.	GS04770TG0172614655				
		Trim	once	per	Worn out	Ok					
						S.No	GS04770TG0452500014				
						S.No	GS04770TG0172614136				
19	Fram					S.No	GS04770TG0172613375				
						S.No	GS04770TG0172613363				
						S.No	GS04770TG0172613364				
		Glue	1 se	per	Should be Fill as p	ok					
		Shor	once	Per		22.113gM					
		Long	once	Per		26.113gM					
		Anod	once	Per	≥15 micro	215 Micron					

20	Junc	Junc	once	Per	As per Pr	300mm						
21	Auto	Sili	once	Per	21±6 gm	26.193g						
		Max	once	Per	As per Sp	2 sec.						
22	JB P	Sold	once	per	As per Sp	17A						
		Sold	once	per	Welding a	Goog						
		A/B	once	Per	As per Sp	Refer Document GSPL/IPQC/QC/011						
		Pott	once	Per	21±6 gm	1:1						
		Nozz	once	ever	Should be	8:10 AM			2:10 PM			
23	OLE	Visu	once	5 pi	Potting s	Ok OK Ok						
		Temp	once	per	25±3■	25.4°C						
		Humi	once	per	≥50%	67%						
26	Clea	Mod	5 pi	per	≥4 hours	4 hrs						
25	Buff	Corn	5 pi	per	Should no	Ok OK Ok						
						S.No	GS04770TG0172614159					
						S.No	GS04770TG0172614139					
						S.No						
						S.No						
						S.No						

		Ambi	once	per	25±3■	24.8°c				
28	Hipo	Modu	once	per	25±3■	25.9°C				
		Suns DCW	once 5 pi	12h per	Sunsimula ≤50µA , >	GS04770TG0172615332				
		Vali	once	ever	As per GS	O.K Ok				
		Silv	once	Two	Should be	ok				
						GS0477OTG0172613342	12.3 µA	2.84	2.01	
29	Post					GS0477OTG0172614174	14.3 µA	2.82	2.27	
		EL I	5 pi	per						
		Volt	once	Shif	As per EW	50.3V, 7.5A				
						S.No	GS04770TG0172613392			
						S.No	GS04770TG0172615332			
					Post EL	S.No	GS04770TG0172613342			
						S.No	GS04770TG0172614174			
30	RFID					S.No				
		RFID	once	per	As per Pr	centre left side				
		Cell	once	per	As per BO	Feb. 2026				

						S.No.	GS04770TG0172613392	
		Back	5 pi	per	Air bubbl	S.No.	GS04770TG0172615332	
						S.No.	GS04770TG0172613342	
						S.No.	GS04770TG0172614174	
						S.No.		
						S.No	GS04770TG0172613392	
32	Dime					S.No	GS04770TG0172615332	
						S.No	GS04770TG0172613342	
						S.No	GS04770TG0172614174	
					As per Mo	S.No		
		L*W	once	per		(2382 × 1134 × 30) mm		
		Mou	once	Per		(1400 × 1091) MM		
33	Pack	Diag	once	Per	≤3mm	0.01mm		
		Corn	once	Per	As per vi	0.02 mm		
		JB Con	ce	Per	As per Pr	300 mm		
		Pack	once	Per	WI For	O.K		
		Cont	once	Per		ok		
		Box	once	Per	Damage,du	Ok		
		Wood	once	Per	Should no	(2400 x 1050 x 146)mm		

C/By: Ku

Reviewed By