GAUTAM SOLAR

Gautam Solar Private Limited

IPQC Check Sheet

Document No.	GSPL/IPQC/IPC/003
Issue Date	01/12/2024
Rev. No./Rev.Date	01/30-08-2025

Date :- 28/2/26 | Time :- 8:30 am | Shift DAY | Po.no.:-

Sr.No.	Stage	Check point	Quantum of Check: Sample Size	Quantum of Check: Frequency	Acceptance Criteria	Monitoring Result	Remarks,if any
1	Shop Floor	Temperature	once	per shift	Temp. 25±3°C	Time 8:30 am 25.1°C	
		Humidity	once	per shift	RH ≤60%	Time 8:30 am 38%	
2	Glass Loader	Glass dimension(L*W*T)	once	per shift	As Per PO	(2272 x 1128 x 2.001) mm	
		Appearance(Visual)	once	per shift	Glass Broken, Crack, Scratches and Line mark not allowed	OK	
3	EVA/EPE Cutting	EVA/EPE Type	once	per shift	As per approved BOM	EP304	
		EVA/EPE dimension(L*W*T)	once	per shift	As per Specification	(2274 x 1125 x 0.694) mm	
		EVA/EPE Status	once	per shift	Not allowed dust & foreign particle/Cut & non Uniform Embossing /Mfg Date	OK / 2026-01-22	
4	Eva/EPE Soldering at edge(If Applicable)	Soldering Temprature and Quality of Soldering	Once	per shift	As per specification and Should be properly soldered (400 ± 20°C)	381°C	
5	Cell Loading	Cell Manufacturer & Eff.	once	per shift	Refer Process Card	Solar Space & 25.50%	
		Cell Size(L*W)	once	per shift	Refer Process Card	(91.89 X 182.33) mm	
		Cell Condition	once	per shift	Free From dust,finger spot,color variation	OK	
		Cleanliness of Cell Loading Area	once	per shift	No unwanted or waste material should be at Cell Loading Area	Clean	
		Verification of Process Parameter	once	per shift	ATW Stringer Specification	Monitoring of ATW STRINGER	
		Cell Cross cutting	once	per shift	Both side cutting should be equal.	Equal	
6	Tabber & stringer	Verification of Process Parameter	once	Month	ATW Stringer specification	ATW Temprature Validation	
		Visual Check after Stringing	once	1 String/TS shift	TS Visual Criteria	TS01A OK, TS01B OK, TS02A OK, TS02B OK, TS03A OK, TS03B OK, TS04A OK, TS04B OK	
		EL Image of Strings	once	1 String/TS/shift	TS EL Criteria	TS01A OK, TS01B OK, TS02A OK, TS02B OK, TS03A OK, TS03B OK, TS04A OK, TS04B OK	
		String length	once	1 String/Stringer/ shift	Refer Process Card	TS01A 1111, TS01B 1111, TS02A 1111, TS02B 1111, TS03A 1111, TS03B 1111, TS04A 1110, TS04B 1110	
		Cell to Cell Gap				TS01A 0.83, TS01B 0.85, TS02A 0.80, TS02B 0.82, TS03A 0.84, TS03B 0.88, TS04A 0.86, TS04B 0.82	

Scanned with OKEN Scanner