GAUTAM SOLAR	Gautam Solar Private Limited	Document No.	GSPL/IPQC/IPC/003
		Issue Date	01/12/2024
	IPQC Check Sheet	Rev. No./Rev.Date	01/30-08-2025

Date :- 28-02-26 | Time :- 08:36 | Shift Day | Po.no.:-

Sr.No.	Stage	Check point	Quantum of Check: Sample Size	Quantum of Check: Frequency	Acceptance Criteria	Monitoring Result	Remarks,if any
20	Junction Box Assembly	Junction Box(Connector Appereance & Cable Length)	once	Per shift	As per Process Card & module drawing	ok / 1300 m.m	
		Silicon Glue Weight on the bottom (g)	once	Per shift	21±6 gm	17.92. g.m	
21	Auto JB Soldering	Max Welding time	once	Per shift	As per Specification	2.05 Sec	
		Soldering current	once	per shift	As per Specification	17. Amps	
		Soldering Quality	once	per shift	Welding area should be fully covered & checked by twizzer,no yellowing allowed	ok	
22	JB Potting	A/B Glue Ratio	once	Per shift	As per Specification	Refer Document GSPL/IPQC/QC/011	
		Potting material weight	once	Per shift	21±6 gm	19.957 g.m	
		Nozzle Changing	once	every 6h	Should be changed after 6 hours or when found issue of damage or extra amount dispensing.	Time: 8:10 Am / Time 2:00 P.m	
23	OLE Potting Inspection (If Applicable)	Visual Check	once	5 piece	Potting should be properly filled, and mounting hole should be as per drawing.	ok / ok / ok / ok / ok	
24	Curing	Temperature	once	per shift	25±3°C	26.3 °C	
		Humidity	once	per shift	≥50%	53%	
		Curing Time(h)	once	Per shift	≥4 hours	4.Hrs	
25	Buffing	Corner Edge,Buffing belt condition	5 pieces	per shift	Should not be sharp & No worn out	ok / ok / ok / ok / ok	
26	Cleaning	Module should be free from Tape,Dust,Dirt,EVA/Backsheet residue,Corner Burrs,Glue residue on (glass,backsheet,JB,Wire etc.)	5 pieces	per shift	Post Lam Visual Criteria	S.No GS04030TN354254440 4	ok
						S.No GS04030TN354254494	ok
						S.No GS04030TN354254498	ok
						S.No GS04030TN354254495	ok
						S.No GS04030TN354254406	ok

Scanned with OKEN Scanner