GAUTAM SOLAR

Gautam Solar Private Limited

IPQC Check Sheet

Document No.	GSPL/IPQC/IPC/003
Issue Date	01/12/2024
Rev. No./Rev.Date	01/30-08-2025

Date :- 8-03-26 Time :- 8:30 Shift Night Po.no.:-

Sr.No.	Stage	Check point	Quantum of Check: Sample Size	Quantum of Check: Frequency	Acceptance Criteria	Monitoring Result					Remarks,if any
20	Junction Box Assembly	Junction Box(Connector Appereance & Cable Length)	once	Per shift	As per Process Card & module drawing	ok | 1300 m.m					
		Silicon Glue Weight on the bottom (g)	once	Per shift	21±6 gm	19.809 g.m					
21	Auto JB Soldering	Max Welding time	once	Per shift	As per Specification	2.05 Sec					
		Soldering current	once	per shift	As per Specification	17 Amps					
		Soldering Quality	once	per shift	Welding area should be fully covered & checked by twizzer,no yellowing allowed	ok					
22	JB Potting	A/B Glue Ratio	once	Per shift	As per Specification	Refer Document GSPL/IPQC/QC/011					
		Potting material weight	once	Per shift	21±6 gm	20.086 g.m					
		Nozzle Changing	once	every 6h	Should be changed after 6 hours or when found issue of damage or extra amount dispensing.	Time: 8:10 Pm	Time 2:00 Am				
23	OLE Potting Inspection (If Applicable)	Visual Check	once	5 piece	Potting should be properly filled, and mounting hole should be as per drawing.	ok	ok	ok	ok	ok	
24	Curing	Temperature	once	per shift	25±3°C	24.8°C					
		Humidity	once	per shift	≥50%	73%					
		Curing Time(h)	once	Per shift	≥4 hours	4 Hrs					
25	Buffing	Corner Edge,Buffing belt condition	5 pieces	per shift	Should not be sharp & No worn out	ok	ok	ok	ok	ok	
26	Cleaning	Module should be free from Tape,Dust,Dirt,EVA/Backsheet residue,Corner Burrs,Glue residue on (glass,backsheet,JB,Wire etc.)	5 pieces	per shift	Post Lam Visual Criteria	S.No	GS0480307N354256 0041				ok
						S.No	GS0480307N354256 0058				ok
						S.No	GS0480307N354256 0110				ok
						S.No	GS0480307N354256 1196				ok
						S.No	GS0480307N354256 0087				ok

Scanned with OKEN Scanner