

Notebook Gemini



```
import pandas as pd
import re
import nltk
from sklearn.feature_extraction.text import TfidfVectorizer

# Load the dataset
df = pd.read_csv('/content/Tweets.csv.zip')

print("Libraries imported and dataset loaded successfully.")
print(df.head())
```

```
Libraries imported and dataset loaded successfully.
tweet_id airline_sentiment airline_sentiment_confidence \
0 570306133677760513 neutral 1.0000
1 570301130888122368 positive 0.3486
2 570301083672813571 neutral 0.6837
3 570301031407624196 negative 1.0000
4 570300817074462722 negative 1.0000

negativereason negativereason_confidence airline \
0 NaN NaN Virgin America
1 NaN 0.0000 Virgin America
2 NaN NaN Virgin America
3 Bad Flight 0.7033 Virgin America
4 Can't Tell 1.0000 Virgin America

airline_sentiment_gold name negativereason_gold retweet_count \
0 NaN cairdin NaN 0
1 NaN jnardino NaN 0
2 NaN yvonnalynn NaN 0
3 NaN jnardino NaN 0
4 NaN jnardino NaN 0

text tweet_coord \
0 @VirginAmerica What @dhepburn said. NaN
1 @VirginAmerica plus you've added commercials t... NaN
2 @VirginAmerica I didn't today... Must mean I n... NaN
3 @VirginAmerica it's really aggressive to blast... NaN
4 @VirginAmerica and it's a really big bad thing... NaN

tweet_created tweet_location user_timezone
0 2015-02-24 11:35:52 -0800 NaN Eastern Time (US & Canada)
1 2015-02-24 11:15:59 -0800 NaN Pacific Time (US & Canada)
2 2015-02-24 11:15:48 -0800 Lets Play Central Time (US & Canada)
3 2015-02-24 11:15:36 -0800 NaN Pacific Time (US & Canada)
4 2015-02-24 11:14:45 -0800 NaN Pacific Time (US & Canada)
```

```
print("First 5 rows of the DataFrame:")
print(df.head())

print("\nDataFrame Info (column names, data types, non-null values):")
df.info()

print("\nMissing values per column:")
print(df.isnull().sum())
```

```
First 5 rows of the DataFrame:
tweet_id airline_sentiment airline_sentiment_confidence \
0 570306133677760513 neutral 1.0000
1 570301130888122368 positive 0.3486
2 570301083672813571 neutral 0.6837
3 570301031407624196 negative 1.0000
4 570300817074462722 negative 1.0000

negativereason negativereason_confidence airline \
0 NaN NaN Virgin America
1 NaN 0.0000 Virgin America
2 NaN NaN Virgin America
3 Bad Flight 0.7033 Virgin America
4 Can't Tell 1.0000 Virgin America

airline_sentiment_gold name negativereason_gold retweet_count \
0 NaN cairdin NaN 0
1 NaN jnardino NaN 0
2 NaN yvonnalynn NaN 0
3 NaN jnardino NaN 0
```

```

4      NaN      jnardino      NaN      0

                                text tweet_coord \
0      @VirginAmerica What @dhepburn said.      NaN
1      @VirginAmerica plus you've added commercials t...      NaN
2      @VirginAmerica I didn't today... Must mean I n...      NaN
3      @VirginAmerica it's really aggressive to blast...      NaN
4      @VirginAmerica and it's a really big bad thing...      NaN

```

```

                                tweet_created tweet_location      user_timezone
0      2015-02-24 11:35:52 -0800      NaN      Eastern Time (US & Canada)
1      2015-02-24 11:15:59 -0800      NaN      Pacific Time (US & Canada)
2      2015-02-24 11:15:48 -0800      Lets Play      Central Time (US & Canada)
3      2015-02-24 11:15:36 -0800      NaN      Pacific Time (US & Canada)
4      2015-02-24 11:14:45 -0800      NaN      Pacific Time (US & Canada)

```

DataFrame Info (column names, data types, non-null values):

```
<class 'pandas.core.frame.DataFrame'>
```

RangeIndex: 14640 entries, 0 to 14639

Data columns (total 15 columns):

#	Column	Non-Null Count	Dtype
0	tweet_id	14640 non-null	int64
1	airline_sentiment	14640 non-null	object
2	airline_sentiment_confidence	14640 non-null	float64
3	negativereason	9178 non-null	object
4	negativereason_confidence	10522 non-null	float64
5	airline	14640 non-null	object
6	airline_sentiment_gold	40 non-null	object
7	name	14640 non-null	object
8	negativereason_gold	32 non-null	object
9	retweet_count	14640 non-null	int64
10	text	14640 non-null	object
11	tweet_coord	1019 non-null	object
12	tweet_created	14640 non-null	object
13	tweet_location	9907 non-null	object
14	user_timezone	9820 non-null	object

```

import nltk
from nltk.corpus import stopwords
from nltk.tokenize import word_tokenize

# Download necessary NLTK data (only needs to be run once)
nltk.download('stopwords', quiet=True)
nltk.download('punkt', quiet=True)

print("NLTK stopwords and punkt tokenizer are ready.")

```

NLTK stopwords and punkt tokenizer are ready.

```

import nltk

# Download the 'punkt_tab' resource which was indicated as missing
nltk.download('punkt_tab', quiet=True)

print("NLTK 'punkt_tab' resource downloaded successfully.")

```

NLTK 'punkt_tab' resource downloaded successfully.

```

import re
from nltk.corpus import stopwords
from nltk.tokenize import word_tokenize

# Initialize stopwords set for efficient lookup
stop_words = set(stopwords.words('english'))

def preprocess_text(text):
    # a. Remove URLs
    text = re.sub(r'http\S+|www\S+|https\S+', '', text, flags=re.MULTILINE)
    # b. Remove user mentions
    text = re.sub(r'@\w+', '', text)
    # c. Remove hashtags
    text = re.sub(r'#\w+', '', text)
    # d. Remove punctuation
    text = re.sub(r'[W_]+', ' ', text) # Replaced with space to avoid merging words
    # e. Remove numbers
    text = re.sub(r'\d+', '', text)
    # f. Convert to lowercase
    text = text.lower()

```

```
# g. Tokenize the text
tokens = word_tokenize(text)
# h. Remove English stopwords
filtered_tokens = [word for word in tokens if word.isalnum() and word not in stop_words]

return filtered_tokens

# Apply the preprocessing function to the 'text' column
df['processed_text'] = df['text'].apply(preprocess_text)

print("Tweet text preprocessing complete. Displaying original and processed text.")
print(df[['text', 'processed_text']].head())
```

Tweet text preprocessing complete. Displaying original and processed text.

	text \	processed_text
0	@VirginAmerica What @dhepburn said.	[said]
1	@VirginAmerica plus you've added commercials t...	[plus, added, commercials, experience, tacky]
2	@VirginAmerica I didn't today... Must mean I n...	[today, must, mean, need, take, another, trip]
3	@VirginAmerica it's really aggressive to blast...	[really, aggressive, blast, obnoxious, enterta...
4	@VirginAmerica and it's a really big bad thing...	[really, big, bad, thing]

```
from sklearn.feature_extraction.text import TfidfVectorizer

# Join the lists of tokens back into strings
df['processed_text_str'] = df['processed_text'].apply(lambda x: ' '.join(x))

# Initialize TfidfVectorizer
tfidf_vectorizer = TfidfVectorizer(tokenizer=lambda x: x.split(), lowercase=False)

# Fit and transform the processed text
tfidf_features = tfidf_vectorizer.fit_transform(df['processed_text_str'])

# Get feature names
feature_names = tfidf_vectorizer.get_feature_names_out()

print("TF-IDF Vectorization complete.")
print(f"Shape of TF-IDF features: {tfidf_features.shape}")
print(f"Total number of features: {len(feature_names)}")
print("First 10 feature names:")
print(feature_names[:10])
```

```
/usr/local/lib/python3.12/dist-packages/sklearn/feature_extraction/text.py:517: UserWarning: The parameter 'token_pattern' will
warnings.warn(
TF-IDF Vectorization complete.
Shape of TF-IDF features: (14640, 9722)
Total number of features: 9722
First 10 feature names:
['aa' 'aaaand' 'aadavantage' 'aadv' 'aadvantage' 'aal' 'aaron' 'aaso' 'ab'
'aback']
```

```
from sklearn.feature_extraction.text import TfidfVectorizer

# Join the lists of tokens back into strings
df['processed_text_str'] = df['processed_text'].apply(lambda x: ' '.join(x))

# Initialize TfidfVectorizer
tfidf_vectorizer = TfidfVectorizer(tokenizer=lambda x: x.split(), lowercase=False)

# Fit and transform the processed text
tfidf_features = tfidf_vectorizer.fit_transform(df['processed_text_str'])

# Get feature names
feature_names = tfidf_vectorizer.get_feature_names_out()

print("TF-IDF Vectorization complete.")
print(f"Shape of TF-IDF features: {tfidf_features.shape}")
print(f"Total number of features: {len(feature_names)}")
print("First 10 feature names:")
print(feature_names[:10])
```

```

/usr/local/lib/python3.12/dist-packages/sklearn/feature_extraction/text.py:517: UserWarning: The parameter 'token_pattern' will
warnings.warn(
TF-IDF Vectorization complete.
Shape of TF-IDF features: (14640, 9722)
Total number of features: 9722
First 10 feature names:
['aa' 'aaaand' 'aadavantage' 'aadv' 'aadvantage' 'aal' 'aaron' 'aaso' 'ab'
 'aback']

```

```

import pandas as pd

# 1. Filter the DataFrame for negative sentiment tweets
negative_tweets_df = df[df['airline_sentiment'] == 'negative']

print(f"Number of negative sentiment tweets: {len(negative_tweets_df)}")

# 2. Extract the processed text strings for negative tweets
negative_text_data = negative_tweets_df['processed_text_str']

# 3. Transform the negative sentiment text using the already fitted TF-IDF vectorizer
tfidf_negative_features = tfidf_vectorizer.transform(negative_text_data)

# 4. Display the shape of the resulting TF-IDF matrix for negative tweets
print("\nTF-IDF vectorization for negative sentiment tweets complete.")
print(f"Shape of TF-IDF features for negative tweets: {tfidf_negative_features.shape}")

# Optionally, display some top terms for negative sentiment
# This part is illustrative and can be expanded if deeper analysis is needed
# For simplicity, we'll just show the shape for now as per the task requirements.

```

Number of negative sentiment tweets: 9178

TF-IDF vectorization for negative sentiment tweets complete.
Shape of TF-IDF features for negative tweets: (9178, 9722)

Start coding or [generate](#) with AI.

```

print("Sample of processed_text_str column:")
print(df['processed_text_str'].head())

```

```

Sample of processed_text_str column:
0                                said
1      plus added commercials experience tacky
2      today must mean need take another trip
3  really aggressive blast obnoxious entertainmen...
4                                really big bad thing
Name: processed_text_str, dtype: object

```

```

print("\nShape of TF-IDF features for the entire corpus:")
print(tfidf_features.shape)

print("\nShape of TF-IDF features for negative sentiment tweets:")
print(tfidf_negative_features.shape)

```

Shape of TF-IDF features for the entire corpus:
(14640, 9722)

Shape of TF-IDF features for negative sentiment tweets:
(9178, 9722)

```

import pandas as pd
import numpy as np

# 1. Sum the TF-IDF scores for each feature across all negative sentiment tweets
# Summing along axis 0 of the sparse matrix and converting to a dense array
sum_tfidf_scores = np.array(tfidf_negative_features.sum(axis=0))[0]

# 2. Create a Pandas Series mapping feature names to summed TF-IDF scores
top_terms_series = pd.Series(sum_tfidf_scores, index=feature_names)

# 3. Sort these terms by their summed TF-IDF scores in descending order
sorted_top_terms = top_terms_series.sort_values(ascending=False)

```

```
# 4. Display the top N terms (e.g., top 20) along with their scores
print("\nTop 20 TF-IDF terms for negative sentiment tweets:")
print(sorted_top_terms.head(20))
```

```
Top 20 TF-IDF terms for negative sentiment tweets:
flight      390.487967
get         185.293127
cancelled   182.218991
service     154.537677
hold        154.142449
hours       153.129098
customer    134.044460
help        130.878358
time        124.018919
delayed     121.466794
still       118.496188
hour        116.539998
plane       115.765994
call        111.372964
flightled   109.498591
us          103.616676
one         100.299923
bag         95.901635
amp         93.879998
gate        93.072301
dtype: float64
```

```
import matplotlib.pyplot as plt

# Select the top 20 terms for visualization
top_20_terms = sorted_top_terms.head(20)

# Create a horizontal bar chart
plt.figure(figsize=(10, 8))
plt.barh(top_20_terms.index[::-1], top_20_terms.values[::-1], color='skyblue')

# Add labels and title
plt.xlabel('Cumulative TF-IDF Score')
plt.ylabel('Terms')
plt.title('Top 20 TF-IDF Terms in Negative Sentiment Tweets')

# Adjust layout to prevent labels from overlapping
plt.tight_layout()

# Display the plot
plt.show()
```

Flight Status	Number of Tweets (approx.)
flight	10
get	8
cancelled	8
service	6
hold	6

[illegible]