ALL-PAIRS SHORTEST PATH ALGORITHM

- The all pair shortest path algorithm is also known as Floyd-Warshall algorithm is used to find all pair shortest path problem from a given weighted-directed graph.
- This algorithm will generate a matrix, which will represent the minimum distance from any node to all other nodes in the graph.
- At first the output matrix is same as given cost matrix of the graph.
- After that the output matrix will be updated with all vertices k as the intermediate vertex.

Floyd Warshall Algorithm


- We initialize the solution matrix same as the input graph matrix as a first step.
- Then we update the solution matrix by considering all vertices as an intermediate vertex.
- The idea is to one by one pick all vertices and updates all shortest paths which include the picked vertex as an intermediate vertex in the shortest path.
- When we pick vertex number k as an intermediate vertex, we already have considered vertices {0, 1, 2... k-1} as intermediate vertices.
- For every pair (i, j) of the source and destination vertices respectively, there are two possible cases.

  1) k is not an intermediate vertex in shortest path from i to j. We keep the value of dist[i][j] as it is.

  2) k is an intermediate vertex in shortest path from i to j.

  - ✓ We update the value of dist[i][j] as dist[i][k] + dist[k][j] if dist[i][j] > dist[i][k] + dist[k][j]

Example



$$\begin{bmatrix} 0 & 1 & -3 & 2 & -4 \\ 3 & 0 & -4 & 1 & -1 \\ 7 & 4 & 0 & 5 & 3 \\ 2 & -1 & -5 & 0 & -2 \\ 8 & 5 & 1 & 6 & 0 \end{bmatrix}$$

$$D^{[0]} = \begin{pmatrix} 0 & 3 & 8 & \infty & -4 \\ \infty & 0 & \infty & 1 & 7 \\ \infty & 4 & 0 & \infty & \infty \\ 2 & \infty & -5 & 0 & \infty \\ \infty & \infty & \infty & 6 & 0 \end{pmatrix}$$

$D^{[1]}$ -Find the shortest path between pair of vertices by using vertex 1 as the intermediate vertex.

$D^{[1]}$

$$\begin{pmatrix} 0 & 3 & 8 & \infty & -4 \\ \infty & 0 & \infty & 1 & 7 \\ \infty & 4 & 0 & \infty & \infty \\ 2 & 5 & -5 & 0 & -2 \\ \infty & \infty & \infty & 6 & 0 \end{pmatrix}$$

$D^{[2]}$

$$\begin{pmatrix} 0 & 3 & 8 & 4 & -4 \\ \infty & 0 & \infty & 1 & 7 \\ \infty & 4 & 0 & 5 & 11 \\ 2 & 5 & -5 & 0 & -2 \\ \infty & \infty & \infty & 6 & 0 \end{pmatrix}$$

$D^{[3]}$

$$\begin{pmatrix} 0 & 3 & 8 & 4 & -4 \\ \infty & 0 & \infty & 1 & 7 \\ \infty & 4 & 0 & 5 & 11 \\ 2 & -1 & -5 & 0 & -2 \\ \infty & \infty & \infty & 6 & 0 \end{pmatrix}$$

D [4]

$$\begin{pmatrix} 0 & 3 & -1 & 4 & -4 \\ 3 & 0 & -4 & 1 & -1 \\ \infty & 4 & 0 & 5 & 3 \\ 2 & -1 & -5 & 0 & -2 \\ 8 & 5 & 1 & 6 & 0 \end{pmatrix}$$

$D^{[5]}$

$$\begin{pmatrix} 0 & 1 & -3 & 2 & -4 \\ 3 & 0 & -4 & -5 & -5 \\ 7 & 4 & 0 & 5 & 3 \\ 2 & -1 & -5 & 0 & -2 \\ 8 & 5 & 1 & 6 & 0 \end{pmatrix}$$

Algorithm Floyd-Warshall


Input − The cost matrix of given Graph.

Output − Matrix for shortest path between every pair of vertices

Floyd-Warshall (W)

1. n ← rows [W]
2. $D^{(0)} \leftarrow W$
3. for k ← 1 to n
4. do for i ← 1 to n
5. do for j ← 1 to n
6. do $d_{ij}^{(k)} \leftarrow \min (d_{ij}^{(k-1)}, d_{ik}^{(k-1)} + d_{kj}^{(k-1)})$

return $D^{(n)}$



G(V,E)

Wij = 0 if i=j

Wij=Weight of the edge between i & j if (i,j) is an element of the edge set E

Wij=∞ if there is no edge between i & j

n=4

D(0)=W

K=1

D(1)

.