

≡

Density Estimation

Building an Anomaly Detection System

Multivariate Gaussian Distribution (Optional)

Review

✓ Reading: Lecture Slides  
10 min

✓ Quiz: Anomaly Detection  
5 questions

Predicting Movie Ratings

Collaborative Filtering

Low Rank Matrix Factorization

Review

✓ Reading: Lecture Slides  
10 min

✓ Quiz: Recommender Systems  
5 questions

✓ Programming Assignment: Anomaly Detection and Recommender Systems  
3h

≡

✓ Congratulations! You passed!

QUIZ 10 MIN

TO PASS 80% or higher

Keep Learning

GRADE 100%

Recommender Systems

Recommender Systems

LATEST SUBMISSION GRADE

100%

Submit your assignment

Try again

DUE Nov 18, 1:29 PM IST

ATTEMPTS 3 every 8 hours

1. Suppose you run a bookstore, and have ratings (1 to 5 stars)

1 / 1 point

of books. Your collaborative filtering algorithm has learned a parameter vector  $\theta_j$  for user  $j$ , and a feature vector  $x^{(i)}$  for each book. You would like to compute the "training error", meaning the average squared error of your system's predictions on all the ratings that you have gotten from your users. Which of these are correct ways of doing so (check all that apply)?

For this problem, let  $m$  be the total number of ratings you have gotten from your users. (Another way of saying this is that  $m = \sum_{i=1}^{n_m} \sum_{j=1}^{n_u} r(i, j)$ ). [Hint: Two of the four options below are correct.]

✓ Correct

2. In which of the following situations will a collaborative filtering system be the most appropriate learning algorithm (compared to linear or logistic regression)?

1 / 1 point

✓ Correct

3. You run a movie empire, and want to build a movie recommendation system based on collaborative filtering. There were three popular review websites (which we'll call A, B and C) which users to go to rate movies, and you have just acquired all three companies that run these websites. You'd like to merge the three companies' datasets together to build a single/unified system. On website A, users rank a movie as having 1 through 5 stars. On website B, users rank on a scale of 1 - 10, and decimal values (e.g., 7.5) are allowed. On website C, the ratings are from 1 to 100. You also have enough information to identify users/movies on one website with users/movies on a different website. Which of the following statements is true?

1 / 1 point

✓ Correct

4. Which of the following are true of collaborative filtering systems? Check all that apply.

1 / 1 point

✓ Correct

5. Suppose you have two matrices  $A$  and  $B$ , where  $A$  is 5x3 and  $B$  is 3x5. Their product is  $C = AB$ , a 5x5 matrix. Furthermore, you have a 5x5 matrix  $R$  where every entry is 0 or 1. You want to find the sum of all elements  $C(i, j)$  for which the corresponding  $R(i, j)$  is 1, and ignore all elements  $C(i, j)$  where  $R(i, j) = 0$ . One way to do so is the following code:

1 / 1 point

```
C = A * B;
total = 0;
for i = 1:5
    for j = 1:5
        if (R(i,j) == 1)
            total = total + C(i,j);
        end
    end
end
```

Which of the following pieces of Octave code will also correctly compute this total? Check all that apply. Assume all options are in code.

✓ Correct