

Natural Language Processing & Word Embeddings

Quiz, 10 questions

✓ **Congratulations! You passed!**

Next Item



1 / 1
point

1.
Suppose you learn a word embedding for a vocabulary of 10000 words. Then the embedding vectors should be 10000 dimensional, so as to capture the full range of variation and meaning in those words.

☐ True

☒ False

Correct

The dimension of word vectors is usually smaller than the size of the vocabulary. Most common sizes for word vectors ranges between 50 and 400.



1 / 1
point

2.
What is t-SNE?

☐ A linear transformation that allows us to solve analogies on word vectors

☒ A non-linear dimensionality reduction technique

Correct

Yes

☐ A supervised learning algorithm for learning word embeddings

☐ An open-source sequence modeling library



1 / 1
point

3. Natural Language Processing & Word Embeddings

Suppose you downloaded a pre-trained word embedding which has been trained on a huge corpus of text. You then use this word embedding to train an RNN for a language task of recognizing if someone is happy from a short snippet of text, using a small training set.

x (input text)	y (happy?)
I'm feeling wonderful today!	1
I'm bummed my cat is ill.	0
Really enjoying this!	1

Then even if the word "ecstatic" does not appear in your small training set, your RNN might reasonably be expected to recognize "I'm ecstatic" as deserving a label $y = 1$.

☒ True

Correct

Yes, word vectors empower your model with an incredible ability to generalize. The vector for "ecstatic" would contain a positive/happy connotation which will probably make your model classified the sentence as a "1".

☐ False



1 / 1
point

4. Which of these equations do you think should hold for a good word embedding? (Check all that apply)

☒ $e_{boy} - e_{girl} \approx e_{brother} - e_{sister}$

Correct

Yes!

☐ $e_{boy} - e_{girl} \approx e_{sister} - e_{brother}$

Un-selected is correct

☒ $e_{boy} - e_{brother} \approx e_{girl} - e_{sister}$

Correct

Yes!

Natural Language Processing & Word Embeddings

Quiz, 10 questions — $e_{brother} \approx e_{sister} - e_{girl}$

Un-selected is correct



1 / 1
point

5.
Let E be an embedding matrix, and let o_{1234} be a one-hot vector corresponding to word 1234. Then to get the embedding of word 1234, why don't we call $E * o_{1234}$ in Python?



It is computationally wasteful.

Correct

Yes, the element-wise multiplication will be extremely inefficient.



The correct formula is $E^T * o_{1234}$.



This doesn't handle unknown words (<UNK>).



None of the above: calling the Python snippet as described above is fine.



1 / 1
point

6.
When learning word embeddings, we create an artificial task of estimating $P(\text{target} \mid \text{context})$. It is okay if we do poorly on this artificial prediction task; the more important by-product of this task is that we learn a useful set of word embeddings.



True

Correct



False



1 / 1
point

7.

Natural Language Processing & Word Embeddings

Quiz, 10 questions

☐ c is the one word that comes immediately before t .

☒ c and t are chosen to be nearby words.



Correct

☐ c is a sequence of several words immediately before t .

☐ c is the sequence of all the words in the sentence before t .



1 / 1
point

8.

Suppose you have a 10000 word vocabulary, and are learning 500-dimensional word embeddings. The word2vec model uses the following softmax function:

$$P(t | c) = \frac{e^{\theta_t^T e_c}}{\sum_{t'=1}^{10000} e^{\theta_{t'}^T e_c}}$$

Which of these statements are correct? Check all that apply.

☒ θ_t and e_c are both 500 dimensional vectors.



Correct

☐ θ_t and e_c are both 10000 dimensional vectors.



Un-selected is correct

☒ θ_t and e_c are both trained with an optimization algorithm such as Adam or gradient descent.



Correct

☐ After training, we should expect θ_t to be very close to e_c when t and c are the same word.



Un-selected is correct

point Natural Language Processing & Word Embeddings

Quiz, 10 questions

Suppose you have a 10000 word vocabulary, and are learning 500-dimensional word embeddings. The GloVe model minimizes this objective:

$$\min \sum_{i=1}^{10,000} \sum_{j=1}^{10,000} f(X_{ij})(\theta_i^T e_j + b_i + b'_j - \log X_{ij})^2$$

Which of these statements are correct? Check all that apply.

☐

θ_i and e_j should be initialized to 0 at the beginning of training.



Un-selected is correct

☐

θ_i and e_j should be initialized randomly at the beginning of training.



Correct

☐

X_{ij} is the number of times word i appears in the context of word j.



Correct

☐

The weighting function $f(\cdot)$ must satisfy $f(0) = 0$.



Correct

The weighting function helps prevent learning only from extremely common word pairs. It is not necessary that it satisfies this function.



1 / 1
point

10.

You have trained word embeddings using a text dataset of m_1 words. You are considering using these word embeddings for a language task, for which you have a separate labeled dataset of m_2 words. Keeping in mind that using word embeddings is a form of transfer learning, under which of these circumstance would you expect the word embeddings to be helpful?

☒

$m_1 \gg m_2$



Correct

☐

$m_1 \ll m_2$

Natural Language Processing & Word Embeddings

Quiz, 10 questions

