


Explain Cron Jobs?

It is a Timer / Scheduler program. It will try to do the activity in schedule way. You want to do some periodic activity then you will write Cron Jobs. Every week Sunday you want to send some **promotional**. Every month Salary Credit. The other way is -- Every day, we need to send some feed to external system.

Q: What CronJob Contains?

- A CronJob consists of a:
 - CronJob: Runtime information
 - Job: What to do
 - Trigger: When to run
- Allows re-using code and items
- CronJobs always run in a SessionContext (i.e. they have a user assigned)



Q: What are the Part of CronJobs? =

- ✓ **Trigger** = This type is used for scheduling when to run the job. Which uses Cron expression [* * * * ? *] which indicates [minutes, hours, day of month, month, day of week, year] to run the job.
- ✓ **CronJob** = This type holds the business logic which is to be performed at particular times and intervals.
- ✓ **Job** = This type consists of logic to be executed which is defined by Job Performable
Create a new class that extends **AbstractJobPerformable** class or implement **JobPerformable** interface.

Q: What are different steps required to create a cron job?

- ✓ **Step 1** = Create new class called "xxxJob.java" by extending **AbstractJobPerformable** class & Override the **perform ()** method & write the business (cron job) logic in this method
- ✓ **Step 2** = Goto xxx-spring.xml file & register the XxxxCronJob.java bean
- ✓ **Step 3** = Rebuild the hybris platform by calling "ant clean all"
- ✓ **Step 4** = Start the hybris server and perform platform update
- ✓ **Step 5** = Create the cron job & register the cron job using trigger

Q: What are the major different types of the preconfigured cronjobs in hybris?

- ✓ SOLR and Lucene related: indexing, updating, removing data
- ✓ Clean up unnecessary data from the database or file system
- ✓ Product Catalog synchronization
- ✓ Regular data export (Product, Price, Inventory, Order Status, and Import / Export).
- ✓ Workflow
- ✓ Impex import.

Q: What are the different ways to create cron job?

- ✓ **Option 1** = Using ImpEx
- ✓ **Option 2** = Using groovy scripts (scripting engine dynamically at runtime. you can create the cron job with groovy script and this script need to execute in hac □ console □ scripting languages)

Cron job example using ImpEx

Scenario – read the records from “TrainingCourses” table for every 1 minutes and display in the logs.
Let’s create the cron job under “ChennaTrainingCourses” project

Step 1 = Create new class called “ChennaTrainingJob.java” by extending **AbstractJobPerformable** class & **Override** the perform () method and write the business (cron job) logic in this method



```
1 package com.chennatrainingcourses.cronjobs;
2
3 import de.hybris.platform.cronjob.enums.CronJobResult;
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20 public class ChennaTrainingJob extends AbstractJobPerformable<CronJobModel>
21 {
22     private static final Logger LOG = Logger.getLogger(ChennaTrainingJob.class);
23
24     @Resource
25     private FlexibleSearchService flexibleSearchService;
26
27     @Override
28     public PerformResult perform(final CronJobModel cronJob)
29     {
30         LOG.info("ChennaTrainingJob is invoked");
31
32         final FlexibleSearchQuery flexibleSearchQuery = new FlexibleSearchQuery(
33             "SELECT {PK},{CODE},{NAME},{DURATION},{AMOUNT} FROM {COURSES}");
34
35         final SearchResult<CoursesModel> coursesSearchResult = flexibleSearchService.search(flexibleSearchQuery);
36
37         final List<CoursesModel> courseModels = coursesSearchResult.getResult();
38
39         // java 8 feature .. Lambda for loop expression..
40         courseModels.forEach(courseModel -> LOG.info(getRecordTorPrint(courseModel)));
41
42         return new PerformResult(CronJobResult.SUCCESS, CronJobStatus.FINISHED);
43     }
44
45     private String getRecordTorPrint(final CoursesModel courseModel)
46     {
47         return courseModel.getCode() + "--" + courseModel.getName() + "--" + courseModel.getDuration() + "--"
48             + courseModel.getAmount();
49     }
50 }
51
```

Step 2 = Goto xxx-spring.xml file & register the xxxJob.java bean

```
<beans xmlns="http://www.springframework.org/schema/beans"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:aop="http://www.springframework.org/schema/aop"
xsi:schemaLocation="http://www.springframework.org/schema/beans
http://www.springframework.org/schema/beans/spring-beans.xsd
http://www.springframework.org/schema/aop
http://www.springframework.org/schema/aop/spring-aop.xsd">
    <bean id="chennaTrainingJob" class="com.chennatrainingcourses.cronjobs.ChennaTrainingJob" >
        <property name="modelService" ref="modelService"/>
        <property name="flexibleSearchService" ref="flexibleSearchService"/>
        <property name="sessionService" ref="sessionService"/>
    </bean>
</beans>
```

```
*chennatrainingcourses-spring.xml
1 <beans xmlns="http://www.springframework.org/schema/beans"
2       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
3       xmlns:aop="http://www.springframework.org/schema/aop"
4       xsi:schemaLocation="http://www.springframework.org/schema/beans
5                           http://www.springframework.org/schema/beans/spring-beans.xsd
6                           http://www.springframework.org/schema/aop
7                           http://www.springframework.org/schema/aop/spring-aop.xsd">
8
9     <bean id="chennaTrainingJob" class="com.chennatrainingcourses.cronjobs.ChennaTrainingJob" >
10        <property name="modelService" ref="modelService"/>
11        <property name="flexibleSearchService" ref="flexibleSearchService"/>
12        <property name="sessionService" ref="sessionService"/>
13    </bean>
14
15 </beans>
```

AbstractJobPerformable
required these properties

Step 3 = Rebuild the hybris platform using “ant clean all”


```
C:\Windows\System32\cmd.exe
Microsoft Windows [Version 6.1.7601]
Copyright (c) 2009 Microsoft Corporation. All rights reserved.

C:\Documentation\training\softwares\HYBRISCOMM62\hybris\bin\platform>ant clean all
```

Step 4 = Start the hybris server & Perform platform update (click on update)

```
C:\Windows\System32\cmd.exe
Microsoft Windows [Version 6.1.7601]
Copyright (c) 2009 Microsoft Corporation. All rights reserved.

C:\Documentation\training\softwares\HYBRISCOMM62\hybris\bin\platform>hybrisserver.bat
```



Note - For each Spring definition of a class implementing the JobPerformable interface, a ServicelayerJob instance gets created and the code attribute of the job is set to the name of the Spring bean.

Step 5 = Create the cron job & register the cron job using trigger


There are 2 ways you can create the cron job and trigger

Option 1 = Goto hac ☐ plat form ☐ ImpEx Import & execute the following script by clicking on the **Import Content** button


```
INSERT_UPDATE CronJob; code[unique=true];job(code);singleExecutable;sessionLanguage(isocode)
;chennaTrainingJob;chennaTrainingJob;false;en
```

```
INSERT_UPDATE Trigger;cronjob(code)[unique=true];cronExpression
;chennaTrainingJob; 0 * * ? * *
```

The cronjob runs for very one minute



Verify the cronjob in the database under “CronJobs” table





Option 2 = Create the file resources/impex/essentialdataJobs.impex with the same content as above & restart the server and perform update (with only essential data checked).


Step 6 = Test the cron job

You can test the cron job using different options.

Option 1 = using hmc

Step 1 = Goto hmc ▢ System ▢ CronJobs ▢ search for the job (chennaTrainingJob) ▢ run the job





You can close the window. The trigger will run cron job for the specified time.

Step 2 = Validate the cron job results by looking the logs (whatever the outcome you are expecting)

```
INFO [chennaTrainingJob::de.hybris.platform.servicelayer.internal.jalo.ServicelayerJob] (chennaTrainingJob) [ChennaTrainingJob] ChennaTrainingJob is invoked
INFO [chennaTrainingJob::de.hybris.platform.servicelayer.internal.jalo.ServicelayerJob] (chennaTrainingJob) [ChennaTrainingJob] 10--Hybris--60 hours--500
INFO [chennaTrainingJob::de.hybris.platform.servicelayer.internal.jalo.ServicelayerJob] (chennaTrainingJob) [ChennaTrainingJob] 11--Fiori--70 hours--600
INFO [chennaTrainingJob::de.hybris.platform.servicelayer.internal.jalo.ServicelayerJob] (chennaTrainingJob) [ChennaTrainingJob] 12--Java--60 hours--500
INFO [chennaTrainingJob::de.hybris.platform.servicelayer.internal.jalo.ServicelayerJob] (chennaTrainingJob) [ChennaTrainingJob] 20--C++--100 hours--500
INFO [chennaTrainingJob::de.hybris.platform.servicelayer.internal.jalo.ServicelayerJob] (chennaTrainingJob) [ChennaTrainingJob] 22--Cloud Computing--80 hours--600
INFO [chennaTrainingJob::de.hybris.platform.servicelayer.internal.jalo.ServicelayerJob] (chennaTrainingJob) [ChennaTrainingJob] 21--Hadoop--80 hours--600
INFO [chennaTrainingJob::de.hybris.platform.servicelayer.internal.jalo.ServicelayerJob] (chennaTrainingJob) [ChennaTrainingJob] 23--Angular2--80 hours--600
```

Note – You can run the cron job using **hmc / back office / manually / javacode** etc.

Q: How to Start a CronJob? = There are different ways to start a cronjob which are given below :

- ✓ **Manually** start using HMC = `hmc > system > cronjobs > select CronJob > "StartCronJobNow"`.
- ✓ **Automatically** running the CronJob Through ImpEx file
- ✓ Using the **ant** command `ant runcronjob -d cronjob="CronJobName"`
- ✓ Using the **javacode** using the CronJob services we can run the cronjob.

Q: How to stop a cronjob? = We can stop the cronjob by following ways:

- ✓ Using the abort method in the java code. It is done automatically after performing the CronJob.
- ✓ Manually from hmc we can stop the CronJob.


Q: Where to see the created CronJob? = `hmc > System > CronJobs`

Q: How to change the CronJob schedule time?



Option 1 = using ImpEx

change cronExpression parameters (specify whatever time you want to execute the cronjob) & execute the script from hac > console > ImpEx Import

```
INSERT_UPDATE Trigger;cronjob(code)[unique=true];cronExpression
;chennaTrainingJob; 0 5 * ? * *
```



Option 2 = change using time schedule the hmc System CronJobs



Q: Explain Cron job Format: -

Table A-1 Cron Expressions Allowed Fields and Values

Name	Required	Allowed Values	Allowed Special Characters
Seconds	Y	0-59	, - * /
Minutes	Y	0-59	, - * /
Hours	Y	0-23	, - * /
Day of month	Y	1-31	, - * ? / L W C
Month	Y	0-11 or JAN-DEC	, - * /
Day of week	Y	1-7 or SUN-SAT	, - * ? / L C #
Year	N	empty or 1970-2099	, - * /

Example A-1 Cron Expressions

Cron expressions can be as simple as `* * * * *` or as complex as `0 0/5 14,18,3-39,52 ? JAN,MAR,SEP MON-FRI 2002-2010`.

Here are some more examples:

A CRON expression is a string representing the schedule for a particular command to execute. The parts of a CRON schedule are as follows:

	Expression	Meaning
* * * * *	* * * ? * *	Every second
- - - - -	0 * * ? * *	Every minute
	0 */2 * ? * *	Every even minute
	0 1/2 * ? * *	Every uneven minute
	0 */2 * ? * *	Every 2 minutes
	0 */3 * ? * *	Every 3 minutes
	0 */4 * ? * *	Every 4 minutes
	0 0 * ? * *	Every hour
	0 0 */2 ? * *	Every hour
	0 0 1 * * ?	Every day at 1am
	0 0 12 * * MON-FRI	Every Weekday at noon
	0 0 12 1 * ?	Every month on the 1st, at noon

Q: What are the **Params & Configurations** required for Job to Execute?

- ✓ Define Second, Min, Hour and etc. (or) **Cron Expression** = Trigger defined through **Impex**
hybris\bin\custom\chennatrainingcore\resources\impex\essentialdataJobs.impex
- ✓ **CronJob** Item Type Definition = *.items.xml
hybris\bin\custom\chennatrainingcore\resources\chennatrainingcore-items.xml
- ✓ Job Definition / **Business Logic** (CronJob1.java extends AbstractJobPerformable) = **Java** class for Job
hybris\hybris\bin\custom\chennatrainingcore\src\org\chennatraining\core\jobs\MyCronJob.java
- ✓ **Bean** Definition of Job (Example: - <bean id ="CronJob1" ...) = *-spring.xml
hybris\bin\custom\chennatrainingcore\resources\chennatrainingcore-spring.xml
- ✓ CronJob Model (Example: - SampleCronJobModel) = Platform

Q: How to see the Job Details? = select * from {servicelayerjob} where {code} = 'ChennaTrainingJob'

Q: How to Run Cron Job through Ant? = `ant runcronjob -Dcronjob=chennaCronJob -Dtenant=master`

Q: Explain Cron Job execution during the Server startup?

- ✓ When we start Hybris server, each trigger will be **evaluated** first, if trigger evaluated time is **overdue** or **matches** the current time then Trigger will be fired which means Cron jobs will be executed immediately.

Q: How much **overdue time** we can allow for the triggers to get fired during the server startup?

This can be done by setting **maxAcceptableDelay** (Value is in Seconds) attribute to the Trigger.

Let's say – Value set = 600 (10 mins) & Trigger is defined to run **@ 8PM**, If you start server **@ 8.10PM** then it will be fired. If you start server **@ 8.11PM** then it will not be fired.

Q: How to run CronJobs in specified cluster? (or) CronJob runs in all nodes / only 1 node? = **Only Single Node.**

Q: How to specify **Which Node CronJob** need to run?

```
CronJobModel myCronJob=modelService.create(CronJobModel.class);
```

```
// Set JobModel to CronJobModel & Set session attributes if required
```

```
myCronJob.setNodeID(3);    modelService.save(myCronjob);  
cronJobService.performCronJob(myCronJob);
```

Note: - If we **don't set any Node Id** for CronJob then it can be executed by any Node within the cluster.

Q: How to set session related attributes to the CronJob? = Sometime CronJob logic requires session attributes like user, sessionLanguage & sessionCurrency etc. **2 ways to set:** -

- ✓ **Session attributes Using Impex:-**

INSERT_UPDATE

```
CronJob;code[unique=true];job(code);sessionUser(uid);sessionLanguage(isocode);sessionCurrency(isocode)  
;ChennaCronJob;chennaJob;user1;en;EUR
```

Note: - These session values can be used while writing the logic inside Perform() method of Job

- ✓ **Session attributes Using Code** = Create instance of CronJobModel & set all session attributes then save Cron job model to DB. Then call **performCronJob()** method by passing the Cron job code.

```
CronJobModel chennaCronJob=modelService.create(CronJobModel.class);
```

```
// set JobModel to CronJobModel
```

```
chennaCronJob.setSessionUser(chennaSessionUserModel);
```

```
chennaCronJob.setSessionLanguage(chennaSessionLanguage);
```

```
chennaCronJob.setSessionCurrency(chennaSessionCurrency);
```

```
modelService.save(chennaCronjob);
```

```
cronJobService.performCronJob(chennaCronJob);
```

Q: How to Abort the CronJob? =

Abort / Terminate a running CronJob ? = Let our CronJob is running from last 2 hour, now you want to abort it, then we can do that in Hybris. Job is Abortable only if 1 of below satisfied: -

- ✓ **(1) isAbortable()** method in CronJob performable class should be **overridden** to **return true**.
- ✓ **(2)** Define a new property in ***-spring.xml** file, where we defined our Job's bean definition
`<property name="abortable" value="true"/>`

Now Job is **abortable** and can be done using below code =

```
cronJobService.requestAbortCronJob(running_cronjob_code);
```

Note: - After aborting CronJob, it results should be results as **ERROR** & status as **ABORTED**

Note: - Execution of CronJob is taken care by **Trigger** as per schedule defined in **Trigger** using **Cron Expression**.

- ✓ **Q1:** Who is responsible for Invoking this Trigger? **Q2:** Who evaluates the Cron Expression?

Task Engine = For every trigger there is always 1 task item gets created in Hybris.

It will keep on polling **Tasks** for every **X seconds** which configured in **local.properties** as:

```
cronjob.trigger.interval=30
```

By **default**, timer is set to **30 Seconds**. If you want to change it then do in **"local.properties"** as above.

Timer task fires a **DB query** to check for any triggers to be fired. If any matches / overdue then fires.

Note: - Don't give **too less** value until its essential (bcoz **DB calls** will be increased).

Task polled by **Task Engine** will check **Cron Expression** whether it matches / exceeded the current time.

Q: What is the Role of Jalo Session in Hybris?

- ✓ The **Jalo layer** in hybris is **deprecated**, not the **jaloSession**.
- ✓ **Whenever a request** is made to hybris server, it may **need** current user details, currency, language, time zone etc to serve that request efficiently. Since **HttpSession** **does not** hold all these details, hybris came up with the concept of **JaloSession**.
- ✓ Whenever a request comes to Hybris, the filter **HybrisInitFilter** creates an object of **JaloSession**. **Every JaloSession object** is associated with a **SessionContext object**, which has current user, language, currency etc and the **current HttpSession** object.
 - o Cron Jobs also run in a **JaloSession**.
 - o **JaloSession** is bound to a **tenant**.
This cannot be changed, after the instance of JaloSession is created.
 - o **JaloSession** is **never** made **persistent** in database.

Q: Explain Model Attributes?

- ✓ Some time it is necessary to get few data in many JSPs, and we don't want to pass them as a part of DTO (data objects). For example, the titles (Mr and Mrs etc). They can be used in many JSPs and tags file, like registration, delivery address etc.
- ✓ In such cases, what we do is, create a convenient method in Abstract controllers, and use model attribute annotation for them. In this way they are available from all JSPs directly using model attribute.

<pre>@ModelAttribute("languages") public Collection<LanguageData> getLanguages() { return storeSessionFacade.getAllLanguages(); }</pre>	<pre>@ModelAttribute("currencies") public Collection<CurrencyData> getCurrencies() { return storeSessionFacade.getAllCurrencies(); }</pre>
---	--

- ✓ These can be accessed directly in JSPs or even tag files. like Current Language : **\${currentLanguage}**