# Deltaport Skid Consortium B.V.

Technical and Commercial Offer

Product: DPS-36

Submitted in response to Material Requisition MR-33kV-GIS-Rev4

## 1. COVER LETTER

This offer remains valid for the period stated in the commercial terms.

Our offer is compliant per the attached Schedule of Deviations.

Yours faithfully,

Dear Sirs,

Deltaport Skid Consortium B.V.

## 2. SCHEDULE OF DEVIATIONS

Deviation 1: Short-time withstand current 50 kA for 1.0 s instead of 3 s.

Deviation 2: RTU marshalling, refer to datasheet section 3.

Deviation 3: Factory acceptance testing, refer to inspection and test plan.

Deviation 4: Delivery terms, refer to commercial terms.

All other clauses - Complied

Information provided by the purchaser is for tender purposes and remains confidential.

The supplier shall comply with the purchaser's site rules and permit-to-work procedures.

This section describes the general obligations of the supplier for the scope defined in this document.

## 3. TECHNICAL DATASHEET

The datasheet below is completed against the purchaser's datasheet template.

Installation: indoor, in a prefabricated substation building.

Insulating medium: fluorine-free gas mixture.

Operating mechanism: motor-charged spring mechanism.

Installation: indoor, in a prefabricated substation building.

Short-time withstand capability tested for 50 kA RMS at 1.0 second thermal duration.

HDHC electrolytic copper busbar system rated 2500 A continuous throughout all MV compartments.

Rated voltage Ur: 36 kV.

Insulating medium: fluorine-free gas mixture.

Operating mechanism: motor-charged spring mechanism.

Insulating medium: fluorine-free gas mixture.

Full IP54 dust and splash sealing with 4-sided IAC AFLR internal arc containment.

Maximum ambient temperature 104 °F without derating.

Operating mechanism: motor-charged spring mechanism.

Mechanical endurance class according to the applicable standard.

Operating mechanism: motor-charged spring mechanism.

IEC 61850 Ed.2 relays DSC-R200 with PRP fibre ports; RTU marshalling excluded, customer SCADA wiring directly to individual bay LV compartments.

Mechanical endurance class according to the applicable standard.

The datasheet below is completed against the purchaser's datasheet template.

Mechanical endurance class according to the applicable standard.

The datasheet below is completed against the purchaser's datasheet template.

Installation: indoor, in a prefabricated substation building.

Insulating medium: fluorine-free gas mixture.

## 4. SINGLE LINE DIAGRAM NOTES

NOTE 4: Cable terminations are of the plug-in type.

NOTE 5: The bus coupler connects both switchgear sections.

NOTE 6: Auxiliary supplies are distributed from the station board.

NOTE 8: Refer to the general arrangement drawing for panel positions.

Drawing DPS-36-SLD - sheet 1

NOTE 5: The bus coupler connects both switchgear sections.

NOTE 6: Auxiliary supplies are distributed from the station board.

NOTE 8: Refer to the general arrangement drawing for panel positions.

NOTE 1: All dimensions are in millimetres unless stated otherwise.

Drawing DPS-36-SLD - sheet 2

NOTE 6: Auxiliary supplies are distributed from the station board.

NOTE 8: Refer to the general arrangement drawing for panel positions.

NOTE 1: All dimensions are in millimetres unless stated otherwise.

NOTE 2: Earthing switches are interlocked with the associated circuit breakers.

Drawing DPS-36-SLD - sheet 3

NOTE 8: Refer to the general arrangement drawing for panel positions.

NOTE 1: All dimensions are in millimetres unless stated otherwise.

NOTE 2: Earthing switches are interlocked with the associated circuit breakers.

NOTE 3: Voltage transformers are fitted on incomer bays only.

Drawing DPS-36-SLD - sheet 4

## 5. BILL OF MATERIALS

Pos 10: Circuit breaker panels with vacuum interrupters.

Pos 12: Current transformers for protection and metering.

Pos 20: Cable termination compartments.

Pos 30: Low voltage compartments with terminal blocks.

Pos 12: Current transformers for protection and metering.

Pos 20: Cable termination compartments.

Pos 30: Low voltage compartments with terminal blocks.

Pos 40: Protection relay assemblies.

Pos 20: Cable termination compartments.

Pos 30: Low voltage compartments with terminal blocks.

Pos 40: Protection relay assemblies.

Pos 50: Gas monitoring devices.

## 6. INSPECTION AND TEST PLAN

Type test certificates from an accredited laboratory are submitted with the offer.

Test results are recorded on test sheets signed by the supplier's quality inspector.

Hold points are agreed with the purchaser during the kick-off meeting.

The inspection and test plan lists all inspections and tests during manufacturing.

Test results are recorded on test sheets signed by the supplier's quality inspector.

Includes 3 days witnessed inspection; additional days billed per tariff.

Hold points are agreed with the purchaser during the kick-off meeting.

The inspection and test plan lists all inspections and tests during manufacturing.

Hold points are agreed with the purchaser during the kick-off meeting.

The inspection and test plan lists all inspections and tests during manufacturing.

Type test certificates from an accredited laboratory are submitted with the offer.

Test results are recorded on test sheets signed by the supplier's quality inspector.

## 7. COMMERCIAL TERMS AND PRICE SCHEDULE

Prices are fixed and firm for the scope described in this offer.

Payment terms: milestone payments as defined in the purchase order.

The offer is subject to the purchaser's general purchasing conditions.

Taxes are shown separately where applicable.

Payment terms: milestone payments as defined in the purchase order.

Delivered At Place (DAP) project site; warranty 24 months from commissioning.

The offer is subject to the purchaser's general purchasing conditions.

Taxes are shown separately where applicable.

The offer is subject to the purchaser's general purchasing conditions.

Total lump-sum price for the complete scope: €439,000

Taxes are shown separately where applicable.

Unit prices for additional bays are available on request.

## 8. QUALITY ASSURANCE

The purchaser reserves the right to audit the supplier and its sub-suppliers.

Material certificates shall be traceable to the delivered equipment.

The supplier shall operate a quality management system certified to ISO 9001.

A quality plan shall be issued for review before manufacturing starts.

Material certificates shall be traceable to the delivered equipment.

The supplier shall operate a quality management system certified to ISO 9001.

A quality plan shall be issued for review before manufacturing starts.

Non-conformances shall be reported to the purchaser together with the proposed corrective action.

## 9. SPARE PARTS

Spare parts shall be interchangeable with the corresponding original parts.

Special tools required for maintenance shall be supplied with the equipment.

Spare part prices shall remain valid as stated in the commercial terms.

A list of recommended spare parts shall be included with the offer.

Special tools required for maintenance shall be supplied with the equipment.

Spare part prices shall remain valid as stated in the commercial terms.

A list of recommended spare parts shall be included with the offer.

Spare parts shall be interchangeable with the corresponding original parts.

## 10. TRAINING

Training shall cover operation, maintenance and safety of the switchgear.

Training material shall be provided to each participant.

The training programme shall be agreed with the purchaser before delivery.

Training shall cover operation, maintenance and safety of the switchgear.

Training material shall be provided to each participant.

The training programme shall be agreed with the purchaser before delivery.

Training shall cover operation, maintenance and safety of the switchgear.

Training material shall be provided to each participant.

## 11. DOCUMENTATION

Document reviews by the purchaser do not relieve the supplier of responsibility for correctness.

Drawings and documents shall be submitted in electronic format for review and approval.

Each document shall carry a title block with document number, revision and approval status.

As-built documentation shall be delivered after commissioning is complete.

Drawings and documents shall be submitted in electronic format for review and approval.

Each document shall carry a title block with document number, revision and approval status.

As-built documentation shall be delivered after commissioning is complete.

Operation and maintenance manuals shall be provided in English and German.